Lake Cable Delivers What You Need, When You Need It.



Lake Cable, LLC proudly presents its full line of Control Cable for use in power and control applications of the Petrochemical, Utility, Iron & Steel, Pulp & Paper and Waste Water Treatment Industries. Lake Cable's new state-of-the-art, Industrial Cable manufacturing facilities produce a diverse line of control products in materials ranging from thermoplastics to high end Low Smoke Zero Halogen.

Lake Cable's engineers draw on decades of manufacturing experience to focus on quality designs and process improvement. We utilize only the finest raw materials in the production of our Lake Cable brand of Control Cables. We have been able to achieve process efficiencies through the utilization of "cell manufacturing" which contributes to higher productivity, cost reduction and the fastest delivery times in the industry!

Our customer service representatives are trained for quick response in answering questions, solving problems and making sure customers' needs are met. Whether your cable need is a standard construction or a specially engineered product, ***when delivery matters, specify Lake Cable!***

Control Cable 600 Volt Industrial Tray Cable (TC)

Multiple Conductors, PVC/Nylon, UL Type TC

APPLICATIONS: Designed for power and control applications in petrochemical, utility, paper, steel mills, waste water and industrial plants. May be used in Class 1, Division 2 Hazardous Locations per NEC Article 501. These cables conform to NEC Article 336 Type TC "Power and Control Tray Cable."


DESCRIPTION: Tested per UL requirements for Type TC cables having THWN, THHN or TFN conductors. Cables are listed for direct burial. These cables conform to NEC Article 336 "Power and Control Tray Cable."

APPROVALS: UL, TC-ER, C(UL), CSA-CIC **FLAME TEST:** Passes IEEE 1202, FT4, UL 1277, ICEA T-29-520 (210,000 BTU)

PART NO.	AWG	AMPS	NO. OF COND.	JACKET THICKNESS	NOM O.D.	WT./ 1000'
V182	18	14	2	.045"	.262"	39
V183	18	14	3	.045"	.275"	49
V184	18	11	4	.045"	.297"	60
V185	18	11	5	.045"	.322"	71
V187	18	9	7	.045"	.348"	89
V189	18	9	9	.045"	.401"	109
V1812	18	7	12	.045"	.447"	143
V1815	18	7	15	.045"	.481"	169
V1819	18	7	19	.060"	.550"	220
V1830	18	6	30	.060"	.671"	334
V1837	18	5	37	.060"	.722"	397
V162	16	18	2	.045"	.288"	49
V163	16	18	3	.045"	.303"	63
V164	16	14	4	.045"	.328"	79
V165	16	14	5	.045"	.357"	92
V166	16	14	6	.045"	.387"	105
V167	16	12	7	.045"	.387"	118

Other conductor counts available upon request.

Composite power and control available upon request.



GAUGE: 18-10 AWG

TEMPERATURE: 90°C

AMPACITY: Based on not more than 3 conductors in raceway or cable or earth with an ambient temperature of 30°C per NEC 310.60. All conductors derated per the NEC.

CONSTRUCTION: Cabled with fillers to make round. 2 conductor cables are flat.

CONDUCTOR: Stranded Bare Copper, Class B per UL 83 and 62.

INSULATION: PVC per UL 62 for Type TFN (18-16) AWG or UL 83 for Type THWN or THHN wire. Average thickness is 15 mils for 18-12 AWG and 20 mils for 10 AWG. PVC insulation is jacketed with nylon meeting UL 62 for Type TFN or UL 83 for Type THWN or THHN wire. Minimum thickness is 4 mils. VW-1.

JACKET: Sunlight Resistant PVC per UL 1277.

COLOR CODE: ICEA Method 1, Table E-2 (see page 5).

LEGEND: PART # AWG COND TYPE TC-ER (UL) PVC/NYLON 90°C DRY 75 °C WET 600V PVC JACKET SUN RES DIR BUR SEQ. FT. PRNT. ROHS.

PACKAGING: Reels

Control Cable 600 Volt Industrial Tray Cable (TC)

Multiple Conductors, PVC/Nylon, Type TC (cont.)

DESCRIPTION: Tested per UL requirements for Type TC cables having THWN, THHN or TFN conductors. Cables are listed for direct burial. These cables conform to NEC Article 336 "Power and Control Tray Cable."


APPROVALS: UL, TC-ER, C(UL), CSA-CIC **FLAME TEST:** Passes IEEE 1202, FT4, UL 1277, ICEA T-29-520 (210,000 BTU)

PART NO.	AWG	AMPS	NO. OF COND.	JACKET THICKNESS	NOM O.D.	WT./ 1000'
V169	16	12	9	.045"	.448"	152
V1612	16	9	12	.045"	.501"	189
V1615	16	9	15	.045"	.580"	243
V1619	16	9	19	.060"	.615"	304
V1625	16	8	25	.060"	.706"	391
V1630	16	8	30	.060"	.754"	466
V1637	16	7	37	.060"	.813"	556
V142	14	25†	2	.045"	.316"	640
V143	14	25†	3	.045"	.334"	85
V144	14	20	4	.045"	.362"	103
V145	14	20	5	.045"	.395"	122
V146	14	20	6	.045"	.429"	143
V147	14	17	7	.045"	.429"	160
V149	14	17	9	.045"	.499"	207
V1412	14	12	12	.060"	.590"	286
V1415	14	12	15	.060"	.646"	340
V1419	14	12	19	.060"	.685"	426
V1425	14	11	25	.060"	.789"	554
V1430	14	11	30	.080"	.884"	685
V1437	14	10	37	.080"	.951"	819
V122	12	30†	2	.045"	.354"	83
V123	12	30†	3	.045"	.375"	110
V124	12	24	4	.045"	.408"	139
V125	12	24	5	.045"	.446"	175
V126	12	24	6	.045"	.486"	203
V127	12	21	7	.045"	.486"	229
V129	12	21	9	.045"	.597"	309
V1212	12	15	12	.060"	.669"	400
V1219	12	15	19	.060"	.780"	604
V1225	12	13	25	.080"	.941"	814
V1230	12	13	30	.080"	1.006"	953
V1237	12	12	37	.080"	1.084"	1197
V102	10	40†	2	.045"	.422"	122
V103	10	40†	3	.045"	.448"	169
V104	10	32	4	.045"	.490"	214
V105	10	32	5	.060"	.568"	275
V107	10	28	7	.060"	.618"	374
V109	10	28	9	.060"	.720"	470
V1012	10	20	12	.060"	.810"	616

Other conductor counts available upon request.

Composite power and control available upon request.

† Unless otherwise specifically permitted in the NEC, the overcurrent protection shall not exceed 15A for 14 AWG, 20A for 12 AWG and 30A for 10 AWG.



GAUGE: 18-10 AWG

TEMPERATURE: 90°C

AMPACITY: Based on not more than 3 conductors in raceway or cable or earth with an ambient temperature of 30°C per NEC 310.60. All conductors derated per the NEC.

CONSTRUCTION: Cabled with fillers to make round. 2 conductor cables are flat.

CONDUCTOR: Stranded Bare Copper, Class B per UL 83 and 62.

INSULATION: PVC per UL 62 for Type TFN (18-16) AWG or UL 83 for Type THWN or THHN wire. Average thickness is 15 mils for 18-12 AWG and 20 mils for 10 AWG. Conductor jacketed with nylon meeting UL 62 for Type TFN or UL 83 for Type THWN or THHN wire. Minimum thickness is 4 mils. VW-1.

JACKET: Sunlight Resistant PVC per UL 1277.

COLOR CODE: ICEA Method 1, Table E-2 (see page 5).

LEGEND: PART # AWG COND. TYPE TC-ER (UL) PVC/NYLON 90°C DRY 75 °C WET 600V PVC JACKET SUN RES DIR BUR SEQ. FT. PRNT. ROHS.

PACKAGING: Reels