DECA CABLES

Deca Cables Inc.
150 North Murray Street
P.O. Box 777
Trenton, Ontario K8V 5W6
Canada

Website: www.decacables.com
Telephone: (613) 392-3585
Facsimile: (613) 392-7908
Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 71-0803

CONSTRUCTION SPECIFICATIONS

Description	TECK 90 3C 8 AWG UNSH AIA 1000V
Conductor	8 AWG 7 Strand Bare Copper - Concentric
Conductor Diameter	0.146" / 3.71 mm
Insulation Type	Cross Linked Polyethylene (XLPE)
Insulation Thickness	0.045" / 1.14 mm
Conductor Identification	Black, Red, Blue
Bonding Conductor	10 AWG 7 Strand Bare Copper - Concentric
Cable Assembly	Conductors are cabled together with a bonding conductor. A PVC jacket is applied over the twisted assembly. An aluminum armour is applied over the inner jacket. An outer PVC jacket is applied over the aluminum armour.
Ripcord	Polyester Ripcord included under the inner jacket
Inner Jacket	0.060" / 1.52 mm (min. avg) Flame Retardant Low Acid Gas PVC
Armour Type	Interlocked Aluminum Armour
Outer Jacket	0.043" / 1.09 mm (min. avg) Flame Retardant Low Acid Gas PVC
Overall Cable Diameter	0.936" / 23.77 mm
Jacket Print	DECA CSA TECK 90 XLPE PVC JACKET 3C 8 AWG 1000V (-40C) HL FT4 SUN RES LL83251 ---- ROHS LAG work order #, month, year, meter markings (every 1 metre)

ELECTRICALS

Voltage	1000V
Conductor Resistance	0.6407 Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified	CSA C22.2 No. 131 Type Teck 90 Cable CSA C22.2 No. 38 Thermoset Insulated Wires and Cables CSA C22.2 No. 174 Cables and Cable Glands for Use in Hazardous Locations			
Applications	Class I, Zone 1,2, and Class II, Division 1,2			
Flame Test Rating	CSA FT4			
Temperature Rating	-40C to 90C Wet/90C Dry			
ROHS	Compliant			
Cable Weight	695	kgs/km	467	lbs/1000ft
Copper Content	270	kgs/km	181	lbs/1000ft
Max Pull Tension	248	kgs	547	lbs
Min Bending Radius	7.50	inches (installed)	191	mms (installed)
Max Cable Length	2450	metres	8038	feet