DECA CABLES

Deca Cables Inc.
150 North Murray Street
P.O. Box 777
Trenton, Ontario K8V 5W6
Canada

Website: www.decacables.com
Telephone: (613) 392-3585
Facsimile: (613) 392-7908
Email: sales@decacables.com

**ISO 9001:2008**

# PRODUCT DATA SHEET

# Part No: 71-1002

## CONSTRUCTION SPECIFICATIONS

| | |
|---|---|
| **Description** | TECK 90 2C 10 AWG UNSH AIA 600V |
| **Conductor** | 10 AWG 7 Strand Bare Copper - Concentric |
| **Conductor Diameter** | 0.116" / 2.95 mm |
| **Insulation Type** | Cross Linked Polyethylene (XLPE) |
| **Insulation Thickness** | 0.030" / 0.76 mm |
| **Conductor Identification** | Black, White |
| **Bonding Conductor** | 12 AWG 7 Strand Bare Copper - Concentric |
| **Cable Assembly** | Conductors are cabled together with a bonding conductor. A PVC jacket is applied over the twisted assembly. An aluminum armour is applied over the inner jacket. An outer PVC jacket is applied over the aluminum armour. |
| **Ripcord** | Polyester Ripcord included under the inner jacket |
| **Inner Jacket** | 0.045" / 1.14 mm (min. avg) Flame Retardant Low Acid Gas PVC |
| **Armour Type** | Interlocked Aluminum Armour |
| **Outer Jacket** | 0.043" / 1.09 mm (min. avg) Flame Retardant Low Acid Gas PVC |
| **Overall Cable Diameter** | 0.742" / 18.85 mm |
| **Jacket Print** | DECA CSA TECK 90 XLPE PVC JACKET 2C 10 AWG 600V (-40C) HL FT4<br>SUN RES LL83251 ---- ROHS LAG<br>work order #, month, year, meter markings (every 1 metre) |

## ELECTRICALS

| | |
|---|---|
| **Voltage** | 600V |
| **Conductor Resistance** | 1.019 Ohms/Mft @20C |

## CERTIFICATIONS AND PHYSICAL PROPERTIES

| | | | | |
|---|---|---|---|---|
| **CSA Certified** | CSA C22.2 No. 131 Type Teck 90 Cable<br>CSA C22.2 No. 38 Thermoset Insulated Wires and Cables<br>CSA C22.2 No. 174 Cables and Cable Glands for Use in Hazardous Locations | | | |
| **Applications** | Class I, Zone 1,2, and Class II, Division 1,2 | | | |
| **Flame Test Rating** | CSA FT4 | | | |
| **Temperature Rating** | -40C to 90C Wet/90C Dry | | | |
| **ROHS** | Compliant | | | |
| **Cable Weight** | 396 | kgs/km | 266 | lbs/1000ft |
| **Copper Content** | 123 | kgs/km | 83 | lbs/1000ft |
| **Max Pull Tension** | 104 | kgs | 229 | lbs |
| **Min Bending Radius** | 6.00 | inches (installed) | 152 | mms (installed) |
| **Nominal Cable Length** | 3000 | metres | 9842 | feet |