General Cable

# Product Data Sheet

RoHS Compliant Directive 2011/65/EU

Part Number: TBD - Ref. ENG.101630 Revision: 10/14/2016

**2C 18 AWG PVC, UNSH, PVC** **SOUND, ALARM AND SECURITY CABLE**

## A. CONSTRUCTION

| | | DIAMETERS |
|---|---|---|
| Conductor: | #18 AWG (Solid) Bare Copper | .040" Nom |
| Insulation: | .008" Wall, Plenum PVC | .056" Nom |
| Cable Assembly: | 2 Conductors with a 6.00" LHL | .115" Nom |
| Ripcord: | Polyester Ripcord | |
| Jacket: | .015" Wall, Plenum PVC | .145" ± .008" |
| Jacket Color: | White | |
| Package: | Pull Pack | |
| Sequential Footage: | Yes | |
| Print Legend: | ***CAROL(R) 18 AWG -- [P/N] -- 75C E60233-8 (UL) CL3P OR FPLP -- (UL)C(UL) CMP -- ROHS -- MADE IN USA (date code - MM/YY) (sequential footage)*** | |

## B. INDUSTRY APPROVALS

| | |
|---|---|
| National Electrical Code | Article 725 |
| UL Standard 13 | Type CL3P |
| National Electrical Code | Article 760 |
| UL Standard 1424 | Type FPLP |
| National Electrical Code | Article 800 |
| UL Standard 444 | Type CMP |
| EU Directive 2011/65/EU (RoHS-2) | RoHS Compliant |

## C. ELECTRICAL PROPERTIES

| | |
|---|---|
| Temperature: | 0°C to +75°C |
| Suggested Working Voltage: | 300 Vrms (Max) |
| Conductor DCR: | 6.52 Ohms/1000ft (Max) @ 20°C |
| Capacitance (Cond-Cond): | 33.5 pF/ft (Nom) @ 1kHz |

## D. COLOR CODE

| COND | COLOR |
|---|---|
| 1 | VIOLET |
| 2 | GRAY |

## E. CUSTOMER APPROVAL

Signature: _____ Date: _____