DATE: 09/07/11

SPECIFICATION SHEET
TAPPAN Spec. H91835.1

H91835.1



INTENDED USES: Wiring for lighting control system devices. Royal Blue stripe / non-plenum installations

CONSTRUCTION:
12 AWG stranded BC 2C UNSHIELDED (POWER & COMMON) plus
18 AWG stranded BC 1C UNSHIELDED (SENSE LINE) plus
22 AWG stranded BC 1 PR, SHIELDED, (MUX DATA);
CABLED AND JACKETED OVERALL.

INSULATION:
12 AWG 2C POWER & COMMON PVC
18 AWG 1C SENSE LINE PVC
22 AWG 1 Pr MUX DATA FOAM PE

COLOR CODE:
12 AWG 2C POWER & COMMON BLACK, RED
18 AWG 1C SENSE LINE ORANGE
22 AWG 1 Pr MUX DATA WHITE, GREEN

SHIELD/DRAIN: (MUX DATA PAIR) FOIL SHIELD, FOIL IN; 24 AWG STRANDED TC DRAIN WIRE

OVERALL JACKET: PVC; LIGHT BLUE w/ROYAL BLUE STRIPE

NOM. DIAMETER: 0.404 INCH

CABLE WT: 83 Lb/1000Ft Approx (EXCLUDING REEL OR BOX)

ELECTRICALS:

COMPONENT:	CAPACITANCE	IMPEDANCE	DC RESISTANCE	Vel. Of Prop.
12 AWG 2C PWR / COMMON	58.3 pF/ft	32 Ohms	1.71 Ohms/Mft	55%
18 AWG 1C SENSE LINE	36.0 pF/ft	51 Ohms	6.92 Ohms/Mft	55%
22 AWG 1PR SHLD DATA	14.9 pF/ft	86 Ohms	17.5 Ohms/Mft	79%

TEMP/VOLTAGE: 75C / 300V

PRINT LEGEND: TAPPAN W & C H91835.1 TYPE LUTR SYSTEM CONTROL – LIGHT BLUE/ROYAL BLUE
E57497 CL3R 12AWG 2/C + 18AWG 1/C + 22AWG 1/PR SHLD (UL) c(UL) FT4 CMG 75C
MADE IN USA RoHS COMPLIANT

UL: CL3R

MISC: MADE IN USA. EQUIVILENT TO GRX-CBL-46L

+/- 10% Manufacturing tolerance
* On non-standard product, customer agrees to accept all lengths manufactured

Tappan Wire & Cable Inc. provides information and specifications on an “as is” basis. Information in specifications described herein are subject to error and/or omission, and subject to change without notice. Although we make all efforts possible to ensure the accuracy and timeliness of the information, Tappan Wire & Cable, will not be held liable for any damages whatsoever, even if advised of the possibility of such damages, arising from the use, or inability to use, the information or specifications herein. Please refer to our “Website Use Policy”, listed on our website, www.tappanwire.com, under the Sales Support Section for full details, or contact your Tappan Representative. This drawing may contain patented or proprietary information. It is the property of Tappan Wire and must not be used in any way detrimental to Tappan Wire. Acceptance by signature of this drawing will be considered as an agreement of and acceptance of the foregoing.

100 Bradley Parkway • Blauvelt, NY 10913
Phone: 1-800-WIRE-911 • Fax: 1-845-353-9315
www.tappanwire.com