100 Bradley Parkway
Blauvelt, NY 10913
Toll-Free (800) 947-3911
Fax (845) 353-9315

SPECIFICATION SHEET

COMPANY: OMNI DATE: 01/23/12

SPECIFICATION SHEET

TWC PART NUMBER: K19957.2/2450AT2/CMP/CL2P

CONSTRUCTION	:	24AWG 7/32 TINNED COPPER 2 IND. SHIELDED PAIR(S)
COLOR CODE	:	CC#555: WHITE/BLUE L.&BLUE/WHITE L.,WHITE/ORANGE L.&ORAN
INSULATION	:	0.019 Inch, Foam Flouro
SHIELD/DRAIN	:	EACH PAIR IS INDIVIDUALLY SHLD FOIL-IN (BLUE OUT). ONE DRAIN WIRE PER PAIR
CAPACITANCE	:	10.8 pF/ft Nom.
VEL OF PROP	:	79.1%
IMPEDANCE	:	119 OHMS
RESISTANCE	:	27.2 OHMS D.C. PER 1000 FT @ 68 DEG. F
TEMP/VOLTAGE	:	150 DEGREES C
JACKET	:	CHROME GRAY, 0.017 Inch, FOAM-SOLEF -- 0.189 Nom OD
CABLE WT	:	24.3 Lb/1000Ft Approx (EXCLUDING REEL OR BOX)
PRINT LEGEND	:	"LOW CAP 24/2PRS INDIV. SHLD" E118871 CMP/CL2P 24AWG 2 PAIRS (UL) c(UL) 150 DEG. C. MADE IN USA
UL	:	CMP/CL2P
MISC	:	MADE IN USA

* +/- 10% Manufacturing tolerance
* On non-standard product, customer agrees to accept all lengths manufactured

APPROVED BY

Tappan Wire & Cable Inc. provides information and specifications on an “as is” basis. Information in specifications described herein are subject to error and/or omission, and subject to change without notice. Although we make all efforts possible to ensure the accuracy and timeliness of the information, Tappan Wire & Cable, will not be held liable for any damages whatsoever, even if advised of the possibility of such damages, arising from the use, or inability to use, the information or specifications herein. Please refer to our “Website Use Policy”, listed on our website, www.tappanwire.com, under the Sales Support Section for full details, or contact your Tappan representative.