UL LISTED CATHODIC PROTECTION CABLE

KALAS
Wire & Cable



FEATURES

– Kalas now carries and is able to supply as standard product UL listed Cathodic Protection Cable. Our cable is backed by stringent auditing and testing to rigid UL standards and requirements which ensure the performance consistency that our customers and Kalas demand
– Special stranding and packaging are available upon request
– Custom print available upon request
– Direct burial
– Sunlight resistant
– Abrasion resistant

CONSTRUCTION

Annealed stranded bare copper conforming to ASTM B-8. A high molecular weight polyethylene (HMW / PE) insulation conforming to ASTM D 1248 I, Class A, Cat.4 Grade E5 is extruded over the copper.

APPLICATIONS

– For Cathodic protection of pipelines, oil tanks, steel piped, well casings, marine craft and other metallic structures
– Rated at 600 Volts

Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

BK/ULPC/02.16

ISO 9001: 2008 CERTIFIED
ISO 14001: 2004 CERTIFIED

RoHS 2002/95/EC

UL LISTED

MADE IN THE USA

UL LISTED CATHODIC PROTECTION CABLE

KALAS Wire & Cable

GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT ~LBS/ 1000 FT.	PART NUMBERS
		in	mm	in	mm			
12	7/0305	0.110	2.79	0.315	8.00	3000	49	480009.XX.001
10	7/0385	0.110	2.79	0.339	8.61	2500	64	480010.XX.001
8	7/0486	0.110	2.79	0.371	9.42	6000	88	480011.XX.001
6	7/0612	0.110	2.79	0.407	10.34	5000	126	480012.XX.001
4	7/0772	0.110	2.79	0.460	11.61	4500	185	480013.XX.001
2	7/0974	0.110	2.79	0.520	13.08	3500	262	480014.XX.001
1	19/0664	0.125	3.18	0.592	15.04	2500	357	480015.XX.001
1/0	19/0745	0.125	3.18	0.633	16.08	2250	415	480016.XX.001
2/0	19/0837	0.125	3.18	0.679	17.25	2000	511	480017.XX.001
4/0	19/1055	0.125	3.18	0.793	20.14	1500	782	480019.XX.001

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

KALAS HEADQUARTERS
167 Greenfield Road
Lancaster, PA 17601

KALAS LOS ANGELES
28365 Constellation Road,
Unit B
Valencia, CA 91355

KALASWIRE.COM
P 717.336.5575
F 717.945.1002