Specification: Tracer-PE
Issue Date:09/14/09
Supersedes: 03/20/09

Kris-Tech Wire Co.

921 Seneca St. • PO Box 4377 • Rome, NY 13442-4377 USA
Telephone 315-339-5268 • Fax 315-339-5277
WWW.KRISTECHWIRE.COM

1.0 Scope: This specification describes single conductor **TRACER/LOCATOR WIRE** insulated with high molecular weight polyethylene (HMWPE) specifically **for use in direct burial applications**. HMWPE is a rugged and durable material considered excellent for moisture and abrasion resistance. The tracer wire's purpose of is to carry an electronic signal for use in locating underground non-metallic pipe. This product is manufactured according to Underwriters Laboratory constructions in both 30 volt and 600 volt versions suitable for use at a maximum continuous operating temperature of 75 degrees C in wet and dry locations.

2.0 Applicable Standards:

2.1 ASTM B-1, B-3, and B-8 for copper conductors.

2.2 ASTM D-1248 for Polyethylene Extrusion Materials, ICEA S-70-547 Weatherproof Resistant Polyethylene Conductors, ICEA S-61-402/NEMA WC5 Thermoplastic Insulated Wire&Cable, ICEA S-95-658/NEMA WC70 Non-Shielded 0 – 2kv Cables.

2.3 UL 1581 Standard for Electrical Wires, Cables, and Flexible Cords.

3.0 Conductors: The single copper conductors shall be solid or stranded annealed or hard uncoated copper per UL83 and ASTM requirements.

4.0 Insulation: The conductor shall be insulated with HMWPE as specified and applied in a concentric manner. The minimum at any point shall not be less than 90% of the specified average thickness in compliance with UL 83.

5.0 Identification: No markings are required. Custom and standard print legends are available.

6.0 Packaging: Standard length spools of 500 ft. or 2500 ft. are packaged and labeled with the product name/description, conductor size, and manufacturer. Custom lengths are available.

7.0 Testing: The wire shall be continuously spark tested at 7500 Volts DC. Other electrical and mechanical tests shall be in accordance with UL 1581.

Type Tracer/Locator Wire – 30V and 600 Volts 60°C

AWG Solid Conductors	Breaking Pounds soft/hard	Insulation Thickness 30v/600v	Nominal Overall Diameter 30v/600v	Approx. Shipping Wgt. (Lbs./Mft.) 30v/600v
18	47/85	0.030”/0.045”	0.10”/0.13”	8/9
16	74/135	0.030”/0.045”	0.11”/0.14”	12/14
14	124/210	0.030”/0.045”	0.12”/0.15”	18/20
12	198/340	0.030”/0.045”	0.14”/0.17”	27/30
10	310/530	0.030”/0.045”	0.16”/0.19”	40/43
8	480/820	0.030”/0.045”	0.20”/0.23”	60/64
6	760/1280	0.030”/0.045”	0.22”/0.25”	92/97

Non-standard colors and custom packaging are available by quotation.