529 Thomas Drive, Bensenville, IL 60106 | TF: 888.518.8086 | FX: 630.860.5944

Specification Sheet

Lake Cable Part #: V168STOS/22DR

Description: 16 AWG 8 triads 7 strand bare copper with PVC/Nylon insulation, aluminum/mylar shields with stranded tinned copper drain wires and an overall PVC jacket 600V control tray cable, approved for use in SUN RES DIR BUR 90°C applications.

1. **Conductor**
   - 1.1. AWG Size & Stranding: 16 AWG 7 Strands Class B
   - 1.2. Material: Annealed Bare Copper
   - 1.3. Conductor Count: 8 Triads

2. **Insulation**
   - 2.1. Material: Polyvinylchloride & Nylon
   - 2.2. Wall Thickness: 0.015" PVC & 0.005" Nylon
   - 2.3. Color Code: Black, Red & White numbered triads

3. **Assembly**
   - 3.1. Triad Lay Length: 3.25" LHL
   - 3.2. Triad Drain Wire: 22 AWG 7 Strand Tinned Copper
   - 3.3. Triad Shield: Foil Free Edged Aluminum/Mylar Tape – 100% coverage
   - 3.4. Cable Lay Length: 10.50" LHL
   - 3.5. Cable Binder: Clear Mylar – 100% coverage
   - 3.6. Cable Shield: Aluminum/Mylar Tape – 100% coverage
   - 3.7. Cable Drain Wire: 16 AWG 7 Strand Tinned Copper
   - 3.8. Fillers: N/A

4. **Jacket**
   - 4.1. Material: Polyvinylchloride
   - 4.2. Wall Thickness: 0.080"
   - 4.3. Diameter: 0.866" ± 0.070"
   - 4.4. Color: Black
   - 4.5. Ripcord: Yes
   - 4.6. Cold Bend Rating: -40°C
   - 4.7. Weight: 442 lbs./Mft.

5. **Markings**
   - 5.1. Type: Cable shall be permanently identified via surface inkjet print
   - 5.2. Legend: LAKE CABLE E208309 16AWG 8TR STOS (UL) TC-ER PVC/NYLON 600V 90'C DRY/WET PVC JACKET SUN RES DIR BUR FT4 "ROHS II" MADE IN USA
   - 5.3. Footage Markers: Yes

6. **Standards**
   - 6.1. Refer to NEC (NFPA 70) article 336 for installation guidelines
   - 6.2. Cable is suitable for use in Class I Division 2 hazardous locations
   - 6.3. UL listed as Type TC-ER per UL Standard 1277 for tray cables
   - 6.4. UL approved for Direct Burial and Sunlight Resistant applications
   - 6.5. Cable meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements
   - 6.6. Meets ICEA S-73-532, where applicable
   - 6.7. All materials used in the manufacture of this cable are RoHS II & REACH compliant
   - 6.8. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

Date

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION