LAKE CABLE, LLC
WHEN DELIVERY MATTERS...
529 Thomas Drive, Bensenville, IL 60106 USA – Ph: 847-238-3000 Toll Free: 888-518-8086 Fax: 630-860-5944

16 AWG 2 Conductor Shielded Type EX Thermocouple Cable Specification

Lake Cable Part #: T6EXH162S

Description: 16 AWG, 2 conductor shielded Type EX thermocouple tray cable constructed with solid Type EP (Chromel) and Type EN (Constantan) extension grade alloy conductors, low smoke cross-linked polyethylene insulation, an aluminum/mylar shield with a stranded tinned copper drain wire and an overall low smoke flame retardant zero halogen polyolefin jacket. Individual conductors are manufactured in accordance with UL Standard 66, Type XLPE. Cable is manufactured in the USA in accordance with UL Standard 1277 and NEC listed Type TC, suitable for use in Class I Division II hazardous locations and approved for installation in cable trays per Article 336 of the National Electric Code. Cable may be installed in open air, in ducts or conduits, in trays or troughs and is approved for direct burial and outdoor, 90°C Wet or Dry, applications. Jacket is sunlight resistant and cable is listed (UL) TC-ER "LS" and meets or exceeds the requirements of IEEE 383 and UL 1581 (1685) 70,000 BTU/HR flame tests.

1. Conductor
- 1.1 AWG Size & Stranding: 16 AWG, Solid
- 1.2 Material: Type EP (Chromel) & Type EN (Constantan) extension grade alloy conductors

2. Insulation
- 2.1 Material: LSXLPE per UL Standard 66, Type XLPE
- 2.2 Wall Thickness: 0.030" - The minimum at any point shall not be less than 90% of the specified wall thickness

3. Color Code
- 3.1 Code: Violet (EP-Chromel) & Red (EN-Constantan)

4. Assembly
- 4.1 Lay Length: Per UL Standard 1277
- 4.2 Fillers: N/A
- 4.3 Binder: Clear Mylar Tape
- 4.4 Shield: Aluminum/Mylar Tape – 100% coverage
- 4.5 Drain Wire: 18 AWG, 7 Strand Tinned Copper

5. Jacket
- 5.1 Material: Low Smoke FR Zero Halogen Polyolefin (LSFR-ZHPO)
- 5.2 Wall Thickness: 0.045" - The minimum at any point shall not be less than 80% of the specified wall thickness
- 5.3 Diameter: 0.319"
- 5.4 Color: Violet
- 5.5 Weight: 60 lbs./Mft.

6. Markings
- 6.1 Type: Cable shall be permanently identified via surface inkjet print
- 6.2 Legend: LAKE CABLE E208309 16AWG 2C SHIELDED (UL) TC-ER "LS" LSXLPE 90'C DRY/WET TYPE EX EXTENSION GRADE THERMOCOUPLE LS0H JACKET SUN RES DIR BUR "ROHS" IEEE 1202 FT4

7. Standards
- 7.1 UL listed as Type TC-ER "LS" per UL Standards 1277 & 1685 LS0H for tray cables
- 7.2 UL approved for Sunlight Resistant, Direct Burial & Low Smoke applications
- 7.3 Cable meets IEEE 383 & UL 1581 (1685) 70,000 BTU/HR flame test requirements
- 7.4 Meets ICEA S-82-522, where applicable
- 7.5 Extension Wire Temperature Range: 0°C to 200°C
- 7.6 All materials used in the manufacture of this cable are RoHS compliant

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION