Technical
Data Sheet

07/19/10 REV. 3 MONTROSE 2000C

.

I. DESCRIPTION:

---

14 AWG (19X#27) TINNED COPPER POLYETHYLENE INSULATED CONDUCTORS, TWO SINGLES TWISTED WITH FOIL SHIELD TAPE PLUS 18 AWG (7X#26) TINNED COPPER DRAIN WIRE, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	150 V RMS (CL2) 600 V RMS (AWM)
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	14 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	2.4 OHMS PER 1000 FEET
NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C:	5.2 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS @ 1 KHZ:	28 PF PER FOOT
NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:*	50.5 PF PER FOOT
NOMINAL INDUCTANCE OF PAIR:	.19 MICRO-H PER FOOT

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C (CL2) -20 TO +80 DEG.C (AWM)
INSULATION MATERIAL:	POLYETHYLENE
INSULATION THICKNESS:	.032” NOMINAL
TWISTED PAIR LAY LENGTH:	3-1/2" (3.4 TWISTS PER FOOT)
COLOR CODE:	BLACK & CLEAR
TYPE SHIELD AND % COVERAGE:	POLYESTER/ALUMINUM TAPE; 100%
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.032” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.348”
MININUM BEND RADIUS:	3-1/2”
NOMINAL WEIGHT:	59 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	95 LBS.
APPLICABLE SPECIFICATIONS:	UL TYPE CL2 OR AWM 20253, ROHS COMPLIANT

Technical
Data Sheet

FLAME RESISTANCE:	UL 1685 VERTICAL TRAY