**Table 310.15(B)(18) (formerly Table 310.18) Allowable Ampacities of Insulated Conductors Rated Up to and Including 2000 Volts, 150°C Through 250°C (302°F Through 482°F). Not More Than Three Current-Carrying Conductors in Raceway or Cable, Based on Ambient Air Temperature of 40°C (104°F)***

| | Temperature Rating of Conductor [See Table 310.104(A).] | | | | |
|---|---|---|---|---|---|
| | 150°C (302°F) | 200°C (392°F) | 250°C (482°F) | 150°C (302°F) | |
| | Type Z | Types FEP, FEPB, PFA, SA | Types PFAH, TFE | Type Z | |
| Size AWG or kcmil | COPPER | | NICKEL OR NICKEL-COATED COPPER | ALUMINUM OR COPPER-CLAD ALUMINUM | Size AWG or kcmil |
| 14 | 34 | 36 | 39 | — | 14 |
| 12 | 43 | 45 | 54 | 30 | 12 |
| 10 | 55 | 60 | 73 | 44 | 10 |
| 8 | 76 | 83 | 93 | 57 | 8 |
| 6 | 96 | 110 | 117 | 75 | 6 |
| 4 | 120 | 125 | 148 | 94 | 4 |
| 3 | 143 | 152 | 166 | 109 | 3 |
| 2 | 160 | 171 | 191 | 124 | 2 |
| 1 | 186 | 197 | 215 | 145 | 1 |
| 1/0 | 215 | 229 | 244 | 169 | 1/0 |
| 2/0 | 251 | 260 | 273 | 198 | 2/0 |
| 3/0 | 288 | 297 | 308 | 227 | 3/0 |
| 4/0 | 332 | 346 | 361 | 260 | 4/0 |

*Refer to 310.15(B)(2) for the ampacity correction factors where the ambient temperature is other than 40°C (104°F).

**Table 310.15(B)(19) (formerly Table 310.19) Allowable Ampacities of Single-Insulated Conductors, Rated Up to and Including 2000 Volts, 150°C Through 250°C (302°F Through 482°F), in Free Air, Based on Ambient Air Temperature of 40°C (104°F)***

| | Temperature Rating of Conductor [See Table 310.104(A).] | | | | |
|---|---|---|---|---|---|
| | 150°C (302°F) | 200°C (392°F) | 250°C (482°F) | 150°C (302°F) | |
| | Type Z | Types FEP, FEPB, PFA, SA | Types PFAH, TFE | Type Z | |
| Size AWG or kcmil | COPPER | | NICKEL, OR NICKEL-COATED COPPER | ALUMINUM OR COPPER-CLAD ALUMINUM | Size AWG or kcmil |
| 14 | 46 | 54 | 59 | — | 14 |
| 12 | 60 | 68 | 78 | 47 | 12 |
| 10 | 80 | 90 | 107 | 63 | 10 |
| 8 | 106 | 124 | 142 | 83 | 8 |
| 6 | 155 | 165 | 205 | 112 | 6 |
| 4 | 190 | 220 | 278 | 148 | 4 |
| 3 | 214 | 252 | 327 | 170 | 3 |
| 2 | 255 | 293 | 381 | 198 | 2 |
| 1 | 293 | 344 | 440 | 228 | 1 |
| 1/0 | 339 | 399 | 532 | 263 | 1/0 |
| 2/0 | 390 | 467 | 591 | 305 | 2/0 |
| 3/0 | 451 | 546 | 708 | 351 | 3/0 |
| 4/0 | 529 | 629 | 830 | 411 | 4/0 |

*Refer to 310.15(B)(2) for the ampacity correction factors where the ambient temperature is other than 40°C (104°F).

**Table 310.15(B)(2)(b) Ambient Temperature Correction Factors Based on 40°C (104°F)**

**For ambient temperatures other than 40°C (104°F), multiply the allowable ampacities specified in the ampacity tables by the appropriate correction factor shown below.**

| Ambient Temperature (°C) | Temperature Rating of Conductor | | | | | | Ambient Temperature (°F) |
|---|---|---|---|---|---|---|---|
| | 60°C | 75°C | 90°C | 150°C | 200°C | 250°C | |
| 10 or less | 1.58 | 1.36 | 1.26 | 1.13 | 1.09 | 1.07 | 50 or less |
| 11–15 | 1.50 | 1.31 | 1.22 | 1.11 | 1.08 | 1.06 | 51–59 |
| 16–20 | 1.41 | 1.25 | 1.18 | 1.09 | 1.06 | 1.05 | 60–68 |
| 21–25 | 1.32 | 1.2 | 1.14 | 1.07 | 1.05 | 1.04 | 69–77 |
| 26–30 | 1.22 | 1.13 | 1.10 | 1.04 | 1.03 | 1.02 | 78–86 |
| 31–35 | 1.12 | 1.07 | 1.05 | 1.02 | 1.02 | 1.01 | 87–95 |
| 36–40 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 96–104 |
| 41–45 | 0.87 | 0.93 | 0.95 | 0.98 | 0.98 | 0.99 | 105–113 |
| 46–50 | 0.71 | 0.85 | 0.89 | 0.95 | 0.97 | 0.98 | 114–122 |
| 51–55 | 0.50 | 0.76 | 0.84 | 0.93 | 0.95 | 0.96 | 123–131 |
| 56–60 | — | 0.65 | 0.77 | 0.90 | 0.94 | 0.95 | 132–140 |
| 61–65 | — | 0.53 | 0.71 | 0.88 | 0.92 | 0.94 | 141–149 |
| 66–70 | — | 0.38 | 0.63 | 0.85 | 0.90 | 0.93 | 150–158 |
| 71–75 | — | — | 0.55 | 0.83 | 0.88 | 0.91 | 159–167 |
| 76–80 | — | — | 0.45 | 0.80 | 0.87 | 0.90 | 168–176 |
| 81–90 | — | — | — | 0.74 | 0.83 | 0.87 | 177–194 |
| 91–100 | — | — | — | 0.67 | 0.79 | 0.85 | 195–212 |
| 101–110 | — | — | — | 0.60 | 0.75 | 0.82 | 213–230 |
| 111–120 | — | — | — | 0.52 | 0.71 | 0.79 | 231–248 |
| 121–130 | — | — | — | 0.43 | 0.66 | 0.76 | 249–266 |
| 131–140 | — | — | — | 0.30 | 0.61 | 0.72 | 267–284 |
| 141–160 | — | — | — | — | 0.50 | 0.65 | 285–320 |
| 161–180 | — | — | — | — | 0.35 | 0.58 | 321–356 |
| 181–200 | — | — | — | — | — | 0.49 | 357–392 |
| 201–225 | — | — | — | — | — | 0.35 | 393–437 |