Unshielded Tray Cable
UL Type TC, 600V, 90°C dry / 75°C wet rated - Lead Free

Composite Conductors with Bare Ground Type THHN/THWN
Composite – 4 Control Conductors with 3 Power Conductors and 1 Bare Ground

Part Number	Control Size	Insulation Thickness PVC/Nylon		Power Size	Insulation Thickness PVC/Nylon		Ground Size	Jacket Thickness		Nominal Diameter over Jacket		Approximate Net Cable Weight		Control Ampacity	Power Ampacity
	AWG	mils	mm	AWG	mils	mm	AWG	mils	mm	inches	mm	lb/kft	kg/km	amps	amps
684126	12	15/4	.38/.10	10	20/4	.51/.10	10	60	1.52	.585	14.86	320	476	21	28
627042	12	15/4	.38/.10	8	30/5	.76/.13	8	60	1.52	.675	17.15	405	603	21	55
627810	12	15/4	.38/.10	6	30/5	.76/.13	8	60	1.52	.720	18.29	530	789	21	75
697680	12	15/4	.38/.10	4	40/6	1.02/.15	6	80	2.03	.890	22.61	760	1131	21	95
682773	12	15/4	.38/.10	2	40/6	1.02/.15	6	80	2.03	1.015	25.78	1061	1579	21	130

Bend Radius: 5 x overall diameter installed
8 x overall diameter during installation pull-in.

Notes:

Dimensions and weights shown are nominal values. They are subject to standard industry tolerances.

Cables with different conductor counts and bare or insulated grounds are also available.

Ampacities are in accordance with NEC Table 310.16 for conductors in a raceway or direct buried at 30°C ambient temperature and 90°C rated conductors. Ampacities for cables having more than three conductors have been derated per NEC Table 310.15(B)(2)(a).

The overcurrent protection shall not exceed 15 amperes for 14 AWG, 20 amperes for 12 AWG, and 30 amperes for 10 AWG copper conductors after any correction factors for ambient temperature and numbers of conductors have been applied per NEC Article 240.4(D).

For correction factors to different ambient temperatures and ampacities for different conductor temperature ratings see NEC Table 310.16.

Color codes:

- Power and Control conductors are black with number coding per Method 4 of ICEA S-73-532.

Unshielded Tray Cable – DuPont Construction* - *(continued)*
UL Type TC, 600V, 90°C dry / 75°C wet rated - Lead Free

Composite Conductors with Bare Ground Type THHN/THWN
Composite – 4 Control Conductors with 3 Power Conductors and 1 Bare Ground

Part Number	Control Size	Insulation Thickness PVC/Nylon		Power Size	Insulation Thickness PVC/Nylon		Ground Size	Jacket Thickness		Nominal Diameter over Jacket		Approximate Net Cable Weight		Control Ampacity	Power Ampacity
	AWG	mils	mm	AWG	mils	mm	AWG	mils	mm	inches	mm	lb/kft	kg/km	amps	amps
697813	14	45	1.14	12	45	1.14	12	60	1.52	0.515	13.08	220	328	17.5	21
697805	14	45	1.14	10	45	1.14	10	60	1.52	0.575	14.61	288	429	17.5	28

Bend Radius: 5 x overall diameter installed
8 x overall diameter during installation pull-in.

P. 16 & 17 Notes:
Dimensions and weights shown are nominal values. They are subject to standard industry tolerances.
(1) Ampacities are in accordance with NEC Table 310.16 for conductors in a raceway or direct buried at 30°C ambient temperature and 90°C rated conductors. Ampacities for cables having more than three conductors have been derated per NEC Table 310.15(B)(2)(a).
(2) Where the 4th conductor is the neutral of a balanced 3 phase system.
(3) For load diversity of 50%, refer to NEC Table B.310.11.
(4) For correction factors to different ambient temperatures and ampacitities for different conductor temperature ratings see NEC Table 310.16.
NEC 240.4(D) requires that overcurrent protection not exceed 15 amperes for 14 AWG, 20 amperes for 12 AWG and 30 amperes for 10 AWG copper conductors after any correction factors for ambient temperature and number of conductors have been applied per NEC Article 240.4(D) through (G).

*Dupont construction means:
- Color code black insulation with white print – numbered conductors (Method 4).
- Nylon fillers – where applicable
- Mylar tape around core