Contact
Industrial Cables
Phone: 866-663-9267
USA.IndustrialCable@nexans.com

ULTREX® XL TC - Unshielded 3 or 4 Conductors With Ground

ULTREX® XL TC - Unshielded 3 Conductors with Ground

Part Number: ULTREX® XL TC - Unshielded 3 Conductors with Ground

Type XHHW-2: UL Type TC, 600 V, 90ºC dry / wet rated - LEAD FREE - Exposed Run (ER) Rated

Description

Applications

Nexans 600 V Ultrex XL Tray Cables are listed as type TC under UL 1277 Electrical Power and Control Cables. These cables may be installed in wet or dry locations; in cable trays, raceways and open air; and are suitable for exposure to weather, direct burial and for Class I, Div. 2 (also Zone 2) and Class II, Div. 2 hazardous locations per NEC.

Cables with 3 or more conductors are UL listed for exposed runs (ER) when installed in accordance with NEC Article 336.10(7).

Construction

Conductor:
Bare, annealed copper conforming to ASTM B3 and Class B stranded in accordance with ASTM B8, from #14 AWG to 1000 kcmil.

Insulation:
Flame-retardant cross-linked polyethylene meeting the requirements for XHHW-2 per UL 44 and the requirements of ICEA S-95-658 for XLPE insulation as standard. Sizes #14 AWG to #8 AWG are VW-1, and sizes #6 AWG and larger are non-VW-1.

Assembly:
Conductors are cabled in concentric layers with interstices filled with suitable fillers, as required. A binder tape of synthetic material assembles the core in a tight circular configuration. Ground wires are sized as required by UL 1277. Sizes #14 AWG to #6 AWG have an insulated green ground wire. Sizes #4 AWG and larger have a bare ground wire.

Jacket:
UL listed sunlight and moisture resistant, sequentially length marked, black polyvinyl chloride (PVC) material meeting the requirements of UL 1277.

Standards

National ICEA S-73-532;
ICEA S-95-658; UL 1277; UL 44

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Contact
Industrial Cables
Phone: 866-663-9267
USA.IndustrialCable@nexans.com

ULTREX® XL TC - Unshielded 3 or 4 Conductors With Ground

ULTREX® XL TC - Unshielded 3 Conductors with Ground

Part Number: ULTREX® XL TC - Unshielded 3 Conductors with Ground

Characteristics

Construction characteristics

Number of conductors	3

ULTREX® XL - UNSHIELDED TRAY CABLE - 3 CONDUCTORS WITH GROUND

Type XHHW-2: UL Type TC, 600 V, 90°C dry / wet rated - LEAD FREE - Exposed Run (ER) Rated

Part Number	Cond. Size	Ground Size	Insulation Thickness		Jacket Thickness		Nominal Diameter over Jacket		Approximate Net Cable Weight		Ampacity(1)
	(AWG/ kcmil)	(AWG)	mils	mm	mils	mm	inches	mm	Lb/kft	kg/km	amps
611517	12	12	30	0.76	45	1.14	0.465	11.82	145	216	30*
295196	10	10	30	0.76	45	1.14	0.524	13.30	205	305	45*
306829	8	10	45	1.14	60	1.52	0.665	16.89	323	480	55
306845	6	8	45	1.14	60	1.52	0.769	19.53	451	672	75
306860	4	8	45	1.14	60	1.52	0.818	20.78	595	886	95
------	3	6	45	1.14	80	2.03	0.917	23.28	824	1226	110
306886	2	6	45	1.14	80	2.03	0.989	25.12	922	1372	130
------	1	6	55	1.40	80	2.03	1.093	27.75	1200	1786	150
306894	1/0	6	55	1.40	80	2.03	1.181	30.00	1358	2021	170
306910	2/0	6	55	1.40	80	2.03	1.273	32.33	1663	2474	195
------	3/0	4	55	1.40	80	2.03	1.405	35.59	2156	3209	225
306928	4/0	4	55	1.40	80	2.03	1.541	39.13	2506	3729	260
619114	250	4	65	1.65	80	2.03	1.634	41.51	2941	4376	290
------	300	3	65	1.65	110	2.79	1.800	45.72	3394	5050	320
619338	350	3	65	1.65	110	2.79	1.934	49.12	4103	6105	350
------	400	3	65	1.65	110	2.79	2.021	51.33	4818	7169	380
619148	500	2	65	1.65	110	2.79	2.190	55.63	5670	8438	430

Bend Radius: 5 x overall diameter installed (up to 2.0") / 6 x overall diameter installed (over 2.0")
8 x overall diameter during installation pull-in.

Notes:
Dimensions and weights shown are nominal values. They are subject to standard industry tolerances.
Cables with different conductor counts are also available.

(1) Ampacities are in accordance with Table 310.16 of NEC for conductors in raceway or direct buried at 30°C ambient temperature and 90°C conductor temperature.
For correction factors for different ambient temperatures and ampacities at different conductor temperatures see Table 310.16 of NEC.
*** NEC 240.4(D) requires that over current protection not exceed 20 amperes for 12 AWG copper conductors and 30 amperes for 10 AWG copper conductors. Exceptions to this may be covered in NEC 240.4(E) through (G).**

Selling delivery information

OPTIONS

The following constructions can be provided on special orders:

* Aluminum alloy conductors in sizes #12 AWG to 1000 kcmil
* Different conductor identification methods
* Different conductor counts
* Shields of aluminum/mylar tape (with or without a tinned copper drain wire)
* Oil Resistant I or Oil Resistant II jackets

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Contact
Industrial Cables
Phone: 866-663-9267
USA.IndustrialCable@nexans.com

ULTREX® XL TC - Unshielded 3 or 4 Conductors With Ground

* CPE jacket
* Composite constructions of different sized conductors.

* Use in Hazardous locations:
Please note that no investigation of these cables has been performed regarding the transmission of gases or vapors through the core. When these cables are used in hazardous locations they should be sealed properly as required by the NEC.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.