OLFLEX® 190/ 190 CY

Extremely Oil Resistant Flexible Control Cable
Now with UL MTW to Comply with NFPA 79 2007

OLFLEX® 190 multi-conductor cable has the highest oil, coolant and solvent resistant PVC jacket for control and power applications in an industrial environment. OLFLEX® 190 is designed for use in all electrical equipment in dry, damp and wet conditions.

Recommended Applications:
For Machinery: CNC machining centers, Grinding machines, Bottling equipment, Conveyors, Processing equipment, Assembly lines and Control panels

Application Advantages:
- Extremely oil resistant (Oil Res I & II)
- Meets NFPA 79 2007 machinery wiring standard
- Excellent industrial power and control cable
- Very flexible and number coded for easy routing and terminating
- Round jacket for optimal seal with a SKINTOP® Strain Relief

OLFLEX® 190 Construction:
Finely stranded bare copper conductors; specially blended PVC/ nylon insulation; non-wicking fillers; dry lubricant; specially formulated oil resistant gray PVC jacket.



OLFLEX® 190 CY Construction:
Finely stranded bare copper conductors; specially blended PVC/ nylon insulation; dry lubricant; non-wicking fillers; gray inner PVC jacket; tinned copper braid (85% coverage); specially formulated oil resistant gray PVC jacket.



Also available with the following options:
- Blue or red insulation
- Black overall jacket

Cable Attributes, See Page 653


Oil Resistance: OR-04


Flame Resistance: FR-02


Motion Type: FL-02


Mechanical Properties: MP-02

Availability:


Standard put-ups are 100ft, 250ft, 500ft, and 1,000ft. Bulk reels can be cut to length.

Complete the installation with:


SKINTOP® Strain Relief: Page 486


EPIC® Connectors: Page 251


OLFLEX® Tubing: Page 546


SKINTOP® MS-SC Page 486

Technical Data:

Minimum Bending Radius		Color Code:	Black with white numbers, plus green/yellow ground, 2 conductor cable does not include ground
- for installation:	4 x cable diameter		
- with shield:	6 x cable diameter		
Temperature Range:		Approvals:	
- for flexible use:	-5°C to +90°C	UL:	- AWM 2587 + 21098 - Type MTW Oil Res I & II - UL 758 80°C - Conforms to NFPA 79 2007
- for stationary use:	-40°C to +90°C	CSA:	- AWM I/II A/B FT 1 - CSA C22.2 210.2 Sec. 7.6.12.1, 8.8.8
Nominal Voltage:	600V	Additional:	- Impact and Crush tests to UL 1277, excluding 20 AWG designs
Test Voltage:	3000V		
Conductor Stranding:	Class 5		

OLFLEX® 190/ 190 CY

Extremely Oil Resistant Flexible Control Cable

Now with UL MTW to Comply with NFPA 79 2007

OLFLEX® 190: Oil Resistant Flexible Control Cable

Part Number	Number of Conductors includes ground	Nominal Outer Diameter inches	mm	Copper Weight lbs/mft	Approx. Weight lbs/mft	kg/km
20 AWG (10/30) 0.50 mm²						
602002	2	.253	6.4	7	39	58
602003	3	.265	6.7	10	41	61
602004	4	.285	7.2	13	51	76
602005	5	.308	7.8	17	60	89
602007	7	.331	8.4	23	81	120
602009	9	.409	10.6	30	100	149
602012	12	.421	10.7	40	168	250
602018	18	.487	12.4	60	198	295
602025	25	.586	14.9	83	243	361
18 AWG (19/30) 1.00 mm²						
601802	2	.277	7.0	13	42	63
601803	3	.291	7.4	19	44	66
601803NG	3	No Ground				
601804	4	.314	8.0	25	54	81
601805	5	.340	8.6	31	64	95
601807	7	.367	9.3	44	84	125
601809	9	.454	11.5	56	140	208
601812	12	.471	12.0	75	142	211
601818	18	.579	14.7	113	207	309
601825	25	.656	16.4	156	277	413
601834	34	.953	24.2	213	494	735
601841	41	1.043	26.5	256	558	830
601850	50	1.110	28.2	313	697	1038
16 AWG (28/30) 1.50 mm²						
601602	2	.303	7.7	18	57	85
601603	3	.319	8.1	27	61	91
601604	4	.345	8.8	36	75	112
601605	5	.375	9.5	45	91	136
601607	7	.406	10.3	64	120	179
601609	9	.509	12.9	82	180	268
601612	12	.557	14.2	109	210	313
601618	18	.644	16.4	163	298	444
601625	25	.733	18.6	227	416	620
601634	34	1.044	26.5	309	946	1408
601641	41	1.144	29.1	372	1230	1830
601650	50	1.219	30.1	454	1500	2232
601661	61	1.294	32.9	554	1800	2679
14 AWG (46/30) 2.50 mm²						
601402	2	.337	8.6	30	87	130
601403	3	.356	9.0	45	93	138
601404	4	.386	9.8	60	122	182
601405	5	.421	10.7	75	145	216
601407	7	.457	11.6	105	192	286
601409	9	.609	15.5	135	271	403
601412	12	.628	16.0	179	402	598
601418	18	.729	18.5	269	575	855
601425	25	.872	22.2	374	860	1280
12 AWG (56/.0117) 4 mm²						
601203	3	.417	10.6	75	156	232
601204	4	.454	11.5	100	198	295
601205	5	.497	12.6	125	238	354
601207	7	.573	14.6	176	363	540
601211	11	.745	18.9	276	398	592
10 AWG (82/.0117) 6 mm²						
601003	3	.492	12.5	110	222	330
601004	4	.570	14.5	147	267	398
601005	5	.623	15.8	184	321	479
8 AWG (72/26) 10 mm²						
600804	4	.695	17.7	245	435	648
600805	5	.764	19.4	306	525	782
6 AWG (115/26) 16 mm²						
600604	4	.870	22.1	393	698	1040
600605	5	.955	24.3	491	842	1254
4 AWG (182/.0157) 25 mm²						
600404	4	1.184	30.1	541	1007	1501
600405	5	1.306	33.2	676	1244	1853
2 AWG (280/.0157) 35 mm²						
600204	4	1.316	33.4	853	1422	2119
600205	5	1.454	36.9	1066	1749	2606

OLFLEX® 190 CY: Shielded Oil Resistant Flexible Control Cable

Part Number	Number of Conductors includes ground	Nominal Outer Diameter inches	mm	Copper Weight lbs/mft	Approx. Weight lbs/mft	kg/km
20 AWG (10/30) 0.50 mm²						
602002CY	2	.329	8.4	23	65	97
602003CY	3	.341	8.7	27	82	122
602007CY	7	.407	10.3	48	112	167
602012CY	12	.497	12.6	71	180	268
602025CY	25	.678	17.2	137	296	441
18 AWG (19/30) 1.00 mm²						
601802CY	2	.353	9.0	26	75	112
601803CY	3	.367	9.3	34	82	122
601804CY	4	.390	9.9	46	105	157
601805CY	5	.416	10.6	54	123	183
601807CY	7	.443	11.3	68	139	207
601812CY	12	.554	14.1	107	230	342
601818CY	18	.678	17.2	162	317	472
601825CY	25	.764	19.4	213	435	648
16 AWG (28/30) 1.50 mm²						
601603CY	3	.395	10.0	48	111	166
601604CY	4	.421	10.7	61	128	191
601605CY	5	.451	11.5	70	149	222
601607CY	7	.482	12.2	91	181	270
601612CY	12	.656	16.7	156	311	464
601618CY	18	.743	18.9	219	456	679
601625CY	25	.897	22.8	292	639	952
14 AWG (46/30) 2.50 mm²						
601403CY	3	.432	11.0	69	148	221
601404CY	4	.462	11.7	86	181	269
601405CY	5	.497	12.6	106	218	325
601407CY	7	.572	14.5	136	283	421
601412CY	12	.736	18.7	226	516	769
601418CY	18	.905	23.0	334	740	1102
12 AWG (56/.0117) 4 mm²						
601203CY	3	.500	12.7	115	226	337
601204CY	4	.585	14.9	146	310	462
601205CY	5	.628	15.9	172	359	535
601207CY	7	.672	17.1	225	493	735
10 AWG (82/.0117) 6 mm²						
601003CY	3	.623	15.8	155	311	463
601004CY	4	.669	17.0	196	385	574
601005CY	5	.731	18.6	238	474	706
601007CY	7	.786	20.0	316	638	950
8 AWG (72/26) 10 mm²						
600804CY	4	.803	20.4	305	569	848
6 AWG (115/26) 16 mm²						
600604CY	4	.994	25.2	467	1114	1660
4 AWG (182/.0157) 25 mm²						
600404CY	4	1.324	33.6	637	1266	1886
2 AWG (280/.0157) 35 mm²						
600204CY	4	1.468	37.3	969	2189	3261

*2 conductor cable does not include ground wire.