RG 11/U Type

Product Construction:

Conductors:
- Copper per ASTM B-3
- Copper-clad steel per ASTM B-869

Insulation/Core:
- Solid and foam polyethylene (PE) designs

Shield:
- Tinned, bare copper or aluminum braid
- Flexfoil® shield

Jacket:
- Premium PVC compound or PE compound

Packaging:
- Please contact Customer Service for packaging and color options

Applications:
- Suitable for RF signal transmission
- Broadcast digital video
- MATV
- CATV†
- Drop cable
- HDTV
- CCTV
- See Coax Connector Cross Reference, pages 192-199

CATALOG NUMBER	AWG SIZE NOM. DCR	INSULATION MATERIAL		SHIELD COVERAGE NOM SHLD DCR	NOMINAL O.D.		NOMINAL CAPACITANCE		VELOCITY OF PROPAGATION, %	NOMINAL IMPEDANCE, Ω	NOMINAL ATTENUATION	
		INCHES	mm		INCHES	mm	pF/ft	pF/m			MHz	dB/100'
C1160 **RG 11/U Type** **JAN-C-17A Type**	18 Ga. (7/26) Tinned Copper 6.1 Ω/Mft.	Solid PE		95% Bare Copper Braid 1.2 Ω/Mft.	Black PVC		20.50	67.26	66	75	1 10 50 100 200 500 1000	0.20 0.70 1.30 2.00 2.90 4.70 7.10
		0.285	6.55		0.400	10.16						
C5011† **RG 11/U Type** **UL CL2, CATV, CM** **c(UL) CM**	14 Ga. Solid Bare Copper 2.5 Ω/Mft.	Foam PE		100% Flexfoil® +95% Bare Copper Braid 1.2 Ω/Mft.	Black PVC		16.20	53.15	85	75	1 10 50 100 200 500 1000 1450 1800 2200 3000	0.13 0.40 0.90 1.30 1.90 3.00 4.40 5.30 5.90 6.53 7.62
		0.280	7.11		0.395	10.03						
C5025 **RG 11/U Type**	14 Ga. Solid Copper-Clad Steel 11.4 Ω/Mft.	Foam PE		97% Bare Copper Braid 1.2 Ω/Mft.	Black PE		16.20	53.15	83	75	1 10 50 100 200 500 1000 1450 1800 2200 3000	0.30 0.70 1.00 1.50 2.20 3.70 5.30 6.38 7.11 7.86 9.18
		0.285	7.24		0.405	10.29						
C5029 **RG 11/U Type** **UL CL2, CM** **c(UL) CM**	14 Ga. Solid Copper-Clad Steel 11.4 Ω/Mft.	Foam PE		100% Flexfoil® Bonded +61% Tinned Copper Braid 3.0 Ω/Mft.	Black PVC		16.20	53.15	85	75	1 10 50 100 200 500 1000 1450 1800 2200 3000	0.30 0.70 0.90 1.30 1.90 3.00 4.40 5.30 5.90 6.53 7.62
		0.280	7.11		0.395	10.03						
C5034 **RG 11/U Type** **1354**	14 Ga. Solid Copper-Clad Steel 11.4 Ω/Mft.	Foam PE		100% Flexfoil® Bonded +40% Aluminum Braid 5.3 Ω/Mft.	Black PVC		16.20	53.15	85	75	1 10 50 100 200 500 1000	0.30 0.70 0.90 1.30 1.90 3.00 4.40
		0.280	7.11		0.395	10.03						

CAROL BRAND

General Cable

RG 11/U Type

Product Construction:

Conductor:
- Stranded or solid copper per ASTM B-3
- Copper-clad steel per ASTM B-869

Insulation/Core:
- Foam polyethylene (PE) design
- Foam fluoropolymer (FEP) design

Shield:
- Bare copper or aluminum braid
- Flexfoil® shield

Jacket:
- Premium fluoropolymer compound or premium polythylene (PE) compound

Packaging:
- Please contact Customer Service for packaging and color options

Applications:
- Suitable for RF signal transmission
- Broadcast/digital video
- MATV
- CATV
- Drop cable
- HDTV
- Direct burial
- See Coax Connector Cross Reference, pages 192-199

CATALOG NUMBER	AWG SIZE NOM. DCR	INSULATION MATERIAL		SHIELD COVERAGE NOM SHLD DCR	NOMINAL O.D.		NOMINAL CAPACITANCE		VELOCITY OF PROPAGATION, %	NOMINAL IMPEDANCE, Ω	NOMINAL ATTENUATION	
		INCHES	mm		INCHES	mm	pF/ft	pF/m			MHz	dB/100'
C3529 **RG 11/U Type** **Quad-Shield** **Plenum** **UL CL2P, CMP** **c(UL) CMP** **CATVP** 	14 Ga. Solid Copper-Clad Steel 11.4 Ω/Mft.	Fluoropolymer		(2) 100% Flexfoil® (1) 60% (2) 40% Aluminum Braids 3.4 Ω/Mft.	PVDF Jacket		16.00	52.50	82	75	1 10 50 100 200 500 1000 1450 1800 2200	0.15 0.47 1.09 1.49 2.35 3.94 6.19 7.45 8.30 9.18
		0.280	7.11		0.372	9.45						
C5043 **RG 11/U Type** **MoistureGuard™** **Direct Burial, Flooded**  	14 Ga. Solid Copper-Clad Steel 11.4 Ω/Mft.	Foam PE		100% Flexfoil® Bonded +60% Aluminum Braid w/water block 5.3 Ω/Mft.	Black PE		16.20	53.15	85	75	1 10 50 100 200 500 1000	0.30 0.70 0.90 1.30 1.90 3.00 4.40
		0.280	7.11		0.395	10.03						

RG 11/U Type

Product Construction:

Conductor:
- Copper per ASTM B-3
- Copper-clad steel per ASTM B-3

Insulation/Core:
- Foam polyethylene (PE) design
- Foam fluoropolymer (FEP) design

Shield:
- Tinned, bare copper or aluminum braid
- Flexfoil® shield

Jacket:
- Premium PVC compound, Flexguard® or PE compound

Packaging:
- Please contact Customer Service for packaging and color options

Applications:
- Suitable for RF signal transmission
- Broadcast digital video
- MATV
- CATV
- Drop cable
- HDTV
- Direct burial
- See Coax Connector Cross Reference, pages 192-199

CATALOG NUMBER	AWG SIZE NOM. DCR	INSULATION MATERIAL		SHIELD COVERAGE NOM SHLD DCR	NOMINAL O.D.		NOMINAL CAPACITANCE		VELOCITY OF PROPAGATION, %	NOMINAL IMPEDANCE, Ω	NOMINAL ATTENUATION	
		INCHES	mm		INCHES	mm	pF/ft	pF/m			MHz	dB/100'
C5039 **RG 11/U Type** **UL CL2, CATV, CM** **CSA CMG** **1354**	14 Ga. Solid Copper-Clad Steel 11.4 Ω/Mft.	Foam PE 0.280	7.11	100% Flexfoil® Bonded +60% Aluminum Braid 4.6 Ω/Mft.	Black PVC 0.395	10.03	16.20	53.15	85	75	1 10 50 100 200 500 1000 1450 1800 2200 3000	0.30 0.70 0.90 1.30 1.90 3.00 4.40 5.30 5.90 6.53 7.62
C5044 **RG 11/U Type** **Quad-Shield** **UL CL2, CATV, CM** **CSA CMG** **1354**	14 Ga. Solid Copper-Clad Steel 11.4 Ω/Mft.	Foam PE 0.280	7.11	(2) 100% Flexfoil® 1st Bonded (1) 61% (2) 40% Aluminum Braids 3.4 Ω/Mft.	Black PVC 0.405	10.29	16.20	53.15	85	75	1 10 50 100 200 500 1000 1450 1800 2200 3000	0.30 0.70 0.90 1.30 1.90 3.00 4.40 5.30 5.90 6.53 7.62
C3528 **RG 11/U Type** **Plenum** **UL CL2P, CMP** **c(UL) CMP** **CATVP**	14 Ga. Solid Copper-Clad Steel 11.4 Ω/Mft.	Fluoropolymer 0.280	7.11	100% Flexfoil® +60% Aluminum Braids 4.6 Ω/Mft.	PVDF Jacket 0.351	8.92	16.00	52.50	82	75	1 10 50 100 200 500 1000 1450 1800 2200	0.15 0.47 1.09 1.49 2.35 3.94 6.19 7.45 8.30 9.18

RG 11/U Type Serial Digital Interface (SDI) Precision Cable

Extended-Distance, 75 Ohm High-End Coaxial Cables for Exacting Video, Analog & Digital Applications

Product Construction:

Conductor:
- Copper per ASTM B-3

Insulation/Core:
- Foam polyethylene (PE) design
- Foam fluoropolymer (FEP) design

Shield:
- Bare copper or tinned copper
- Flexfoil® shield

Jacket:
- Premium PVC compound or fluoropolymer

Packaging:
- Please contact Customer Service for packaging and color options

Applications:
- Suitable for RF signal transmission
- Broadcast-grade Serial Digital Interface (SDI)
- Analog/digital video
- MATV
- CATV
- CCTV†
- Drop cable
- HDTV
- See Coax Connector Cross Reference, pages 192-199

CATALOG NUMBER	AWG SIZE NOM. DCR	INSULATION MATERIAL		SHIELD COVERAGE NOM SHLD DCR	NOMINAL O.D.		NOMINAL CAPACITANCE		VELOCITY OF PROPAGATION, %	NOMINAL IMPEDANCE, Ω	NOMINAL ATTENUATION	
		INCHES	mm		INCHES	mm	pF/ft	pF/m			MHz	dB/100'
395058† RG 11/U Type UL CM c(UL) CMG 	14 Ga. Solid Bare Copper 2.6 Ω/Mft.	Foam PE		95% Bare Copper Braid 1.2 Ω/Mft.	Flame-Retardant PVC		16.20	52.50	84	75	1 10 50 100 200 400 540 1000 2250 3000	0.17 0.35 0.90 1.30 1.90 2.90 3.37 4.59 6.88 7.94
		0.285	7.24		0.405	10.29						
395029 RG 11/U Type UL CMR c(UL) CMG 	14 Ga. Solid Bare Copper 2.6 Ω/Mft.	Foam PE		Dual Flexfoil® + 95% Tinned Copper Braid 1.5 Ω/Mft.	Flame-Retardant PVC		16.20	53.10	83	75	1 3.6 135 270 540 1500 2250 3000	0.15 0.28 1.62 2.31 3.29 5.60 6.94 8.10
		0.280	7.11		0.405	10.29						
495015† RG 11/U Type UL CMP c(UL) CMP 	14 Ga. Solid Bare Copper 2.6 Ω/Mft.	Fluoropolymer		95% Bare Copper Braid 1.2 Ω/Mft.	PVDF		16.20	52.50	84	75	1 10 50 100 200 400 540 1000 2250 3000	0.17 0.35 0.90 1.30 1.90 2.90 3.37 4.59 6.88 7.94
		0.280	7.11		0.351	8.92						
495016† RG 11/U Type UL CMP c(UL) CMP 	14 Ga. Solid Bare Copper 2.6 Ω/Mft.	Fluoropolymer		Dual Flexfoil® + 60% AL Braid 3.0 Ω/Mft.	PVDF		16.20	53.10	84	75	1 10 50 100 200 400 540 1000 2250 3000	0.15 0.40 1.00 1.50 2.20 3.30 3.83 5.22 7.83 9.04
		0.280	7.11		0.351	8.92						
495027 RG 11/U Type UL CMP c(UL) CMP 	14 Ga. Solid Bare Copper 2.6 Ω/Mft.	Fluoropolymer		Dual Flexfoil® + 95% Tinned Copper Braid Shield 1.5 Ω/Mft.	PVDF		16.20	53.10	84	75	1 3.6 135 270 540 1500 2250 3000	0.12 0.24 1.63 2.49 3.89 7.88 10.61 12.35
		0.280	7.11		0.348	8.84						