
Type SJT

105°C 300 Volt UL/CSA Portable Cord



TYPE SJT — 300 VOLT — UL/CSA

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	NOMINAL INS. THICKNESS		NOMINAL O.D.		CURRENT AMPS†	APPROX. NET WEIGHT LBS/M'(S)	STD. CTN.
				INCHES	mm	INCHES	mm			
86112*	2	18	16/30	0.030	0.76	0.285	7.24	10	45	1000'
86113	3	18	16/30	0.030	0.76	0.310	7.87	10	55	1000'

* Non-stock item; minimum quantity purchase required.
† Green conductor for grounding only. Ampacities based on NEC table 400.5(A).
(S) Actual shipping weight may vary.

Product Construction:

Conductors:
- 18 AWG fully annealed stranded bare copper per ASTM B-174

Insulation:
- Premium-grade, color-coded PVC
- Color code: See chart below

Jacket:
- Polyvinylchloride (PVC), white
- Temperature range: -20°C to +105°C

Jacket Marking:
- (SIZE) (mm^2) 105°C SJT E# (UL) --- CSA LL# FT-2 RoHS MADE IN USA 300V

Applications:
- For use in most hospital equipment

Features:
- Resists:
  - Acids
  - Alkalies
  - Ozone

Industry Approvals:
- UL Listed
- CSA Certified
- RoHS Compliant

Packaging:
- 250' (76.2 m)
- Other put-ups available on special order

COLOR CODE CHART

NO. OF CONDUCTORS	COLOR
2	Black, White
3	Black, White, Green