PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

Seoprene® 300V SJEOOW

Construction Parameters:

CONDUCTOR: 18 AWG - 10 AWG Class K stranded bare copper per ASTM B-174
INSULATION: TPE
JACKET: TPE
COLOR: Black (Other colors available upon request)
COLOR: *White

PRINT LEGEND: CCI SEOPRENE 105C XX AWG (X.XX mm^2) X/C SJEOOW E54864 (UL) 300V -50C TO 105C -- CSA LL39753 SJTOOW (TPE) 300V -50C TO 105C FT2 WATER RESISTANT

INDENT P-241-3-MSHA

***INDENT LEGEND:** CCI SEOPRENE 105 18 AWG (0.82mm2) 4/C SJEOOW E54864 (PLANT ID CODE) (UL) 300V -50C TO 105C -- CSA LL39753 SJTOOW(TPE) 300V -50C TO 105C FT2 WATER RESISTANT P-241-3-MSHA

Ink Jet Legend: XX/XX/XX (MONTH/DAY/YEAR) HH:MM (HOUR/MINUTE)

PHYSICAL PROPERTIES:

TEMPERATURE RANGE -50°C to 105°C
WATER RESISTANT: Yes

ELECTRICAL PROPERTIES:

VOLTAGE RATING: 300V rms, Max

Industry Approvals:

- o UL Standard 62
- o CSA Standard C22.2 No. 49
- o NEC Article 501.140 Class I Div. 2
- o NEC Article 400
- o Federal Spec JC580
- o Passes CSA FT2 Flame Test
- o MSHA
- o EPA 40 CFR, Part 26, Subpart C, heavy metals per Table 1, TCLP method

Part Number	AWG	No. Cond.	Stranding	Insulation Wall, Nom.		O.D., Nom.		Net Weight		Amps*	Nom. DCR Ω/1M'	Color Code
				Inches	mm	Inches	mm	Lb./kft.	kg/km			
23225	**18**	**2**	16/30	0.030	0.76	0.285	7.24	37	55	10	6.59	BLACK, WHITE
23325	**18**	**3**	16/30	0.030	0.76	0.308	7.82	49	73	10	6.59	BLACK, WHITE, RED
23425	**18**	**4**	16/30	0.030	0.76	0.328	8.33	59	88	7	6.59	BLACK, WHITE, RED, GREEN
23226	**16**	**2**	26/30	0.030	0.76	0.310	7.87	46	68	13	4.05	BLACK, WHITE
23326	**16**	**3**	26/30	0.030	0.76	0.328	8.33	59	88	13	4.05	BLACK, WHITE, RED
23426	**16**	**4**	26/30	0.030	0.76	0.353	8.97	73	109	10	4.05	BLACK, WHITE, RED, GREEN
23227	**14**	**2**	41/30	0.030	0.76	0.340	8.64	60	89	18	2.55	BLACK, WHITE
23327	**14**	**3**	41/30	0.030	0.76	0.363	9.22	79	118	18	2.55	BLACK, WHITE, RED
23427	**14**	**4**	41/30	0.030	0.76	0.393	9.98	98	146	15	2.55	BLACK, WHITE, RED, GREEN
23228	**12**	**2**	65/30	0.030	0.76	0.410	10.41	90	134	25	1.61	BLACK, WHITE
23328	**12**	**3**	65/30	0.030	0.76	0.428	10.87	116	173	25	1.61	BLACK, WHITE, RED
23428	**12**	**4**	65/30	0.030	0.76	0.468	11.89	150	223	20	1.61	BLACK, WHITE, RED, GREEN
23229	**10**	**2**	104/30	0.045	1.14	0.545	13.84	155	231	30	0.98	BLACK, WHITE
23329	**10**	**3**	104/30	0.045	1.14	0.573	14.55	200	298	30	0.98	BLACK, WHITE, RED
23429	**10**	**4**	104/30	0.045	1.14	0.628	15.95	257	382	25	0.98	BLACK, WHITE, RED, GREEN

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.
**** Ampacity based on NEC Table 400.5(A) and CEC Table 12.***

This product complies with European Directive 2011/65/EU (RoHS-2)
The customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: January 8, 2014

© 2014 CCI