100 Bradley Parkway
Blauvelt, NY 10913
Toll-Free (800) 947-3911
Fax (845) 353-9315

SPECIFICATION SHEET

COMPANY: OMNI DATE: 01/23/12

SPECIFICATION SHEET

TWC PART NUMBER: R41076.1/1880AT8M/CMR/CL3R

CONSTRUCTION	:	18AWG 19/0092 TINNED COPPER 8 CONDUCTORS. OVERALL FOIL.
COLOR CODE	:	CC#17: BLACK,RED,WHITE,GREEN,BROWN,BLUE,ORANGE,YELLOW
INSULATION	:	0.017 Inch, 75C PVC
SHIELD/DRAIN	:	OVERALL FOIL SHIELD, FOIL-OUT (BLUE IN). 20AWG 7/0121 TC.
CAPACITANCE	:	51 pF/ft Nom.
VEL OF PROP	:	45.6%
IMPEDANCE	:	44 OHMS
RESISTANCE	:	6.92 OHMS D.C. PER 1000 FT @ 68 DEG. F
TEMP/VOLTAGE	:	/300V
JACKET	:	CHROME GRAY, 0.037 Inch, PVC -- 0.339 Nom OD
CABLE WT	:	84.7 Lb/1000Ft Approx (EXCLUDING REEL OR BOX)
PRINT LEGEND	:	E118871 CMR/CL3R/FPLR 18AWG (UL) c(UL) CMG OR AWM STYLE 2598 300V MADE IN USA
UL	:	CMR/CL3R
MISC	:	MADE IN USA

+/- 10% Manufacturing tolerance
* On non-standard product, customer agrees to accept all lengths manufactured

APPROVED BY

Tappan Wire & Cable Inc. provides information and specifications on an “as is” basis. Information in specifications described herein are subject to error and/or omission, and subject to change without notice. Although we make all efforts possible to ensure the accuracy and timeliness of the information, Tappan Wire & Cable, will not be held liable for any damages whatsoever, even if advised of the possibility of such damages, arising from the use, or inability to use, the information or specifications herein. Please refer to our “Website Use Policy”, listed on our website, www.tappanwire.com, under the Sales Support Section for full details, or contact your Tappan representative.