
OMNICABLE

(800) 292-OMNI

PVC/Nylon Insulation
NEC Type MC
90°C - 600 Volt - UL Listed



Conductor:
- Annealed copper, class B strand per ASTM B-3 & B-8

Insulation:
- Thermoset, low smoke zero halogen silicone rubber

Circuit Identification:
- Printed numbers per ICEA Method 4

Inner Jacket:
- Thermoset, low smoke zero halogen silicone rubber

Armor:
- Continuously welded and corrugated copper

Outer Jacket (optional):
- Black Low Smoke, zero halogen polyolefin

Features:
- 2-hour fire rating per UL 2196
- Low smoke, Halogen free design
- Simple to terminate with commercially available brass MC connectors
- Printed number coding allows for easy circuit identification
- Uses conventional stripping tools
- Available in long lengths
- Welded armor forms an impervious barrier
- Armor is impact & crush resistant
- Fire-rated splice available (FHIT 120)

Applications:
- Emergency tunnel ventilation
- Emergency tunnel lighting
- Fire pump feeders
- Emergency generator feeders

Standards:
- UL listed, NEC Type MC in accordance with UL Standard 1569
- 2 hour fire rated per UL standard 2196 following ASTM E119 (1,850°F with water hose stream)
- Electrical Circuit Integrity Systems (FHIT) """" System No. 120 of the UL Fire Resistance Directory
- Meets and exceeds fire rated cable requirements in NFPA 130 for Transit applications
- Meets and exceeds cable requirements in NFPA 502 for Tunnel applications
- Exceeds NEC Article 695 & 700 fire endurance requirements
- Rated FT-4 / IEEE 1202 Vertical Flame test; -ST1, limited smoke
- For use in wet locations to 90°C
- Armored with copper sheath that exceeds the NEC requirement for equipment grounding conductor
- Complies with NFPA 130 and 502 total smoke released and low toxicity

Part #	AWG Size	No. of Cond.	Nom. Core Diameter	Nom. Armor Diameter	Nom. O.D.	Lbs./M?
HVM1402	14	2	.47"	.78"	.88	450
HVM1403	14	3	.50"	.82"	.92	510
HVM1404	14	4	.57"	.89"	.99	580
HVM1202	12	2	.51"	.82"	.92	500
HVM1203	12	3	.56"	.89"	.99	590
HVM1204	12	4	.62"	.94"	1.04	670
HVM1002	10	2	.58"	.89"	.99	570
HVM1003	10	3	.61"	.94"	1.04	670
HVM1004	10	4	.67"	1.00"	1.10	750
HVM0803	8	3	.72"	1.04"	1.14	820
HVM0804	8	4	.80"	1.16"	1.26	960
HVM0603	6	3	.80"	1.16"	1.26	1000
HVM0604	6	4	.89"	1.22"	1.32	1160
HVM0403	4	3	.91"	1.24"	1.34	1140
HVM0404	4	4	1.01"	1.35"	1.45	1480
HVM0303	3	3	.97"	1.30"	1.40	1410
HVM0304	3	4	1.07"	1.40"	1.50	1700
HVM0203	2	3	1.04"	1.38"	1.48	1600
HVM0204	2	4	1.15"	1.50"	1.60	1940
HVM0103	1	3	1.20"	1.59"	1.69	1990
HVM0104	1	4	1.34"	1.73"	1.85	2550
HVM1/001	1/0	1	.65"	1.00"	1.10	790
HVM1/001	1/0	3	1.29"	1.67"	1.79	2350
HVM1/001	1/0	4	1.43"	1.82"	1.94	2750
HVM2/001	2/0	1	.70"	1.04"	1.14	910
HVM2/001	2/0	3	1.39"	1.80"	1.92	2700
HVM2/001	2/0	4	1.54"	1.95"	2.07	3320
HVM3/001	3/0	1	.75"	1.08"	1.18	1065
HVM3/001	3/0	3	1.49"	1.92"	2.04	3130
HVM3/001	3/0	4	1.68"	2.13"	2.25	3950
HVM4/001	4/0	1	.80"	1.16"	1.26	1220
HVM4/001	4/0	3	1.62"	2.04"	2.16	3670
HVM4/001	4/0	4	1.82"	2.25"	2.37	4680
HVM25001	250	1	.89"	1.22"	1.32	1620
HVM25001	250	3	1.81"	2.25"	2.37	4380
HVM25001	250	4	2.01"	2.46"	2.61	5470
HVM35001	350	1	1.00"	1.35"	1.45	2000
HVM35001	350	3	2.03"	2.48"	2.63	5620
HVM35001	350	4	2.26"	2.71"	2.86	7050
HVM50001	500	1	1.12"	1.48"	1.58	2575
HVM50001	500	3	2.31"	2.82"	2.97	7420
HVM50001	500	4	2.60"	3.13"	3.30	9520
HVM75001	750	1	1.33"	1.73"	1.85	3600

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.