PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

Royal® 600V EPR/CPE PAIRS, SPOS, TYPE TC-ER

Construction Parameters:

CONDUCTOR: 18 AWG - 16 AWG Class B stranded tinned copper per ASTM B-33 and B-8

INSULATION: Flame-retartdant Ethylene Propylene Rubber (EPR)

COLOR CODE: Black/ White; Alpha-numeric print; alternate & inverted

SHIELDING Individual and overall 100% coverage, tinned copper drain wire with an aluminum/polyester foil shield

JACKET: Black sunlight and moisture resistant, flame-retardant Thermoplastic Chlorinated Polyethyene (CPE)

PRINT LEGEND: CCI ROYAL XX AWG XX SHIELDED PAIRS EPR/CPE TYPE TC-ER E79496 (UL) 600V 90C DRY/90C WET OIL RES I SUNLIGHT RESISTANT DIRECT BURIAL FT4/IEEE 1202 -- SEQUENTIAL MARKING

PHYSICAL PROPERTIES:

TEMPERATURE RANGE: -30°C to 90°C; (90°C Dry/90°C Wet)

OIL RESISTANCE: OIL RES I

SUNLIGHT RESISTANT: Yes

DIRECT BURIAL: Yes

ELECTRICAL PROPERTIES:

VOLTAGE RATING: 600V rms, Max

Industry Approvals:

- o UL Standard 1277 Type TC-ER
- o NEC Article 336
- o Passes UL 1685 Flame Test
- o Passes FT4/IEEE 1202 Flame Test
- o Passes IEEE 383 Flame Test (70,000 btu)
- o ICEA S-73-532
- o EPA 40 CFR, Part 26, Subpart C, heavy metals per Table 1, TCLP method

Part Number	Gauge	No. Pairs	Stranding	Insulation Wall, Nom.		Jacket Wall, Nom.		O.D., Nom.		Net Weight	
				Inches	mm	Inches	mm	Inches	mm	Lb./kft.	kg/km
791882	**18**	**2**	7/0.0152	0.030	0.76	0.045	1.14	0.487	12.37	93	138
791884	**18**	**4**	7/0.0152	0.030	0.76	0.060	1.52	0.622	15.80	172	256
791888	**18**	**8**	7/0.0152	0.030	0.76	0.060	1.52	0.744	18.90	279	415
791877	**18**	**12**	7/0.0152	0.030	0.76	0.080	2.03	0.916	23.27	424	631
791894	**18**	**24**	7/0.0152	0.030	0.76	0.080	2.03	1.480	37.59	790	1176
791896	**18**	**36**	7/0.0152	0.030	0.76	0.080	2.03	1.424	36.17	1135	1689
791682	**16**	**2**	7/0.0192	0.030	0.76	0.045	1.14	0.474	12.04	133	198
791684	**16**	**4**	7/0.0192	0.030	0.76	0.060	1.52	0.629	15.98	211	314
791688	**16**	**8**	7/0.0192	0.030	0.76	0.080	2.03	0.860	21.84	403	600
791677	**16**	**12**	7/0.0192	0.030	0.76	0.080	2.03	1.154	29.31	554	824
791694	**16**	**24**	7/0.0192	0.030	0.76	0.080	2.03	1.383	35.13	1068	1589
791696	**16**	**36**	7/0.0192	0.030	0.76	0.080	2.03	1.962	49.83	1545	2299

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.

This product complies with European Directive 2011/65/EU (RoHS-2)

The customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: May 7, 2015

© 2013 CCI