100 Bradley Parkway
Blauvelt, NY 10913
Toll-Free (800) 947-3911
Fax (845) 353-9315

SPECIFICATION SHEET

COMPANY: OMNI DATE: 01/23/12

SPECIFICATION SHEET

TWC PART NUMBER: T20004.1/2280AT4M/CMP/CL3P

CONSTRUCTION	:	22AWG 7/0096 TINNED COPPER 4 CONDUCTORS. OVERALL FOIL.
COLOR CODE	:	CC#17: BLACK,RED,WHITE,GREEN
INSULATION	:	0.007 Inch, FEP
SHIELD/DRAIN	:	OVERALL FOIL SHIELD, FOIL-IN (SILVER OUT). 24AWG 7/32 TC.
CAPACITANCE	:	27.7 pF/ft Nom.
VEL OF PROP	:	68.2%
IMPEDANCE	:	54 OHMS
RESISTANCE	:	17.5 OHMS D.C. PER 1000 FT @ 68 DEG. F
TEMP/VOLTAGE	:	200 DEGREES C
JACKET	:	GRAY FEP, 0.012 Inch, FEP -- 0.128 Nom OD
CABLE WT	:	18.8 Lb/1000Ft Approx (EXCLUDING REEL OR BOX)
PRINT LEGEND	:	E118871 CMP/CL3P/FPLP 22AWG (UL) c(UL) 200 DEG. C. MADE IN USA
UL	:	CMP/CL3P
MISC	:	MADE IN USA

* +/- 10% Manufacturing tolerance
* On non-standard product, customer agrees to accept all lengths manufactured

APPROVED BY

Tappan Wire & Cable Inc. provides information and specifications on an “as is” basis. Information in specifications described herein are subject to error and/or omission, and subject to change without notice. Although we make all efforts possible to ensure the accuracy and timeliness of the information, Tappan Wire & Cable, will not be held liable for any damages whatsoever, even if advised of the possibility of such damages, arising from the use, or inability to use, the information or specifications herein. Please refer to our “Website Use Policy”, listed on our website, www.tappanwire.com, under the Sales Support Section for full details, or contact your Tappan representative.