529 Thomas Drive, Bensenville, IL 60106 | TF: 888.518.8086 | FX: 630.860.5944 | www.lakecable.com

# Specification Sheet

## Lake Cable Part #: MCVX162S/16DR/M1

**Description:** 16 AWG 2 conductor 7 strand bare copper with XLPE insulation, an aluminum/mylar shield with a stranded tinned copper drain wire, a PVC inner jacket, interlocked aluminum armor and an overall PVC jacket 600V metal clad cable, approved for use in SUN RES DIR BUR OIL RES I 90°C applications.

**Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.**

_____
**Signature**

_____
**Company**

**1. Conductor**

| | |
|---|---|
| 1.1. AWG Size & Stranding: | 16 AWG 7 Strands Class B |
| 1.2. Material: | Annealed Bare Copper |
| 1.3. Conductor Count: | 2 Conductors |

**2. Insulation**

| | |
|---|---|
| 2.1. Material: | Cross-linked Polyethylene |
| 2.2. Wall Thickness: | 0.030” |
| 2.3. Color Code: | Method 1, Table E-1 |

**3. Assembly**

| | |
|---|---|
| 3.1. Lay Length: | Per UL Standard 1277 |
| 3.2. Fillers: | N/A |
| 3.3. Binder: | Clear Mylar |
| 3.4. Shield: | Aluminum/Mylar Tape - 100% coverage |
| 3.5. Drain Wire: | 16 AWG 7 Strand Tinned Copper |

**4. Inner Jacket**

| | |
|---|---|
| 4.1. Material: | Polyvinylchloride |
| 4.2. Wall Thickness: | 0.045” |
| 4.3. Color: | Black |
| 4.4. Inner Jacket Markings: | N/A |

**5. Interlocked Armor**

| | |
|---|---|
| 5.1. Material: | Interlocked Aluminum |

**6. Outer Jacket**

| | |
|---|---|
| 6.1. Material: | Polyvinylchloride |
| 6.2. Wall Thickness: | 0.050” |
| 6.3. Diameter: | 0.683” |
| 6.4. Color: | Black |
| 6.5. Ripcord: | Yes |
| 6.6. Cold Bend Rating: | -40°C |
| 6.7. Weight: | 196 lbs./Mft. |

**7. Markings**

| | |
|---|---|
| 7.1. Type: | Cable shall be permanently identified via surface inkjet print |
| 7.2. Legend: | LAKE CABLE E318324 16AWG 2C SHIELDED (UL) MC XLPE 600V 90’C DRY/WET LOCATIONS CABLE “FOR CT USE” INTERLOCKED ALUMINUM ARMOR PVC JACKET SUN RES DIR BUR OIL RES I FT4 “ROHS” |
| 7.3. Footage Markers: | Yes |

# Specification Sheet

## Lake Cable Part #: MCVX162S/16DR/M1

**8. Standards**

8.1. UL listed as Type MC per UL Standard 1569 for metal clad cables
8.2. Cable is suitable for use in Class I Division II hazardous locations
8.3. UL approved for Direct Burial, Sunlight and Oil I Resistant applications
8.4. Cable meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements
8.5. Meets ICEA S-73-532, where applicable
8.6. All materials used in the manufacture of this cable are RoHS compliant
8.7. Made in the USA

***ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION***