
LDB-9-02x12-D-ZP-D BK *00

Part Number: **F90240209B**



Applications: Blown Installation, CATV and DataCom, Long Distance OSP, Outdoor Plant Duct Installation

General Construction:

The cable contains 24 color-coded single-mode optical fibers per ITU-T G.652D contained in 2 color-coded loose tubes, each tube contains 12 fibers. These tubes are filled with a thixotropic gel to prevent the ingress of water and SZ stranded around a dielectric central strength member. 3Fillers are used preserve cable geometry. Fiber-glass strength yarns reinforce the cable core and an outer jacket completes the cable structure.

The Drawing for illustration purposes only.

Outer Jacket Material: PE
Outer Diameter: 9.5 mm nom.
Weight: 75 kg/km

Design & Materials

Buffer Material:	PBT
Tube Diameter:	2.1 mm nom.
Color code:	Per TIA/EIA 598-C
Central Strength Member:	FRP
Cabling:	SZ
Strength Elements:	E-Glass Yarns
Fiber Containing Tubes:	2
Total Number of Tubes:	5
Number of fibers:	24
Waterblocking:	Dry Waterblocking
Outer Jacket Thickness:	1.5 mm nom.
Outer Jacket Color:	Black
Marking:	Per request

Standards

Applicable Standards:	IEC 60794, ISO/IEC 11801, TIA/EIA-568
Installation:	Guidelines as per IEC 60794-1-1 Annex A

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Performance

Max. Tensile Strength - Short Term:	2700 N
Max. Tensile Strength - Long Term:	60% of Max. tensile load N
Impact Resistance:	4.4 N•m
Impact Resistance:	3 cycles
Max. Crush Resistance:	400 N/cm
Min. Bend Radius for Installation:	20xD mm
Min. Bend Radius for Operation:	10xD mm
Repeated Bending:	25 cycles
Max. Operating Temperature:	+70 °C
Min. Operating Temperature:	-40 °C
Max. Storage Temperature:	+70 °C
Min. Storage Temperature:	-40 °C
UV resistance:	Yes
Waterblocking:	Yes

Prepared By	Revised By	Version Num	Modified on
Yoram Berman	Olga Kirshner	1.2	17-01-2012

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.