SLA-6-01x06-ZV-D OFNR BK

Part Number: **F60060143B**



Applications:	Campus Backbone, Campus Distribution cabling, General purpose all-dielectric outdoor LAN, Outdoor Plant Duct Installation
General Construction:	The cable contains 6 color coded multi-mode 62.5/125µm optical fibers, each with a 250µm outer diameter. The optical fibers are contained in a loose tube filled with thixotropic gel, that is reinforced and protected by waterblocking fiber- glass strength yarns and jacketed.
Outer Jacket Material:	FR-PVC
Outer Diameter:	8.5 mm nom.
Weight:	90 kg/km

Design & Materials

Buffer Material:	PBT
Tube Diameter:	3.3 mm nom.
Strength Elements:	E-Glass Yarns
Number of fibers:	6
Waterblocking:	Dry Waterblocking
Rip-Cord:	Yes
Outer Jacket Thickness:	1.8 mm nom.
Outer Jacket Color:	Black
Marking:	Per request

Standards

Applicable Standards:	IEC 60794
Installation:	Guidelines as per IEC 60794-1-1 Annex A

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Performance

Tensile Strength - Short Term:	1500 N max.
Tensile Strength - Long Term:	900 N max.
Max. Crush Resistance:	400 N/cm
Min. Bend Radius for Installation:	170 mm
Min. Bend Radius for Operation:	85 mm
Max. Operating Temperature:	+70 °C
Min. Operating Temperature:	-20 °C
Max. Storage Temperature:	+70 °C
Min. Storage Temperature:	–40 °C
UV resistance:	Yes
Waterblocking:	Yes

Prepared By	Revised By	Version Num	Modified on
Yoram Berman	Olga Kirshner	1.2	17-01-2012

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.