Technical
Data Sheet

05/24/10 REV. 2 MONTROSE 2002C

.

I. DESCRIPTION:

16 AWG (19X#29) TINNED COPPER POLYETHYLENE INSULATED CONDUCTORS, THREE SINGLES TWISTED WITH FOIL SHIELD TAPE PLUS 20 AWG (7X#28) TINNED COPPER DRAIN WIRE, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS (CM) 600 V RMS (AWM)
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	11 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	3.9 OHMS PER 1000 FEET
NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C:	7.3 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS @ 1 KHZ:	24 PF PER FOOT
NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:*	43.25 PF PER FOOT

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C
INSULATION MATERIAL:	POLYETHYLENE
INSULATION THICKNESS:	.0315” NOMINAL
LAY LENGTH:	4" (3.0 TWISTS PER FOOT)
COLOR CODE:	BLACK, CLEAR, RED
TYPE SHIELD AND % COVERAGE:	POLYESTER/ALUMINUM TAPE; 100%
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.032” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.330”
MININUM BEND RADIUS:	3-1/4”
NOMINAL WEIGHT:	59 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	91 LBS.
APPLICABLE SPECIFICATIONS:	UL & C(UL) TYPE CM, UL AWM 2107, ROHS COMPLIANT
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY