Technical
Data Sheet

05/24/10 REV. 2 MONTROSE 2004C

.

I. DESCRIPTION:

---

18 AWG (16X#30) TINNED COPPER POLYETHYLENE INSULATED CONDUCTORS, THREE SINGLES TWISTED WITH FOIL SHIELD TAPE PLUS 22 AWG (7X#30) TINNED COPPER DRAIN WIRE, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	8 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	6.0 OHMS PER 1000 FEET
NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C:	11.0 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS @ 1 KHZ:	32 PF PER FOOT
NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:*	57.5 PF PER FOOT

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C
INSULATION MATERIAL:	POLYETHYLENE
INSULATION THICKNESS:	.016” NOMINAL
LAY LENGTH:	2-1/4" (5.3 TWISTS PER FOOT)
COLOR CODE:	BLACK, RED & CLEAR
TYPE SHIELD AND % COVERAGE:	POLYESTER/ALUMINUM TAPE; 100%
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.025” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.224”
MININUM BEND RADIUS:	2-1/4”
NOMINAL WEIGHT:	30.5 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	62.5 LBS.
APPLICABLE SPECIFICATIONS:	UL & C(UL) TYPE CM, UL AWM 2093, ROHS COMPLIANT
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY