Technical
Data Sheet

07/19/10 REV. 3 MONTROSE 2005C

.

I. DESCRIPTION:

18 AWG (19X#30) TINNED COPPER POLYETHYLENE INSULATED CONDUCTORS, FOUR SINGLES TWISTED WITH FOIL SHIELD TAPE PLUS 22 AWG (7X#30) TINNED COPPER DRAIN WIRE, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	6.5 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	5.7 OHMS PER 1000 FEET
NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C:	11.0 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN ADJACENT CONDUCTORS @ 1 KHZ:	40 PF PER FOOT
NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:*	72 PF PER FOOT

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C (CM) -20 TO +80 DEG.C (AWM)
INSULATION MATERIAL:	PVC
INSULATION THICKNESS:	.011” NOMINAL
LAY LENGTH:	2-3/4" (4.4 TWISTS PER FOOT)
COLOR CODE:	BLACK, RED, WHITE, GREEN
TYPE SHIELD AND % COVERAGE:	POLYESTER/ALUMINUM TAPE; 100%
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.032” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.227”
MININUM BEND RADIUS:	2-1/4”
NOMINAL WEIGHT:	39 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	99 LBS.
APPLICABLE SPECIFICATIONS:	UL TYPE CM, C(UL) TYPE CMG, UL AWM 2464, ROHS COMPLIANT

Technical
Data Sheet

FLAME RESISTANCE:	UL 1685 VERTICAL TRAY, CSA FT4