Technical
Data Sheet

05/24/10 REV. 2 MONTROSE 2006C

.

I. DESCRIPTION:

20 AWG (7X#28) TINNED COPPER POLYETHYLENE INSULATED CONDUCTORS, TWO SINGLES TWISTED WITH FOIL SHIELD TAPE PLUS 24 AWG (7X#32) TINNED COPPER DRAIN WIRE, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	6 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	9.5 OHMS PER 1000 FEET
NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C:	17.25 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS @ 1 KHZ:	26 PF PER FOOT
NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:*	46.75 PF PER FOOT
NOMINAL INDUCTANCE OF PAIR:	.19 MICRO-H PER FOOT

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C
INSULATION MATERIAL:	POLYETHYLENE
INSULATION THICKNESS:	.016” NOMINAL
TWISTED PAIR LAY LENGTH:	2" (6 TWISTS PER FOOT)
COLOR CODE:	BLACK & CLEAR
TYPE SHIELD AND % COVERAGE:	POLYESTER/ALUMINUM TAPE; 100%
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.020” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.180”
MININUM BEND RADIUS:	1-3/4”
NOMINAL WEIGHT:	16 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	28 LBS.
APPLICABLE SPECIFICATIONS:	UL & C(UL) TYPE CM, UL AWM 2092, ROHS COMPLIANT
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY