Technical
Data Sheet

07/16/10 REV. 4 MONTROSE 2011C

.

I. DESCRIPTION:

18 AWG (16X#30) TINNED COPPER PVC INSULATED CONDUCTORS, TWO SINGLES TWISTED, UNSHIELDED, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	8 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	6.0 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS @ 1 KHZ:	26 PF PER FOOT
NOMINAL INDUCTANCE OF PAIR:	.18 MICRO-H PER FOOT

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C
INSULATION MATERIAL:	PVC
INSULATION THICKNESS:	.016” NOMINAL
TWISTED PAIR LAY LENGTH:	2-3/4" (4.4 TWISTS PER FOOT)
COLOR CODE:	BLACK & WHITE
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.015” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.188”
MININUM BEND RADIUS:	1-7/8”
NOMINAL WEIGHT:	17 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	41.5 LBS.
APPLICABLE SPECIFICATIONS:	UL TYPE CM, C(UL) TYPE CMG ROHS COMPLIANT
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY, CSA FT4