Technical
Data Sheet

05/24/10 REV. 2 MONTROSE 2022C

.

I. DESCRIPTION:

---

22 AWG (7X#30) TINNED COPPER POLYPROPYLENE INSULATED CONDUCTORS, TWO PAIRS TWISTED ON A COMMON AXIS EACH WITH AN INDIVIDUAL FOIL SHIELD TAPE (FOIL SIDE OUT) PLUS A COMMON 24 AWG (7X#32) TINNED COPPER DRAIN WIRE, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	4 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	14.9 OHMS PER 1000 FEET
NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C:	13.75 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS OF A PAIR @ 1 KHZ:	32.5 PF PER FOOT
NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:*	58.5 PF PER FOOT
NOMINAL INDUCTANCE OF PAIR:	.17 MICRO-H PER FOOT

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C
INSULATION MATERIAL:	POLYPROPYLENE
INSULATION THICKNESS:	.0085” NOMINAL
TWISTED PAIR LAY LENGTH:	1.8" (6.7 TWISTS PER FOOT)
COLOR CODE:	BLACK & RED, WHITE & GREEN
TYPE SHIELDS AND % COVERAGE:	POLYESTER/ALUMINUM TAPE; 100%
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.020” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.160”
MININUM BEND RADIUS:	1-5/8”
NOMINAL WEIGHT:	17 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	36.5 LBS.
APPLICABLE SPECIFICATIONS:	UL & C(UL) TYPE CM, ROHS COMPLIANT
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY