Technical
Data Sheet

07/19/10 REV. 3 MONTROSE 2042C

.

I. DESCRIPTION:

18 AWG (16X#30) TINNED COPPER POLYETHLYENE INSULATED CONDUCTORS, THREE PAIRS TWISTED EACH WITH AN INDIVIDUAL FOIL SHIELD TAPE (FOIL SIDE IN) AND 22 AWG (7X#30) TINNED COPPER DRAIN WIRE, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	5.5 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	6.1 OHMS PER 1000 FEET
NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C:	10.3 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS OF A PAIR @ 1 KHZ:	32 PF PER FOOT
NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:*	57.5 PF PER FOOT
NOMINAL INDUCTANCE OF PAIR:	.18 MICRO-H PER FOOT

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C (CM) -20 TO +80 DEG.C (AWM)
INSULATION MATERIAL:	POLYETHYLENE
INSULATION THICKNESS:	.016” NOMINAL
TWISTED PAIR LAY LENGTH:	2.25" (5.3 TWISTS PER FOOT)
COLOR CODE:	BLACK & RED, BLACK & WHITE, BLACK & GREEN
TYPE SHIELDS AND % COVERAGE:	POLYESTER/ALUMINUM TAPE; 100%
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.032” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.384”
MININUM BEND RADIUS:	3-7/8”
NOMINAL WEIGHT:	65 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	125 LBS.
APPLICABLE SPECIFICATIONS:	UL & C(UL) TYPE CM,

Technical
Data Sheet

	UL AWM 2919, ROHS COMPLIANT
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY