Technical
Data Sheet

07/19/10 REV. 3 MONTROSE 2044C

.

I. DESCRIPTION:

20 AWG (7X#28) TINNED COPPER PVC INSULATED CONDUCTORS, TWO PAIRS TWISTED EACH WITH AN INDIVIDUAL FOIL SHIELD TAPE (FOIL SIDE IN) AND 24 AWG (7X#32) TINNED COPPER DRAIN WIRE, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	4.75 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	9.7 OHMS PER 1000 FEET
NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C:	14.9 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS OF A PAIR @ 1 KHZ:	52.5 PF PER FOOT
NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:*	94.5 PF PER FOOT
NOMINAL INDUCTANCE OF PAIR:	.17 MICRO-H PER FOOT

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C (CM) -20 TO +80 DEG.C (AWM)
INSULATION MATERIAL:	PVC
INSULATION THICKNESS:	.011” NOMINAL
TWISTED PAIR LAY LENGTH:	1.75" (6.9 TWISTS PER FOOT)
COLOR CODE:	BLACK & RED, WHITE & GREEN
TYPE SHIELDS AND % COVERAGE:	POLYESTER/ALUMINUM TAPE; 100%
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.040” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.301”
MININUM BEND RADIUS:	3”
NOMINAL WEIGHT:	43 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	56 LBS.
APPLICABLE SPECIFICATIONS:	UL TYPE CM, C(UL) TYPE CMG,

Technical
Data Sheet

FLAME RESISTANCE:	UL AWM 2464, ROHS COMPLIANT UL 1685 VERTICAL TRAY, CSA FT4