Technical
Data Sheet

07/19/10 REV. 4 MONTROSE 2045C

.

I. DESCRIPTION:

---

22 AWG (7X#30) TINNED COPPER PVC INSULATED CONDUCTORS, TWO SINGLES TWISTED WITH FOIL SHIELD TAPE PLUS 24 AWG (7X#32) TINNED COPPER DRAIN WIRE, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	5 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	14.9 OHMS PER 1000 FEET
NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C:	17.25 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS @ 1 KHZ:	40 PF PER FOOT
NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:*	72 PF PER FOOT
NOMINAL INDUCTANCE OF PAIR:	.19 MICRO-H PER FOOT

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C (CM) -20 TO +80 DEG.C (AWM)
INSULATION MATERIAL:	PVC
INSULATION THICKNESS:	.013” NOMINAL
TWISTED PAIR LAY LENGTH:	1-5/8" (7.4 TWISTS PER FOOT)
COLOR CODE:	BLACK & RED
TYPE SHIELD AND % COVERAGE:	POLYESTER/ALUMINUM TAPE; 100%
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.032” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.177”
MININUM BEND RADIUS:	1-3/4”
NOMINAL WEIGHT:	15 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	18 LBS.
APPLICABLE SPECIFICATIONS:	UL TYPE CM, UL TYPE CMG, UL AWM 2464,

Technical
Data Sheet

	ROHS COMPLIANT
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY, CSA FT4