Technical
Data Sheet

07/19/10 REV. 3 MONTROSE 2046C

.

I. DESCRIPTION:

---

24 AWG (7X#32) TINNED COPPER POLYETHYLENE INSULATED CONDUCTORS, TWO SINGLES TWISTED WITH AN OVERALL FOIL TAPE, 24 AWG (7X#32) TINNED COPPER DRAIN WIRE PLUS TINNED COPPER BRAID SHIELD, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	3.5 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	23.25 OHMS PER 1000 FEET
NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C:	2.75 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS @ 1 KHZ:	15.5 PF PER FOOT
NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:*	28 PF PER FOOT
NOMINAL INDUCTANCE OF PAIR:	.25 MICRO-H PER FOOT

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C (CM) -20 TO +80 DEG.C (AWM)
INSULATION MATERIAL:	POLYETHYLENE
INSULATION THICKNESS:	.024” NOMINAL
TWISTED PAIR LAY LENGTH:	2.5" (4.8 TWISTS PER FOOT)
COLOR CODE:	WHITE/BLUE & BLUE/WHITE
TYPE SHIELDS AND % COVERAGE:	POLYESTER/ALUMINUM TAPE (100%) & TINNED COPPER BRAID (90%)
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.032” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.232”
MININUM BEND RADIUS:	2-3/8”
NOMINAL WEIGHT:	28 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	51 LBS.
APPLICABLE SPECIFICATIONS:	UL & C(UL) TYPE CM, UL AWM 2919,

Technical
Data Sheet

	ROHS COMPLIANT
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY