Technical
Data Sheet

07/19/10 REV. 3 MONTROSE 2048C

.

I. DESCRIPTION:

---

24 AWG (7X#32) TINNED COPPER FOAMED POLYETHYLENE INSULATED CONDUCTORS, TWO PAIRS TWISTED EACH WITH AN INDIVIDUAL FOIL SHIELD TAPE (FOIL SIDE IN) AND 24 AWG (7X#32) TINNED COPPER DRAIN WIRE, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

---

| | |
|---|---|
| MAXIMUM OPERATING VOLTAGE: | 300 V RMS |
| MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C: | 3 AMPS |
| NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C: | 23.5 OHMS PER 1000 FEET |
| NOMINAL SHIELD D.C. RESISTANCE @ 20 DEG. C: | 15.6 OHMS PER 1000 FEET |
| NOMINAL CAPACITANCE BETWEEN CONDUCTORS OF A PAIR @ 1 KHZ: | 15 PF PER FOOT |
| NOMINAL CAPACITANCE CONDUCTOR TO SHIELD @ 1 KHZ:* | 27 PF PER FOOT |
| NOMINAL INDUCTANCE OF PAIR: | .22 MICRO-H PER FOOT |

*ONE CONDUCTOR OTHER CONDUCTORS AND SHIELD

.

III. PHYSICAL CHARACTERISTICS:

---

| | |
|---|---|
| TEMPERATURE RATING: | -20 TO +75 DEG.C |
| INSULATION MATERIAL: | FOAMED POLYETHYLENE |
| INSULATION THICKNESS: | .016” NOMINAL |
| TWISTED PAIR LAY LENGTH: | 1.75" (6.9 TWISTS PER FOOT) |
| COLOR CODE: | BLACK & RED, BLACK & WHITE |
| TYPE SHIELDS AND % COVERAGE: | POLYESTER/ALUMINUM TAPE; 100% |
| JACKET MATERIAL: | PVC |
| JACKET THICKNESS: | .048” NOMINAL |
| JACKET COLOR: | GRAY |
| NOMINAL DIAMETER: | .304” |
| MININUM BEND RADIUS: | 3” |
| NOMINAL WEIGHT: | 34 LBS. PER 1000 FEET |
| MAXIMUM PULLING TENSION: | 22 LBS. |
| APPLICABLE SPECIFICATIONS: | UL & C(UL) TYPE CM, UL AWM 2493, ROHS COMPLIANT |

Technical
Data Sheet

| | |
|---|---|
| FLAME RESISTANCE: | UL 1685 VERTICAL TRAY |