Technical
Data Sheet

07/19/10 REV. 3 MONTROSE 2049C

.

I. DESCRIPTION:

18 AWG (16X#30) TINNED COPPER PVC INSULATED CONDUCTORS, TWO SINGLES TWISTED, UNSHIELDED, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	8 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	6.0 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN CONDUCTORS @ 1 KHZ:	27 PF PER FOOT
NOMINAL INDUCTANCE OF PAIR:	.17 MICRO-H PER FOOT

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C (CM) -20 TO +80 DEG.C (AWM)
INSULATION MATERIAL:	PVC
INSULATION THICKNESS:	.014” NOMINAL
TWISTED PAIR LAY LENGTH:	2" (6.0 TWISTS PER FOOT)
COLOR CODE:	BLACK & RED
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.032” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.210”
MININUM BEND RADIUS:	2-1/8”
NOMINAL WEIGHT:	22 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	41.5 LBS.
APPLICABLE SPECIFICATIONS:	UL TYPE CM, C(UL) TYPE CMG, UL AWM 2464, ROHS COMPLIANT
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY, CSA FT4