Technical
Data Sheet

07/19/10 REV. 4 MONTROSE 2051C

.

I. DESCRIPTION:

20 AWG (7X#28) TINNED COPPER PVC INSULATED CONDUCTORS, FOUR SINGLES TWISTED, UNSHIELDED, PVC JACKET.

.

II. ELECTRICAL CHARACTERISTICS:

MAXIMUM OPERATING VOLTAGE:	300 V RMS
MAXIMUM CONTINUOUS CURRENT PER CONDUCTOR @ 25 DEG. C:	5 AMPS
NOMINAL CONDUCTOR D.C. RESISTANCE @ 20 DEG. C:	9.5 OHMS PER 1000 FEET
NOMINAL CAPACITANCE BETWEEN ADJACENT CONDUCTORS @ 1 KHZ:	23.5 PF PER FOOT

.

III. PHYSICAL CHARACTERISTICS:

TEMPERATURE RATING:	-20 TO +75 DEG.C (CM) -20 TO +80 DEG.C (AWM)
INSULATION MATERIAL:	PVC
INSULATION THICKNESS:	.0145” NOMINAL
LAY LENGTH:	2-3/4" (4.4 TWISTS PER FOOT)
COLOR CODE:	BLACK, WHITE, RED, GREEN
JACKET MATERIAL:	PVC
JACKET THICKNESS:	.032” NOMINAL
JACKET COLOR:	GRAY
NOMINAL DIAMETER:	.217”
MININUM BEND RADIUS:	2-1/8”
NOMINAL WEIGHT:	29 LBS. PER 1000 FEET
MAXIMUM PULLING TENSION:	56 LBS.
APPLICABLE SPECIFICATIONS:	UL TYPE CM, C(UL) TYPE CMG, UL AWM 2464 ROHS COMPLIANT
FLAME RESISTANCE:	UL 1685 VERTICAL TRAY, CSA FT4