Drop Wire

Spec. 4295

BELL SYSTEM TYPE F DROP AND RDUP (RUS) PE-7

Product Construction:

Conductors:

- 18½ AWG solid 30% conductivity extra high strength copper-covered steel

Sheath:

- Black, flame-, weather- and abrasion-resistant PVC compound extruded over two conductors in a parallel configuration

Polarity Identification:

- Polarity ridge on one leg of the web located at 45˚ above the major axis of the wire cross-section

Application(s):

- Self-supporting one pair parallel conductor drop wire intended for aerial service connection to the subscriber

Compliance:

- Telecordia (Bellcore) Specification GR-3163-CORE
- Rural Development Utility Program (RDUP) Bulletin 1753 F-204 (RUS PE-7)
- ANSI/ICEA S-89-648-1993
- RoHS Compliant (effective 1/1/10)

Packaging:

- Available in Pull-Pac™ cartons (PP), coils in cartons (CL/CTN) and reels (RL)



CATALOG NUMBER	PAIRS AWG	O.D. (INCHES)	WEIGHT (LBS/MFT)	STANDARD LENGTH (FT)
7021421	1/18½	0.130 x 0.255	25	1000 CL
7021496	1/18½	0.130 x 0.255	30	1000 PP

Data subject to change without notice. Contact your Customer Service Representative for latest information.

RoHS Compliant Effective 1/1/10

Passes UL VW-1 Flame Test
Underwriters Laboratories Inc.

Listed Type MISC.

C Rural Wire

Spec. 4283

BELL SYSTEM TYPE

Product Construction:

Conductors:

- 14 or 12 AWG solid 30% conductivity extra high strength copper-covered steel

Sheath:

- Black, high density polyethylene compound extruded over two conductors in a parallel configuration

Polarity Identification:

- Polarity ridge on one minor face of the insulation located at 45˚ above the major axis of the wire cross-section

Application(s):


- Self-supporting one pair parallel conductor drop wire intended for aerial distribution in rural exchange areas

Compliance:

- Telcordia (Bellcore) Specification TA-TSY-000125
- RoHS Compliant (effective 1/1/10)

Packaging:

- Available in coils (CL) and reels (RL)



Nominal Cable Data

CATALOG NUMBER	PAIRS AWG	O.D. (INCHES)	WEIGHT (LBS/MFT)	STANDARD LENGTH (FT)
6307482	1/14	0.160 x 0.280	40	1000 CL
3114733	1/14	0.160 x 0.280	45	5000 (21") RL
7013881	1/14	0.160 x 0.280	45	5500 (29") RL
2091013	1/12	0.190 x 0.315	60	4000 (21") RL

Data subject to change without notice. Contact your Customer Service Representative for latest information.