Advanced Digital Cable, Inc.	Specification Sheet for 150C plenum 75 Ohm RG 11/U with 14 awg copper-clad steel conductor.	Date:	1/14/04
		Part Number:	7-9112
Drawn by:	Customer Approval:	UL Type:	CL3P/CMP

Construction Details:

This cable is constructed with a core composed of a 14 awg solid copper-clad steel center conductor insulated with gas injected foamed FEP Teflon. The core is shielded with an aluminum/polyester/aluminum foil and an aluminum braid with 65% coverage. A natural colored low smoke flame resistant Solef PVDF jacket completes the package.

Physical Specifications

Conductors: 1 – 14 awg solid copper-clad steel .064”

Dielectric: 106 mil wall of foamed FEP Teflon to a nominal diameter of .275”.

Shield: Aluminum/polyester/aluminum with 25% min. overlap.

Braid: Aluminum braid with 65% coverage.

Jacket: 22 mil natural colored low smoke flame retardant 150 deg. C Solef PVDF to a nominal diameter of .349”

Print: Black ink:
RG 11/U 14 AWG (UL) TYPE CMP OR CL3P 150C OR c(UL) CMP E179333

Put Up: Reels per customer specification.

Electrical Specifications

Nominal Attenuation

MHz	dB/100 feet
10	.50
50	1.00
100	1.40
200	2.10
400	2.90
700	3.90
900	4.42
1000	4.70
1200	5.00
1450	5.90
1800	6.57

Impedance: 75 Ohms

Capacitance: 15.8 pF/foot

Velocity of Prop.: 84%