Temporary Jumper Cable

Single Conductor
4 AWG - 500 kcmil
90°C Damp or Dry Locations
5/15kV EPR Insulation, Non-Shielded

APPLICATIONS

Southwire's Temporary Jumper Cables are intended for use as flexible power leads to by-pass portions of aerial power lines. They are also used in equipment where a non-shielded flexible cable is required. Access to these cables is limited to authorized personnel.

SPECIFICATIONS

Southwire's Temporary Jumper Cable meets the following applicable requirements:

- ICEA S-96-659
- File Listing: ES16748

CONSTRUCTION

Southwire's Temporary Jumper Cable is manufactured using a flexible rope stranded annealed uncoated copper. The conductor shield is a nylon semi-conducting tape. Temporary Jumper Cable is insulated with heat, moisture, and ozone resistant ethylene propylene rubber.

Southwire
One Southwire Drive
Carrollton, Ga. 30119 USA

MADE IN ★ THE USA

Copyright 2010, Southwire Company.
All Rights Reserved.

®Southwire is a registered trademark of Southwire Company.

Temporary Jumper Cable

Southwire Part Number	Size AWG or kcmil	No. Of. Strands	Nominal Conductor Diameter (in)	Approximate O.D (in)	Amps	Approximate Net Weight (lbs/Mft)
-	4	259	.272	.715	150	-
569424	2	259	.330	.775	195	420
-	1	259	.375	.820	225	-
569423	1/0	259	.420	.865	260	580
569425	2/0	259	.474	.920	300	685
569487	4/0	516	.540	.985	400	950
569427	350	855	.775	1.240	550	1500
569428	500	1235	.930	1.395	685	2055
Ampacities are based on single conductor cables isolated in air. Conductor temperature of 90 °C and ambient air temperature of 40 °C per Table 310.69 of the 2002 NEC.						

Southwire
One Southwire Drive
Carrollton, Ga. 30119 USA

MADE IN ★ THE USA

Copyright 2010, Southwire Company.
All Rights Reserved.

®Southwire is a registered trademark of Southwire Company.