

07 — Setup & API Keys

Environment, secrets, database setup, seed strategy and Antigravity handoff

CampusFlow • Production Specification • v1.0 • October 2026

1. Environment Templates

```
# backend/.env.example
DATABASE_URL=""
AUTH_SECRET=""
APP_URL="http://localhost:5173"
API_URL="http://localhost:3000"
AI_PROVIDER_KEY=""
CLOUDINARY_CLOUD_NAME=""
CLOUDINARY_API_KEY=""
CLOUDINARY_API_SECRET=""
REDIS_URL=""
SENTRY_DSN=""

# frontend/.env.local.example
VITE_API_URL="http://localhost:3000"
```

2. Key Sources

DATABASE_URL: Neon PostgreSQL connection string.

AUTH_SECRET: generate locally, e.g. openssl rand -base64 32.

AI_PROVIDER_KEY: Google AI Studio / Gemini API key.

Cloudinary: Cloudinary dashboard.

REDIS_URL: managed Redis if enabled.

SENTRY_DSN: Sentry project.

3. .gitignore

```
.env
.env.local
*.csv
node_modules/
dist/
uploads/
.DS_Store
coverage/
*.log
```

4. File Map

backend/.env — real local secrets; never commit.

backend/prisma/schema.prisma — database schema.

backend/prisma/seed.ts — anonymized development seed.

backend/src/services/summary.service.ts — AI adapter.

backend/src/services/scrapper.service.ts — official ingestion.

frontend/.env.local — frontend API URL.

README.md — setup and coding-agent handoff.

5. Commands

```
cd backend
npm install
npx prisma migrate dev
npx prisma db seed
npm run dev

cd ../frontend
npm install
npm run dev
```

6. Seed / Privacy

Development seed uses anonymized accounts such as student_f1_01@moderncoe.edu.in. Real student CSV data stays local and is never committed. Normalize imported emails by removing whitespace and lowercasing.

7. Antigravity Handoff

Read docs 01-06 first.

Read backend/prisma/schema.prisma.

Implement Phase 0-1: foundation → college-email auth → dashboard → notices → deadlines → events → transaction-safe registration → rate limit → .env.example.

If AI_PROVIDER_KEY is missing, use safe mock mode.

Never commit real CSV, credentials or secrets.

Run migrations and anonymized seed.

Do not replace required behavior with fake UI.

Test auth, authorization, dashboard, notice publishing, registration race conditions, validation and mobile layout.

8. Health Endpoint

GET /health

```
{"status": "ok", "db": "ok", "timestamp": "ISO-8601"}
```

9. Five-Minute Setup Checklist

- Create backend .env.
- Create frontend .env.local.
- Create Neon database and set DATABASE_URL.
- Generate AUTH_SECRET.
- Optionally configure AI/Cloudinary.
- Run Prisma migration.
- Run anonymized seed.
- Start backend and frontend.
- Check /health.
- Test local seed login.