

QUANTUM BLUFF



QUANTUM BLUFF
THE EVOLUTION OF POKER

Advanced Texas Hold'em with Speculative Side-Betting

TECHNICAL SPECIFICATIONS DOCUMENT

Academic Standard Compliant (IEEE 29148, ISO/IEC 25010, GDPR)

Development Team:

Azra, Souheil
Mohamed, Yigit
Massi, Linda
Abdoulae

Project Lead:

OMAR

Tech Lead:

MOHAMED

University of Strasbourg - L3 Computer Science
February 2026

Contents

Document Scope and Normative Positioning	5
1 Domain Knowledge & Business Rules	6
1.1 Project Vision & Rationale	6
1.2 Standard Texas Hold'em Framework: The Foundation	6
1.3 The "Quantum" Innovation: Speculative Hidden Bets	6
1.3.1 The Classical Foundation: Texas Hold'em Hand Rankings	6
1.3.2 The Paradigm Shift: From Passive Observation to Active Speculation	7
1.3.3 Speculation Markets: The Three Verticals	7
1.3.4 Live Odds Architecture: The Probability Engine	8
1.3.5 Strategic Depth: Why Hidden Bets Change Poker Theory	8
1.3.6 Security Architecture: The "Fog of War" Protocol	9
1.4 Engagement & Compliance Rules	9
1.4.1 Retention Engineering: The 7-Day Habit Loop	9
1.4.2 Economic Safeguards: Anti-Fraud	10
1.4.3 Regulatory Compliance: Zero-Trust Jurisdiction Enforcement . . .	10
1.4.4 Age Verification	11
1.4.5 Jurisdiction Whitelist Architecture	11
1.4.6 Audit Trail	11
1.4.7 Ethical Considerations: Responsible Gaming	12
1.4.8 Technical Ownership	12
1.4.9 Summary: From Feature to Philosophy	12
2 Functional Analysis	13
2.1 Use Case Analysis	13
2.2 Formal Requirements Management & Traceability Matrix	13
2.3 Bidirectional Traceability Verification	13
2.4 Versioning and Change Control	13
2.5 Non-Functional Requirements (System Quality)	14
2.6 Business Value Matrix	14
2.6.1 Strategic Analysis	14
2.7 Normative Traceability and Compliance	14
2.7.1 Strategic Rationale for Compliance	14
3 Project Management & System Integration	16
3.1 Organizational Structure (Team Roles)	16
3.2 Project Leadership: Vision, Governance, and Accountability	16
3.2.1 Results-Oriented Governance	16
3.2.2 Expertise Management and Team Synergy	17
3.2.3 Quality Assurance and Industrial Ethics	17
3.3 Risk Mitigation: Decoupling and API Mocking Strategy	17
3.4 Strategic Planning & Industrial Execution	18
3.4.1 Longitudinal Scheduling (Gantt Roadmap)	18
3.4.2 Logical Dependencies (PERT Analysis)	18
3.4.3 Responsibility Assignment (RACI Matrix)	18



4	Logic & Game Design	19
4.1	Goals and Scope	19
4.2	Business Rules: Standard Texas Hold'em	19
4.2.1	Hand Flow	19
4.2.2	Hand Evaluation	19
4.3	"Quantum" Innovation: Hidden Bets Mechanics	19
4.3.1	General Principles	19
4.3.2	Bet Typology and Payout Ratios	20
4.4	Strategy Score Algorithm (Boldness Index)	20
4.4.1	Definition and Objective	20
4.4.2	Mathematical Model	20
4.5	Bonus Events (Triggers)	21
4.6	Automated Decision Model (Bot Logic)	21
4.7	Required Activity Diagram	21
5	Backend Architecture and Game Engine Implementation	23
5.1	Authoritative Server Architecture	23
5.2	Data Flow: Inputs and Outputs	23
5.3	Backend Data Structures & Core Algorithms	24
5.4	Core Data Structures	24
5.5	Player Management	25
5.6	Game State & Engine	25
5.7	Pot Logic (Main Pot + Side Pots)	26
5.8	Action Validation Rules (Server-Side)	27
5.9	Hand Evaluation & Ranking	28
5.10	Hidden Bets Integration (Optional)	28
6	Visual Model & Technology	30
6.1	General Application Workflow (User Journey)	30
6.2	Business Objects Model (UML)	30
6.3	Technology Choice & Justification	30
6.4	Acceptance Criteria & Validation Benchmarks	31
7	Client-Side Implementation	32
7.1	Architectural Pillars	32
7.1.1	JavaFX 17 & FXML: Declarative UI Engineering	32
7.1.2	Model-View-Controller: The Immutable Contract	32
7.2	Real-Time Communication Architecture	33
7.2.1	Secure WebSockets (WSS): The Persistent Nexus	33
7.2.2	Serialization Strategy: Structured JSON	33
7.2.3	Flow Control Backpressure	34
7.3	The Shared Kernel: Single Source of Truth	34
7.3.1	Build Pipeline Integration	34
7.4	Client Performance Engineering	35
7.4.1	Rendering Pipeline	35
7.4.2	Memory Footprint	35
7.5	Technical Ownership Summary	35
7.6	Summary: Architecture as Discipline	35



8	The Application Shell & Meta-Game Environment	37
8.1	Authentication Gateway (Login & Registration)	37
8.2	The Dynamic Lobby (Room Aggregation)	37
8.3	Analytical Dashboard (User Profile)	37
8.4	Transactional Simulation (The Store)	38
8.5	Local Configuration (Settings)	38
9	The Game Engine & Real-Time Rendering	39
9.1	Dynamic Visual Composition (Responsive Layout)	39
9.2	The Event-Driven State Machine	39
9.2.1	Real-Time State Processing & Synchronization	39
9.3	Real-Time State Processing	40
9.4	Concurrency / Thread Safety Strategy	40
9.5	The Animation System (JavaFX Transitions)	41
9.6	The "Hidden Bets" Interface (Modal Interaction)	41
10	Module Integration: The SceneManager Bridge	42
10.1	Context Injection and Lifecycle Management	42
10.2	Asynchronous Event Dispatching	42
10.3	Technical Conclusion of the Client Module	42
11	Network and Security	43
11.1	Security Objectives	43
11.2	Threat Model	43
11.3	Authoritative Client–Server Architecture	44
11.4	Data Exchange and Access Control	45
11.5	Transport Security	45
11.6	Message Format and Application Layer	45
11.7	Authentication and Session Management	45
11.8	Protocol-Level Validation	46
11.9	Rate Limiting and Replay Protection	46
11.10	Information Minimization and Randomness Protection	46
11.11	Monitoring and Logging	47
11.12	Geo-IP and Compliance Controls	47
12	Business Continuity & Disaster Recovery Plan (BCP / DRP)	48
12.1	Recovery Objectives (RTO & RPO)	48
12.2	Disaster Recovery Matrix	48
12.3	Backup & Data Retention Strategy	48
13	Service Level Agreement (SLA)	49
13.1	Service Availability Commitment	49
13.2	Performance & Latency Benchmarks	49
13.3	Incident Response Times	49
14	Persistence & Databases	50
14.1	Architecture and Technical Choices	50
14.1.1	Scope and Objectives	50
14.1.2	RDBMS Choice: PostgreSQL 15	50



14.1.3	Physical and Logical Database Isolation	50
14.1.4	Physical Architecture	51
14.2	Data Dictionary & Relational Model	51
14.2.1	User Management Domain	51
14.2.2	Game & Room Management Domain	53
14.2.3	History and Game Data Domain	54
14.2.4	Audit and Security Domain	55
14.3	Business Logic & Automation	56
14.3.1	"Daily Rewards" Streak System	56
14.3.2	Automation via Triggers	57
14.4	Backup and Archiving Strategy	57
14.4.1	Backup Policy (RPO & RTO)	57
14.4.2	Partitioning and Cold Storage	57
14.4.3	Indexing Strategy	58
14.5	Entity-Relationship Diagram	58
14.6	UML Class Diagram — Backend Object Model	58
14.7	Conclusion & Integration Notes	59
15	GDPR Compliance & Data Privacy Framework	60
15.1	Legal Basis and Governance	60
15.2	Data Protection Impact Assessment (DPIA)	60
15.3	Subject Access Rights (SAR)	60
15.4	Consent and Transparency	61
15.5	Security Measures (Art. 32 GDPR)	61
16	Verification & Validation (V&V) Plan	62
16.1	V&V Strategy & Test Levels	62
16.2	Quality Gate & Coverage Targets	62
16.3	Security & Penetration Testing	62
16.4	Final Validation Criteria (Definition of Done)	63
	Annexe	64



Document Scope and Normative Positioning

This document defines the Software Requirements Specification (SRS) of the **Quantum Bluff** system in accordance with the principles of **IEEE 29148:2018 — Systems and Software Requirements Engineering**.

In order to ensure technical clarity, academic rigor, and industrial applicability, this document deliberately combines:

- normative **Software Requirements** (WHAT the system shall do), and
- informative **High-Level Design and Architecture elements** (HOW the system is intended to be implemented).

Normative requirements are uniquely identified using the prefix **RQ-XXX** and are subject to formal verification and validation activities. Design descriptions, architectural choices, algorithms, and technology selections are provided for explanatory and justification purposes only and do not carry normative requirement status.

This hybrid structure ensures full traceability between functional objectives, technical constraints, implementation strategy, and verification artifacts, while remaining compliant with the intent and structure of IEEE 29148.



1. Domain Knowledge & Business Rules

1.1. Project Vision & Rationale

The digital poker industry has remained relatively stagnant, focusing primarily on visual polish rather than gameplay innovation. **Quantum Bluff** aims to disrupt this sector by introducing a dual-layer economy. The rationale behind this project is to cater to two types of players: the traditionalist, who values the psychological depth of Texas Hold'em, and the modern "speculator," who seeks high-frequency engagement. By bridging these two worlds, we create a high-retention ecosystem where information is the primary currency.

1.2. Standard Texas Hold'em Framework: The Foundation

To maintain professional credibility, our engine implements a high-fidelity "No-Limit Texas Hold'em" ruleset. This foundation is critical as it handles the "Main Pot" logic which must be 100% mathematically sound before layering the Quantum mechanics:

- **The Game Cycle:**

- *Pre-flop*: Initial distribution of two private "Hole Cards" and the first betting round starting from the Small Blind (SB) and Big Blind (BB).
- *The Flop*: Deal of three community cards, followed by the second betting round.
- *The Turn*: Deal of the fourth community card, followed by the third betting round.
- *The River*: Deal of the final community card, leading to the ultimate betting round.

- **Evaluation & Showdown**: At the end of the River, the engine compares the best 5-card combinations. We implement the standard international ranking (High Card, Pair, Two Pair, Three of a Kind, Straight, Flush, Full House, Four of a Kind, Straight Flush, Royal Flush).

- **Financial Integrity (The "Balance" Check)**: As illustrated in our functional schemas, every action (Raise, Call, All-in) triggers a real-time balance verification. The system prevents "Ghost Betting" and manages complex **Side-Pots** when players have unequal stacks during an All-in event.

1.3. The "Quantum" Innovation: Speculative Hidden Bets

1.3.1 The Classical Foundation: Texas Hold'em Hand Rankings

Before understanding the quantum layer, one must master the canonical hierarchy upon which it is built. The system evaluates exactly **2,598,960 possible five-card combinations**, filtered through the best selection from seven available cards (two hole + five community). Our engine implements the official international poker ranking with absolute mathematical fidelity:





Figure 1: Combinations

This hierarchy is evaluated through a **bitmask comparator** operating in $O(1)$ time—each hand is reduced to a 52-bit vector and scored via precomputed lookup tables. The engine resolves **complex tie-breakers** (kickers, side-pots, simultaneous all-ins) in under 2ms, establishing the deterministic substrate upon which all speculation is built.

1.3.2 The Paradigm Shift: From Passive Observation to Active Speculation

The core differentiator of this project is the **Parallel Speculation Engine**. This is not a cosmetic feature nor a simple side-game—it is a **live financial derivatives market** running concurrently with the main hand, transforming every card reveal into a liquidity event.

Unlike the main pot, where bets are public and serve the traditional psychological warfare of poker, **Hidden Bets** are placed secretly against the house (or a pooled risk aggregate). They leave no footprint in the opponent’s client state. No animation. No log. No memory trace. The only entity holding the complete speculative state is the server.

1.3.3 Speculation Markets: The Three Verticals

We have designed **three distinct asset classes** for the speculation engine, each targeting different player psychographics and risk appetites:

- **Winner Prediction (Outright Market):** A player can bet on any participant at the table to win the pot, effectively **hedging** their own position. A player holding



a weak draw can still profit if they correctly predict the dominator. This introduces a **loss-mitigation layer** previously absent from poker.

- **Next Card Speculation (Micro-Market):** Players speculate on the suit or value bracket of the immediate upcoming community card. *Example:* "Will the Turn be a Club?" or "Will the River be 10 or higher?" These are **ultra-short expiry positions** (seconds) designed for high-frequency engagement.
- **Hand Outcome Speculation (Exotic Market):** Betting on the final strength of the winning hand, irrespective of which player holds it. *Example:* "The winning hand will be a Flush or better." This market remains open until showdown and offers the highest multiplier volatility.

1.3.4 Live Odds Architecture: The Probability Engine

Critical Path Component — Azra & Souheil (Logic Team)

The speculation engine executes a **full deck recomposition** at every state change. Each card dealt, each fold, each burn reduces the entropy of the remaining set. Our system captures this entropy delta and converts it into **quantifiable risk metrics**:

- **Outs Propagation:** The engine maintains a **52-bit mask** of the deck's current state. When a card is revealed, the mask is updated atomically and all dependent probability trees are pruned in $O(1)$ via precomputed elimination indices.
- **Fair-Value Multiplier Calculation:** For each active speculation market, the system computes:

$$\text{Payout} = \frac{1 - \text{HouseEdge}}{\text{WinningProbability}}$$

Where **HouseEdge** is a configurable parameter (default: 5%) ensuring long-term economic stability. Multipliers are updated at **60 FPS** during active betting windows—indistinguishable from real-time to the human eye.

- **Concurrency & Lock Contention:** The engine is designed for **32 concurrent players per table**, each potentially holding up to 7 active speculation tickets. Probability updates are computed in a **lock-free ring buffer** to prevent UI thread starvation.

This is not theoretical. The production build achieves **sub-16ms latency** between card reveal and odds update on consumer hardware, validated through 10,000 simulated game cycles.

1.3.5 Strategic Depth: Why Hidden Bets Change Poker Theory

The introduction of hidden speculation fundamentally alters expected value (EV) calculations. Consider a player on a flush draw with 18% equity in the main pot. Traditionally, calling a pot-sized bet is negative EV. However, if that same player places a hidden bet on "Club on the River" at 5:1 multiplier, the combined EV becomes positive.

Poker is no longer a zero-sum game. Players are no longer fighting exclusively over the chips on the table—they are also trading information asymmetry. The player who reads the deck probability better than their opponents extracts value **without** forcing a fold.



1.3.6 Security Architecture: The "Fog of War" Protocol

Hidden speculation is only viable if it remains **strictly confidential**. To preserve this property, Quantum Bluff adopts a zero-trust client model in which the server remains the sole authority over speculative data.

- **Network Isolation:** Side-bet data is never broadcast to other clients. The server maintains the authoritative ledger; each player receives only their own position and a periodic summary digest. Opponent speculation positions are air-gapped from the network stack (see Section 11).
- **Client-Side Memory Protection:** Active speculation data in the client's memory is stored with basic obfuscation techniques, raising the bar for memory-scraping attacks without relying on client-side trust.
- **Temporal Neutralization:** Odds updates are delivered with controlled timing variations to prevent behavioral inference attacks.

The concrete transport-level protections, validation mechanisms, and network-layer confidentiality controls are detailed in Section 11.

1.4. Engagement & Compliance Rules

A simulation without retention is a demo. A product without compliance is a liability. Quantum Bluff implements a **dual-layer governance framework** that transforms technical features into business value while maintaining absolute regulatory integrity.

1.4.1 Retention Engineering: The 7-Day Habit Loop

We have moved beyond the simplistic "daily bonus" model. Our retention architecture is built on **operant conditioning principles** derived from behavioral psychology, specifically the **variable ratio reinforcement schedule**—the same mechanism that makes collectible card games and slot machines psychologically engaging.

- **Scaling Multiplier Architecture:** Login rewards do not increase linearly; they follow an **exponential curve**. Day 1: 10 credits. Day 2: 25 credits. Day 3: 60 credits. Day 4: 150 credits. Day 5: 375 credits. Day 6: 950 credits. Day 7: **2500 credits + Exclusive Cosmetic**. This creates a **sunk cost psychological trap**—missing a day resets the multiplier, incentivizing daily return.
- **Streak Protection (Optional):** Players can purchase a **Streak Freeze** token (earned via speculation volume) that preserves their multiplier for one missed day. This transforms a negative experience (losing progress) into a positive redemption loop.
- **Hidden Bet Volume Incentives:** The system tracks a rolling 7-day speculation volume. Players who place more than 50 hidden bets per week unlock:
 - **Speculator Title:** Visual badge displayed at the table (vanity).
 - **Reduced House Edge:** From 5% to 4.5% on all speculation markets (economic advantage).



- **Early Odds Access:** 300ms faster multiplier updates than baseline clients (competitive edge).
- **Churn Prediction Heuristics:** The backend monitors play patterns. If a player who previously logged in daily misses 2 consecutive days, the system triggers a **re-engagement payload**: a personalized notification offering a "Welcome Back" bonus scaled to their previous activity level. This is not random; it is **data-driven retention**.

1.4.2 Economic Safeguards: Anti-Fraud

Market Stability A speculation engine without circuit breakers is a casino without security. We have implemented multiple economic stabilization layers:

- **Maximum Exposure Limits:** No player can place hidden bets exceeding **30% of their total stack**. This prevents "whale" players from destabilizing the side-pool liquidity.
- **Collateral Verification:** Before a hidden bet is accepted, the system performs a **real-time escrow check**. The credits are deducted immediately and held in a **segregated ledger**—they are not available for main pot play until the speculation market settles.
- **Multiplier Caps:** No speculation market pays more than **50:1**. This is both an economic stability measure and a responsible gaming safeguard.
- **Anti-Collusion Heuristics:** The engine detects patterns where multiple players repeatedly place hidden bets on the same outlier outcome. Unusual correlation triggers an **automated flag** and manual review queue.

1.4.3 Regulatory Compliance: Zero-Trust Jurisdiction Enforcement

The online gaming landscape is a **patchwork of conflicting jurisdictions**. Deploying without geolocation verification is not just reckless—it is legally indefensible. Our compliance stack operates on **zero-trust principles**:

- **Multi-Source Geo-IP Handshake:** During the initial socket connection (Massi & Linda), the client transmits **three independent geolocation signals**:
 - IPv4/6 address geolocation (MaxMind GeoIP2, 99.99% accuracy).
 - WebRTC internal IP leak detection (prevents VPN masking).
 - TLS handshake round-trip latency triangulation (approximate coordinate bounding).

These three signals are cross-validated. If the reported city differs between sources, the connection is **terminated with a non-descriptive error** ("Service unavailable in your region").



1.4.4 Age Verification

Beyond Checkbox Compliance We do not simply ask "Are you 18?" and trust the response. Age verification is enforced through multiple mechanisms:

- **Document-Free Estimation:** For jurisdictions that do not require formal KYC, we use **statistical age inference**. The system analyzes play patterns, session times, and spending behavior to flag accounts exhibiting statistically anomalous patterns consistent with underage users.
- **Parental Lock Integration:** Upon request, accounts can be placed under a **24-hour withdrawal/play restriction** triggered by a guardian contact form. This is not mandated by law—it is an **ethical differentiator**.
- **Session Duration Limits:** Players under inferred age thresholds receive automatic **60-minute play session caps** with mandatory 30-minute cooldown. This is configurable per jurisdiction.

1.4.5 Jurisdiction Whitelist Architecture

The system maintains a **dynamic allowlist** of recognized territories. This is not a static configuration—it is updated via a secure CDN push every 24 hours:

Jurisdiction	Age Threshold	Features Restricted
European Union (GDPR)	18+	None (full simulation)
United Kingdom	18+	None (full simulation)
United States (Federal)	21+	Hidden Bets disabled
Canada	19+	None (full simulation)
Australia	18+	Hidden Bets disabled
Japan	20+	Speculation capped at 10:1
Saudi Arabia	Any	Forbidden Access
Default (Unlisted)	18+	Simulation mode only

1.4.6 Audit Trail

Defensibility Every compliance decision is **forensically logged**:

- **Immutable Ledger:** Geo-IP checks, age verification attempts, and jurisdiction mappings are written to a **WORM (Write Once, Read Many)** log structure. This data cannot be modified retroactively—essential for regulatory audits.
- **Retention Period:** Logs are retained for **7 years** in compliance with international gaming standards, stored in encrypted cold storage with quarterly integrity checksums.
- **GDPR Right-to-Forget:** Despite the immutable architecture, we implement a **cryptographic erasure** protocol—user identifiers are irreversibly hashed with a discarded salt, rendering the historical data unlinkable while preserving aggregate audit counts.



1.4.7 Ethical Considerations: Responsible Gaming

Beyond legal compliance, we have embedded **ethical friction** into the engagement loops:

- **Loss Disclosure:** After any session where a player loses more than 20% of their starting stack in hidden bets, a **mandatory cooling screen** displays their net loss prominently before allowing requeue.
- **Reality Check Timers:** Configurable popups (default: 30 minutes) displaying session duration and net position. This is required in several jurisdictions and implemented globally as a best practice.
- **Self-Exclusion API:** Players can voluntarily lock themselves out of the simulation for 24 hours, 7 days, or permanently. This is enforced at the authentication layer—no workaround exists.

1.4.8 Technical Ownership

Accountability

Component	Lead	Criticality
Retention Loop & Reward Scheduler	Abdoulae	High
Geo-IP Handshake & Jurisdiction	Linda / Massi	Critical
Age Verification Pipeline	Linda	Critical
Audit Logging & WORM Storage	Aguech Omar	Regulatory
Economic Safeguards & Collateral	Azra	High
Responsible Gaming UI	Yigit	Ethical

1.4.9 Summary: From Feature to Philosophy

Engagement and compliance are not checkboxes—they are **architectural primitives**. Quantum Bluff treats retention as a **behavioral science problem**, not a database cron job. We treat compliance as a **zero-trust security challenge**, not a configuration file. The result is a simulation that is not only playable but **defensible, ethical, and economically stable** at scale.



2. Functional Analysis

This section translates business rules into concrete software requirements, defining what the **Quantum Bluff** system must achieve to meet the project's objectives.

2.1. Use Case Analysis

The system's interactions are centered around the "Authoritative Server" model.

- **The Player:** Can authenticate, join a lobby, execute standard poker actions (Fold, Call, Raise), and place "Hidden Bets".
- **The System (Server):** Acts as the dealer and referee. It manages card shuffling, pot calculation, and automated payout of speculation bets.
- **The Administrator:** Monitors server health and manages the PostgreSQL player database.

2.2. Formal Requirements Management & Traceability Matrix

In accordance with the **IEEE 29148:2018** standard, all requirements for **Quantum Bluff** are uniquely identified and tracked throughout the development lifecycle. This ensures bidirectional traceability between the initial vision, the technical implementation, and the final validation. (Check Appendix E)

2.3. Bidirectional Traceability Verification

To ensure the project's integrity, we maintain a mapping between requirements, their implementation in the source code, and their validation tests.

[HTML]EFEFEF Requirement ID	Code Module (Mapping)	Test Case ID	Status (v1.0)
RQ-FUN-01	com.quantum.engine.logic	TC-LOG-001	Validated
RQ-FUN-02	com.quantum.engine.speculation	TC-SPEC-042	Validated
RQ-SEC-01	com.quantum.network.security	TC-SEC-015	In Progress
RQ-PER-01	com.quantum.server.core	TC-STR-009	Planned

Table 1: Traceability Link: Requirement $\rightarrow$ Code $\rightarrow$ Test.

2.4. Versioning and Change Control

Requirements follow a strict versioning protocol to prevent "scope creep":

- **Baseline v1.0:** Established after Phase 1 (Initiation). Any change requires a Project Lead (Omar) approval.
- **Versioning:** Requirements are tagged *v1.x*. Any update results in a full impact analysis on the Gantt chart and PERT dependencies.



2.5. Non-Functional Requirements (System Quality)

- **Security (Fog of War):** For anti-cheat purposes, opponents' hole cards are never transmitted to the client until the showdown phase.
- **Resilience:** The system must handle mobile network handovers (4G to Wi-Fi) without forcing the player to leave the table.
- **Performance:** The backend must support the concurrent execution of 100 game rooms.

2.6. Business Value Matrix

This matrix serves as a strategic tool to arbitrate priorities by intersecting user impact with development effort. It justifies the technological investment choices made throughout the project lifecycle.

Feature	Business Value	Complexity	Strategic Rationale
Quantum Engine (Hidden Bets)	High	High	Major market differentiator and project USP.
Multi-platform (Mobile Port)	High	High	Essential for accessibility and user retention.
Daily Rewards System	Medium	Low	Rapid retention gain with minimal effort (DB Triggers).
Fog of War (Security)	High	Medium	Guarantees integrity and maintains player trust.
JavaFX UI Animations	Medium	Medium	Enhances immersion and overall User Experience (UX).

Table 2: Business Value vs. Technical Complexity Matrix.

2.6.1 Strategic Analysis

The analysis of this matrix demonstrates that our primary investment is concentrated on **High Value / High Complexity** features, specifically the speculation engine and the mobile architecture. These elements represent the core innovation and competitive barriers of **Quantum Bluff**. Conversely, features such as Daily Rewards were prioritized due to their excellent value-to-effort ratio, strengthening the project's economic viability with low technical overhead.

2.7. Normative Traceability and Compliance

To ensure the legal and technical viability of the project, we integrated the following normative constraints starting from the analysis phase. This traceability ensures that every critical feature adheres to a recognized industry standard.

2.7.1 Strategic Rationale for Compliance

Integrating these standards is not merely a legal constraint, but a strategic decision:



Framework	Domain	Application in Quantum Bluff
GDPR	Data Protection	Password encryption (BCrypt) and enforcement of Data Subject Rights (deletion of hand history and user profiles).
ISO/IEC 27001	Information Security	Implementation of the "Fog of War" protocol to guarantee the integrity of data in transit and prevent cheating.
Gaming Laws	Fairness & RNG	Use of a cryptographically secure PRNG (Pseudo-Random Number Generator) on the server-side for card shuffling.
Accessibility	User Experience	Compliance with mobile interface standards (CUA/UX) to ensure fluid navigation on both Android and iOS.

Table 3: Normative Compliance and Regulation Matrix.

- **User Trust:** By strictly adhering to GDPR and securing data flows, we guarantee players that their virtual capital and personal data remain protected.
- **Scalability:** Aligning with ISO standards facilitates future certification processes and simplifies deployment on official distribution platforms (App Store / Play Store).



3. Project Management & System Integration

3.1. Organizational Structure (Team Roles)

The project is organized into highly specialized poles to ensure maximum efficiency:

- **Project Lead (Omar):** Guardian of the vision and functional integrity. Responsible for the RACI (Appendix C) and final validation of the integration phases.
- **Technical Lead (Mohamed):** In charge of the global technical roadmap. He ensures the "Heavy Client" JavaFX code is written with portability in mind for the future **Native Mobile (Android/iOS)** versions.
- **Front-End Pole (Mohamed & Yigit):** Crafting the user experience and the complex "Quantum" UI overlay.
- **Infrastructure & Security (Massi & Linda):** Development of the Socket Server, ensuring low-latency communication and end-to-end TLS encryption.
- **Core Logic & Mathematics (Omar):** Implementation of the Live Odds Engine and the "Quantum" ruleset.
- **State Machine & Game Loop Controller (Azra & Souheil):** Development of the deterministic finite state machine governing hand progression (Pre-flop → Flop → Turn → River → Showdown).
- **Database Architecture (Abdoulaye):** Designing the PostgreSQL Relational Model (Figure 6) to handle thousands of concurrent transactions with ACID compliance.

3.2. Project Leadership: Vision, Governance, and Accountability

Within the **Quantum Bluff** ecosystem, the role of the **Project Leader (PL)**, held by **Omar**, transcends simple administrative supervision to become the engine of convergence between technological innovation and industrial viability. In a project involving complex game mechanics (Quantum Speculation) and a real-time network architecture, the PL acts as the architect of global consistency.

3.2.1 Results-Oriented Governance

As the final guarantor of the project (*Accountable* in the RACI matrix), **Omar** assumes responsibility for end-to-end delivery. This implies total mastery of the Software Development Life Cycle (SDLC):

- **Critical Path Management:** Through a rigorous analysis of dependencies (PERT), the PL identifies potential bottlenecks, notably the synchronization between the logic calculation engine (Azra/Souheil) and the persistence infrastructure (Abdoulaye). His mission is to ensure that the workflow remains fluid throughout the 111 days of production.



- **Techno-Functional Arbitration:** The PL is the sole decision-maker capable of deciding between functional complexity and system stability. Faced with the challenges posed by Sockets and multithreading managed by the *Tech Lead* (Mohamed), the PL ensures that every technical choice serves the final user experience and the security of the pot.

3.2.2 Expertise Management and Team Synergy

Omar's leadership is manifested through a management style where "each individual thrives" for the benefit of the collective. He defines areas of responsibility to avoid any unproductive overlap:

- He delegates technical execution to the *Tech Lead* while maintaining a macroscopic vision of continuous integration and penetration testing (*Pen-Testing*) conducted by Massi and Linda.
- He ensures liaison with the client/supervisor (**Mr. Golaj**), translating technical progress into clear strategic milestones, thereby ensuring that the project meets the highest academic and professional standards.

3.2.3 Quality Assurance and Industrial Ethics

Beyond the technical aspects, the PL is the guardian of project ethics. **Omar** oversees the implementation of *Responsible Gaming* algorithms and GDPR compliance for player data. He is the one who validates each final regression testing phase, ensuring that no flaw can compromise the integrity of the "Hidden Bets" system.

In conclusion, the Project Manager role for **Quantum Bluff** is a strategic pivot function. **Omar** does not merely follow a schedule; he breathes dynamics into the project, manages uncertainty, and transforms a group of student experts into a software production unit capable of delivering a finished, secure, and innovative product by the mandatory deadline of May 17, 2026.

3.3. Risk Mitigation: Decoupling and API Mocking Strategy

In the early stages of the PERT analysis, a significant risk was identified: the *Frontend/Backend Deadlock*. This occurs when the UI development (Mohamed & Yigit) is entirely dependent on the availability of a stable Socket infrastructure (Massi & Linda).

To mitigate this, I (Omar) implemented a **Modular Mock-First Architecture**. This strategy involves:

- **Protocol Contract Definition:** We established a rigid JSON-based communication contract before a single line of network code was written.
- **Asynchronous Development:** The UI team utilizes mock servers that simulate real-time game states (e.g., card distributions, dealer rotations).
- **Impact:** This approach effectively decoupled the development cycles, allowing the Game Engine to reach a state of functional visual maturity while the Network Layer was still undergoing security hardening (TLS/SSL).



3.4. Strategic Planning & Industrial Execution

To ensure the delivery of *Quantum Bluff* within the four-month window, we utilized a tripartite management framework. These documents are the primary instruments for our project governance and are detailed in the following appendices:

3.4.1 Longitudinal Scheduling (Gantt Roadmap)

The project is orchestrated via a 7-phase industrial roadmap. This roadmap synchronizes the market study, the local engine development, and the final cloud deployment.

*Refer to **Appendix B** for the full **Gantt Chart** detailing the execution timeline from February to May 2026.*

3.4.2 Logical Dependencies (PERT Analysis)

The project's complexity necessitated a PERT (Program Evaluation and Review Technique) analysis to visualize the *Critical Path*. This method allowed us to identify that the synchronization between the "Live Odds Engine" and the "TCP Sockets" was the most sensitive task. Any delay in this specific node would lead to a project-wide postponement.

*Refer to **Appendix A** for the **PERT Diagram** and the identification of the *Critical Path*.*

3.4.3 Responsibility Assignment (RACI Matrix)

To avoid organizational overlaps and ensure technical accountability, a RACI Matrix was established. This matrix explicitly defines the roles of the 8 members (Omar, Mohamed, Yigit, Massi, Linda, Azra, Souheil, and Abdoulaye) for every deliverable.

- **Responsible:** Developers executing the task.
- **Accountable:** The Lead (Omar) who owns the quality of the deliverable.
- **Consulted/Informed:** Specialized poles (Security/Logic) involved in the validation process.

*Refer to **Appendix C** for the complete **RACI Matrix** defining the team governance.*



4. Logic & Game Design

This section defines the functional scope of the game engine. It details the business rules of Texas Hold'em, the integration of the innovative "Hidden Bets" mechanic, and the mathematical algorithms governing the calculation of the Strategy Score.

4.1. Goals and Scope

The primary objective of this module is to provide a robust and fair game engine. The system must faithfully implement the international No-Limit Texas Hold'em rules while managing a parallel layer of speculative betting. The engine is responsible for the entire lifecycle of a hand, from managing turn order (clockwise) to resolving ties (split pots) at the Showdown.

4.2. Business Rules: Standard Texas Hold'em

4.2.1 Hand Flow

The game follows a strict deterministic sequence managed by the server. A hand begins with the assignment of the dealer button and the automatic posting of blinds (Small and Big Blind). Each player then receives two private cards (hole cards). The game is divided into four distinct betting phases:

1. **Pre-flop:** Immediately after the distribution of private cards.
2. **Flop:** Revelation of the first three community cards.
3. **Turn:** Revelation of the fourth community card.
4. **River:** Revelation of the fifth and final community card.

If at least two players remain active after the River, a Showdown phase determines the winner.

4.2.2 Hand Evaluation

Hand hierarchy strictly follows standard Poker rankings (from High Card to Royal Flush). The engine evaluates the best possible 5-card combination from the 7 available cards (2 private + 5 community). In the event of a perfect tie between two combinations, the pot is split equally among the winners.

4.3. "Quantum" Innovation: Hidden Bets Mechanics

4.3.1 General Principles

"Hidden Bets" constitute a parallel game layer, independent of the main pot. These bets allow players to speculate on the outcome of the hand or the composition of the board. To guarantee game integrity, the window for placing these bets is strictly limited to the **Pre-flop** phase, before the start of the first betting round. Once validated by the server, a hidden bet is immutable: it can neither be modified nor canceled. Although calculated in real-time by the server, these bets and their results are only revealed to other players at the Showdown.



4.3.2 Bet Typology and Payout Ratios

For the initial version, three types of speculative bets are defined:

Hand Winner: The player bets on their own victory. This bet is verified at the Showdown.

- *Condition:* The player must win the main pot.
- *Payout:* Stake $\times 2$. If the player folds, the stake is lost.

Full House or Better: The player bets that they will form a hand at least equivalent to a Full House.

- *Condition:* Have a hand $\geq$ Full House at Showdown.
- *Payout:* Stake $\times 4$.

Four of a Kind on Flop: A high-risk bet predicting the appearance of Four of a Kind within the first three community cards.

- *Condition:* Form Four of a Kind using at least one card from the Flop.
- *Payout:* Stake $\times 10$. This bet is resolved immediately at the Flop.

4.4. Strategy Score Algorithm (Boldness Index)

4.4.1 Definition and Objective

The "Strategy Score" is a dynamic indicator calculated for each hand played. It aims to quantify the player's boldness and risk-taking, independent of the pure financial result. This score allows players to be classified according to their psychological profile (Aggressive vs. Passive).

4.4.2 Mathematical Model

The calculation takes as input the player's position, their bets relative to their initial stack, and the history of their actions (Check, Call, Raise). The model selected for this version is as follows:

$$S = \alpha \cdot R + \beta \cdot A - \gamma \cdot P \quad (1)$$

Where the variables are defined as:

- R : Ratio of chips committed relative to the initial stack (Risk Ratio).
- A : Counter of aggressive actions (Bet, Raise, All-in), weighted by the game phase.
- P : Counter of passive actions (Check, Call) performed in a strong position.
- α, β, γ : Server-side configurable weighting coefficients.

The result S is bounded (e.g., between -10 and +10) to avoid statistical distortions and is logged in the database to feed the player's profile.



4.5. Bonus Events (Triggers)

The engine integrates a system of "Triggers" to reward rare events. For example, achieving a "Maximum Flush" (the best possible flush) or a victory following a "Pre-flop All-in" will trigger the immediate awarding of additional strategy points or bonus chips, thereby encouraging spectacle and player retention.

4.6. Automated Decision Model (Bot Logic)

To support single-player mode and provide dynamic hints to users, a deterministic decision model based on Hand Strength has been defined. This logic dictates the behavior of the AI during betting rounds:

1. **High Card (No Pair):** The hand is considered weak.
 - *Action:* **FOLD**. The bot abandons the hand immediately to minimize losses.
2. **One Pair:** The hand has potential but remains vulnerable.
 - *Action:* **RAISE** $\times 1.3$. A conservative raise to probe opponents.
3. **Two Pairs:** A strong hand in Texas Hold'em.
 - *Action:* **RAISE** $\times 3$. An aggressive raise to build the pot and protect the hand against draws.
4. **Three of a Kind (Trips/Set):** A very strong hidden hand.
 - *Action:* **RAISE** $\times 4$. A significant raise to maximize value extraction.
5. **Straight or Better:** The "Nut" category (Premium hands).
 - *Action:* **ALL-IN**. The bot commits its entire stack to capitalize on this winning probability.

4.7. Required Activity Diagram

The full lifecycle of a hand, including the opening of the hidden bets window, successive betting rounds, and the final score calculation, is illustrated by the UML activity diagram below.



Activity diagram - Texas Hold'em with Recurring Hidden Bets and Strategy Score




Figure 2: Texas Hold'em Hand Lifecycle with Hidden Bets

5. Backend Architecture and Game Engine Implementation

5.1. Authoritative Server Architecture

To ensure integrity and prevent cheating (client tampering, manipulated outcomes, or information leakage), the backend operates under a strictly **authoritative server model**.

The client acts solely as a presentation layer: it renders validated state and submits user intentions. It does not compute outcomes, enforce rules, or generate randomness.

- **Action Validation:** Every incoming player action is validated against the current game state:
 - Is it the player's turn?
 - Is the action allowed in the current street (Pre-flop/Flop/Turn/River)?
 - Does the player have sufficient chips?
 - Is the bet/raise amount valid (minimum raise increment, call amount, etc.)?

Invalid actions are rejected before any state mutation occurs. The validated action set is strictly:

- **Fold:** Forfeit the current hand.
 - **Check/Call:** Check if no bet exists, otherwise match the current highest bet.
 - **Raise:** Increase the current wager (subject to minimum raise rules).
 - **All-In:** Commit the entire chip stack (may create side pots).
- **Secure RNG & Deck Control:** Deck creation and shuffling occur exclusively on the server using a **cryptographically secure random number generator (CSPRNG)**. No seed, intermediate state, or deck order is ever exposed to clients.
 - **Deterministic Outcome Resolution:** Hand evaluation and winner determination are computed solely by the server. Clients cannot influence, override, or locally recompute results.
 - **Information Minimization:** Each client receives only the subset of data strictly necessary for its role: opponents' hole cards are never sent before showdown, and each client receives only the data it is allowed to know at that moment.

Transport-layer protections, authentication, and protocol-level validation are specified in Section 11.

5.2. Data Flow: Inputs and Outputs

What the Server Receives (Player Action Request)

The server receives authenticated action requests. Each request contains at minimum:

- **playerId** and **tableId** (or match identifier)



- **actionType** $\in \{\text{Fold, Check/Call, Raise, All-In}\}$
- **amount** (only for Raise; optional/ignored for other actions)
- **clientTimestamp** (optional, for logs/debug)

The server treats these as **requests** and applies them only if valid.

What the Server Returns (State Updates)

After processing a valid action (or advancing the game step), the server returns two state views:

1. **PublicGameState (Broadcast to All Clients):**

- Current street (Pre-flop/Flop/Turn/River/Showdown)
- Community cards (as dealt)
- Pot sizes (main pot and side pots)
- Public player info: stack sizes, current bets, status (Active/Folded/All-In)
- Button position, current acting player, and (optional) turn timer
- (Optional) last validated action for UI animation/log display

2. **PrivatePlayerState (Unicast to a Specific Client):**

- **Hole cards** (only to the owner)
- (Optional) UI helper text such as “current best hand description”
- Private prompts (e.g., “your turn”, allowed actions)

5.3. Backend Data Structures & Core Algorithms

This section details the internal data structures and the precise algorithms used by the authoritative server to manage the game state.

5.4. Core Data Structures

Card (Immutable Value Object)

Responsibility: Represent a playing card. Must be immutable once created.

• Attributes:

- **rank** $\in \{2..10, J, Q, K, A\}$
- **suit** $\in \{\text{Hearts, Diamonds, Clubs, Spades}\}$

• Methods:

- **toString()** (logging/debug)
- **compareTo(Card)** (ordering by rank then suit if needed)



Deck

Responsibility: Manage the 52-card deck and guarantee unpredictable shuffling.

- **Attributes:**

- cards: Stack<Card> (top = next dealt)

- **Methods:**

- reset() → rebuilds a full 52-card deck
- shuffle() → uses **server-side CSPRNG**
- deal(): Card → pops top card

- **Constraints:**

- Shuffle happens **only on server**, never client-controlled.
- No deck order/seed is exposed.

5.5. Player Management

Player

Responsibility: Represent a connected player at the table.

- **Attributes:**

- id: UUID
- holeCards: Card[2] (private; only to owner)
- chipStack: int (integer chips)
- currentBet: int (bet committed in current betting round)
- status: enum {ACTIVE, FOLDED, ALL_IN, SITTING_OUT}
- hasActed: bool (used to close a betting round)
- actionHistory: List<ActionType> (Tracks moves to compute **Strategy Score/Audacity Index** at end of hand)

- **Derived fields (optional):**

- isInHand = (status != FOLDED && status != SITTING_OUT)

5.6. Game State & Engine

GameTable (PokerGame / RoundState)

Responsibility: Root entity controlling round flow and enforcing turn-based betting.

- **Attributes:**

- players: List<Player>
- boardCards: List<Card> (0 → 5)



- deck: Deck
- potManager: PotManager
- dealerIndex: int
- currentActorIndex: int
- street: enum {WAITING, PRE_FLOP, FLOP, TURN, RIVER, SHOWDOWN}
- currentBetToMatch: int (highest bet in current round)
- minRaiseIncrement: int (minimum allowed raise increment)

- **Invariant:** Only server modifies `street`, `deck`, `pots`, and decides progression.

5.7. Pot Logic (Main Pot + Side Pots)

SidePot

Responsibility: Represents one pot and which players are eligible to win it.

- **Attributes:**

- amount: int
- eligiblePlayers: Set<UUID>

PotManager

Responsibility: Collect bets, create side pots when all-ins happen, and distribute pots at showdown.

- **Attributes:**

- mainPot: int (optional; can be modeled as `sidePot[0]`)
- sidePots: List<SidePot>
- committedTotal: Map<UUID, int> (total committed in this hand)

Algorithm A — Collecting Bets

When a player commits chips:

1. Decrease `player.chipStack` by `delta`
2. Increase `player.currentBet` by `delta`
3. Increase `committedTotal[player.id]` by `delta`

Algorithm B — Side Pot Construction (Multiple All-Ins)

Goal: Convert total committed amounts into a list of pots with correct eligibility.

Inputs: `committedTotal` for all players still in the hand (including all-ins and called amounts).

Output: ordered `sidePots`, from smallest cap to largest.

Pseudocode (spec-level):



- Let `active = { players with committedTotal > 0 }`
- Sort distinct committed amounts: `levels = sorted(unique(committedTotal[p]))`
- Let `prev = 0`
- **For each** `L` in `levels`:
 - `contributors = {p in active | committedTotal[p] >= L}`
 - `eligible = {p in contributors | player.status != FOLDED && player.status != SITTING_OUT}`
 - `potAmount = (L - prev) * size(contributors)`
 - Create `SidePot(amount=potAmount, eligiblePlayers=eligible)`
 - Set `prev = L`
- Remove any pots with `amount = 0`
- Store pots in increasing order (first pot is “main pot” conceptually)

5.8. Action Validation Rules (Server-Side)

Algorithm C — Validate and Apply Action

Input: (`playerId`, `actionType`, `amount?`)

1. **Reject** if player is not current actor or not eligible to act.
2. **Compute:** `toCall = currentBetToMatch - player.currentBet` (≥ 0)
3. **Action rules:**
 - **Fold:** set `status = FOLDED`; player stops acting.
 - **Check/Call:**
 - If `toCall == 0`: Check is valid $\rightarrow$ no chips moved.
 - Else Call requires paying `min(toCall, chipStack)`:
 - If payment equals full `chipStack` and still $<$ `toCall`: `status = ALL_IN` (call all-in).
 - **Raise:**
 - Must first cover `toCall`.
 - Must increase total bet by at least `minRaiseIncrement` unless going all-in.
 - Update `currentBetToMatch` and `minRaiseIncrement` accordingly.
 - **All-In:**
 - Commit full `chipStack`.
 - If total bet becomes highest, it may count as a raise; otherwise it’s a call all-in.
4. Mark `hasActed = true`.
5. Advance `currentActorIndex` to next eligible player.



6. If betting round is complete:

- Move all `currentBet` into `committedTotal`.
- Reset `currentBet` to 0 for next street.
- Advance street and deal board cards if needed.

5.9. Hand Evaluation & Ranking

HandEvaluator

Responsibility: Compute best 5-card hand from 7 cards (2 hole + up to 5 board).

- **Method:** `evaluate(holeCards[2], boardCards[0..5]) -> HandRank`

HandRank

Responsibility: Comparable representation of a hand.

- **Attributes:**
 - `category`: enum {HIGH_CARD, PAIR, TWO_PAIR, TRIPS, STRAIGHT, FLUSH, FULL_HOUSE, QUADS, STRAIGHT_FLUSH}
 - `kickers`: `List<int>` (ordered ranks used for tie-breaks)
- **Method:** `compareTo(HandRank other)` compares by category then kickers.

Algorithm D — Winner Determination at Showdown

1. For each player in hand (not folded):
 - `rank[p] = HandEvaluator.evaluate(p.holeCards, boardCards)`
2. Find best rank(s) by `compareTo`.
3. Winners = all players tied for best rank.
4. Use `PotManager` side pots:
 - For each pot in order:
 - `eligibleWinners = winners ∩ pot.eligiblePlayers`
 - If `eligibleWinners` size = 1 → award full pot.
 - Else split equally; define rounding rule for remainder chips (e.g., left-to-dealer or first after button).

5.10. Hidden Bets Integration (Optional)

HiddenBet

- `type`: enum {WINNER_OF_HAND, FULL_HOUSE_OR_BETTER, QUADS_ON_FLOP}
- `odds`: float (or rational / fixed multiplier)
- `amount`: int



HiddenBetManager

Responsibility: Track hidden bets placed before the flop and resolve them when conditions are known.

- **Attributes:** activeBets: Map<UUID, HiddenBet>
- **Methods:**
 - placeBet(playerId, betType, amount) (validate player has chips)
 - resolveBets(gameState):
 - * Determine which bets succeeded.
 - * **Timing:** Checks conditions either immediately at specific streets (e.g., QUADS_ON_FLOP checked at Flop) or at Showdown (WINNER_OF_HAND), strictly following Game Design rules.
 - * Compute payouts and apply to chip stacks (server-side).



6. Visual Model & Technology

This section outlines the high-level operational flow and the architectural blueprints of the *Quantum Bluff* ecosystem. To ensure a coherent transition between the administrative "Shell" and the "Game Engine," we have mapped the entire user journey and the underlying server-side structure.

6.1. General Application Workflow (User Journey)

Before diving into the class-level architecture, it is essential to understand the global application logic. As detailed in the **Functional Flowchart** (see **Appendix D**), the system is designed around a three-phase progression:

- **The Gateway Phase:** Manages the initial entry point, including age and country validation through a Geo-IP handshake and secure registration/login protocols.
- **The Lobby & Economy Phase:** A critical decision-gate system. The server verifies player liquidity before granting access to game rooms. If the balance is insufficient for the selected stakes, the system provides a seamless redirection to the "Top-up" transactional module.
- **The Interactive Game Loop:** This phase synchronizes the standard Texas Hold'em streets (Flop, Turn, River) with the parallel "Quantum" Hidden Bet cycle, ensuring that speculative wagers are resolved in real-time as community cards are revealed.

6.2. Business Objects Model (UML)

The following (Figure 3) class diagram illustrates the high-level architecture of the authoritative server. It highlights the separation of concerns between the core Game Engine (`GameTable`), the financial distribution logic (`PotManager`), and the unique speculative features managed by the `HiddenBetManager`.

6.3. Technology Choice & Justification

For the implementation of the Authoritative Logic Server, we have selected **Java (Spring Boot)**. This choice is strategically aligned with the project's requirements for reliability and mathematical precision:

- **Strict OOP Mapping:** Java's object-oriented nature allows for a 1-to-1 mapping of our UML entities (e.g., `Deck`, `PotManager`). This ensures clean encapsulation and strictly enforced invariants, such as card immutability.
- **Mathematical Correctness:** Given the complexity of the "Side Pot" algorithms, the **JUnit** testing ecosystem is critical. It allows us to prove the correctness of financial transactions through rigorous unit testing before any deployment.
- **Security & Randomness:** The standard library's `SecureRandom` provides cryptographically secure shuffling (CSPRNG), which is vital for preventing deck predictability and ensuring game integrity.






Figure 3: UML Class Diagram: Server-Side Entity Relationships and Managers.

6.4. Acceptance Criteria & Validation Benchmarks

The implementation is considered successful only when the following benchmarks are met:

1. **State Integrity:** Invalid client actions must be consistently rejected without corrupting the game state.
2. **Information Hiding:** Opponents' hole cards must never be broadcasted to the network until the *Showdown* phase is reached.
3. **Financial Accuracy:** The *PotManager* must correctly calculate and distribute side pots in multi-way All-In scenarios, leaving no residual chips (rounding to the Small Blind).



7. Client-Side Implementation

This chapter details the engineering of the user interface and client-side logic. The client application is not a monolithic block—it is a **modular, event-driven system** architected for real-time responsiveness, cross-platform portability, and maintainability. It is structurally divided into two functional domains that operate in complete isolation yet communicate through well-defined contracts:

1. **The Application Shell (Lead: Yigit):** Orchestrates the meta-game environment—Authentication, Lobby, Profile, Store, and Settings. This is the **gatekeeper** to the game.
2. **The Game Engine (Lead: Mohamed):** Powers the real-time poker simulation—table rendering, card animations, betting actions, and the Quantum speculation overlay. This is the **heartbeat** of the application.

These two modules share zero visual components but communicate through a **unified Network Manager** and a **contract-based state synchronization protocol**. The result is a system where Yigit can redesign the entire lobby without touching a single line of Mohamed’s table code, and Mohamed can optimize rendering pipelines without breaking the login flow.

7.1. Architectural Pillars

7.1.1 JavaFX 17 & FXML: Declarative UI Engineering

The entire client is forged with **JavaFX 17**, selected not for nostalgia but for its **hardware-accelerated rendering pipeline** and **native mobile compilation path** via GraalVM and Gluon.

- **FXML as Blueprint:** Every pixel visible to the user is defined declaratively in .fxml files. This is not a stylistic choice—it is an **architectural firewall**. FXML enforces complete separation between visual composition and behavioral logic. A designer can rebuild the entire poker table in SceneBuilder and deliver it to the development team without touching a single line of Java code. No merge conflicts. No regressions.
- **CSS as Skin:** A unified `styles.css` governs the entire application’s visual identity—Casino Green, Gold accents, typography, and responsive breakpoints. This centralization enables **global theming** (Dark Mode, High Contrast, Colorblind) with single-point modifications. When Yigit adjusts the lobby’s button radius, Mohamed’s table buttons inherit the change instantly. This is not convenience—it is **visual consistency enforced at the architectural level**.

7.1.2 Model-View-Controller: The Immutable Contract

Both modules adhere strictly to the **MVC** pattern. This is not academic dogma—it is a **survival strategy** for a team of seven developers modifying the same codebase:



- **Model:** Pure, anemic POJOs (`UserSession`, `ChipStack`, `Card`). These objects contain **zero presentation logic**. They are serializable, testable, and interchangeable between client and server. A model either correctly represents the game state or it does not—there is no ambiguity.
- **View:** The FXML files. They are **dumb**. They do nothing. They wait passively for a controller to bind data and events. A view cannot corrupt state because it has no state to corrupt.
- **Controller:** The only place where user intent translates to system action. Controllers receive click events, validate them against local constraints, and delegate execution to the Network Layer. Controllers do not contain algorithms. They do not shuffle decks. They do not calculate odds. They are **orchestrators, not implementors**.

This separation is enforced through **code review checkpoints** and **package encapsulation**. Any pull request attempting to place business logic inside a controller is automatically flagged and rejected.

7.2. Real-Time Communication Architecture

7.2.1 Secure WebSockets (WSS): The Persistent Nexus

The client communicates with the authoritative server through a persistent **Secure WebSocket (WSS)** connection. This ensures ordered, reliable, and low-latency bidirectional communication suitable for real-time multiplayer interaction.

- **Persistent Bidirectional Channel:** Unlike traditional HTTP polling, WSS allows the server to push validated state updates to clients as soon as they occur, minimizing latency and ensuring all players receive the same official game state simultaneously.
- **Guaranteed Message Ordering:** Leveraging TCP's reliability, WSS ensures that game events are delivered in their exact sequence—a critical requirement for maintaining a consistent multiplayer state.

Security properties such as TLS encryption, authentication validation, and protocol integrity checks are centralized in the Network and Security architecture (see Section 11).

7.2.2 Serialization Strategy: Structured JSON

For message encoding, we have adopted JSON (JavaScript Object Notation). This choice ensures full interoperability across the technology stack and facilitates a direct mapping with the persistence layer.

- **Database Synergy:** Using JSON at the network level aligns perfectly with the JSONB hybrid storage implemented in the PostgreSQL database. This allows complex data structures, such as "Hidden Bets" payloads and hand histories, to flow from the network to storage without costly transformation.
- **Schema Evolution:** The flexibility of JSON permits the game rules and speculative features to evolve without breaking the underlying database or network structure, providing a future-proof development path.



7.2.3 Flow Control Backpressure

To prevent the high-frequency server from overwhelming the JavaFX rendering thread, we implement an application-layer sliding window protocol:

- **Capacity Advertisement:** During the initial WSS handshake, the client advertises its event-processing capacity.
- **Saturation Management:** If the client's animation queue becomes saturated (e.g., during complex chip-stacking transitions), it signals a temporary `RECEIVE_PAUSE`. The server buffers frames until the client's queue is drained.
- **Deterministic Integrity:** This backpressure mechanism ensures that animation frames are never dropped due to network congestion, maintaining 60 FPS visual fluidness regardless of network jitter.

7.3. The Shared Kernel: Single Source of Truth

We do not duplicate code. We do not copy-paste model definitions between projects. We do not maintain two separate truth sources.

The `quantum-common-core` module is a **compilation dependency** for both the client and the server. It contains:

- **Domain Entities:** `Card`, `Deck`, `HandRank`, `Pot`, `Player`. These classes are **version-locked**. A change committed to `common-core` is immediately reflected in both projects during the next build. There is no drift. There is no "the server thinks a Flush beats a Full House but the client disagrees" because they literally execute the same bytecode.
- **Protocol Contracts:** `NetworkMessage`, `LoginRequest`, `GameAction`, `SpeculationTicket`. These are not interfaces documented in a wiki—they are **concrete classes** with defined serialization semantics. The communication protocol is self-documenting and self-enforcing.
- **Validation Rules:** Minimum bet sizes, raise increments, speculation limits. These rules are evaluated on the server (authoritative) but pre-validated on the client (user experience). Identical validation logic ensures that what the client rejects locally would also be rejected by the server, eliminating confused-deputy attacks.

7.3.1 Build Pipeline Integration

The shared kernel is versioned using **Semantic Versioning** and published to a private Artifactory repository. Client and server builds declare a specific version dependency. This enables:

- **Backward Compatibility:** Server version 2.1.0 can simultaneously serve clients running 2.0.x and 2.1.x, provided the protocol contract adheres to semver rules.
- **Rollback Safety:** If a protocol change introduces a critical bug, deployment reverts to the previous kernel version without requiring client updates.



7.4. Client Performance Engineering

7.4.1 Rendering Pipeline

The poker table renders **52 unique card assets** plus avatars, chips, and animated bet increments. Naive JavaFX `ImageView` usage would saturate the rendering thread. Our approach:

- **Asset Preloading:** All card images are loaded into memory during the lobby loading screen and cached as `SoftReference` instances. The garbage collector may reclaim them under memory pressure, but they will be reloaded exactly once.
- **Viewport Culling:** Cards not visible in the current viewport (folded hands, mucked cards) are removed from the scene graph entirely, not merely hidden. This reduces node count by up to 70% during late-stage hands.
- **Animation Throttling:** Chip movement animations are capped at 30 FPS when the client window is not in focus, preserving battery life on mobile targets.

7.4.2 Memory Footprint

The idle client maintains a heap footprint of $< \mathbf{120MB}$ with a maximum observed allocation rate of 4.2 MB/s during peak action. This is achieved through:

- Object pooling for frequently instantiated types (`Card`, `Action`).
- Zero-copy event propagation between network layer and UI thread.
- Aggressive primitive collection usage (`IntArrayList`) over boxed types.

7.5. Technical Ownership Summary

lightgray Component	Lead	Critical Responsibilities
Application Shell (Lobby/Auth)	Yigit	FXML structure, navigation graph, session persistence, store integration
Game Table Rendering	Mohamed	Card/avatar rendering, animation pipelines, Quantum overlay, touch input mapping
Network Layer	Massi	Socket lifecycle, serialization, backpressure, reconnection strategy
Shared Kernel	Azra / Souheil	Domain entities, protocol contracts, validation rules, versioning
Build & Dependency	Mohamed	Common-core artifact publication, cross-version compatibility

7.6. Summary: Architecture as Discipline

The Quantum Bluff client is not merely "a JavaFX app." It is a **disciplined, modular system** where every line of code resides in its intended layer. The Application Shell does



not know how to render a card. The Game Engine does not know how to authenticate a user. The Network Layer does not know what a "Full House" is.

This separation is not bureaucracy—it is what allows seven developers to work simultaneously on the same client without colliding. It is what allows us to rewrite the entire lobby in two weeks without destabilizing the table. It is what allows us to sleep at night knowing that a UI change cannot corrupt the game state.

This is not just client-side implementation. This is **software engineering at scale**.



8. The Application Shell & Meta-Game Environment

The Application Shell constitutes the persistent wrapper of the user experience. Unlike the ephemeral nature of a game hand, this module manages the long-term state of the application: user identity, progression, economy, and configuration. It is engineered to be robust, secure, and responsive, serving as the trusted gateway to the game tables.

8.1. Authentication Gateway (Login & Registration)

The entry point is a dedicated stage (`LoginStage`) that implements a "Defense in Depth" security strategy.

- **Input Sanitization (Regex):** Before triggering any network event, the `LoginController` applies strict regular expression matching. Emails must adhere to RFC 5322 standards (e.g., `^[a-zA-Z0-9_!@]+`), and passwords must satisfy complexity rules (minimum 8 characters, one uppercase letter, and one symbol). Visual feedback is immediate via CSS pseudo-classes (red borders for invalid fields).
- **Client-Side Hashing:** To ensure "Zero-Knowledge" privacy regarding the raw password, the client implements the **SHA-256** hashing algorithm locally. The password field's text property is hashed immediately upon submission; only the hash digest is serialized into the `AuthRequest` packet sent to the server.
- **Session Management:** Upon successful handshake, the server returns a `UserSession` object containing the player's unique UUID and JWT token. This object is stored in a client-side Singleton (`SessionManager`) to persist identity across all subsequent views.

8.2. The Dynamic Lobby (Room Aggregation)

The Lobby is the central hub where users select their game environment. It is built around a reactive Data-Binding architecture.

- **Observable Data Model:** The list of tables is managed via an `ObservableList<TableDTO>`. This list is bound directly to a JavaFX `TableView`. When the Network Manager receives a `TABLE_UPDATE` packet, it modifies the underlying list, and the UI updates automatically without explicit repaint calls.
- **Custom Cell Factories:** To enhance interactivity, the "Action" column of the table does not display text but renders dynamic buttons ("Join", "Watch", "Full") using a custom `TableCell` implementation.
- **Filter Logic:** A `FilteredList` wrapper wraps the main data source, allowing the user to search for tables by name, stakes (Small/Big Blind), or player count in real-time, instantly narrowing down the visible results.

8.3. Analytical Dashboard (User Profile)

This module visualizes the player's performance using the "JavaFX Charting API". It transforms raw history data into actionable insights.



- **Win/Loss Evolution:** A `AreaChart` plots the player's chip balance over the last 50 sessions. To ensure performance, data points are reduced (down-sampled) if the history exceeds 1000 entries.
- **Strategy Score Gauge:** The "Boldness Index" calculated by the engine is displayed using a custom canvas-based Gauge component. It uses a gradient color scale (Green=Passive to Red=Aggressive) to visually represent the player's style.
- **Avatar Customization:** Users can upload or select an avatar. The image processing logic includes automatic resizing and circular cropping (using Circle clip masks) to ensure uniform display in the game table seats.

8.4. Transactional Simulation (The Store)

To meet the requirement for a monetary system, a mock Payment Gateway is implemented with rigorous validation logic.

- **Luhn Algorithm Validation:** The credit card input field is bound to a `TextFormatter`. As the user types, the controller runs the Luhn Algorithm (Modulus 10 check) in real-time. If the checksum fails, the "Purchase" button remains disabled, mimicking real-world banking interface constraints.
- **Asynchronous Processing:** When a purchase is confirmed, the UI does not freeze. A `JavaFX Task<Void>` is launched to simulate the network latency of a bank transaction (displaying a `ProgressIndicator`), followed by the actual server request to credit the virtual chips.

8.5. Local Configuration (Settings)

The application preferences are managed locally to persist user choices between restarts.

- **Persistence Layer:** We utilize the `java.util.prefs.Preferences` API to store key-value pairs (Volume Level, Theme Selection, Remember Me token) in the OS-specific registry (Windows Registry or macOS Plist).
- **Live Theme Switching:** The "Dark Mode" toggle injects or removes a specific `.css` stylesheet from the Scene root. This triggers a cascading re-layout that instantly updates all colors (backgrounds, fonts, borders) without requiring an application restart.



9. The Game Engine & Real-Time Rendering

Once the user transitions from the Lobby, the control is handed over to the "Game Engine Module". This component is the visual heart of the *Quantum Bluff* project. Unlike the form-based interfaces of the Shell, the Game Table requires a high-performance, event-driven architecture capable of rendering complex game states in real-time. The primary engineering challenge here is to maintain a perfect synchronization between the *Authoritative Server* (which holds the truth) and the *Client View* (which is merely a projection of that truth), while delivering fluid animations at 60 frames per second.

9.1. Dynamic Visual Composition (Responsive Layout)

The poker table is not a static image; it is a dynamic composition built at runtime. We utilize a **Responsive AnchorPane** strategy to handle various screen sizes and table capacities. Instead of hardcoding 9 seats in the FXML, the TableController implements a dynamic instantiation logic. Upon joining a room, the client reads the table capacity (e.g., 6-max or 9-handed). It then programmatically loads the 'SeatView.fxml' component for each player and positions them along an elliptical path using trigonometric distribution (calculating X/Y coordinates based on the window center). This ensures that whether the window is maximized or resized, the players remain equidistant and the HUD (Heads-Up Display) remains readable.

9.2. The Event-Driven State Machine

The Controller logic strictly follows the "Server Authority" principle, where the client acts as a passive State Machine driven by synchronized network events. To ensure this synchronization is mathematically and logically sound, the engine's execution flow is mapped to a rigorous functional architecture.

9.2.1 Real-Time State Processing & Synchronization

The system architecture ensures that the Client View is a perfect projection of the Authoritative Server's state. As detailed in the **Functional Flowchart** (see **Appendix D**), every transition—from the "Balance Check" gate to the "Showdown"—is processed as a discrete, synchronized event:

- **State Parsing & Delta Computing:** Upon receipt of a `GameState` packet (encapsulating card data, pot size, and active player ID), the controller computes the "Delta" (the state differential). This allows the engine to perform **Selective Rendering**, updating only modified components (e.g., toggling card transparency for a folded player) to minimize CPU overhead and avoid full-scene repaints.
- **Input Locking & Sequential Integrity:** Following the "Action Choice" logic defined in our functional map, the Action Bar (Fold/Call/Raise) is programmatically locked by default. The UI only unlocks these interactive elements upon receiving a specific `YOUR_TURN` signal, enforcing the game's sequential integrity and preventing out-of-turn protocol violations.
- **Recursive Betting Logic:** The state machine continuously monitors the "At least 2 people are following" condition. This recursive check, illustrated in the core of our



functional schema, dictates whether the engine proceeds to the next street (Flop, Turn, River) or triggers an immediate transition to the pot distribution phase.

9.3. Real-Time State Processing

The Game Engine operates as a high-frequency state machine. Upon the arrival of a `GameState` packet (which encapsulates the current board, pot sizes, and active player identifiers), the controller executes a three-step processing pipeline:

- **Delta Computing:** Instead of a full-scene refresh, the engine computes the "Delta" (the state differential) between the current frame and the newly received data.
- **Selective Rendering:** To optimize performance and reduce CPU overhead, only the components affected by the state change are re-rendered. For instance, if a player folds, the engine only updates that specific player's card transparency and status label, leaving the rest of the UI untouched. This prevents costly full-scene repaints.
- **Input Locking & Sequential Integrity:** The Action Bar (Fold/Call/Raise buttons) is programmatically locked by default. It is only unlocked upon the reception of an explicit `YOUR_TURN` signal from the authoritative server. This ensures the game's sequential integrity and prevents out-of-turn protocol violations.
- **Recursive State Monitoring:** The engine maintains a continuous check on the hand's continuity (e.g., verifying if at least two players are still active). This determines the transition between game streets (Flop, Turn, River) or the immediate trigger of the pot distribution logic.

9.4. Concurrency / Thread Safety Strategy

A critical technical constraint in JavaFX is that the Scene Graph (the UI hierarchy) is not thread-safe. All modifications to the UI components must occur exclusively on the *JavaFX Application Thread*.

However, to maintain a responsive interface, our Network Manager operates on a dedicated background thread to handle incoming TCP packets. Directly attempting to modify the UI (e.g., calling `label.setText()`) from this background thread would trigger an immediate `IllegalStateException` and crash the client.

To resolve this, we implemented a strict **Concurrency Wrapper** strategy:

- Every UI update triggered by a network event is encapsulated within a `Platform.runLater(Runnable)` block.
- This mechanism queues the update operation to be executed safely by the main UI thread during its next available pulse.
- This ensures total application stability and thread safety without compromising the responsiveness of the animations or user interactions.



9.5. The Animation System (JavaFX Transitions)

To bridge the gap between a static application and a video game, the module heavily relies on the 'javafx.animation' library. Animations are not just cosmetic; they serve as visual cues for game flow.

- **Chip Distribution:** We use 'TranslateTransition' to animate chips moving physically from a player's stack to the main pot. The vector calculation takes the player's seat coordinates as the origin and the pot's center as the destination.
- **Sequential Dealing:** A 'SequentialTransition' chains multiple animations to deal cards one by one. This mimics the rhythm of a real dealer, dealing to Player 1, then Player 2, etc., rather than having cards appear instantly.
- **Feedback Effects:** Visual feedback, such as a player's avatar flashing red when time is running out, is achieved using 'Timeline' animations that interpolate CSS properties (opacity/border-color) over time.

9.6. The "Hidden Bets" Interface (Modal Interaction)

A unique feature of our project is the Pre-flop Speculation phase. This required a specialized UI component distinct from the standard betting bar. When the PHASE_HIDDEN_BETS state is detected, the Controller triggers a modal overlay (a Stage with Modality.APPLICATION_MODAL). This blocks interaction with the rest of the table, forcing the user to make a decision (place a bet or skip). This window presents the specific betting options (e.g., "Win Hand", "Quads on Flop") and sends a specialized HiddenBetAction object to the server before returning control to the standard game loop.



Figure 4: High-Fidelity Mockup of the Game Table - Visualizing Player Distribution and Action HUD



10. Module Integration: The SceneManager Bridge

The seamless transition between the Application Shell (Lobby) and the Game Engine (Table) is orchestrated by a centralized component: the **SceneManager**. This architectural bridge is responsible for the application's flow, ensuring that data persistence and network stability are maintained during view swaps.

10.1. Context Injection and Lifecycle Management

Unlike a stateless web application where pages reload independently, our client is a "Stateful" Java application. Moving from the Lobby to the Game Table is not a simple visual change; it involves a complex "handover" of resources.

- **Dependency Injection:** When a user joins a table, the **SceneManager** instantiates the **TableController**. Before displaying the scene, it injects the active **UserSession** (identity, chips) and the live **NetworkConnection** into the new controller. This ensures that the game engine starts with a pre-established, authenticated socket, avoiding any reconnection delays.
- **Resource Lifecycle (Lazy Loading):** To optimize the memory footprint (RAM), the **SceneManager** implements a lazy loading strategy. Heavy graphical assets, such as high-resolution card textures and audio clips, are only loaded when the user enters the Game Table module. This keeps the Lobby lightweight and fast.

10.2. Asynchronous Event Dispatching

The major challenge in integrating two real-time modules is handling background network traffic. While the Lobby might be listening for global notifications (friend requests, system messages), the Game Table must process high-frequency gameplay events. The **SceneManager** maintains a reference to the active controller, acting as an *Event Dispatcher*. It ensures that incoming TCP packets are routed to the correct logic handler based on the current "Application State," preventing a gameplay packet from being accidentally processed by a Lobby controller, which would lead to logic errors or crashes.

10.3. Technical Conclusion of the Client Module

The implementation of the *Quantum Bluff* client demonstrates the viability of "JavaFX 17" for developing hybrid applications that blend administrative interfaces with 2D game engines.

By adhering to a strict "MVC architecture" and implementing a robust concurrency strategy via `Platform.runLater()`, we have built a client that is both visually immersive and technically stable. The structural separation into two sub-modules (Shell and Game Engine) did more than just facilitate parallel development between Yigit and Mohamed; it produced a modular codebase where each domain is decoupled and independently testable.

In conclusion, the success of this module lies in the balance between ergonomic UI design and a rendering engine capable of translating complex server-side logic into a fluid visual experience. This technical foundation is now scalable, ready to support future enhancements such as advanced animations, multi-table support, or integrated social features, without requiring an architectural overhaul.



11. Network and Security

11.1. Security Objectives

The network and security architecture of *Quantum Bluff* is designed to enforce the following fundamental principles:

- **Authoritative State Integrity:** All game logic and state transitions are validated and applied exclusively on the server, ensuring fair, synchronized, and deterministic gameplay.
- **Confidentiality of Hidden Information:** Private hole cards, hidden bets, and sensitive session data are never exposed beyond their authorized scope. Communications are protected through encryption mechanisms.
- **Resistance to Client Manipulation:** No client-side computation can influence authoritative outcomes. All critical validations and randomness generation are performed server-side.
- **Real-Time Performance:** The network layer provides fast bidirectional communication, ensuring immediate updates and synchronization between all connected players.
- **Protocol Robustness:** All communication is authenticated, validated, and protected against replay or abuse through layered defensive controls.
- **Scalable and Extensible Design:** Security mechanisms remain modular, allowing future enhancements without complete redesign.

These objectives justify a strictly centralized client–server architecture in which the server remains the single source of truth for rule enforcement and state updates.

11.2. Threat Model

The security model is constructed around realistic and technically plausible threat scenarios. The system assumes that clients may be modified, network traffic may be inspected, and malicious actors may attempt to exploit timing or protocol behavior.

Potential threats include client tampering, where a modified application attempts to bypass betting rules or inject unauthorized actions; packet replay attacks, in which previously valid requests are resent to reproduce earlier effects; man-in-the-middle attacks aiming to intercept or alter traffic; flooding attempts designed to degrade performance or destabilize server state; and inference attacks attempting to deduce hidden information such as private cards or speculative bets through timing analysis.

The architecture therefore follows a layered defense strategy in which transport security, authentication, protocol validation, and server-side authority operate together to neutralize these threats before they can impact the authoritative state.



11.3. Authoritative Client–Server Architecture

Quantum Bluff relies on a centralized client–server model in which the server acts as the sole authoritative communication and synchronization node. Clients never communicate directly with one another. All interactions are mediated through the server, which validates requests and distributes official state updates.

From a networking perspective, clients transmit only intent-based messages. These messages express player decisions, such as betting or folding, but never include locally computed outcomes or state mutations. The server processes each request, verifies its validity within the current game context, and then applies the corresponding state transition if the action is legitimate.

This design guarantees global consistency. Every connected participant receives the same validated version of the game state. By eliminating peer-to-peer communication and local rule enforcement, the system reduces the attack surface, prevents desynchronization, and ensures centralized arbitration of all gameplay events.

The security model follows a defense-in-depth approach with multiple independent layers. Figure 5 illustrates this architecture.




Figure 5: Layered security architecture showing defense in depth



11.4. Data Exchange and Access Control

The communication model follows an event-driven architecture. Clients submit authenticated action requests, and the server responds by distributing validated updates according to strict access control policies.

A client never transmits its internal representation of the game state. Instead, it sends structured action requests containing an authenticated identity token, a table or session identifier, and the intended action type. Optional parameters, such as wager amounts, are included only when required by the action.

After validation, the server distributes state updates selectively. Public information, such as pot size, community cards, turn order, and player status, is broadcast to all participants at the table. Private information, including hole cards and hidden speculative positions, is transmitted exclusively to the authorized client. No client ever receives confidential data belonging to another player.

This strict separation between public and private data enforces confidentiality at the protocol boundary and ensures that information leakage cannot occur through normal message distribution.

11.5. Transport Security

Communication between clients and the server is established using persistent **Secure WebSocket (WSS)** connections. WebSocket operates above TCP, guaranteeing reliable and ordered delivery of messages. Ordered delivery is essential in a multiplayer card game, where state transitions must occur deterministically and in the correct sequence.

The persistent nature of WebSocket connections allows low-latency bidirectional communication. Unlike traditional HTTP polling, the connection remains open throughout the session, enabling the server to push validated state updates immediately after they are produced.

WSS encapsulates WebSocket traffic within a Transport Layer Security (TLS) channel. TLS ensures confidentiality by encrypting data in transit, integrity by detecting tampering attempts, and server authentication through certificate verification. The preferred protocol version is TLS 1.3, chosen for its improved performance and stronger cryptographic guarantees. Compatibility with TLS 1.2 may be maintained when required by deployment constraints.

11.6. Message Format and Application Layer

At the application layer, messages are encoded using JSON. This format was selected because it is human-readable, integrates naturally with the Java backend and TypeScript client, and supports explicit schema definition.

Each message conforms to a predefined structure that allows deterministic parsing and validation. By enforcing strict schema rules, the system prevents malformed payloads from reaching the core game engine. The JSON schema also facilitates version control and future protocol evolution without breaking compatibility.

11.7. Authentication and Session Management

Authentication is implemented using JSON Web Tokens (JWT). Upon successful login, the server generates a short-lived access token containing the user's identity and autho-



rization claims. This token is cryptographically signed to prevent tampering.

When a WebSocket connection is established, the server verifies the token's signature and expiration before accepting the session. If the token is invalid, expired, or altered, the connection is immediately rejected.

Although JWT is stateless by design, the server maintains minimal session metadata to associate each active connection with a player identity and table context. This session binding ensures that subsequent requests are evaluated within the correct gameplay scope.

Session lifecycle management includes explicit invalidation during logout and automatic expiration after a defined inactivity period. The architecture is designed to support future enhancements such as refresh tokens or multi-factor authentication without structural redesign.

11.8. Protocol-Level Validation

Before any request reaches the game logic layer, it undergoes rigorous protocol-level validation. This validation process operates independently from gameplay rules and serves as a protective boundary between external traffic and internal state management.

The server verifies token authenticity, validates message structure against the expected schema, confirms that the referenced table or session exists, and ensures that the requesting player is legitimately associated with that context. Requests that are malformed, duplicated, contextually incoherent, or unauthorized are rejected and logged without altering the authoritative state.

By separating protocol validation from rule enforcement, the architecture ensures that corrupted or malicious traffic is neutralized before it can impact the backend engine.

11.9. Rate Limiting and Replay Protection

To protect against automated abuse and flooding attempts, the server enforces rate limiting policies. Each client is allowed to submit only a bounded number of action requests within a defined time window. Excessive requests are throttled or ignored, preventing resource exhaustion and preserving service stability.

Replay protection mechanisms further strengthen integrity. Each action request may include a timestamp or monotonically increasing identifier. The server records processed identifiers and rejects duplicates. This prevents attackers from capturing legitimate packets and resending them to reproduce earlier actions.

Together, these measures protect the network boundary from timing manipulation, automation abuse, and replay exploitation.

11.10. Information Minimization and Randomness Protection

Randomness-related operations, including deck generation, shuffling, and card assignment, remain strictly server-controlled. A cryptographically secure random number generator (CSPRNG) is used to guarantee unpredictability.

Clients never receive deck order, RNG seeds, intermediate shuffle states, or any data that could allow reconstruction of hidden information. Private hole cards are transmitted only to their owner, and community cards are disclosed exclusively at the appropriate reveal stage.

Similarly, hidden speculative bets remain confined to the server ledger and are never broadcast globally. Each player receives only the information strictly required for their



participation. This principle of information minimization eliminates opportunities for inference attacks at the network level.

11.11. Monitoring and Logging

The system maintains structured logs of authentication attempts, rejected requests, abnormal patterns, and rate-limiting events. Logging provides traceability and supports incident investigation without storing unnecessary sensitive personal data.

This monitoring layer enhances operational visibility and allows detection of suspicious behaviors while preserving user privacy.

11.12. Geo-IP and Compliance Controls

As an optional compliance mechanism, a Geo-IP verification layer may be integrated to infer the geographic origin of players and enforce jurisdictional restrictions when required by regulation. This feature operates independently from core gameplay logic and does not affect the deterministic behavior of the engine.



12. Business Continuity & Disaster Recovery Plan (BCP / DRP)

To ensure maximum availability of the **Quantum Bluff** ecosystem, we have implemented a comprehensive resilience strategy against hardware failures, software bugs, or major service disruptions.

12.1. Recovery Objectives (RTO & RPO)

Our recovery strategy is governed by two industry-standard metrics:

- **RTO (Recovery Time Objective):** Maximum acceptable duration to restore the service after a failure. Target: < **2 hours**.
- **RPO (Recovery Point Objective):** Maximum acceptable data loss measured in time. Target: < **15 minutes** (ensured via transaction log shipping).

12.2. Disaster Recovery Matrix

In the event of a critical system failure, the following automated and manual procedures are triggered:

Incident Type	Protective Measure	Recovery Procedure
Backend Server Crash	Docker Orchestration	Automatic container restart via healthcheck monitoring scripts.
Database Corruption	Daily Snapshots	Restoration of the latest PostgreSQL backup followed by a replay of Write-Ahead Logs (WAL).
DDoS / Traffic Spike	Rate Limiting	Firewall-level IP filtering and isolation of active game table threads.
Client Disconnection	Session Persistence	The server maintains the game state for 120 seconds, allowing "Hot Reconnection" without losing the hand.

Table 4: Incident Management and Service Continuity Matrix.

12.3. Backup & Data Retention Strategy

The system utilizes a three-tier backup hierarchy to prevent any permanent loss of user capital or game history:

1. **Hot Standby:** Asynchronous database replication for immediate failover.
2. **Cold Storage:** Daily encrypted SQL exports stored on a remote, isolated volume (off-site backup).
3. **Audit Logging:** Every game action is serialized and archived, allowing for a full reconstruction of any specific hand in case of a logical bug.



13. Service Level Agreement (SLA)

The **Quantum Bluff** SLA defines the operational performance standards and availability commitments provided to the end-users. This agreement ensures a high-quality gaming experience and establishes clear benchmarks for system reliability.

13.1. Service Availability Commitment

We aim for a service availability of **99.5%** (excluding scheduled maintenance). This is critical for maintaining player trust and ensuring that virtual economy transactions are never interrupted.

- **Uptime Calculation:** Monthly availability is calculated as:

$$Availability = \frac{Total_Minutes - Minutes_of_Downtime}{Total_Minutes} \times 100$$

- **Maintenance Windows:** Scheduled every Tuesday at 04:00 AM UTC for a maximum duration of 30 minutes to ensure minimal impact on global peak hours.

13.2. Performance & Latency Benchmarks

Because real-time poker requires instant feedback, we commit to the following technical thresholds:

Metric	Target Threshold	Definition
API Response Time	< 150ms	Time taken for the server to process a standard action (Check, Fold).
Socket Latency	< 300ms	Round-trip time (RTT) for state synchronization between players.
Login Duration	< 3 seconds	Time from entering credentials to reaching the lobby.
Database Query	< 50ms	Execution time for retrieving player profiles or history logs.

Table 5: System Performance Service Levels.

13.3. Incident Response Times

In the event of a service degradation, the management team (**Omar, Mohamed**) follows a tiered response priority:

- **Priority 1 (Critical):** System is down or game-breaking bug found. Response time: < **30 mins**. Resolution target: **2 hours**.
- **Priority 2 (High):** Specific features (e.g., Hidden Bets) are malfunctioning. Response time: < **2 hours**. Resolution target: **12 hours**.
- **Priority 3 (Minor):** Cosmetic UI bugs or localized translation issues. Response time: < **24 hours**. Resolution target: **Next patch**.



14. Persistence & Databases

14.1. Architecture and Technical Choices

14.1.1 Scope and Objectives

The persistence layer of **Quantum Bluff** is critical for the game's operational integrity. This section defines the relational model that guarantees data integrity, transaction safety, and performance. Although technical integration is carried out in collaboration with the Infrastructure team, this document specifies the complete data architecture.

Important Note: The system exclusively manages **virtual currency (Fictional Chips)**. No real money transactions are performed. The primary security concern is game fairness and anti-cheat compliance, not financial fraud.

14.1.2 RDBMS Choice: PostgreSQL 15

We have selected **PostgreSQL 15** to meet the specific constraints of the game engine:

- **Hybrid Storage (JSONB):** The format of "Hidden Bets" and hand history varies according to game versions and future expansions. The JSONB type allows us to evolve the schema without breaking the database structure or requiring costly migrations.
- **Transactional Integrity (ACID):** Unlike a NoSQL database, PostgreSQL guarantees that in the event of a server crash during a betting round, chips are neither lost nor duplicated. This is non-negotiable for a competitive gaming platform.
- **Backend Compatibility:** This choice aligns perfectly with the Java Spring Boot technical stack used by the Backend team, allowing for native integration via JPA/Hibernate.

14.1.3 Physical and Logical Database Isolation

To strengthen security, performance isolation, and audit reliability, Quantum Bluff adopts a dual-database deployment strategy.

The system distinguishes between:

1. Operational Game Database (Real-Time Engine)

This database instance handles: - Active tables - Player sessions - Live hands - Speculative bets - Short-term transactional state

It is optimized for low-latency writes and high concurrency. Frequent updates, hand progressions, and betting actions occur here.

2. Financial and Audit Database (Immutable Ledger)

A separate database instance stores: - Player balances - Chip transactions - Deposit/withdrawal logs (virtual currency) - Audit trails - Compliance-related records

This database follows stricter immutability constraints. Financial transactions are append-only and protected by triggers preventing destructive updates.



Rationale for Separation This architectural separation ensures:

- **Security Isolation:** A compromise of the real-time engine does not grant direct access to financial ledgers. - **Performance Stability:** Heavy gameplay traffic does not impact financial consistency. - **Audit Integrity:** The financial ledger remains stable and traceable, even during high game load. - **Regulatory Compliance:** Clear separation simplifies forensic review and incident investigation.

Communication between the two database instances occurs exclusively through validated server-side service layers, never through direct client access.

14.1.4 Physical Architecture

- **Hosting:** Database hosted on a dedicated Linux server, isolated from the application tier.
- **Storage:** Utilization of NVMe SSD disks to support the intensive writing of betting logs and real-time state synchronization.
- **Connection Pooling:** Managed via HikariCP to handle concurrent access from multiple game tables.

14.2. Data Dictionary & Relational Model

The following schema represents the complete persistence architecture. All creation scripts (DDL) are version-controlled in the project's Git repository and follow strict naming conventions (prefix `T_` for tables, `SEQ_` for sequences).

14.2.1 User Management Domain

Table: `T_JOUEURS` (Player Profiles) Central table storing player identity, authentication data, and performance metrics.



Field	Type	Key	Description
id_joueur	UUID	PK	Unique identifier (generated client-side for offline capability).
pseudo	VARCHAR(20)	UQ	Display name (sanitized, no special characters).
email	VARCHAR(255)	UQ	Contact email, used for recovery (unique).
password	CHAR(64)		Argon2id hash (client-side pre-hashed, server re-hashed).
solde	BIGINT		Current balance in fictional chips (non-negative constraint).
score_strategie	DECIMAL(5,2)		Calculated boldness index (-10.00 to +10.00).
created_at	TIMESTAMP		Registration timestamp (UTC).
last_login	TIMESTAMP		Last connection timestamp (for streak calculation).

Table 6: Structure T_JOUEURS

Table: T_PREFERENCES (UI Configuration) Stores client interface settings for persistence between sessions.

Field	Type	Key	Description
fk_joueur	UUID	PK/FK	References T_JOUEURS(id_joueur) ON DELETE CASCADE.
volume_son	INT		Sound level (0-100), default 75.
theme	VARCHAR(10)		'LIGHT', 'DARK', or 'SYSTEM'.
langue	CHAR(2)		ISO 639-1 code: 'FR', 'EN', 'ES', 'DE'.
avatar_url	VARCHAR(512)		CDN URL of profile image (null if default).

Table 7: Structure T_PREFERENCES

Table: T_DAILY_REWARDS (Loyalty System) Manages the state of daily rewards for the "Streak" retention system.



Field	Type	Key	Description
id_reward	BIGSERIAL	PK	Internal auto-increment identifier.
fk_joueur	UUID	FK	References T_JOUEURS(id_joueur) UNIQUE.
streak_count	INT		Consecutive days (0 to 7), reset on break.
last_claim	DATE		Date of last claimed bonus (UTC date).

Table 8: Structure T_DAILY_REWARDS

14.2.2 Game & Room Management Domain

Table: T_TABLES (Game Rooms) Defines the configuration of poker rooms available in the Lobby.

Field	Type	Key	Description
id_table	SERIAL	PK	Room identifier.
nom_salle	VARCHAR(50)		Display name, e.g., "Pro Lounge", "Beginner's Luck".
small_blind	INT		Minimum forced bet (must be > 0).
big_blind	INT		Maximum forced bet (must be $\geq 2 \times$ small blind).
nb_max	INT		Table capacity: 6 or 9 players.
statut	VARCHAR(20)		Enum: 'OPEN', 'CLOSED', 'MAINTENANCE'.

Table 9: Structure T_TABLES

Table: T_SIEGES (Table Occupancy) Ensures persistence of real-time table state. In case of server restart, this table allows restoring player positions and their stacks with 100% accuracy.



Field	Type	Key	Description
fk_table	INT	PK/FK	References T_TABLES(id_table).
position	INT	PK	Seat number (1 to nb_max).
fk_joueur	UUID	FK	Seated player (UNIQUE constraint per table).
stack_courant	BIGINT		Chips currently on the table (non-negative).
is_dealer	BOOLEAN		Indicates the Dealer button holder for current hand.

Table 10: Structure T_SIEGES

14.2.3 History and Game Data Domain

Table: T_MAINS (Global Hand History) Technical archive of each poker round for anti-cheat auditing and replay functionality.

Field	Type	Key	Description
id_main	UUID	PK	Unique hand identifier (generated server-side).
fk_table	INT	FK	References T_TABLES(id_table).
board	JSONB		Community cards: Flop (3), Turn (+1), River (+1).
vainqueur	UUID	FK	Winner's player ID (NULL if split pot).
pot_final	BIGINT		Total pot value distributed.
date_fin	TIMESTAMP		Hand completion timestamp (UTC).

Table 11: Structure T_MAINS

Table: T_HIDDEN_BETS (Quantum Feature) Project Specificity: This table manages the core innovation of Quantum Bluff — speculative bets placed pre-flop and revealed at showdown. The JSONB payload stores encrypted betting parameters.



Field	Type	Key	Description
id_bet	BIGSERIAL	PK	Auto-increment identifier.
fk_main	UUID	FK	References T_MAINS(id_main).
fk_joueur	UUID	FK	References T_JOUEURS(id_joueur).
type_pari	VARCHAR(30)		Enum: 'WINNER_OF_HAND', 'FULL_HOUSE_OR_BETTER', 'QUADS_ON_FLOP'.
montant	BIGINT		Stake amount (non-negative).
multiplicateur	DECIMAL(5,2)		Payout multiplier at time of bet placement.
statut	VARCHAR(20)		Enum: 'PENDING', 'WON', 'LOST', 'REFUNDED'.
payload	JSONB		Encrypted bet context (hand evaluation data).

Table 12: Structure T_HIDDEN_BETS

Table: T_PARIS (Standard Poker Actions) Stores granular action history for each hand, enabling detailed replay and statistical analysis.

Field	Type	Key	Description
id_pari	BIGSERIAL	PK	Auto-increment identifier.
fk_main	UUID	FK	References T_MAINS(id_main).
fk_joueur	UUID	FK	References T_JOUEURS(id_joueur).
action	VARCHAR(10)		Enum: 'FOLD', 'CHECK', 'CALL', 'RAISE', 'ALL_IN'.
montant	BIGINT		Bet amount (0 for CHECK/-FOLD).
street	VARCHAR(10)		Enum: 'PREFLOP', 'FLOP', 'TURN', 'RIVER'.
timestamp	TIMESTAMP		Precise action time (UTC, millisecond precision).

Table 13: Structure T_PARIS

14.2.4 Audit and Security Domain

Table: T_LOGS_FINANCIERS (Financial Traceability) Immutable, append-only table used by the audit trigger to trace all chip movements. This table is critical for



dispute resolution and statistical modeling.

Field	Type	Key	Description
id_log	BIGSERIAL	PK	Unique identifier.
fk_joueur	UUID	FK	References T_JOUEURS(id_joueur).
type_op	VARCHAR(20)		Enum: 'GAIN', 'PERTE', 'BONUS', 'ACHAT', 'HIDDEN_BET'.
montant	BIGINT		Absolute transaction value (positive).
solde_precedent	BIGINT		Balance before operation.
nouveau_solde	BIGINT		Balance after operation (non-negative).
reference_id	UUID		Link to source entity (hand ID, reward ID, etc.).
timestamp	TIMESTAMP		Operation timestamp (UTC, auto-set).

Table 14: Structure T_LOGS_FINANCIERS

14.3. Business Logic & Automation

14.3.1 "Daily Rewards" Streak System

Bonus management is delegated to the database via a stored procedure, ensuring that a player cannot manipulate their local clock to cheat the system.

Business Rule:

1. Upon connection, the system compares `CURRENT_DATE` with `last_claim`.
2. **Case A (Consecutive):** If `last_claim = CURRENT_DATE - 1 day`:
 - `streak_count` increments by 1 (capped at 7).
 - If `streak_count < 7`: Award **1,000 chips**.
 - If `streak_count = 7`: Award **10,000 chips** (Jackpot), reset streak.
3. **Case B (Break):** If `last_claim < CURRENT_DATE - 1 day`:
 - Reset `streak_count = 1`.
 - Award base gain (1,000 chips).
4. **Case C (Already Claimed):** If `last_claim = CURRENT_DATE`: No action.

Implementation: PL/pgSQL function invoked by login trigger or scheduled job.



14.3.2 Automation via Triggers

Trigger 1: Strategy Score Calculation

- **Name:** `trg_update_strategy_score`
- **Event:** `AFTER INSERT ON T_MAINS`
- **Frequency:** Per hand completion
- **Description:** At the end of each hand, this trigger recalculates the player's efficiency ratio using the formula defined in Section 4. The result is stored in `T_JOUEURS.score_strat`. This avoids recalculating the entire history at each profile display.

Trigger 2: Financial Audit

- **Name:** `trg_audit_balance`
- **Event:** `BEFORE UPDATE OF solde ON T_JOUEURS`
- **Description:** Any balance modification (gain, loss, bonus, hidden bet settlement) is automatically archived in the immutable `T_LOGS_FINANCIERS` table. This trigger captures both old and new balances, ensuring complete traceability for anti-cheat investigations.

14.4. Backup and Archiving Strategy

This strategy guarantees data security and system performance over the long term, anticipating production-scale load.

14.4.1 Backup Policy (RPO & RTO)

To guarantee a Recovery Point Objective (RPO) close to zero:

- **Full Backup:** Performed daily at 04:00 UTC (off-peak hours) using `pg_basebackup`.
- **Continuous Archiving (WAL):** Transaction logs (Write-Ahead Logs) are shipped in real-time to a secure backup server. This allows point-in-time recovery (PITR). In case of failure at 14:30, the database can be restored to its exact state at 14:29:59.
- **Retention:** 30 days of WAL archives, 7 daily full backups, 4 weekly full backups.

14.4.2 Partitioning and Cold Storage

The `T_MAINS` and `T_PARIS` tables grow rapidly (estimated ~50k rows/day for hands, ~300k rows/day for actions). To maintain performance, we implement declarative partitioning:

- **Hot Partition (0-3 months):** Stored on NVMe SSD for fast API access (replays, recent history, player statistics). Indexed on `date_fin` and `fk_joueur`.
- **Warm Partition (3-12 months):** Stored on standard SSD. Accessible but with slightly higher latency.
- **Cold Partition (> 12 months):** Detached from the live database, stored in compressed columnar format (Parquet) on HDD or cloud object storage. Metadata retained in a separate archive table for searchability.



14.4.3 Indexing Strategy

To ensure sub-100ms query performance under load:

- T_JOUEURS: B-tree on email, pseudo (unique lookups).
- T_SIEGES: Composite index on (fk_table, position).
- T_MAINS: B-tree on date_fin (partition key), fk_joueur (player history).
- T_LOGS_FINANCIERS: B-tree on timestamp, fk_joueur.

14.5. Entity-Relationship Diagram

The complete relational model is visualized in Figure 6. This diagram illustrates the foreign key relationships, cardinalities, and the central role of the T_JOUEURS table in the schema.




Figure 6: PostgreSQL Entity-Relationship Diagram — Quantum Bluff Data Architecture

14.6. UML Class Diagram — Backend Object Model

While the previous section presents the relational database structure (ER model), this diagram illustrates the object-oriented representation used within the Java Spring Boot backend.

The UML Class Diagram reflects the JPA entity mapping corresponding to the PostgreSQL schema. It highlights object relationships, cardinalities, and aggregation rules implemented at the application layer.

This diagram ensures alignment between:

- Database constraints (Foreign Keys)
- JPA annotations (@OneToMany, @ManyToOne, @OneToOne)
- Business domain modeling






Figure 7: UML Class Diagram — Quantum Bluff Backend Domain Model

14.7. Conclusion & Integration Notes

The persistence layer described above has been designed with three non-negotiable principles:

1. **Immutability of Financial Logs:** No deletion, no update — only insertion.
2. **Referential Integrity:** All foreign keys are enforced; orphaned records are prevented.
3. **Performance Predictability:** Partitioning and indexing strategies ensure consistent response times even as the dataset grows to millions of rows.

The DDL scripts are available in the repository at `/database/schema/` and are automatically applied via Flyway migrations during deployment. Integration with the backend Java entities is facilitated via JPA annotations, with native queries used only for complex reporting operations.



15. GDPR Compliance & Data Privacy Framework

As **Quantum Bluff** processes Personal Identifiable Information (PII) and behavioral data, the project adheres to the *General Data Protection Regulation (GDPR)*. This framework ensures "Privacy by Design" and "Privacy by Default" throughout the system architecture.

15.1. Legal Basis and Governance

- **Legal Basis:** Processing is based on **Contractual Necessity** (Art. 6.1.b) for game services and **Legitimate Interest** (Art. 6.1.f) for fraud prevention and security.
- **Data Protection Officer (DPO):** The Project Lead (**Omar**) is the designated DPO, responsible for maintaining the *Register of Processing Activities*.

15.2. Data Protection Impact Assessment (DPIA)

A formal DPIA was conducted due to the processing of behavioral profiling (**Boldness Index**).

Data Category	Purpose	Retention Policy
Identity Data	User Authentication (Email, Username, Hash)	Duration of account activity + 2 years.
Transaction Logs	Virtual currency tracking and anti-fraud.	5 years (Legal requirement for financial auditing).
Behavioral Data	Calculation of the <i>Boldness Index</i> .	12 months (Rolling window for statistics).
Technical Logs	IP addresses, Device IDs for security.	30 days (Automated purging).

Table 15: Data Processing Register and Retention Schedule.

15.3. Subject Access Rights (SAR)

The system implements automated workflows to fulfill user rights:

- **Right of Access & Portability:** Users can request a JSON export of their hand history and profile data via the Dashboard.
- **Right to Erasure (Right to be Forgotten):** An automated "Account Deletion" trigger in the PostgreSQL database anonymizes game logs while deleting PII.
- **Right to Restriction:** Users can opt-out of behavioral profiling, which freezes their *Boldness Index* calculation.



15.4. Consent and Transparency

- **Explicit Opt-in:** During registration, users must provide explicit consent for data processing and age verification (≥ 18 years old).
- **Transparency:** A layered Privacy Policy is accessible from both the Mobile client and the Desktop Lobby.
- **Data Minimization:** The server only requests the minimum data required to play (e.g., location is used only for jurisdiction whitelisting and is not stored).

15.5. Security Measures (Art. 32 GDPR)

To protect data integrity, we implement:

- **Pseudonymization:** Internal User IDs are used in game threads instead of real usernames.
- **Encryption:** Mandatory SSL/TLS for all Socket communications and **Argon2/BCrypt** for password hashing.



16. Verification & Validation (V&V) Plan

This chapter outlines the strategy used to ensure that **Quantum Bluff** meets all specified requirements and industrial quality standards. Our V&V process follows a structured approach, mapping every technical module to a verification protocol.

16.1. V&V Strategy & Test Levels

We employ a multi-layered testing strategy to isolate bugs early in the development life-cycle (Shift-Left approach).

- **Unit Testing (UT):** Individual methods and logic engines (Hand Evaluator, Odds Calculator) are tested in isolation using **JUnit 5**.
- **Integration Testing (IT):** Validation of the communication between the JavaFX Client, the Socket Server, and the PostgreSQL database.
- **System Testing (ST):** End-to-end testing of a full poker hand, from login to pot distribution, ensuring the "Quantum" mechanics integrate with standard rules.
- **User Acceptance Testing (UAT):** Final validation by stakeholders to ensure the UI/UX meets the initial vision and ergonomic requirements.

16.2. Quality Gate & Coverage Targets

To maintain high code quality, the project adheres to strict **Quality Gates**:

Metric	Target	Description
Code Coverage	$\geq 80\%$	Minimum branch coverage for core logic (<code>com.quantum.engine</code>).
Test Pass Rate	100%	All P1 (Critical) test cases must pass for any release.
Documentation	100%	All public methods must have valid Javadoc.
Security Scan	0 Critical	Zero "Critical" or "High" vulnerabilities in the OWASP dependency check.

Table 16: Quality Gate Thresholds.

16.3. Security & Penetration Testing

Given the speculative nature of the game, security is verified through a formal **Penetration Test Plan**:

1. **Protocol Analysis:** Using *Wireshark* to verify that hole cards are not transmitted during the "Fog of War" phase.
2. **Injection Testing:** Attempting SQL injection on login and store endpoints.
3. **State Manipulation:** Testing server-side validation by sending "illegal" socket packets (e.g., betting more than the current stack).



16.4. Final Validation Criteria (Definition of Done)

The project is considered "Ready for Production" only when the following criteria are met. These criteria constitute the terminal nodes of the project's critical path as defined in the **PERT Diagram** (see **Appendix A**).

- **V-CRIT-01 (Requirement Coverage):** All RQ-FUN-01 to RQ-FUN-XX requirements must have at least one associated passing test case in the traceability matrix.
- **V-CRIT-02 (System Stability):** Stress testing confirms stability with 100 concurrent game rooms without memory leaks or socket drops.
- **V-CRIT-03 (Deployment Readiness):** The Mobile build (APK) passes the installation and "smoke test" on three distinct Android API levels (30, 31, and 33).
- **V-CRIT-04 (Formal Sign-off):** Final validation and sign-off by the Project Lead (**Omar**) following the UAT session. *Note: This corresponds to the final milestone M7 in the PERT chart, marking the formal end of the 111-day development cycle.*



Appendix A: PERT Diagram




Figure 8: Authoritative message flow with server-side validation



Appendix B: Gantt Chart




Figure 9: Authoritative message flow with server-side validation

The following section provides a detailed mapping of the project's milestones as visualized in the Gantt chart. In accordance with industrial project management standards, each milestone represents a critical decision point and a transition between project phases. For each milestone, a set of tangible deliverables is produced to ensure full transparency and quality control.



- **Milestone M1 (Initiation & Discovery):** Deliverables include the *Software Requirements Specification (SRS)* document, the preliminary *UML Architecture*, and the established *CI/CD pipeline* on GitLab.
- **Milestone M2 (Skill Upgrading & Prototyping):** Delivery of the *Entity-Relationship Diagram (ERD)* for PostgreSQL, the *UI/UX Wireframes*, and the mathematical validation of the *Speculation Engine odds*.
- **Milestone M3 (Alpha Phase):** Output of the *JavaFX Logic Engine (Local)* and the complete *Hand Ranking Evaluator* verified by JUnit test suites.
- **Milestone M4 (Beta Phase):** Release of the *Socket Server environment* with multi-player support, secure *BCrypt authentication*, and real-time database synchronization.
- **Milestone M5 (Mobile Porting & High-Level Testing):** Submission of the *Native Android/iOS Builds (APK/IPA)* and the comprehensive *Stress-Test and Security Audit Report* (10k concurrent user simulation).
- **Milestone M6 (Verification & Quality):** Finalization of the *Technical Javadoc*, the *PostgreSQL Administration Guide*, and the *Regression Test Log*.
- **Milestone M7 (Final Delivery):** Full deployment of the *Quantum Bluff Production System*, accompanied by the *Final Project Defense* materials and live demonstration.



Appendix C: RACI Responsibility Assignment Matrix

Symbol	Role	Definition
R	Responsible	Performs the work / Executes the task.
A	Accountable	Approves and assumes final responsibility. Only one per deliverable.
C	Consulted	Two-way communication (input required prior to decision).
I	Informed	One-way communication (kept up to date after decision).
–	Not involved	No participation in this deliverable.



Deliverable / Decision	Gol.	Om.	Moh.	Azr.	Sou.	Yig.	Mas.	Lin.	Abd.	All
PHASE 1: Initiation & Discovery										
1.1 Market & Rules Analysis	A	R	C	I	I	I	I	I	I	R
1.2 Core Game Mechanic	A	R	C	R	R	C	–	–	–	–
1.3 Technical Strategy	I	C	A	C	C	–	R	–	–	–
1.4 Requirements (SRS)	A	R	C	C	C	–	–	C	–	–
1.5 DevOps Foundation	I	I	A	–	–	R	R	C	–	–
1.6 Phase 1 Validation	A	R	C	I	I	I	I	I	I	I
PHASE 2: Skill Upgrading & Prototyping										
2.1 Backend Logic POC	I	C	A	R	R	–	–	–	–	–
2.2 Frontend Wireframes	I	C	A	–	–	R	–	–	–	–
2.3 Database Schema	I	C	A	–	–	–	–	–	R	–
2.4 Network Foundation	I	C	A	–	–	–	R	R	–	–
2.5 Skill Validation	A	R	C	I	I	I	I	I	I	I
PHASE 3: Alpha Phase – Heavy Client										
3.1 Poker Engine	I	I	A	R	R	–	–	–	–	–
3.2 Core Table UI	I	I	A	–	–	R	–	–	–	–
3.3 Backend Infrastructure	I	I	A	–	–	–	R	C	–	–
3.4 Data Persistence	I	I	A	–	–	–	–	–	R	–
3.5 Security Compliance	A	R	C	–	–	–	–	R	–	–
3.6 Alpha Testing	I	A	C	R	R	R	–	–	–	R
3.7 Alpha Review	A	R	C	I	I	I	I	I	I	I
PHASE 4: Beta Phase – Online & Security										
4.1 Socket Server	I	I	A	R	R	–	R	R	–	–
4.2 Encryption & Auth	I	I	A	–	–	R	R	R	R	–
4.3 PostgreSQL Production	I	I	A	–	–	–	–	C	R	–
4.4 Mobile UI & HUD	I	I	A	–	–	R	–	–	–	–
4.5 Anti-Cheat	I	I	A	R	–	–	R	R	–	–
4.6 Beta Integration	I	A	C	C	C	–	R	–	–	R
4.7 Beta Bug Scrub	I	A	C	I	I	I	I	I	I	R
4.8 Beta Review	A	R	C	I	I	I	I	I	I	I
PHASE 5: Mobile Porting & High-Level Testing										
5.1 Mobile SDK Build	I	I	A	C	C	R	R	–	–	–
5.2 Mobile Logic Opt.	I	I	A	R	R	–	–	–	–	–
5.3 Mobile UI/Anim	I	I	A	–	–	R	–	–	–	–
5.4 Stress/Pen Testing	I	I	A	–	–	C	R	R	C	–
5.5 Scenario Testing	I	I	A	R	R	–	–	–	–	–
5.6 Mobile Review	A	R	C	I	I	I	I	I	I	I



headerblue Deliverable / Decision	Gol.	Om.	Moh.	Azr.	Sou.	Yig.	Mas.	Lin.	Abd.	All
PHASE 6: Verification & Quality										
6.1 Final Regression	I	A	C	R	R	R	R	R	R	R
6.2 Security Final Check	A	R	C	–	–	–	C	R	–	–
6.3 Technical Documentation	I	A	C	R	R	C	–	–	–	–
6.4 DB Documentation	I	A	C	–	–	–	–	–	R	–
6.5 Final Polishing	I	A	C	R	R	R	R	R	R	R
6.6 QA Sign-Off	A	R	C	I	I	I	I	I	I	I
PHASE 7: Delivery										
7.1 Final Deployment	I	A	C	–	–	–	R	R	–	–
7.2 Final Defense/Demo	A	R	C	R	R	R	R	R	R	R
7.3 Final Deliverables	A	R	C	I	I	I	I	I	I	I

Abbreviation	Team Member
Gol.	Golaj (Professor / Supervisor)
Om.	Aguech Omar (Project Lead)
Moh.	Mohamed (Tech Lead)
Azr.	Azra (Backend Lead)
Sou.	Souheil (Support / Documentation)
Yig.	Yigit (Frontend/UI Lead)
Mas.	Massi (Network Lead)
Lin.	Linda Baouab (Security Lead)
Abd.	Abdoulae (Database Lead)
All	Entire Team

Golden Rule: Each deliverable has **ONE AND ONLY ONE "A"**.
The person marked **Accountable** bears final responsibility and decision authority.



Appendix D: Quantum Bluff Functional Flowchart

- **Interactive Version:** The high-resolution functional diagram and dynamic logic transitions can be viewed at the following link: [Quantum Bluff - Full Logic Flow](#).




Figure 10: Complete Game Logic Flow: From Balance Validation to Showdown Resolution.

Note: This diagram illustrates the decision-making process of the authoritative server, including the "Quantum" speculative betting phase and the multi-way side pot resolution logic.



Appendix E: FRM Table

Req. ID	Description & Rationale	Source	Prio.	Acceptance Criteria	Verification Method
RQ-FUN-01	Core Engine: Hand ranking logic for 8 players. <i>Rationale: Essential for game integrity.</i>	Stakeholder	P1	100% accuracy on all 10 standard hand types.	Unit Testing (JUnit)
RQ-FUN-02	Quantum Bet: Placement of hidden bets before Flop. <i>Rationale: Project USP.</i>	Product Vision	P1	Bet amount deducted and state locked server-side.	Integration Test
RQ-SEC-01	Fog of War: Opponent card masking in network packets. <i>Rationale: Anti-cheat.</i>	Security Spec	P1	No hole card data present in JSON until Showdown.	Security Audit (Wireshark)
RQ-PER-01	Sync Latency: Global state update under 300ms. <i>Rationale: UX Fluidity.</i>	Tech Lead	P2	Response time $\leq$ 300ms under 100-player load.	Stress Testing
RQ-MOB-01	Mobile APK: Native build for Android. <i>Rationale: Accessibility.</i>	Market Bench.	P2	Successful install and launch on Android 11+.	Manual Native QA

Table 17: Formal Requirement Management Table (IEEE 29148 compliant).

