OPL1000_WIFI_BLE_API_GUIDE

1.0.1.23

Generated by Doxygen 1.8.14

Contents

Chapter 1

SDK PREVIEW

- BLE APIs :
  - GAP APIs : ble GAP APIs
  - GATT APIs : ble GATT APIs
  - CM APIs : ble CM APIs
  - MSG APIs : ble MSG APIs
  - SMP APIs : ble SMP APIs
- WiFi APIs :
  - Station APIs : station APIs
  - Common APIs : common APIs
  - Enumerations : enumerations

Chapter 2

Module Index

2.1 Modules

Here is a list of all modules:

Chapter 3

Data Structure Index

3.1 Data Structures

Here are the data structures with brief descriptions:

Chapter 4

Module Documentation

4.1 BLE ALL APIs

BLE ALL APIs.

Modules

- BLE CM APIs
- BLE GAP APIs
- BLE GATT APIs
- BLE MSG APIs
- BLE SMP APIs

4.1.1 Detailed Description

BLE ALL APIs.

4.2 BLE CM APIs

Data Structures

- struct LE_CM_CONNECTION_COMPLETE_IND_T
- struct LE_CM_MSG_ADVERTISE_REPORT_IND_T
- struct LE_CM_MSG_CONN_PARA_REQ_T
- struct LE_CM_MSG_CONN_UPDATE_COMPLETE_IND_T
- struct LE_CM_MSG_DATA_LEN_CHANGE_IND_T
- struct LE_CM_MSG_DIRECT_ADV_REPORT_IND_T
- struct LE_CM_MSG_DISCONNECT_COMPLETE_IND_T
- struct LE_CM_MSG_ENCRYPTION_CHANGE_IND_T
- struct LE_CM_MSG_ENCRYPTION_REFRESH_IND_T
- struct LE_CM_MSG_INIT_COMPLETE_CFM_T
- struct LE_CM_MSG_LTK_REQ_IND_T
- struct LE_CM_MSG_READ_ADV_TX_POWER_CFM_T
- struct LE_CM_MSG_READ_BD_ADDR_CFM_T
- struct LE_CM_MSG_READ_CHANNEL_MAP_CFM_T
- struct LE_CM_MSG_READ_RESOLVING_LIST_SIZE_CFM_T
- struct LE_CM_MSG_READ_RSSI_CFM_T
- struct LE_CM_MSG_READ_TX_POWER_CFM_T
- struct LE_CM_MSG_READ_WHITE_LIST_SIZE_CFM_T
- struct LE_CM_MSG_SET_DATA_LENGTH_CFM_T
- struct LE_CM_MSG_SET_DISCONNECT_CFM_T
- struct LE_CM_MSG_SIGNAL_UPDATE_REQ_T
- struct LE_CM_REQ_STATUS_T

Typedefs

- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_ADD_TO_RESOLVING_LIST_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_ADD_TO_WHITE_LIST_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_CANCEL_CONNECTION_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_CLEAR_RESOLVING_LIST_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_CLEAR_WHITE_LIST_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_CREATE_CONNECTION_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_ENTER_ADVERTISING_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_ENTER_SCANNING_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_EXIT_ADVERTISING_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_EXIT_SCANNING_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_REMOVE_FROM_RESOLVING_LIST_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_REMOVE_FROM_WHITE_LIST_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_ADVERTISING_DATA_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_ADVERTISING_PARAMS_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_CHANNEL_MAP_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_RANDOM_ADDRESS_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_RPA_TIMEOUT_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_SCAN_PARAMS_CFM_T
- typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_SCAN_RSP_DATA_CFM_T

Enumerations

- enum {
  LE_CM_MSG_INIT_COMPLETE_CFM = LE_CM_MSG_BASE, LE_CM_MSG_SET_DISCONNECT_CFM,
  LE_CM_MSG_DISCONNECT_COMPLETE_IND, LE_CM_MSG_SET_ADVERTISING_DATA_CFM,
  LE_CM_MSG_SET_SCAN_RSP_DATA_CFM, LE_CM_MSG_SET_ADVERTISING_PARAMS_CFM,
  LE_CM_MSG_ENTER_ADVERTISING_CFM, LE_CM_MSG_EXIT_ADVERTISING_CFM,
  LE_CM_MSG_SET_SCAN_PARAMS_CFM, LE_CM_MSG_ENTER_SCANNING_CFM,
  LE_CM_MSG_EXIT_SCANNING_CFM, LE_CM_MSG_CREATE_CONNECTION_CFM,
  LE_CM_MSG_CANCEL_CONNECTION_CFM, LE_CM_MSG_READ_TX_POWER_CFM,
  LE_CM_MSG_READ_BD_ADDR_CFM, LE_CM_MSG_READ_RSSI_CFM,
  LE_CM_MSG_SET_RANDOM_ADDRESS_CFM, LE_CM_MSG_READ_ADV_TX_POWER_CFM,
  LE_CM_MSG_READ_WHITE_LIST_SIZE_CFM LE_CM_MSG_CLEAR_WHITE_LIST_CFM,
  LE_CM_MSG_ADD_TO_WHITE_LIST_CFM, LE_CM_MSG_REMOVE_FROM_WHITE_LIST_CFM,
  LE_CM_MSG_SET_CHANNEL_MAP_CFM, LE_CM_MSG_READ_CHANNEL_MAP_CFM,
  LE_CM_MSG_SET_DATA_LENGTH_CFM, LE_CM_MSG_DATA_LEN_CHANGE_IND,
  LE_CM_MSG_ADD_TO_RESOLVING_LIST_CFM LE_CM_MSG_REMOVE_FROM_RESOLVING_LIST_CFM,
  LE_CM_MSG_CLEAR_RESOLVING_LIST_CFM, LE_CM_MSG_READ_RESOLVING_LIST_SIZE_CFM,
  LE_CM_MSG_SET_RPA_TIMEOUT_CFM, LE_CM_MSG_SIGNAL_UPDATE_REQ,
  LE_CM_MSG_CONN_UPDATE_COMPLETE_IND, LE_CM_MSG_CONN_PARA_REQ,
  LE_CM_MSG_ENCRYPTION_CHANGE_IND LE_CM_MSG_ENCRYPTION_REFRESH_IND,
  LE_CM_MSG_LTK_REQ_IND, LE_CM_MSG_ADVERTISE_REPORT_IND, LE_CM_MSG_DIRECT_ADV_REPORT_IND,
  LE_CM_CONNECTION_COMPLETE_IND,
  LE_CM_MSG_READ_LOCAL_RPA_CFM, LE_CM_MSG_TOP }

  BLE connection management message id.

Functions

- void LeCmInit (TASK appTask)

  BLE Connection Management Module Init.

4.2.1 Detailed Description

4.2.2 Typedef Documentation

4.2.2.1 LE_CM_MSG_ADD_TO_RESOLVING_LIST_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_ADD_TO_RESOLVING_LIST_CFM_T
```

4.2.2.2 LE_CM_MSG_ADD_TO_WHITE_LIST_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_ADD_TO_WHITE_LIST_CFM_T
```

4.2.2.3 LE_CM_MSG_CANCEL_CONNECTION_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_CANCEL_CONNECTION_CFM_T
```

4.2.2.4 LE_CM_MSG_CLEAR_RESOLVING_LIST_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_CLEAR_RESOLVING_LIST_CFM_T
```

4.2.2.5 LE_CM_MSG_CLEAR_WHITE_LIST_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_CLEAR_WHITE_LIST_CFM_T
```

4.2.2.6 LE_CM_MSG_CREATE_CONNECTION_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_CREATE_CONNECTION_CFM_T
```

4.2.2.7 LE_CM_MSG_ENTER_ADVERTISING_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_ENTER_ADVERTISING_CFM_T
```

4.2.2.8 LE_CM_MSG_ENTER_SCANNING_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_ENTER_SCANNING_CFM_T
```

4.2.2.9 LE_CM_MSG_EXIT_ADVERTISING_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_EXIT_ADVERTISING_CFM_T
```

4.2.2.10 LE_CM_MSG_EXIT_SCANNING_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_EXIT_SCANNING_CFM_T
```

4.2.2.11 LE_CM_MSG_REMOVE_FROM_RESOLVING_LIST_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_REMOVE_FROM_RESOLVING_LIST_CFM_T
```

4.2.2.12 LE_CM_MSG_REMOVE_FROM_WHITE_LIST_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_REMOVE_FROM_WHITE_LIST_CFM_T
```

4.2.2.13 LE_CM_MSG_SET_ADVERTISING_DATA_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_ADVERTISING_DATA_CFM_T
```

4.2.2.14 LE_CM_MSG_SET_ADVERTISING_PARAMS_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_ADVERTISING_PARAMS_CFM_T
```

4.2.2.15 LE_CM_MSG_SET_CHANNEL_MAP_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_CHANNEL_MAP_CFM_T
```

4.2.2.16 LE_CM_MSG_SET_RANDOM_ADDRESS_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_RANDOM_ADDRESS_CFM_T
```

4.2.2.17 LE_CM_MSG_SET_RPA_TIMEOUT_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_RPA_TIMEOUT_CFM_T
```

4.2.2.18 LE_CM_MSG_SET_SCAN_PARAMS_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_SCAN_PARAMS_CFM_T
```

4.2.2.19 LE_CM_MSG_SET_SCAN_RSP_DATA_CFM_T

```
typedef LE_CM_REQ_STATUS_T LE_CM_MSG_SET_SCAN_RSP_DATA_CFM_T
```

4.2.3 Enumeration Type Documentation

4.2.3.1 anonymous enum

```
anonymous enum
```

BLE connection management message id.

Enumerator

LE_CM_MSG_INIT_COMPLETE_CFM	initialize complete
LE_CM_MSG_SET_DISCONNECT_CFM	set disconnect confirm
LE_CM_MSG_DISCONNECT_COMPLETE_IND	disconnect complete indication
LE_CM_MSG_SET_ADVERTISING_DATA_CFM	set advertising data confirm
LE_CM_MSG_SET_SCAN_RSP_DATA_CFM	set scan response data confirm
LE_CM_MSG_SET_ADVERTISING_PARAMS_CFM	set advertising parameters confirm
LE_CM_MSG_ENTER_ADVERTISING_CFM	enter advertising confirm
LE_CM_MSG_EXIT_ADVERTISING_CFM	exit advertising confirm
LE_CM_MSG_SET_SCAN_PARAMS_CFM	set scan parameters confirm
LE_CM_MSG_ENTER_SCANNING_CFM	enter scanning confirm
LE_CM_MSG_EXIT_SCANNING_CFM	exit scanning confirm
LE_CM_MSG_CREATE_CONNECTION_CFM	create connection confirm
LE_CM_MSG_CANCEL_CONNECTION_CFM	cancel connection confirm
LE_CM_MSG_READ_TX_POWER_CFM	read tx power confirm
LE_CM_MSG_READ_BD_ADDR_CFM	read device address confirm
LE_CM_MSG_READ_RSSI_CFM	read RSSI confirm
LE_CM_MSG_SET_RANDOM_ADDRESS_CFM	set random address confirm
LE_CM_MSG_READ_ADV_TX_POWER_CFM	read advertising tx power confirm
LE_CM_MSG_READ_WHITE_LIST_SIZE_CFM	read whitelist size confirm
LE_CM_MSG_CLEAR_WHITE_LIST_CFM	clear whitelist confirm
LE_CM_MSG_ADD_TO_WHITE_LIST_CFM	add to whitelist confirm
LE_CM_MSG_REMOVE_FROM_WHITE_LIST_CFM	remove from whitelist confirm
LE_CM_MSG_SET_CHANNEL_MAP_CFM	set channel map confirm
LE_CM_MSG_READ_CHANNEL_MAP_CFM	read channel map confirm
LE_CM_MSG_SET_DATA_LENGTH_CFM	set data length confirm
LE_CM_MSG_DATA_LEN_CHANGE_IND	data length change indication
LE_CM_MSG_ADD_TO_RESOLVING_LIST_CFM	add to resolving list confirm
LE_CM_MSG_REMOVE_FROM_RESOLVING_LIST_CFM	remove from resolving list confirm
LE_CM_MSG_CLEAR_RESOLVING_LIST_CFM	clear resolving list confirm
LE_CM_MSG_READ_RESOLVING_LIST_SIZE_CFM	read resolving list size confirm
LE_CM_MSG_SET_RPA_TIMEOUT_CFM	set resolving private address timeout confirm
LE_CM_MSG_SIGNAL_UPDATE_REQ	signal update request

Enumerator

LE_CM_MSG_CONN_UPDATE_COMPLETE_IND	connection update complete indication
LE_CM_MSG_CONN_PARA_REQ	connection parameters request
LE_CM_MSG_ENCRYPTION_CHANGE_IND	encryption change indication
LE_CM_MSG_ENCRYPTION_REFRESH_IND	encryption refresh indication
LE_CM_MSG_LTK_REQ_IND	long term key indication
LE_CM_MSG_ADVERTISE_REPORT_IND	advertising report indication
LE_CM_MSG_DIRECT_ADV_REPORT_IND	direct advertising report indication
LE_CM_CONNECTION_COMPLETE_IND	connection complete indication
LE_CM_MSG_READ_LOCAL_RPA_CFM	read local resolving private address confirm
LE_CM_MSG_TOP	top of CM message id

4.2.4 Function Documentation

4.2.4.1 LeCmInit()

```
void LeCmInit (
            TASK appTask )
```

BLE Connection Management Module Init.

Parameters

the	reference of BLE task.

Returns

None.

4.3 BLE GAP APIs

Data Structures

- struct LE_GAP_ADVERTISING_PARAM_T
- struct LE_GAP_CONN_PARAM_T
- struct LE_GAP_SCAN_PARAM_T

Macros

- #define GAP_ADTYPE_128BIT_COMPLETE 0x07
- #define GAP_ADTYPE_128BIT_MORE 0x06
- #define GAP_ADTYPE_16BIT_COMPLETE 0x03
- #define GAP_ADTYPE_16BIT_MORE 0x02
- #define GAP_ADTYPE_32BIT_COMPLETE 0x05
- #define GAP_ADTYPE_32BIT_MORE 0x04
- #define GAP_ADTYPE_3D_INFO_DATA 0x3D
- #define GAP_ADTYPE_ADV_INTERVAL 0x1A
- #define GAP_ADTYPE_APPEARANCE 0x19
- #define GAP_ADTYPE_FLAGS 0x01
- #define GAP_ADTYPE_FLAGS_BREDR_NOT_SUPPORTED 0x04
- #define GAP_ADTYPE_FLAGS_GENERAL 0x02
- #define GAP_ADTYPE_FLAGS_LIMITED 0x01
- #define GAP_ADTYPE_LE_BD_ADDR 0x1B
- #define GAP_ADTYPE_LE_ROLE 0x1C
- #define GAP_ADTYPE_LOCAL_NAME_COMPLETE 0x09
- #define GAP_ADTYPE_LOCAL_NAME_SHORT 0x08
- #define GAP_ADTYPE_MANUFACTURER_SPECIFIC 0xFF
- #define GAP_ADTYPE_OOB_CLASS_OF_DEVICE 0x0D
- #define GAP_ADTYPE_OOB_SIMPLE_PAIRING_HASHC 0x0E
- #define GAP_ADTYPE_OOB_SIMPLE_PAIRING_RANDR 0x0F
- #define GAP_ADTYPE_POWER_LEVEL 0x0A
- #define GAP_ADTYPE_PUBLIC_TARGET_ADDR 0x17
- #define GAP_ADTYPE_RANDOM_TARGET_ADDR 0x18
- #define GAP_ADTYPE_SERVICE_DATA 0x16
- #define GAP_ADTYPE_SERVICE_DATA_128BIT 0x21
- #define GAP_ADTYPE_SERVICE_DATA_32BIT 0x20
- #define GAP_ADTYPE_SERVICES_LIST_128BIT 0x15
- #define GAP_ADTYPE_SERVICES_LIST_16BIT 0x14
- #define GAP_ADTYPE_SIGNED_DATA 0x13
- #define GAP_ADTYPE_SIMPLE_PAIRING_HASHC_256 0x1D
- #define GAP_ADTYPE_SIMPLE_PAIRING_RANDR_256 0x1E
- #define GAP_ADTYPE_SLAVE_CONN_INTERVAL_RANGE 0x12
- #define GAP_ADTYPE_SM_OOB_FLAG 0x11
- #define GAP_ADTYPE_SM_TK 0x10
- #define GAP_PUBLIC_ADDR 0
- #define GAP_RAND_ADDR_NRPA 2
- #define GAP_RAND_ADDR_RPA 3
- #define GAP_RAND_ADDR_STATIC 1
- #define GAP_SCAN_TYPE_ACTIVE 1
- #define GAP_SCAN_TYPE_PASSIVE 0
- #define GAP_TX_PWR_CURR_VAL 0
- #define GAP_TX_PWR_MAX_VAL 1

- #define GAPBOND_IO_CAP_DISPLAY_ONLY 0x00
- #define GAPBOND_IO_CAP_DISPLAY_YES_NO 0x01
- #define GAPBOND_IO_CAP_KEYBOARD_DISPLAY 0x04
- #define GAPBOND_IO_CAP_KEYBOARD_ONLY 0x02
- #define GAPBOND_IO_CAP_NO_INPUT_NO_OUTPUT 0x03
- #define GAPBOND_PAIRING_MODE_INITIATE 0x02
- #define GAPBOND_PAIRING_MODE_NO_PAIRING 0x00
- #define GAPBOND_PAIRING_MODE_WAIT_FOR_REQ 0x01
- #define LE_GAP_ADV_MAX_SIZE 31

Functions

- LE_ERR_STATE LeGapAddToResolvingList (LE_BT_ADDR_T *bt_addr, UINT8 *irk)

  Add device to resolving-list.
- LE_ERR_STATE LeGapAddToWhiteList (LE_BT_ADDR_T *bt_addr)

  Add device to whitelist.
- LE_ERR_STATE LeGapAdvertisingEnable (BOOL start)

  Enable or disable advertising function.
- LE_ERR_STATE LeGapCentralConnectReq (LE_BT_ADDR_T *taddr, UINT8 own_addr_type)

  Central connect request.
- LE_ERR_STATE LeGapCentralSetDataChannel (UINT8 *ch)

  Central set data channel.
- LE_ERR_STATE LeGapClearResolvingList (void)

  Clear the resolving-list in the controller.
- LE_ERR_STATE LeGapClearWhiteList (void)

  Clear whitelist in the controller.
- LE_ERR_STATE LeGapConnectCancelReq (void)

  Cancel connect request.
- void LeGapConnParaRequestRsp (UINT16 conn_hdl, BOOL accept)

  Connection parameters request response.
- void LeGapConnUpdateRequest (UINT16 conn_hdl, LE_CONN_PARA_T *para)

  Connection parameters update request.
- void LeGapConnUpdateResponse (UINT16 conn_hdl, UINT8 identifier, BOOL accept)

  Connection parameters update response.
- LE_ERR_STATE LeGapDisconnectReq (UINT16 conn_hdl)

  Disconnect the physical connection.
- LE_ERR_STATE LeGapGenRandAddr (UINT8 type, BD_ADDR addr)

  Called to generation random address.
- void LeGapGetBtAddr (void)

  Get owner device address.
- void LeGapReadAdvChannelTxPower (void)

  Read ADV channel txpower.
- LE_ERR_STATE LeGapReadChannelMap (UINT16 conn_hdl)

  Read channel map.
- void LeGapReadResolvingListSize (void)

  Read the resolving-list size in the controller.
- LE_ERR_STATE LeGapReadRssi (UINT16 conn_hdl)

  Read RSSI value from controller.
- LE_ERR_STATE LeGapReadTxPower (UINT16 conn_hdl, UINT8 type)

  Read tx power value for the specified connection.
- void LeGapReadWhiteListSize (void)

Read whitelist size in the controller.

- LE_ERR_STATE LeGapRemoveFromWhiteList (LE_BT_ADDR_T *bt_addr)

  Remove device from whitelist.
- LE_ERR_STATE LeGapScanningReq (BOOL start, BOOL filter)

  Request scanning start.
- LE_ERR_STATE LeGapSetAdvData (UINT8 len, UINT8 *data)

  Called to set ADV data.
- LE_ERR_STATE LeGapSetAdvParameter (LE_GAP_ADVERTISING_PARAM_T *params)

  Called to set ADV parameters.
- LE_ERR_STATE LeGapSetConnParameter (UINT16 interval_min, UINT16 interval_max, UINT16 slave_↩ latency, UINT16 supervision_timeout)

  Called to set connection parameters.
- LE_ERR_STATE LeGapSetDataChannelPduLen (UINT16 conn_hdl, UINT16 tx_octets, UINT16 tx_time)

  Set data channel PDU length.
- LE_ERR_STATE LeGapSetRandAddr (BD_ADDR addr)

  Called to set random address.
- LE_ERR_STATE LeGapSetRpaTimeout (UINT16 timeout)

  Set resolvable private address timeout.
- LE_ERR_STATE LeGapSetStaticAddr (BD_ADDR addr)

  Called to set static address.
- LE_ERR_STATE LeSetScanParameter (LE_GAP_SCAN_PARAM_T *params)

  Called to set scan parameters.
- LE_ERR_STATE LeSetScanRspData (UINT8 len, UINT8 *data)

  Called to set scan response data.

4.3.1 Detailed Description

4.3.2 Macro Definition Documentation

4.3.2.1 GAP_ADTYPE_128BIT_COMPLETE

```
#define GAP_ADTYPE_128BIT_COMPLETE 0x07
```

4.3.2.2 GAP_ADTYPE_128BIT_MORE

```
#define GAP_ADTYPE_128BIT_MORE 0x06
```

4.3.2.3 GAP_ADTYPE_16BIT_COMPLETE

```
#define GAP_ADTYPE_16BIT_COMPLETE 0x03
```

4.3.2.4 GAP_ADTYPE_16BIT_MORE

```
#define GAP_ADTYPE_16BIT_MORE 0x02
```

4.3.2.5 GAP_ADTYPE_32BIT_COMPLETE

```
#define GAP_ADTYPE_32BIT_COMPLETE 0x05
```

4.3.2.6 GAP_ADTYPE_32BIT_MORE

```
#define GAP_ADTYPE_32BIT_MORE 0x04
```

4.3.2.7 GAP_ADTYPE_3D_INFO_DATA

```
#define GAP_ADTYPE_3D_INFO_DATA 0x3D
```

4.3.2.8 GAP_ADTYPE_ADV_INTERVAL

```
#define GAP_ADTYPE_ADV_INTERVAL 0x1A
```

4.3.2.9 GAP_ADTYPE_APPEARANCE

```
#define GAP_ADTYPE_APPEARANCE 0x19
```

4.3.2.10 GAP_ADTYPE_FLAGS

```
#define GAP_ADTYPE_FLAGS 0x01
```

4.3.2.11 GAP_ADTYPE_FLAGS_BREDR_NOT_SUPPORTED

```
#define GAP_ADTYPE_FLAGS_BREDR_NOT_SUPPORTED 0x04
```

4.3.2.12 GAP_ADTYPE_FLAGS_GENERAL

```
#define GAP_ADTYPE_FLAGS_GENERAL 0x02
```

4.3.2.13 GAP_ADTYPE_FLAGS_LIMITED

```
#define GAP_ADTYPE_FLAGS_LIMITED 0x01
```

4.3.2.14 GAP_ADTYPE_LE_BD_ADDR

```
#define GAP_ADTYPE_LE_BD_ADDR 0x1B
```

4.3.2.15 GAP_ADTYPE_LE_ROLE

```
#define GAP_ADTYPE_LE_ROLE 0x1C
```

4.3.2.16 GAP_ADTYPE_LOCAL_NAME_COMPLETE

```
#define GAP_ADTYPE_LOCAL_NAME_COMPLETE 0x09
```

4.3.2.17 GAP_ADTYPE_LOCAL_NAME_SHORT

```
#define GAP_ADTYPE_LOCAL_NAME_SHORT 0x08
```

4.3.2.18 GAP_ADTYPE_MANUFACTURER_SPECIFIC

```
#define GAP_ADTYPE_MANUFACTURER_SPECIFIC 0xFF
```

4.3.2.19 GAP_ADTYPE_OOB_CLASS_OF_DEVICE

```
#define GAP_ADTYPE_OOB_CLASS_OF_DEVICE 0x0D
```

4.3.2.20 GAP_ADTYPE_OOB_SIMPLE_PAIRING_HASHC

```
#define GAP_ADTYPE_OOB_SIMPLE_PAIRING_HASHC 0x0E
```

4.3.2.21 GAP_ADTYPE_OOB_SIMPLE_PAIRING_RANDR

```
#define GAP_ADTYPE_OOB_SIMPLE_PAIRING_RANDR 0x0F
```

4.3.2.22 GAP_ADTYPE_POWER_LEVEL

```
#define GAP_ADTYPE_POWER_LEVEL 0x0A
```

4.3.2.23 GAP_ADTYPE_PUBLIC_TARGET_ADDR

```
#define GAP_ADTYPE_PUBLIC_TARGET_ADDR 0x17
```

4.3.2.24 GAP_ADTYPE_RANDOM_TARGET_ADDR

```
#define GAP_ADTYPE_RANDOM_TARGET_ADDR 0x18
```

4.3.2.25 GAP_ADTYPE_SERVICE_DATA

```
#define GAP_ADTYPE_SERVICE_DATA 0x16
```

4.3.2.26 GAP_ADTYPE_SERVICE_DATA_128BIT

```
#define GAP_ADTYPE_SERVICE_DATA_128BIT 0x21
```

4.3.2.27 GAP_ADTYPE_SERVICE_DATA_32BIT

```
#define GAP_ADTYPE_SERVICE_DATA_32BIT 0x20
```

4.3.2.28 GAP_ADTYPE_SERVICES_LIST_128BIT

```
#define GAP_ADTYPE_SERVICES_LIST_128BIT 0x15
```

4.3.2.29 GAP_ADTYPE_SERVICES_LIST_16BIT

```
#define GAP_ADTYPE_SERVICES_LIST_16BIT 0x14
```

4.3.2.30 GAP_ADTYPE_SIGNED_DATA

```
#define GAP_ADTYPE_SIGNED_DATA 0x13
```

4.3.2.31 GAP_ADTYPE_SIMPLE_PAIRING_HASHC_256

```
#define GAP_ADTYPE_SIMPLE_PAIRING_HASHC_256 0x1D
```

4.3.2.32 GAP_ADTYPE_SIMPLE_PAIRING_RANDR_256

```
#define GAP_ADTYPE_SIMPLE_PAIRING_RANDR_256 0x1E
```

4.3.2.33 GAP_ADTYPE_SLAVE_CONN_INTERVAL_RANGE

```
#define GAP_ADTYPE_SLAVE_CONN_INTERVAL_RANGE 0x12
```

4.3.2.34 GAP_ADTYPE_SM_OOB_FLAG

```
#define GAP_ADTYPE_SM_OOB_FLAG 0x11
```

4.3.2.35 GAP_ADTYPE_SM_TK

```
#define GAP_ADTYPE_SM_TK 0x10
```

4.3.2.36 GAP_PUBLIC_ADDR

```
#define GAP_PUBLIC_ADDR 0
```

4.3.2.37 GAP_RAND_ADDR_NRPA

```
#define GAP_RAND_ADDR_NRPA 2
```

4.3.2.38 GAP_RAND_ADDR_RPA

```
#define GAP_RAND_ADDR_RPA 3
```

4.3.2.39 GAP_RAND_ADDR_STATIC

```
#define GAP_RAND_ADDR_STATIC 1
```

4.3.2.40 GAP_SCAN_TYPE_ACTIVE

```
#define GAP_SCAN_TYPE_ACTIVE 1
```

4.3.2.41 GAP_SCAN_TYPE_PASSIVE

```
#define GAP_SCAN_TYPE_PASSIVE 0
```

4.3.2.42 GAP_TX_PWR_CURR_VAL

```
#define GAP_TX_PWR_CURR_VAL 0
```

4.3.2.43 GAP_TX_PWR_MAX_VAL

```
#define GAP_TX_PWR_MAX_VAL 1
```

4.3.2.44 GAPBOND_IO_CAP_DISPLAY_ONLY

```
#define GAPBOND_IO_CAP_DISPLAY_ONLY 0x00
```

4.3.2.45 GAPBOND_IO_CAP_DISPLAY_YES_NO

```
#define GAPBOND_IO_CAP_DISPLAY_YES_NO 0x01
```

4.3.2.46 GAPBOND_IO_CAP_KEYBOARD_DISPLAY

```
#define GAPBOND_IO_CAP_KEYBOARD_DISPLAY 0x04
```

4.3.2.47 GAPBOND_IO_CAP_KEYBOARD_ONLY

```
#define GAPBOND_IO_CAP_KEYBOARD_ONLY 0x02
```

4.3.2.48 GAPBOND_IO_CAP_NO_INPUT_NO_OUTPUT

```
#define GAPBOND_IO_CAP_NO_INPUT_NO_OUTPUT 0x03
```

4.3.2.49 GAPBOND_PAIRING_MODE_INITIATE

```
#define GAPBOND_PAIRING_MODE_INITIATE 0x02
```

4.3.2.50 GAPBOND_PAIRING_MODE_NO_PAIRING

```
#define GAPBOND_PAIRING_MODE_NO_PAIRING 0x00
```

4.3.2.51 GAPBOND_PAIRING_MODE_WAIT_FOR_REQ

```
#define GAPBOND_PAIRING_MODE_WAIT_FOR_REQ 0x01
```

4.3.2.52 LE_GAP_ADV_MAX_SIZE

```
#define LE_GAP_ADV_MAX_SIZE 31
```

4.3.3 Function Documentation

4.3.3.1 LeGapAddToResolvingList()

```
LE_ERR_STATE LeGapAddToResolvingList (
            LE_BT_ADDR_T * bt_addr,
            UINT8 * irk )
```

Add device to resolving-list.

Parameters

bt_addr	BT device address.
irk	IRK, Identity Resolving Key

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.2 LeGapAddToWhiteList()

```
LE_ERR_STATE LeGapAddToWhiteList (
            LE_BT_ADDR_T * bt_addr )
```

Add device to whitelist.

Parameters

bt_addr	BT device address.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.3 LeGapAdvertisingEnable()

```
LE_ERR_STATE LeGapAdvertisingEnable (
             BOOL start )
```

Enable or disable advertising function.

Parameters

start	TRUE is enable, FALSE is disable.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.4 LeGapCentralConnectReq()

```
LE_ERR_STATE LeGapCentralConnectReq (
             LE_BT_ADDR_T * taddr,
             UINT8 own_addr_type )
```

Central connect request.

Parameters

taddr	advertisers device address.
own_addr_type	owner address type.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.5 LeGapCentralSetDataChannel()

```
LE_ERR_STATE LeGapCentralSetDataChannel (
             UINT8 * ch )
```

Central set data channel.

Parameters

ch	data channel.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.6 LeGapClearResolvingList()

```
LE_ERR_STATE LeGapClearResolvingList (
            void  )
```

Clear the resolving-list in the controller.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.7 LeGapClearWhiteList()

```
LE_ERR_STATE LeGapClearWhiteList (
            void  )
```

Clear whitelist in the controller.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.8 LeGapConnectCancelReq()

```
LE_ERR_STATE LeGapConnectCancelReq (
            void  )
```

Cancel connect request.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.9 LeGapConnParaRequestRsp()

```
void LeGapConnParaRequestRsp (
            UINT16 conn_hdl,
            BOOL accept )
```

Connection parameters request response.

Parameters

conn_hdl	connection handle.
accept	TRUE is accept, FALSE is not.

Returns

None.

4.3.3.10 LeGapConnUpdateRequest()

```
void LeGapConnUpdateRequest (
            UINT16 conn_hdl,
            LE_CONN_PARA_T * para )
```

Connection parameters update request.

Parameters

conn_hdl	connection handle.
para	update connection parameters.

Returns

None.

4.3.3.11 LeGapConnUpdateResponse()

```
void LeGapConnUpdateResponse (
            UINT16 conn_hdl,
            UINT8 identifier,
            BOOL accept )
```

Connection parameters update response.

Parameters

conn_hdl	connection handle.
identifier	TBD
accept	accept request, or not.

Returns

None.

4.3.3.12 LeGapDisconnectReq()

```
LE_ERR_STATE LeGapDisconnectReq (
             UINT16 conn_hdl )
```

Disconnect the physical connection.

Parameters

conn_hdl	connection handle.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.13 LeGapGenRandAddr()

```
LE_ERR_STATE LeGapGenRandAddr (
             UINT8 type,
             BD_ADDR addr )
```

Called to generation random address.

Parameters

type	address type.
addr	address.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.14 LeGapGetBtAddr()

```
void LeGapGetBtAddr (
             void  )
```

Get owner device address.

4.3.3.15 LeGapReadAdvChannelTxPower()

```
void LeGapReadAdvChannelTxPower (
            void  )
```

Read ADV channel txpower.

4.3.3.16 LeGapReadChannelMap()

```
LE_ERR_STATE LeGapReadChannelMap (
            UINT16 conn_hdl )
```

Read channel map.

Parameters

conn_hdl	connection handle.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.17 LeGapReadResolvingListSize()

```
void LeGapReadResolvingListSize (
            void  )
```

Read the resolving-list size in the controller.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.18 LeGapReadRssi()

```
LE_ERR_STATE LeGapReadRssi (
            UINT16 conn_hdl )
```

Read RSSI value from controller.

Parameters

conn_hdl	connection handle.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.19 LeGapReadTxPower()

```
LE_ERR_STATE LeGapReadTxPower (
             UINT16 conn_hdl,
             UINT8 type )
```

Read tx power value for the specified connection.

Parameters

conn_hdl	connection handle.
type	current tx power, or maxinum tx power. Don't support.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.20 LeGapReadWhiteListSize()

```
void LeGapReadWhiteListSize (
             void  )
```

Read whitelist size in the controller.

4.3.3.21 LeGapRemoveFromWhiteList()

```
LE_ERR_STATE LeGapRemoveFromWhiteList (
             LE_BT_ADDR_T * bt_addr )
```

Remove device from whitelist.

Remove device from resolving-list.

Parameters

bt_addr	BT device address.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.22 LeGapScanningReq()

```
LE_ERR_STATE LeGapScanningReq (
            BOOL start,
            BOOL filter )
```

Request scanning start.

Parameters

start	TRUE is start, FALSE is not.
filter	scan policy, refer to LE_HCI_SCAN_FILT_* in ble_hci_if.h

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.23 LeGapSetAdvData()

```
LE_ERR_STATE LeGapSetAdvData (
            UINT8 len,
            UINT8 * data )
```

Called to set ADV data.

Parameters

len	ADV data length.
data	ADV data.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.24 LeGapSetAdvParameter()

```
LE_ERR_STATE LeGapSetAdvParameter (
            LE_GAP_ADVERTISING_PARAM_T * params )
```

Called to set ADV parameters.

Parameters

params	advertising params.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.25 LeGapSetConnParameter()

```
LE_ERR_STATE LeGapSetConnParameter (
             UINT16 interval_min,
             UINT16 interval_max,
             UINT16 slave_latency,
             UINT16 supervision_timeout )
```

Called to set connection parameters.

Parameters

interval_min	mininum connection interval.
interval_max	maxinum connection interval.
slave_letency	slave letency.
supervision_timeout	supervison timeout.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.26 LeGapSetDataChannelPduLen()

```
LE_ERR_STATE LeGapSetDataChannelPduLen (
             UINT16 conn_hdl,
```

```
            UINT16 tx_octets,
            UINT16 tx_time )
```

Set data channel PDU length.

Parameters

tx_octets	the maximum number of octets in the Payload field that the local device will send to the remote device.
tx_time	the maximum number of microseconds that the local device will take to transmit a PDU to the remote device.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.27 LeGapSetRandAddr()

```
LE_ERR_STATE LeGapSetRandAddr (
            BD_ADDR addr )
```

Called to set random address.

Parameters

addr	the random address which should be set.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.28 LeGapSetRpaTimeout()

```
LE_ERR_STATE LeGapSetRpaTimeout (
            UINT16 timeout )
```

Set resolvable private address timeout.

Parameters

timeout	RPA_Timeout, measured in seconds.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.29 LeGapSetStaticAddr()

```
LE_ERR_STATE LeGapSetStaticAddr (
             BD_ADDR addr )
```

Called to set static address.

Parameters

addr	the static address which should be set.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.30 LeSetScanParameter()

```
LE_ERR_STATE LeSetScanParameter (
             LE_GAP_SCAN_PARAM_T * params )
```

Called to set scan parameters.

Parameters

params	scan parameters.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.3.3.31 LeSetScanRspData()

```
LE_ERR_STATE LeSetScanRspData (
             UINT8 len,
             UINT8 * data )
```

Called to set scan response data.

Parameters

len	scan response data length.
data	scan response data.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4 BLE GATT APIs

Data Structures

- struct LE_GATT_ATTR_T
- struct LE_GATT_MSG_ACCESS_READ_IND_T
- struct LE_GATT_MSG_ACCESS_WRITE_IND_T
- struct LE_GATT_MSG_CHAR_DESCRIPTOR_INFO_IND_T
- struct LE_GATT_MSG_CHARACTERISTIC_DECL_INFO_IND_T
- struct LE_GATT_MSG_CHARACTERISTIC_VAL_IND_T
- struct LE_GATT_MSG_CONFIRMATION_CFM_T
- struct LE_GATT_MSG_EXCHANGE_MTU_CFM_T
- struct LE_GATT_MSG_EXCHANGE_MTU_IND_T
- struct LE_GATT_MSG_EXECUTE_WRITE_RELIABLE_CFM_T
- struct LE_GATT_MSG_FIND_ALL_CHAR_DESC_CFM_T
- struct LE_GATT_MSG_FIND_ALL_PRIMARY_SERVICE_CFM_T
- struct LE_GATT_MSG_FIND_CHARACTERISTIC_CFM_T
- struct LE_GATT_MSG_FIND_INCLUDED_SERVICE_CFM_T
- struct LE_GATT_MSG_FIND_PRIMARY_SERVICE_BY_UUID_CFM_T
- struct LE_GATT_MSG_INCLUDE_SERVICE_INFO_IND_T
- struct LE_GATT_MSG_INDICATE_IND_T
- struct LE_GATT_MSG_NOTIFY_CFM_T
- struct LE_GATT_MSG_NOTIFY_IND_T
- struct LE_GATT_MSG_OPERATION_TIMEOUT_T
- struct LE_GATT_MSG_PREPARE_WRITE_RELIABLE_CFM_T
- struct LE_GATT_MSG_READ_CHAR_VAL_BY_UUID_CFM_T
- struct LE_GATT_MSG_READ_CHARACTERISTIC_VALUE_CFM_T
- struct LE_GATT_MSG_READ_LONG_CHAR_VAL_CFM_T
- struct LE_GATT_MSG_READ_MULTIPLE_CHAR_VAL_CFM_T
- struct LE_GATT_MSG_SERVICE_INFO_IND_T
- struct LE_GATT_MSG_SIGNED_WRITE_CFM_T
- struct LE_GATT_MSG_WRITE_CHAR_VAL_RELIABLE_CFM_T
- struct LE_GATT_MSG_WRITE_CHAR_VALUE_CFM_T
- struct LE_GATT_MSG_WRITE_LONG_CHAR_VALUE_CFM_T
- struct LE_GATT_MSG_WRITE_NO_RSP_CFM_T
- struct LE_GATT_SERVICE_T

Macros

- #define CHAR_AGGREGATE_DESCRIPTOR(len, pVal) {0, LE_GATT_UUID16, (UINT16 *)&gcCharAggregateUuid, LE_GATT_PERMIT_READ, 0, len, (UINT8 *)(pVal)}
- #define CHAR_CLIENT_CONFIG_DESCRIPTOR(permit, pVal) {0, LE_GATT_UUID16, (UINT16 *)&gcClientCharConfigUuid, LE_GATT_PERMIT_READ | permit, 0, 2, (UINT8 *)(pVal)}
- #define CHAR_DECL_UUID16_ATTR_VAL(prop, type) {(prop), 0, 0, UINT16_LO(type), UINT16_HI(type)}
- #define CHAR_EXT_PROP_DESCRIPTOR(pVal) {0, LE_GATT_UUID16, (UINT16 *)&gcCharExtPropUuid, LE_GATT_PERMIT_READ, 0, 2, (UINT8 *)(pVal)}
- #define CHAR_PRESENT_FORMAT_DESCRIPTOR(pVal) {0, LE_GATT_UUID16, (UINT16 *)&gcCharFormatUuid, LE_GATT_PERMIT_READ, 0, 7, (UINT8 *)(pVal)}
- #define CHAR_SERVER_CONFIG_DESCRIPTOR(permit, pVal) {0, LE_GATT_UUID16, (UINT16 *)&gcServerCharConfigUuid, LE_GATT_PERMIT_READ | permit, 0, 2, (UINT8 *)(pVal)}
- #define CHAR_USER_DESC_DESCRIPTOR(permit, maxLen, len, pVal) {0, LE_GATT_UUID16, (UINT16 *)&gcCharUserDescUuid, permit, maxLen, len, (UINT8 *)(pVal)}

- #define CHARACTERISTIC_DECL_UUID128(pVal) {0, LE_GATT_UUID16, (UINT16 *)&gcCharacteristicUuid, LE_GATT_PERMIT_READ, 0, 19, (UINT8 *)(pVal)}
- #define CHARACTERISTIC_DECL_UUID16(pVal) {0, LE_GATT_UUID16, (UINT16 *)&gcCharacteristicUuid, LE_GATT_PERMIT_READ, 0, 5, (UINT8 *)(pVal)}
- #define CHARACTERISTIC_UUID128(pUuid, permit, maxLen, len, pVal) {0, LE_GATT_UUID128, (UINT16 *)pUuid, permit, maxLen, len, (UINT8 *)(pVal)}
- #define CHARACTERISTIC_UUID16(pUuid, permit, maxLen, len, pVal) {0, LE_GATT_UUID16, (UINT16 *)pUuid, permit, maxLen, len, (UINT8 *)(pVal)}
- #define GATT_CHAR_AGG_FORMAT_UUID 0x2905
- #define GATT_CHAR_EXT_PROPS_UUID 0x2900
- #define GATT_CHAR_FORMAT_UUID 0x2904
- #define GATT_CHAR_USER_DESC_UUID 0x2901
- #define GATT_CHARACTERISTIC_UUID 0x2803
- #define GATT_CLIENT_CHAR_CFG_UUID 0x2902
- #define GATT_EXT_REPORT_REF_UUID 0x2907
- #define GATT_INCLUDE_UUID 0x2802
- #define GATT_PRIMARY_SERVICE_UUID 0x2800
- #define GATT_REPORT_REF_UUID 0x2908
- #define GATT_SECONDARY_SERVICE_UUID 0x2801
- #define GATT_SERV_CHAR_CFG_UUID 0x2903
- #define GATT_VALID_RANGE_UUID 0x2906
- #define INCLUDE_DECL_UUID128(pVal) {0, LE_GATT_UUID16, (UINT16 *)&gcIncludeUuid, LE_GATT_PERMIT_READ, 0, 4, (UINT8 *)(pVal)}
- #define INCLUDE_DECL_UUID128_ATTR_VAL() {0, 0, 0, 0}
- #define INCLUDE_DECL_UUID16_ATTR_VAL(uuid) {0, 0, 0, 0, UINT16_LO(uuid), UINT16_HI(uuid)}
- #define INCLUDE_DECL_UUINT16(pVal) {0, LE_GATT_UUID16, (UINT16 *)&gcIncludeUuid, LE_GATT_PERMIT_READ, 0, 6, (UINT8 *)(pVal)}
- #define LE_ATT_UUID_SIZE 2
- #define LE_GATT_CHAR_PROP_AUTH 0x40
- #define LE_GATT_CHAR_PROP_BCAST 0x01

  Characteristic Properties Bit.
- #define LE_GATT_CHAR_PROP_EXT_PROP 0x80
- #define LE_GATT_CHAR_PROP_IND 0x20
- #define LE_GATT_CHAR_PROP_NTF 0x10
- #define LE_GATT_CHAR_PROP_RD 0x02
- #define LE_GATT_CHAR_PROP_WR 0x08
- #define LE_GATT_CHAR_PROP_WR_NO_RESP 0x04
- #define LE_GATT_CLIENT_CFG_INDICATION 0x02
- #define LE_GATT_CLIENT_CFG_NOTIFICATION 0x01
- #define LE_GATT_EXT_PROP_RELIABLE_WR 0x0001
- #define LE_GATT_EXT_PROP_WR_AUX 0x0002
- #define LE_GATT_FLAG_PREPARE_WRITE 0x02
- #define LE_GATT_FLAG_WRITE_CMD 0x01
- #define LE_GATT_FLAG_WRITE_REQ 0x00
- #define LE_GATT_PERM_AUTH_READABLE (0x1<<4)
- #define LE_GATT_PERM_AUTH_WRITABLE (0x1<<6)
- #define LE_GATT_PERM_NONE (0x00)
- #define LE_GATT_PERM_READ (0x1<<1)
- #define LE_GATT_PERM_RELIABLE_WRITE (0x1<<5)
- #define LE_GATT_PERM_WRITE_CMD (0x1<<2)
- #define LE_GATT_PERM_WRITE_REQ (0x1<<3)
- #define LE_GATT_PERMIT_AUTHEN_READ (0x0040)
- #define LE_GATT_PERMIT_AUTHEN_WRITE (0x0080)
- #define LE_GATT_PERMIT_AUTHOR_READ (0x0004)
- #define LE_GATT_PERMIT_AUTHOR_WRITE (0x0008)

- #define LE_GATT_PERMIT_ENCRYPT_READ (0x0010)
- #define LE_GATT_PERMIT_ENCRYPT_WRITE (0x0020)
- #define LE_GATT_PERMIT_READ (0x0001)
- #define LE_GATT_PERMIT_READABLE (LE_GATT_PERMIT_READ | LE_GATT_PERMIT_AUTHEN_READ | LE_GATT_PERMIT_AUTHOR_READ | LE_GATT_PERMIT_ENCRYPT_READ | LE_GATT_PERMIT_SC_AUTHEN_READ)
- #define LE_GATT_PERMIT_SC_AUTHEN_READ (0x0100)
- #define LE_GATT_PERMIT_SC_AUTHEN_WRITE (0x0200)
- #define LE_GATT_PERMIT_WRITABLE (LE_GATT_PERMIT_WRITE | LE_GATT_PERMIT_AUTHEN_WRITE | LE_GATT_PERMIT_AUTHOR_WRITE | LE_GATT_PERMIT_ENCRYPT_WRITE | LE_GATT_PERMIT_SC_AUTHEN_WRITE)
- #define LE_GATT_PERMIT_WRITE (0x0002)
- #define PRIMARY_SERVICE_DECL_UUID128(pUuid) {0, LE_GATT_UUID16, (UINT16 *)&gcPrimaryServiceUuid, LE_GATT_PERMIT_READ, 0, 16, (UINT8 *)(pUuid)}
- #define PRIMARY_SERVICE_DECL_UUID16(pUuid) {0, LE_GATT_UUID16, (UINT16 *)&gcPrimaryServiceUuid, LE_GATT_PERMIT_READ, 0, 2, (UINT8 *)(pUuid)}
- #define SECONDARY_SERVICE_DECL_UUID128(pUuid) {0, LE_GATT_UUID16, (UINT16 *)&gcSecondaryServiceUuid, LE_GATT_PERMIT_READ, 0, 16, (UINT8 *)(pUuid)}
- #define SECONDARY_SERVICE_DECL_UUID16(pUuid) {0, LE_GATT_UUID16, (UINT16 *)&gcSecondaryServiceUuid, LE_GATT_PERMIT_READ, 0, 2, (UINT8 *)(pUuid)}

Enumerations

- enum {
  LE_GATT_MSG_INIT_CFM = LE_GATT_MSG_BASE, LE_GATT_MSG_EXCHANGE_MTU_IND,
  LE_GATT_MSG_EXCHANGE_MTU_CFM, LE_GATT_MSG_ACCESS_READ_IND,
  LE_GATT_MSG_ACCESS_WRITE_IND, LE_GATT_MSG_SERVICE_INFO_IND,
  LE_GATT_MSG_FIND_ALL_PRIMARY_SERVICE_CFM,
  LE_GATT_MSG_FIND_PRIMARY_SERVICE_BY_UUID_CFM,
  LE_GATT_MSG_FIND_INCLUDED_SERVICE_CFM, LE_GATT_MSG_CHARACTERISTIC_DECL_INFO_IND,
  LE_GATT_MSG_FIND_CHARACTERISTIC_CFM, LE_GATT_MSG_CHAR_DESCRIPTOR_INFO_IND,
  LE_GATT_MSG_FIND_ALL_CHAR_DESC_CFM, LE_GATT_MSG_CHARACTERISTIC_VAL_IND,
  LE_GATT_MSG_READ_CHARACTERISTIC_VALUE_CFM LE_GATT_MSG_READ_CHAR_VAL_BY_UUID_CFM,
  LE_GATT_MSG_READ_LONG_CHAR_VAL_CFM, LE_GATT_MSG_READ_MULTIPLE_CHAR_VAL_CFM,
  LE_GATT_MSG_WRITE_CHAR_VALUE_CFM, LE_GATT_MSG_WRITE_LONG_CHAR_VALUE_CFM,
  LE_GATT_MSG_WRITE_CHAR_VAL_RELIABLE_CFM, LE_GATT_MSG_PREPARE_WRITE_RELIABLE_CFM,
  LE_GATT_MSG_EXECUTE_WRITE_RELIABLE_CFM, LE_GATT_MSG_WRITE_NO_RSP_CFM,
  LE_GATT_MSG_SIGNED_WRITE_CFM, LE_GATT_MSG_NOTIFY_IND, LE_GATT_MSG_NOTIFY_CFM,
  LE_GATT_MSG_INDICATE_IND,
  LE_GATT_MSG_CONFIRMATION_CFM, LE_GATT_MSG_OPERATION_TIMEOUT,
  LE_GATT_MSG_SIGN_RESOLUTION_FAIL, LE_GATT_MSG_INCLUDE_SERVICE_INFO_IND,
  LE_GATT_MSG_TOP }

  BLE GATT message id.

Functions

- LE_ERR_STATE LeGattAccessReadRsp (UINT16 conn_hdl, UINT16 handle, UINT8 att_err)

  Gatt access read response.
- LE_ERR_STATE LeGattAccessWriteRsp (UINT16 conn_hdl, UINT8 method, UINT16 handle, UINT8 att_err)

  Gatt access write response.
- LE_ERR_STATE LeGattChangeAttrVal (LE_GATT_SERVICE_T *svc, UINT16 attrId, UINT16 len, void *val)

  Change attribute value.
- LE_ERR_STATE LeGattCharValConfirmation (UINT16 conn_hdl)

  Prepare write characteristic value response.
- LE_ERR_STATE LeGattCharValIndicate (UINT16 conn_hdl, UINT16 hdl, UINT16 len, UINT8 *pval)

  Gatt characteristic value indication.

- LE_ERR_STATE LeGattCharValNotify (UINT16 conn_hdl, UINT16 hdl, UINT16 len, UINT8 *pval)

  Gatt characteristic value notification.
- LE_ERR_STATE LeGattExchangeMtuReq (UINT16 conn_hdl, UINT16 mtu)

  Exchange MTU request.
- LE_ERR_STATE LeGattExchangeMtuRsp (UINT16 conn_hdl, UINT16 mtu)

  Exchange MTU response.
- LE_ERR_STATE LeGattExecuteWriteCharValReliable (UINT16 conn_hdl, BOOL yesno)

  Execute write characteristic value request.
- LE_ERR_STATE LeGattFindAllCharacteristic (UINT16 conn_hdl, UINT16 start_hdl, UINT16 end_hdl)

  Find all characteristic.
- LE_ERR_STATE LeGattFindAllCharDescriptor (UINT16 conn_hdl, UINT16 start_hdl, UINT16 end_hdl)

  Find all characteristic description.
- LE_ERR_STATE LeGattFindAllPrimaryService (UINT16 conn_hdl)

  Find all primary service.
- LE_ERR_STATE LeGattFindCharacteristicByUuid (UINT16 conn_hdl, UINT16 start_hdl, UINT16 end_hdl, UINT8 format, UINT16 *uuid)

  Find characteristic by UUID.
- LE_ERR_STATE LeGattFindIncludedService (UINT16 conn_hdl, UINT16 start_hdl, UINT16 end_hdl)

  Find include service.
- LE_ERR_STATE LeGattFindPrimaryServiceByUuid (UINT16 conn_hdl, UINT8 format, UINT16 *uuid)

  Find primary service by UUID.
- UINT16 LeGattGetAttrHandle (LE_GATT_SERVICE_T *svc, UINT16 attrId)

  Get attribute handle.
- LE_ERR_STATE LeGattGetAttrVal (LE_GATT_SERVICE_T *svc, UINT16 attrId, UINT16 *len, void *val)

  Get attribute value.
- UINT16 LeGattGetAttrValLen (LE_GATT_SERVICE_T *svc, UINT16 attrId)

  Get the length of attribute value.
- UINT16 LeGattGetAttrValMaxLen (LE_GATT_SERVICE_T *svc, UINT16 attrId)

  Get the max length of attribute value.
- void LeGattInit (TASK appTask)

  BLE Gatt module init.
- LE_ERR_STATE LeGattModifyAttrVal (LE_GATT_SERVICE_T *svc, UINT16 attrId, UINT16 offset, UINT16 len, void *val)

  Modify attribute value.
- LE_ERR_STATE LeGattPrepareWriteCharValReliable (UINT16 conn_hdl, UINT16 handle, UINT16 offset, UINT16 len, UINT8 *val)

  Prepare write characteristic value request.
- LE_ERR_STATE LeGattReadCharValByUuid (UINT16 conn_hdl, UINT16 start_hdl, UINT16 end_hdl, UINT8 format, UINT16 *uuid)

  Read a characteristic value by UUID.
- LE_ERR_STATE LeGattReadCharValue (UINT16 conn_hdl, UINT16 handle)

  Read a characteristic value.
- LE_ERR_STATE LeGattReadLongCharVal (UINT16 conn_hdl, UINT16 handle, UINT16 offset)

  Read a long characteristic value.
- LE_ERR_STATE LeGattReadMultipleCharVal (UINT16 conn_hdl, UINT16 count, UINT16 *handle)

  Read Multiple characteristic values.
- LE_ERR_STATE LeGattRegisterIncludeService (UINT16 inc_hdl, UINT16 start_hdl, UINT16 end_hdl, UINT16 uuid)

  Called to register an include service.
- LE_GATT_SERVICE_T * LeGattRegisterService (LE_GATT_ATTR_T *attrTable, UINT16 numAttr)

  Called to register a service.

- LE_ERR_STATE LeGattSignedWriteNoRsp (UINT16 conn_hdl, UINT16 handle, UINT16 len, UINT8 *val)

  Signed write without response.
- void LeGattStopCurrentProcedure (UINT16 conn_hdl)

  Stop current procedure.
- LE_ERR_STATE LeGattWriteCharVal (UINT16 conn_hdl, UINT16 handle, UINT16 len, UINT8 *val)

  Write characteristic value.
- LE_ERR_STATE LeGattWriteCharValReliable (UINT16 conn_hdl, UINT16 handle, UINT16 offset, UINT16 len, UINT8 *val)

  Write characteristic value reliable.
- LE_ERR_STATE LeGattWriteLongCharVal (UINT16 conn_hdl, UINT16 handle, UINT16 offset, UINT16 len, UINT8 *val)

  Write long characteristic value.
- LE_ERR_STATE LeGattWriteNoRsp (UINT16 conn_hdl, UINT16 handle, UINT16 len, UINT8 *val)

  Write without response.

Variables

- const UINT16 gcCharacteristicUuid
- const UINT16 gcCharAggregateUuid
- const UINT16 gcCharExtPropUuid
- const UINT16 gcCharFormatUuid
- const UINT16 gcCharUserDescUuid
- const UINT16 gcClientCharConfigUuid
- const UINT16 gcExtReportRefUuid
- const UINT16 gcIncludeUuid
- const UINT16 gcPrimaryServiceUuid
- const UINT16 gcReportRefUuid
- const UINT16 gcSecondaryServiceUuid
- const UINT16 gcServerCharConfigUuid
- const UINT16 gcValidRangeUuid

4.4.1 Detailed Description

4.4.2 Macro Definition Documentation

4.4.2.1 CHAR_AGGREGATE_DESCRIPTOR

```
#define CHAR_AGGREGATE_DESCRIPTOR(
              len,
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)&gcCharAggregateUuid, LE_GATT_PERMIT_READ,
0, len, (UINT8 *)(pVal)}
```

4.4.2.2 CHAR_CLIENT_CONFIG_DESCRIPTOR

```
#define CHAR_CLIENT_CONFIG_DESCRIPTOR(
              permit,
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)&gcClientCharConfigUuid, LE_GATT_PERMIT_READ
| permit, 0, 2, (UINT8 *)(pVal)}
```

4.4.2.3 CHAR_DECL_UUID16_ATTR_VAL

```
#define CHAR_DECL_UUID16_ATTR_VAL(
              prop,
              type ) {(prop), 0, 0, UINT16_LO(type), UINT16_HI(type)}
```

4.4.2.4 CHAR_EXT_PROP_DESCRIPTOR

```
#define CHAR_EXT_PROP_DESCRIPTOR(
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)&gcCharExtPropUuid, LE_GATT_PERMIT_READ, 0,
2, (UINT8 *)(pVal)}
```

4.4.2.5 CHAR_PRESENT_FORMAT_DESCRIPTOR

```
#define CHAR_PRESENT_FORMAT_DESCRIPTOR(
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)&gcCharFormatUuid, LE_GATT_PERMIT_READ, 0,
7, (UINT8 *)(pVal)}
```

4.4.2.6 CHAR_SERVER_CONFIG_DESCRIPTOR

```
#define CHAR_SERVER_CONFIG_DESCRIPTOR(
              permit,
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)&gcServerCharConfigUuid, LE_GATT_PERMIT_READ
| permit, 0, 2, (UINT8 *)(pVal)}
```

4.4.2.7 CHAR_USER_DESC_DESCRIPTOR

```
#define CHAR_USER_DESC_DESCRIPTOR(
              permit,
              maxLen,
              len,
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)&gcCharUserDescUuid, permit, maxLen, len,
(UINT8 *)(pVal)}
```

4.4.2.8 CHARACTERISTIC_DECL_UUID128

```
#define CHARACTERISTIC_DECL_UUID128(
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)&gcCharacteristicUuid, LE_GATT_PERMIT_READ,
0, 19, (UINT8 *)(pVal)}
```

4.4.2.9 CHARACTERISTIC_DECL_UUID16

```
#define CHARACTERISTIC_DECL_UUID16(
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)&gcCharacteristicUuid, LE_GATT_PERMIT_READ,
0, 5, (UINT8 *)(pVal)}
```

4.4.2.10 CHARACTERISTIC_UUID128

```
#define CHARACTERISTIC_UUID128(
              pUuid,
              permit,
              maxLen,
              len,
              pVal ) {0, LE_GATT_UUID128, (UINT16 *)pUuid, permit, maxLen, len, (UINT8 *)(p↩
Val)}
```

4.4.2.11 CHARACTERISTIC_UUID16

```
#define CHARACTERISTIC_UUID16(
              pUuid,
              permit,
              maxLen,
              len,
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)pUuid, permit, maxLen, len, (UINT8 *)(pVal)}
```

4.4.2.12 GATT_CHAR_AGG_FORMAT_UUID

```
#define GATT_CHAR_AGG_FORMAT_UUID 0x2905
```

4.4.2.13 GATT_CHAR_EXT_PROPS_UUID

```
#define GATT_CHAR_EXT_PROPS_UUID 0x2900
```

4.4.2.14 GATT_CHAR_FORMAT_UUID

```
#define GATT_CHAR_FORMAT_UUID 0x2904
```

4.4.2.15 GATT_CHAR_USER_DESC_UUID

```
#define GATT_CHAR_USER_DESC_UUID 0x2901
```

4.4.2.16 GATT_CHARACTERISTIC_UUID

```
#define GATT_CHARACTERISTIC_UUID 0x2803
```

4.4.2.17 GATT_CLIENT_CHAR_CFG_UUID

```
#define GATT_CLIENT_CHAR_CFG_UUID 0x2902
```

4.4.2.18 GATT_EXT_REPORT_REF_UUID

```
#define GATT_EXT_REPORT_REF_UUID 0x2907
```

4.4.2.19 GATT_INCLUDE_UUID

```
#define GATT_INCLUDE_UUID 0x2802
```

4.4.2.20 GATT_PRIMARY_SERVICE_UUID

```
#define GATT_PRIMARY_SERVICE_UUID 0x2800
```

4.4.2.21 GATT_REPORT_REF_UUID

```
#define GATT_REPORT_REF_UUID 0x2908
```

4.4.2.22 GATT_SECONDARY_SERVICE_UUID

```
#define GATT_SECONDARY_SERVICE_UUID 0x2801
```

4.4.2.23 GATT_SERV_CHAR_CFG_UUID

```
#define GATT_SERV_CHAR_CFG_UUID 0x2903
```

4.4.2.24 GATT_VALID_RANGE_UUID

```
#define GATT_VALID_RANGE_UUID 0x2906
```

4.4.2.25 INCLUDE_DECL_UUID128

```
#define INCLUDE_DECL_UUID128(
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)&gcIncludeUuid, LE_GATT_PERMIT_READ, 0, 4,
(UINT8 *)(pVal)}
```

4.4.2.26 INCLUDE_DECL_UUID128_ATTR_VAL

```
#define INCLUDE_DECL_UUID128_ATTR_VAL( ) {0, 0, 0, 0}
```

4.4.2.27 INCLUDE_DECL_UUID16_ATTR_VAL

```
#define INCLUDE_DECL_UUID16_ATTR_VAL(
              uuid ) {0, 0, 0, 0, UINT16_LO(uuid), UINT16_HI(uuid)}
```

4.4.2.28 INCLUDE_DECL_UUINT16

```
#define INCLUDE_DECL_UUINT16(
              pVal ) {0, LE_GATT_UUID16, (UINT16 *)&gcIncludeUuid, LE_GATT_PERMIT_READ, 0, 6,
(UINT8 *)(pVal)}
```

4.4.2.29 LE_ATT_UUID_SIZE

```
#define LE_ATT_UUID_SIZE 2
```

4.4.2.30 LE_GATT_CHAR_PROP_AUTH

```
#define LE_GATT_CHAR_PROP_AUTH 0x40
```

4.4.2.31 LE_GATT_CHAR_PROP_BCAST

```
#define LE_GATT_CHAR_PROP_BCAST 0x01
```

Characteristic Properties Bit.

4.4.2.32 LE_GATT_CHAR_PROP_EXT_PROP

```
#define LE_GATT_CHAR_PROP_EXT_PROP 0x80
```

4.4.2.33 LE_GATT_CHAR_PROP_IND

```
#define LE_GATT_CHAR_PROP_IND 0x20
```

4.4.2.34 LE_GATT_CHAR_PROP_NTF

```
#define LE_GATT_CHAR_PROP_NTF 0x10
```

4.4.2.35 LE_GATT_CHAR_PROP_RD

```
#define LE_GATT_CHAR_PROP_RD 0x02
```

4.4.2.36 LE_GATT_CHAR_PROP_WR

```
#define LE_GATT_CHAR_PROP_WR 0x08
```

4.4.2.37 LE_GATT_CHAR_PROP_WR_NO_RESP

```
#define LE_GATT_CHAR_PROP_WR_NO_RESP 0x04
```

4.4.2.38 LE_GATT_CLIENT_CFG_INDICATION

```
#define LE_GATT_CLIENT_CFG_INDICATION 0x02
```

4.4.2.39 LE_GATT_CLIENT_CFG_NOTIFICATION

```
#define LE_GATT_CLIENT_CFG_NOTIFICATION 0x01
```

4.4.2.40 LE_GATT_EXT_PROP_RELIABLE_WR

```
#define LE_GATT_EXT_PROP_RELIABLE_WR 0x0001
```

4.4.2.41 LE_GATT_EXT_PROP_WR_AUX

```
#define LE_GATT_EXT_PROP_WR_AUX 0x0002
```

4.4.2.42 LE_GATT_FLAG_PREPARE_WRITE

```
#define LE_GATT_FLAG_PREPARE_WRITE 0x02
```

4.4.2.43 LE_GATT_FLAG_WRITE_CMD

```
#define LE_GATT_FLAG_WRITE_CMD 0x01
```

4.4.2.44 LE_GATT_FLAG_WRITE_REQ

```
#define LE_GATT_FLAG_WRITE_REQ 0x00
```

4.4.2.45 LE_GATT_PERM_AUTH_READABLE

```
#define LE_GATT_PERM_AUTH_READABLE (0x1<<4)
```

4.4.2.46 LE_GATT_PERM_AUTH_WRITABLE

```
#define LE_GATT_PERM_AUTH_WRITABLE (0x1<<6)
```

4.4.2.47 LE_GATT_PERM_NONE

```
#define LE_GATT_PERM_NONE (0x00)
```

4.4.2.48 LE_GATT_PERM_READ

```
#define LE_GATT_PERM_READ (0x1<<1)
```

4.4.2.49 LE_GATT_PERM_RELIABLE_WRITE

```
#define LE_GATT_PERM_RELIABLE_WRITE (0x1<<5)
```

4.4.2.50 LE_GATT_PERM_WRITE_CMD

```
#define LE_GATT_PERM_WRITE_CMD (0x1<<2)
```

4.4.2.51 LE_GATT_PERM_WRITE_REQ

```
#define LE_GATT_PERM_WRITE_REQ (0x1<<3)
```

4.4.2.52 LE_GATT_PERMIT_AUTHEN_READ

```
#define LE_GATT_PERMIT_AUTHEN_READ (0x0040)
```

4.4.2.53 LE_GATT_PERMIT_AUTHEN_WRITE

```
#define LE_GATT_PERMIT_AUTHEN_WRITE (0x0080)
```

4.4.2.54 LE_GATT_PERMIT_AUTHOR_READ

```
#define LE_GATT_PERMIT_AUTHOR_READ (0x0004)
```

4.4.2.55 LE_GATT_PERMIT_AUTHOR_WRITE

```
#define LE_GATT_PERMIT_AUTHOR_WRITE (0x0008)
```

4.4.2.56 LE_GATT_PERMIT_ENCRYPT_READ

```
#define LE_GATT_PERMIT_ENCRYPT_READ (0x0010)
```

4.4.2.57 LE_GATT_PERMIT_ENCRYPT_WRITE

```
#define LE_GATT_PERMIT_ENCRYPT_WRITE (0x0020)
```

4.4.2.58 LE_GATT_PERMIT_READ

```
#define LE_GATT_PERMIT_READ (0x0001)
```

4.4.2.59 LE_GATT_PERMIT_READABLE

```
#define LE_GATT_PERMIT_READABLE (LE_GATT_PERMIT_READ | LE_GATT_PERMIT_AUTHEN_READ |
LE_GATT_PERMIT_AUTHOR_READ| LE_GATT_PERMIT_ENCRYPT_READ | LE_GATT_PERMIT_SC_AUTHEN_READ)
```

4.4.2.60 LE_GATT_PERMIT_SC_AUTHEN_READ

```
#define LE_GATT_PERMIT_SC_AUTHEN_READ (0x0100)
```

4.4.2.61 LE_GATT_PERMIT_SC_AUTHEN_WRITE

```
#define LE_GATT_PERMIT_SC_AUTHEN_WRITE (0x0200)
```

4.4.2.62 LE_GATT_PERMIT_WRITABLE

```
#define LE_GATT_PERMIT_WRITABLE (LE_GATT_PERMIT_WRITE | LE_GATT_PERMIT_AUTHEN_WRITE |
LE_GATT_PERMIT_AUTHOR_WRITE| LE_GATT_PERMIT_ENCRYPT_WRITE | LE_GATT_PERMIT_SC_AUTHEN_WRITE)
```

4.4.2.63 LE_GATT_PERMIT_WRITE

```
#define LE_GATT_PERMIT_WRITE (0x0002)
```

4.4.2.64 PRIMARY_SERVICE_DECL_UUID128

```
#define PRIMARY_SERVICE_DECL_UUID128(
              pUuid ) {0, LE_GATT_UUID16, (UINT16 *)&gcPrimaryServiceUuid, LE_GATT_PERMIT_READ,
0, 16, (UINT8 *)(pUuid)}
```

4.4.2.65 PRIMARY_SERVICE_DECL_UUID16

```
#define PRIMARY_SERVICE_DECL_UUID16(
              pUuid ) {0, LE_GATT_UUID16, (UINT16 *)&gcPrimaryServiceUuid, LE_GATT_PERMIT_READ,
0, 2, (UINT8 *)(pUuid)}
```

4.4.2.66 SECONDARY_SERVICE_DECL_UUID128

```
#define SECONDARY_SERVICE_DECL_UUID128(
              pUuid ) {0, LE_GATT_UUID16, (UINT16 *)&gcSecondaryServiceUuid, LE_GATT_PERMIT_READ,
0, 16, (UINT8 *)(pUuid)}
```

4.4.2.67 SECONDARY_SERVICE_DECL_UUID16

```
#define SECONDARY_SERVICE_DECL_UUID16(
              pUuid ) {0, LE_GATT_UUID16, (UINT16 *)&gcSecondaryServiceUuid, LE_GATT_PERMIT_READ,
0, 2, (UINT8 *)(pUuid)}
```

4.4.3 Enumeration Type Documentation

4.4.3.1 anonymous enum

```
anonymous enum
```

BLE GATT message id.

Enumerator

LE_GATT_MSG_INIT_CFM	initialize confirm message
LE_GATT_MSG_EXCHANGE_MTU_IND	exchange MTU indication
LE_GATT_MSG_EXCHANGE_MTU_CFM	exchange MTU confirm
LE_GATT_MSG_ACCESS_READ_IND	access read indication
LE_GATT_MSG_ACCESS_WRITE_IND	access write indication
LE_GATT_MSG_SERVICE_INFO_IND	service infomation indication
LE_GATT_MSG_FIND_ALL_PRIMARY_SERVICE_CFM	find all primary service confirm
LE_GATT_MSG_FIND_PRIMARY_SERVICE_BY_UUID_CFM	find primary service by UUID fonfirm
LE_GATT_MSG_FIND_INCLUDED_SERVICE_CFM	find include service confirm
LE_GATT_MSG_CHARACTERISTIC_DECL_INFO_IND	characteristic declaration info indication
LE_GATT_MSG_FIND_CHARACTERISTIC_CFM	find characteristic confirm
LE_GATT_MSG_CHAR_DESCRIPTOR_INFO_IND	characteristic descriptor info indication
LE_GATT_MSG_FIND_ALL_CHAR_DESC_CFM	find all characteristic descriptors confirm
LE_GATT_MSG_CHARACTERISTIC_VAL_IND	characteristic value, indication message
LE_GATT_MSG_READ_CHARACTERISTIC_VALUE_CFM	read characteristic value, confirm message
LE_GATT_MSG_READ_CHAR_VAL_BY_UUID_CFM	read characteristic value by UUID confirm message
LE_GATT_MSG_READ_LONG_CHAR_VAL_CFM	read long characteristic value confirm mesage
LE_GATT_MSG_READ_MULTIPLE_CHAR_VAL_CFM	read multiple characteristic value confirm
LE_GATT_MSG_WRITE_CHAR_VALUE_CFM	write characteristic value confirm
LE_GATT_MSG_WRITE_LONG_CHAR_VALUE_CFM	write long characteristic value confirm
LE_GATT_MSG_WRITE_CHAR_VAL_RELIABLE_CFM	write characteristic value reliable confirm
LE_GATT_MSG_PREPARE_WRITE_RELIABLE_CFM	prepare write reliable confirm
LE_GATT_MSG_EXECUTE_WRITE_RELIABLE_CFM	execute write reliable confirm

Enumerator

LE_GATT_MSG_WRITE_NO_RSP_CFM	write no response confirm
LE_GATT_MSG_SIGNED_WRITE_CFM	signed write confirm
LE_GATT_MSG_NOTIFY_IND	notify indication
LE_GATT_MSG_NOTIFY_CFM	notify confirm
LE_GATT_MSG_INDICATE_IND	indicate indication
LE_GATT_MSG_CONFIRMATION_CFM	confirmation confirm
LE_GATT_MSG_OPERATION_TIMEOUT	operation timeout
LE_GATT_MSG_SIGN_RESOLUTION_FAIL	sign resolution fail
LE_GATT_MSG_INCLUDE_SERVICE_INFO_IND	include service infomation
LE_GATT_MSG_TOP	top of GATT message id

4.4.4 Function Documentation

4.4.4.1 LeGattAccessReadRsp()

```
LE_ERR_STATE LeGattAccessReadRsp (
             UINT16 conn_hdl,
             UINT16 handle,
             UINT8 att_err )
```

Gatt access read response.

Parameters

conn_hdl	connection handle.
handle	attribute handle.
att_err	0 is OK, others refer to LE_ATT_ERR_∗ in ble_att_if.h.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.2 LeGattAccessWriteRsp()

```
LE_ERR_STATE LeGattAccessWriteRsp (
             UINT16 conn_hdl,
             UINT8 method,
             UINT16 handle,
             UINT8 att_err )
```

Gatt access write response.

Parameters

conn_hdl	connection handle.
method	refer to LE_GATT_FLAG_* in ble_gatt_if.h
handle	attribute handle.
att_err	0 is OK, others refer to LE_ATT_ERR_* in ble_att_if.h.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.3 LeGattChangeAttrVal()

```
LE_ERR_STATE LeGattChangeAttrVal (
             LE_GATT_SERVICE_T * svc,
             UINT16 attrId,
             UINT16 len,
             void * val )
```

Change attribute value.

Parameters

	svc	service.
	attr↩ Id	attribute index of service.
in	*len*	attribute value length.
in	*val*	attribute value.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.4 LeGattCharValConfirmation()

```
LE_ERR_STATE LeGattCharValConfirmation (
             UINT16 conn_hdl )
```

Prepare write characteristic value response.

Parameters

conn_hdl	connection handle.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.5 LeGattCharValIndicate()

```
LE_ERR_STATE LeGattCharValIndicate (
             UINT16 conn_hdl,
             UINT16 hdl,
             UINT16 len,
             UINT8 * pval )
```

Gatt characteristic value indication.

Parameters

conn_hdl	connection handle.
hdl	characteristic value handle.
len	value length.
pval	value.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.6 LeGattCharValNotify()

```
LE_ERR_STATE LeGattCharValNotify (
             UINT16 conn_hdl,
             UINT16 hdl,
             UINT16 len,
             UINT8 * pval )
```

Gatt characteristic value notification.

Parameters

conn_hdl	connection handle.
hdl	characteristic value handle.
len	value length.
pval	value.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.7 LeGattExchangeMtuReq()

```
LE_ERR_STATE LeGattExchangeMtuReq (
             UINT16 conn_hdl,
             UINT16 mtu )
```

Exchange MTU request.

Parameters

conn_hdl	connection handle.
mtu	MTU.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.8 LeGattExchangeMtuRsp()

```
LE_ERR_STATE LeGattExchangeMtuRsp (
             UINT16 conn_hdl,
             UINT16 mtu )
```

Exchange MTU response.

Parameters

conn_hdl	connection handle.
mtu	MTU.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.9 LeGattExecuteWriteCharValReliable()

```
LE_ERR_STATE LeGattExecuteWriteCharValReliable (
             UINT16 conn_hdl,
             BOOL yesno )
```

Execute write characteristic value request.

Parameters

conn_hdl	connection handle.
yesno	execute write or not.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.10 LeGattFindAllCharacteristic()

```
LE_ERR_STATE LeGattFindAllCharacteristic (
             UINT16 conn_hdl,
             UINT16 start_hdl,
             UINT16 end_hdl )
```

Find all characteristic.

Parameters

conn_hdl	connection handle.
start_hdl	start handle.
end_hdl	end handle.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.11 LeGattFindAllCharDescriptor()

```
LE_ERR_STATE LeGattFindAllCharDescriptor (
             UINT16 conn_hdl,
             UINT16 start_hdl,
             UINT16 end_hdl )
```

Find all characteristic description.

Parameters

conn_hdl	connection handle.
start_hdl	start handle.
end_hdl	end handle.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.12 LeGattFindAllPrimaryService()

```
LE_ERR_STATE LeGattFindAllPrimaryService (
             UINT16 conn_hdl )
```

Find all primary service.

Parameters

conn_hdl	connection handle.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.13 LeGattFindCharacteristicByUuid()

```
LE_ERR_STATE LeGattFindCharacteristicByUuid (
             UINT16 conn_hdl,
             UINT16 start_hdl,
             UINT16 end_hdl,
             UINT8 format,
             UINT16 * uuid )
```

Find characteristic by UUID.

Parameters

conn_hdl	connection handle.
start_hdl	start handle.
end_hdl	end handle.
format	UUID type.
uuid	UUID.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.14 LeGattFindIncludedService()

```
LE_ERR_STATE LeGattFindIncludedService (
             UINT16 conn_hdl,
             UINT16 start_hdl,
             UINT16 end_hdl )
```

Find include service.

Parameters

conn_hdl	connection handle.
start_hdl	start handle.
end_hdl	end handle.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.15 LeGattFindPrimaryServiceByUuid()

```
LE_ERR_STATE LeGattFindPrimaryServiceByUuid (
             UINT16 conn_hdl,
             UINT8 format,
             UINT16 * uuid )
```

Find primary service by UUID.

Parameters

conn_hdl	connection handle.
format	UUID type.
uuid	UUID.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.16 LeGattGetAttrHandle()

```
UINT16 LeGattGetAttrHandle (
            LE_GATT_SERVICE_T * svc,
            UINT16 attrId )
```

Get attribute handle.

Parameters

svc	service.
attr↩ Id	attribute index of service.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.17 LeGattGetAttrVal()

```
LE_ERR_STATE LeGattGetAttrVal (
            LE_GATT_SERVICE_T * svc,
            UINT16 attrId,
            UINT16 * len,
            void * val )
```

Get attribute value.

Parameters

	svc	service.
	attr↩ Id	attribute index of service.
out	*len*	attribute value length.
out	*val*	attribute value.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.18 LeGattGetAttrValLen()

```
UINT16 LeGattGetAttrValLen (
            LE_GATT_SERVICE_T * svc,
            UINT16 attrId )
```

Get the length of attribute value.

Parameters

svc	service.
attr↩ Id	attribute index of service.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.19 LeGattGetAttrValMaxLen()

```
UINT16 LeGattGetAttrValMaxLen (
            LE_GATT_SERVICE_T * svc,
            UINT16 attrId )
```

Get the max length of attribute value.

Parameters

svc	service.
attr↩ Id	attribute index of service.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.20 LeGattInit()

```
void LeGattInit (
            TASK appTask )
```

BLE Gatt module init.

Parameters

appTask	the reference of BLE task.

Returns

None.

4.4.4.21 LeGattModifyAttrVal()

```
LE_ERR_STATE LeGattModifyAttrVal (
             LE_GATT_SERVICE_T * svc,
             UINT16 attrId,
             UINT16 offset,
             UINT16 len,
             void * val )
```

Modify attribute value.

Parameters

svc	servie.
attrId	attribute index of service.
offset	modify offset.
len	modify length.
val	modify value.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.22 LeGattPrepareWriteCharValReliable()

```
LE_ERR_STATE LeGattPrepareWriteCharValReliable (
             UINT16 conn_hdl,
             UINT16 handle,
             UINT16 offset,
             UINT16 len,
             UINT8 * val )
```

Prepare write characteristic value request.

Parameters

conn_hdl	connection handle.
handle	characteristic value handle.
offset	offset written.
len	length written.
val	value.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.23 LeGattReadCharValByUuid()

```
LE_ERR_STATE LeGattReadCharValByUuid (
             UINT16 conn_hdl,
             UINT16 start_hdl,
             UINT16 end_hdl,
             UINT8 format,
             UINT16 * uuid )
```

Read a characteristic value by UUID.

Parameters

conn_hdl	connection handle.
start_hdl	start handle.
end_hdl	end handle.
format	UUID type.
uuid	UUID.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.24 LeGattReadCharValue()

```
LE_ERR_STATE LeGattReadCharValue (
             UINT16 conn_hdl,
             UINT16 handle )
```

Read a characteristic value.

Parameters

conn_hdl	connection handle.
handle	characteristic value handle.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.25 LeGattReadLongCharVal()

```
LE_ERR_STATE LeGattReadLongCharVal (
            UINT16 conn_hdl,
            UINT16 handle,
            UINT16 offset )
```

Read a long characteristic value.

Parameters

conn_hdl	connection handle.
handle	characteristic value handle.
offset	characteristic value offset.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.26 LeGattReadMultipleCharVal()

```
LE_ERR_STATE LeGattReadMultipleCharVal (
            UINT16 conn_hdl,
            UINT16 count,
            UINT16 * handle )
```

Read Multiple characteristic values.

Parameters

conn_hdl	connection handle.
count	handle count.
handle	handle table.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.27 LeGattRegisterIncludeService()

```
LE_ERR_STATE LeGattRegisterIncludeService (
            UINT16 inc_hdl,
```

```
            UINT16 start_hdl,
            UINT16 end_hdl,
            UINT16 uuid )
```

Called to register an include service.

Parameters

inc_hdl	include service handle.
start_hdl	start handle.
end_hdl	end handle.
uuid	include service UUID.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.28 LeGattRegisterService()

```
LE_GATT_SERVICE_T* LeGattRegisterService (
            LE_GATT_ATTR_T * attrTable,
            UINT16 numAttr )
```

Called to register a service.

Parameters

attrTable	service attribute table.
numAttr	the attribute number of service.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.29 LeGattSignedWriteNoRsp()

```
LE_ERR_STATE LeGattSignedWriteNoRsp (
            UINT16 conn_hdl,
            UINT16 handle,
            UINT16 len,
            UINT8 * val )
```

Signed write without response.

Parameters

conn_hdl	connection handle.
handle	characteristic value handle.
len	length of the data to be written.
val	the value to be written.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.30 LeGattStopCurrentProcedure()

```
void LeGattStopCurrentProcedure (
            UINT16 conn_hdl )
```

Stop current procedure.

Parameters

conn_hdl	connection handle.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.31 LeGattWriteCharVal()

```
LE_ERR_STATE LeGattWriteCharVal (
            UINT16 conn_hdl,
            UINT16 handle,
            UINT16 len,
            UINT8 * val )
```

Write characteristic value.

Parameters

conn_hdl	connection handle.
handle	characteristic value handle.
len	length of the data to be written.
val	the value to be written.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.32 LeGattWriteCharValReliable()

```
LE_ERR_STATE LeGattWriteCharValReliable (
             UINT16 conn_hdl,
             UINT16 handle,
             UINT16 offset,
             UINT16 len,
             UINT8 * val )
```

Write characteristic value reliable.

Parameters

conn_hdl	connection handle.
handle	characteristic value handle.
offset	offset written.
len	length written.
val	value.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.33 LeGattWriteLongCharVal()

```
LE_ERR_STATE LeGattWriteLongCharVal (
             UINT16 conn_hdl,
             UINT16 handle,
             UINT16 offset,
             UINT16 len,
             UINT8 * val )
```

Write long characteristic value.

Parameters

conn_hdl	connection handle.
handle	characteristic value handle.
offset	value position offset.
len	length of the data to be written.
val	the value to be written.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.4.34 LeGattWriteNoRsp()

```
LE_ERR_STATE LeGattWriteNoRsp (
             UINT16 conn_hdl,
             UINT16 handle,
             UINT16 len,
             UINT8 * val )
```

Write without response.

Parameters

conn_hdl	connection handle.
handle	characteristic value handle.
len	length of the data to be written.
val	the value to be written.

Returns

- SYS_ERR_SUCCESS: success.
- others: refer to error code in ble_err.h.

4.4.5 Variable Documentation

4.4.5.1 gcCharacteristicUuid

```
const UINT16 gcCharacteristicUuid
```

4.4.5.2 gcCharAggregateUuid

```
const UINT16 gcCharAggregateUuid
```

4.4.5.3 gcCharExtPropUuid

```
const UINT16 gcCharExtPropUuid
```

4.4.5.4 gcCharFormatUuid

```
const UINT16 gcCharFormatUuid
```

4.4.5.5 gcCharUserDescUuid

```
const UINT16 gcCharUserDescUuid
```

4.4.5.6 gcClientCharConfigUuid

```
const UINT16 gcClientCharConfigUuid
```

4.4.5.7 gcExtReportRefUuid

```
const UINT16 gcExtReportRefUuid
```

4.4.5.8 gcIncludeUuid

```
const UINT16 gcIncludeUuid
```

4.4.5.9 gcPrimaryServiceUuid

```
const UINT16 gcPrimaryServiceUuid
```

4.4.5.10 gcReportRefUuid

```
const UINT16 gcReportRefUuid
```

4.4.5.11 gcSecondaryServiceUuid

```
const UINT16 gcSecondaryServiceUuid
```

4.4.5.12 gcServerCharConfigUuid

```
const UINT16 gcServerCharConfigUuid
```

4.4.5.13 gcValidRangeUuid

```
const UINT16 gcValidRangeUuid
```

4.5 BLE MSG APIs

Data Structures

- struct LE_SYS_MSG_BUF_OVERFLOW_T

Macros

- #define LE_ATT_MSG_BASE 0x1400
- #define LE_CM_MSG_BASE 0x1100
- #define LE_GATT_MSG_BASE 0x1500
- #define LE_HCI_MSG_BASE 0x1000
- #define LE_L2CAP_MSG_BASE 0x1200
- #define LE_SMP_MSG_BASE 0x1300
- #define LE_SYS_MSG_BASE 0x8000
- #define MESSAGE_ALLOCATE(M, S) PanicUnlessMalloc(sizeof(M##_T) + S)
- #define MESSAGE_BULID(M) M##_T *msg = PanicUnlessMalloc(sizeof(M##_T))
- #define MESSAGE_DATA_BULID(M, S) M##_T *msg = PanicUnlessMalloc(sizeof(M##_T) + S)
- #define MESSAGE_OFFSET(M) ((UINT8 *)msg + sizeof(M##_T))
- #define T_HOUR(h) ((UINT32)((h) * (UINT32)1000 * (UINT32)60) * (UINT32)60)
- #define T_MIN(m) ((UINT32)((m) * (UINT32)1000 * (UINT32)60))
- #define T_SEC(s) ((UINT32)((s) * (UINT32)1000))

Typedefs

- typedef MsgData MESSAGE
- typedef UINT16 MESSAGEID
- typedef void const * MsgData
- typedef const UINT8 * MsgLock
- typedef MsgLock MSGLOCK
- typedef UINT16 MSGSUBID
- typedef UINT32 MSGTIMER
- typedef TASKPACK * Task
- typedef Task TASK
- typedef void(* TASKHANDLER) (Task, UINT16, MsgData)
- typedef void ** TASKPACK

Enumerations

- enum { LE_SYS_MSG_BUF_OVERFLOW = (LE_SYS_MSG_BASE + 1), LE_SYS_MSG_TOP }

  BLE system message id.

Functions

- UINT16 LeCancelAllMessage (TASK task, MESSAGEID id)

  Cancel all message in queue.
- UINT16 LeCancelAllSubMessage (TASK task, MESSAGEID id, MSGSUBID subId)

  Cancel all sub message in queue.
- BOOL LeCancelFirstMessage (TASK task, MESSAGEID id)

  Cancel the first message in queue.
- BOOL LeCancelFirstSubMessage (TASK task, MESSAGEID id, MSGSUBID subId)

  Cancel the first sub message in queue.
- UINT16 LeGetSubMsgId (UINT16 *s)

  Get sub message id.
- BOOL LeHostCreateTask (TASK task, TASKHANDLER hdl)

  Create BLE task.
- void LeHostMessageLoop (void)

  message loop run.
- void LeSendMessage (TASK task, MESSAGEID msgId, MESSAGE msg)

  Send message to BLE task.
- void LeSendMessageAfter (TASK task, MESSAGEID msgId, MESSAGE msg, UINT32 delay)

  Delay, then send message to BLE task.
- void LeSendMessageUnlock (TASK task, MESSAGEID id, MESSAGE msg, MSGLOCK lock)

  Send message until lock is 0.
- void LeSendSubMessage (TASK task, MESSAGEID msgId, MSGSUBID subId, MESSAGE msg)

  Send sub message.
- void LeSendSubMessageAfter (TASK task, MESSAGEID msgId, MSGSUBID subId, MESSAGE msg, UIN↩ T32 delay)

  Delay, then send sub message.
- void LeSendSubMessageUnlock (TASK task, MESSAGEID id, MSGSUBID subId, MESSAGE msg, MSGLOCK lock)

  Send sub message until lock is 0.

4.5.1 Detailed Description

4.5.2 Macro Definition Documentation

4.5.2.1 LE_ATT_MSG_BASE

```
#define LE_ATT_MSG_BASE 0x1400
```

4.5.2.2 LE_CM_MSG_BASE

```
#define LE_CM_MSG_BASE 0x1100
```

4.5.2.3 LE_GATT_MSG_BASE

```
#define LE_GATT_MSG_BASE 0x1500
```

4.5.2.4 LE_HCI_MSG_BASE

```
#define LE_HCI_MSG_BASE 0x1000
```

4.5.2.5 LE_L2CAP_MSG_BASE

```
#define LE_L2CAP_MSG_BASE 0x1200
```

4.5.2.6 LE_SMP_MSG_BASE

```
#define LE_SMP_MSG_BASE 0x1300
```

4.5.2.7 LE_SYS_MSG_BASE

```
#define LE_SYS_MSG_BASE 0x8000
```

4.5.2.8 MESSAGE_ALLOCATE

```
#define MESSAGE_ALLOCATE(
              M,
              S ) PanicUnlessMalloc(sizeof(M##_T) + S)
```

4.5.2.9 MESSAGE_BULID

```
#define MESSAGE_BULID(
              M ) M##_T *msg = PanicUnlessMalloc(sizeof(M##_T))
```

4.5.2.10 MESSAGE_DATA_BULID

```
#define MESSAGE_DATA_BULID(
              M,
              S ) M##_T *msg = PanicUnlessMalloc(sizeof(M##_T) + S)
```

4.5.2.11 MESSAGE_OFFSET

```
#define MESSAGE_OFFSET(
              M ) ((UINT8 *)msg + sizeof(M##_T))
```

4.5.2.12 T_HOUR

```
#define T_HOUR(
              h ) ((UINT32)((h) * (UINT32)1000 * (UINT32)60) * (UINT32)60)
```

4.5.2.13 T_MIN

```
#define T_MIN(
              m ) ((UINT32)((m) * (UINT32)1000 * (UINT32)60))
```

4.5.2.14 T_SEC

```
#define T_SEC(
              s ) ((UINT32)((s) * (UINT32)1000))
```

4.5.3 Typedef Documentation

4.5.3.1 MESSAGE

```
typedef MsgData MESSAGE
```

4.5.3.2 MESSAGEID

```
typedef UINT16 MESSAGEID
```

4.5.3.3 MsgData

```
typedef void const* MsgData
```

4.5.3.4 MsgLock

```
typedef const UINT8* MsgLock
```

4.5.3.5 MSGLOCK

```
typedef MsgLock MSGLOCK
```

4.5.3.6 MSGSUBID

```
typedef UINT16 MSGSUBID
```

4.5.3.7 MSGTIMER

```
typedef UINT32 MSGTIMER
```

4.5.3.8 Task

```
typedef TASKPACK* Task
```

4.5.3.9 TASK

```
typedef Task TASK
```

4.5.3.10 TASKHANDLER

```
typedef void(* TASKHANDLER) (Task, UINT16, MsgData)
```

4.5.3.11 TASKPACK

```
typedef void** TASKPACK
```

4.5.4 Enumeration Type Documentation

4.5.4.1 anonymous enum

```
anonymous enum
```

BLE system message id.

Enumerator

LE_SYS_MSG_BUF_OVERFLOW	message buffer overflow
LE_SYS_MSG_TOP	top of system message id

4.5.5 Function Documentation

4.5.5.1 LeCancelAllMessage()

```
UINT16 LeCancelAllMessage (
            TASK task,
            MESSAGEID id )
```

Cancel all message in queue.

Parameters

task	task.
id	message id.

Returns

0 is ok, others is error.

4.5.5.2 LeCancelAllSubMessage()

```
UINT16 LeCancelAllSubMessage (
            TASK task,
            MESSAGEID id,
            MSGSUBID subId )
```

Cancel all sub message in queue.

Parameters

task	the task of recvice message.
id	message id.
subId	sub message id.

Returns

0 is ok, others is error.

4.5.5.3 LeCancelFirstMessage()

```
BOOL LeCancelFirstMessage (
            TASK task,
            MESSAGEID id )
```

Cancel the first message in queue.

Parameters

task	task.
id	message id.

Returns

True is ok, false is error.

4.5.5.4 LeCancelFirstSubMessage()

```
BOOL LeCancelFirstSubMessage (
            TASK task,
            MESSAGEID id,
            MSGSUBID subId )
```

Cancel the first sub message in queue.

Parameters

task	the task of recvice message.
id	message id.
subId	sub message id.

Returns

True is ok, false is error.

4.5.5.5 LeGetSubMsgId()

```
UINT16 LeGetSubMsgId (
            UINT16 * s )
```

Get sub message id.

Parameters

sub	message id.

Returns

0 is ok, others is error.

4.5.5.6 LeHostCreateTask()

```
BOOL LeHostCreateTask (
            TASK task,
            TASKHANDLER hdl )
```

Create BLE task.

Parameters

task	the reference of BLE task.
hdl	callback handle of BLE task.

Returns

TRUE is success, FALSE is failed.

4.5.5.7 LeHostMessageLoop()

```
void LeHostMessageLoop (
            void  )
```

message loop run.

Returns

None.

4.5.5.8 LeSendMessage()

```
void LeSendMessage (
            TASK task,
            MESSAGEID msgId,
            MESSAGE msg )
```

Send message to BLE task.

Parameters

task	reference of BLE task.
msg↩ Id	message ID.
msg	message.

Returns

None.

4.5.5.9 LeSendMessageAfter()

```
void LeSendMessageAfter (
            TASK task,
```

```
            MESSAGEID msgId,
            MESSAGE msg,
            UINT32 delay )
```

Delay, then send message to BLE task.

Parameters

task	reference of BLE task.
msg↩ Id	message ID.
msg	message.
delay	delay time, ms.

Returns

None.

4.5.5.10 LeSendMessageUnlock()

```
void LeSendMessageUnlock (
            TASK task,
            MESSAGEID id,
            MESSAGE msg,
            MSGLOCK lock )
```

Send message until lock is 0.

Parameters

task	the task of recvice message.
id	message id.
msg	message.
lock	lock number.

Returns

None.

4.5.5.11 LeSendSubMessage()

```
void LeSendSubMessage (
            TASK task,
            MESSAGEID msgId,
            MSGSUBID subId,
            MESSAGE msg )
```

Send sub message.

Parameters

task	the task of recvice message.
msg↩ Id	message id.
subId	sub message id.
msg	message.

Returns

None.

4.5.5.12 LeSendSubMessageAfter()

```
void LeSendSubMessageAfter (
            TASK task,
            MESSAGEID msgId,
            MSGSUBID subId,
            MESSAGE msg,
            UINT32 delay )
```

Delay, then send sub message.

Parameters

task	the task of recvice message.
msg↩ Id	message id.
subId	sub message id.
msg	message.
delay	delay time.

Returns

None.

4.5.5.13 LeSendSubMessageUnlock()

```
void LeSendSubMessageUnlock (
            TASK task,
            MESSAGEID id,
            MSGSUBID subId,
            MESSAGE msg,
            MSGLOCK lock )
```

Send sub message until lock is 0.

Parameters

task	the task of recvice message.
id	message id.
sub↩ Id	sub message id.
msg	message.
lock	lock number.

Returns

None.

4.6 BLE SMP APIs

Data Structures

- struct LE_SMP_MSG_ENCRYPTION_CHANGE_IND_T
- struct LE_SMP_MSG_ENCRYPTION_REFRESH_IND_T
- struct LE_SMP_MSG_OOB_DATA_REQUEST_IND_T
- struct LE_SMP_MSG_PAIRING_ACTION_IND_T
- struct LE_SMP_MSG_PAIRING_COMPLETE_IND_T
- struct LE_SMP_MSG_PASSKEY_DISPLAY_IND_T
- struct LE_SMP_MSG_PASSKEY_INPUT_IND_T
- struct LE_SMP_MSG_SC_OOB_DATA_REQUEST_IND_T
- struct LE_SMP_MSG_SLAVE_SECURITY_REQUEST_IND_T
- struct LE_SMP_MSG_USER_CONFIRM_IND_T
- struct LE_SMP_SC_OOB_DATA_T

Macros

- #define LE_MAX_BOND_COUNT 8
- #define LE_SM_IO_CAP_DISP_ONLY 0x00
- #define LE_SM_IO_CAP_DISP_YES_NO 0x01
- #define LE_SM_IO_CAP_KEYBOARD_DISP 0x04
- #define LE_SM_IO_CAP_KEYBOARD_ONLY 0x02
- #define LE_SM_IO_CAP_NO_IO 0x03
- #define LE_SM_PAIR_MITM_NO 0x00
- #define LE_SM_PAIR_MITM_YES 0x01
- #define LE_SM_PAIR_OOB_NO 0x00
- #define LE_SM_PAIR_OOB_YES 0x01
- #define LE_SM_PAIR_SC_NO 0x00
- #define LE_SM_PAIR_SC_YES 0x01

Enumerations

- enum {
  LE_SMP_MSG_SLAVE_SECURITY_REQUEST_IND = LE_SMP_MSG_BASE, LE_SMP_MSG_PAIRING_ACTION_IND,
  LE_SMP_MSG_PASSKEY_DISPLAY_IND, LE_SMP_MSG_PASSKEY_INPUT_IND,
  LE_SMP_MSG_OOB_DATA_REQUEST_IND, LE_SMP_MSG_SC_OOB_DATA_REQUEST_IND,
  LE_SMP_MSG_USER_CONFIRM_IND LE_SMP_MSG_ENCRYPTION_CHANGE_IND,
  LE_SMP_MSG_ENCRYPTION_REFRESH_IND, LE_SMP_MSG_PAIRING_COMPLETE_IND,
  LE_SMP_LONG_TERM_KEY_REQ, LE_SMP_KEYS_IND,
  LE_SMP_MSG_TOP }

  BLE SMP message id.
- enum {
  LE_SMP_PAIR_JUST_WORK, LE_SMP_PAIR_OOB, LE_SMP_PAIR_PASSKEY_INPUT, LE_SMP_PAIR_DISPLAY,
  LE_SMP_PAIR_NUM_COMPARE }

Functions

- void LeSmpInit (TASK appTask)

  BLE SMP Module Init.
- void LeSmpOobAuthDataRsp (UINT16 conn_hdl, UINT8 *data, UINT16 len)

  SMP OOB authenticate data response.
- UINT16 LeSmpOobPresent (UINT16 conn_hdl, BOOL oob_present)

  SMP OOB present.
- void LeSmpPasskeyInput (UINT16 conn_hdl, UINT32 passkey)

  Input passkey.
- UINT16 LeSmpScOobComputeConfirmVal (UINT8 *rand, UINT8 *confirm)

  SMP secure connection OOB compute confirm value.
- void LeSmpScOobDataRsp (UINT16 conn_hdl, UINT8 *our_rand, LE_SMP_SC_OOB_DATA_T *peer)

  OOB data response.
- UINT16 LeSmpSecurityReq (UINT16 conn_hdl)

  BLE SMP security request.
- UINT16 LeSmpSecurityRsp (UINT16 conn_hdl, BOOL accept)

  BLE SMP security request.
- UINT16 LeSmpSetDefaultConfig (UINT8 iocap, BOOL mitm, BOOL sc, BOOL bond)

  Set default configure for pairing.
- UINT16 LeSmpUserConfirmRsp (UINT16 conn_hdl, BOOL accept)

  User confirm response.

4.6.1 Detailed Description

4.6.2 Macro Definition Documentation

4.6.2.1 LE_MAX_BOND_COUNT

```
#define LE_MAX_BOND_COUNT 8
```

4.6.2.2 LE_SM_IO_CAP_DISP_ONLY

```
#define LE_SM_IO_CAP_DISP_ONLY 0x00
```

display only

4.6.2.3 LE_SM_IO_CAP_DISP_YES_NO

```
#define LE_SM_IO_CAP_DISP_YES_NO 0x01
```

display + yes or no

4.6.2.4 LE_SM_IO_CAP_KEYBOARD_DISP

```
#define LE_SM_IO_CAP_KEYBOARD_DISP 0x04
```

display + keyboard

4.6.2.5 LE_SM_IO_CAP_KEYBOARD_ONLY

```
#define LE_SM_IO_CAP_KEYBOARD_ONLY 0x02
```

keyboard only

4.6.2.6 LE_SM_IO_CAP_NO_IO

```
#define LE_SM_IO_CAP_NO_IO 0x03
```

no input and output

4.6.2.7 LE_SM_PAIR_MITM_NO

```
#define LE_SM_PAIR_MITM_NO 0x00
```

4.6.2.8 LE_SM_PAIR_MITM_YES

```
#define LE_SM_PAIR_MITM_YES 0x01
```

4.6.2.9 LE_SM_PAIR_OOB_NO

```
#define LE_SM_PAIR_OOB_NO 0x00
```

4.6.2.10 LE_SM_PAIR_OOB_YES

```
#define LE_SM_PAIR_OOB_YES 0x01
```

4.6.2.11 LE_SM_PAIR_SC_NO

```
#define LE_SM_PAIR_SC_NO 0x00
```

4.6.2.12 LE_SM_PAIR_SC_YES

```
#define LE_SM_PAIR_SC_YES 0x01
```

4.6.3 Enumeration Type Documentation

4.6.3.1 anonymous enum

```
anonymous enum
```

BLE SMP message id.

Enumerator

LE_SMP_MSG_SLAVE_SECURITY_REQUEST_IND	slave security request
LE_SMP_MSG_PAIRING_ACTION_IND	pairing action indication
LE_SMP_MSG_PASSKEY_DISPLAY_IND	passkey display indication
LE_SMP_MSG_PASSKEY_INPUT_IND	passkey input indication
LE_SMP_MSG_OOB_DATA_REQUEST_IND	OOB date request indication
LE_SMP_MSG_SC_OOB_DATA_REQUEST_IND	SC OOB data request indication
LE_SMP_MSG_USER_CONFIRM_IND	user confirm indication
LE_SMP_MSG_ENCRYPTION_CHANGE_IND	encryption change indication
LE_SMP_MSG_ENCRYPTION_REFRESH_IND	encryption refresh indication
LE_SMP_MSG_PAIRING_COMPLETE_IND	pairing complete indication
LE_SMP_LONG_TERM_KEY_REQ	long term key request
LE_SMP_KEYS_IND	keys indication
LE_SMP_MSG_TOP	top of SMP message id

4.6.3.2 anonymous enum

```
anonymous enum
```

Enumerator

LE_SMP_PAIR_JUST_WORK	just work
LE_SMP_PAIR_OOB	out of band
LE_SMP_PAIR_PASSKEY_INPUT	passkey entry
LE_SMP_PAIR_DISPLAY	display
LE_SMP_PAIR_NUM_COMPARE	number compare

4.6.4 Function Documentation

4.6.4.1 LeSmpInit()

```
void LeSmpInit (
            TASK appTask )
```

BLE SMP Module Init.

Parameters

appTask	the reference of BLE task.

Returns

None.

4.6.4.2 LeSmpOobAuthDataRsp()

```
void LeSmpOobAuthDataRsp (
            UINT16 conn_hdl,
            UINT8 * data,
            UINT16 len )
```

SMP OOB authenticate data response.

Parameters

conn_hdl	connection handle.
data	response data.
len	data length.

Returns

None.

4.6.4.3 LeSmpOobPresent()

```
UINT16 LeSmpOobPresent (
            UINT16 conn_hdl,
            BOOL oob_present )
```

SMP OOB present.

Parameters

conn_hdl	connection handle.
oob_present	present or not.

Returns

0 is Ok, others refer to SMP_ERR_∗ in ble_err.h.

4.6.4.4 LeSmpPasskeyInput()

```
void LeSmpPasskeyInput (
            UINT16 conn_hdl,
            UINT32 passkey )
```

Input passkey.

Parameters

conn_hdl	connection handle.
passkey	passkey.

Returns

None.

4.6.4.5 LeSmpScOobComputeConfirmVal()

```
UINT16 LeSmpScOobComputeConfirmVal (
            UINT8 * rand,
            UINT8 * confirm )
```

SMP secure connection OOB compute confirm value.

Parameters

rand	random data.
confirm	confirm data.

Returns

0 is Ok, others refer to SMP_ERR_∗ in ble_err.h.

4.6.4.6 LeSmpScOobDataRsp()

```
void LeSmpScOobDataRsp (
             UINT16 conn_hdl,
             UINT8 * our_rand,
             LE_SMP_SC_OOB_DATA_T * peer )
```

OOB data response.

Parameters

conn_hdl	connection handld.
our_rand	our random data.
peer	peer OOB data.

Returns

None.

4.6.4.7 LeSmpSecurityReq()

```
UINT16 LeSmpSecurityReq (
             UINT16 conn_hdl )
```

BLE SMP security request.

Parameters

conn_hdl	connection handle.

Returns

0 is Ok, others refer to SMP_ERR_∗ in ble_err.h.

4.6.4.8 LeSmpSecurityRsp()

```
UINT16 LeSmpSecurityRsp (
             UINT16 conn_hdl,
             BOOL accept )
```

BLE SMP security request.

Parameters

conn_hdl	connection handle.
accept	TRUE is accept, FALSE is not.

Returns

0 is Ok, others refer to SMP_ERR_∗ in ble_err.h.

4.6.4.9 LeSmpSetDefaultConfig()

```
UINT16 LeSmpSetDefaultConfig (
            UINT8 iocap,
            BOOL mitm,
            BOOL sc,
            BOOL bond )
```

Set default configure for pairing.

Parameters

iocap	IO capability.
mitm	TRUE is MITM protected, FALSE is not.
sc	TRUE is request BLE secure connection pairing, FALSE is not.
bond	TRUE: bonding, FALSE: no bonding.

Returns

0 is Ok, others refer to SMP_ERR_∗ in ble_err.h.

4.6.4.10 LeSmpUserConfirmRsp()

```
UINT16 LeSmpUserConfirmRsp (
            UINT16 conn_hdl,
            BOOL accept )
```

User confirm response.

Parameters

conn_hdl	connection handle.
accept	yes or no.

Returns

0 is Ok, others refer to SMP_ERR_∗ in ble_err.h.

4.7 WIFI APIs

WIFI APIs.

Modules

- WIFI Common APIs
- WIFI STA APIs
- Enumeration

Data Structures

- struct wifi_active_scan_time_t

  Range of active scan times per channel.
- struct wifi_ap_config_t

  This structure is the Wi-Fi configuration for initialization for Soft-AP mode.
- struct wifi_auto_connect_info_f

  WiFi auto connect info parameters.
- union wifi_config_t

  Wi-Fi configuration for initialization.
- struct wifi_fast_scan_threshold_t

  Structure describing parameters for a Wi-Fi fast scan.
- struct wifi_init_config_t

  WiFi stack configuration parameters.
- struct wifi_scan_config_t

  Parameters for an SSID scan.
- struct wifi_scan_info_t

  This structure defines the inforamtion of scanned APs.
- struct wifi_scan_list_t

  This structure defines the list of scanned APs with their corresponding information.
- union wifi_scan_time_t

  Aggregate of active & passive scan time per channel.
- struct wifi_sta_config_t

  This structure is the Wi-Fi configuration for initialization for STA mode.

Macros

- #define WIFI_BEACON_INTERVAL_LENGTH (2)

  Beacon interval length in a frame header.
- #define WIFI_CAPABILITY_INFO_LENGTH (2)

  Length of capability information in a frame header.
- #define WIFI_LENGTH_802_11 (24)

  Length of 802.11 MAC header.
- #define WIFI_LENGTH_PASSPHRASE (64)

  The maximum length of passphrase used in WPA-PSK and WPA2-PSK encryption types.
- #define WIFI_MAC_ADDRESS_LENGTH (6)

  MAC address length.
- #define WIFI_MAX_LENGTH_OF_SSID (32+1)

  The maximum length of SSID.
- #define WIFI_MAX_SCAN_AP_NUM (16)

  maximum number of ap list items which can stored
- #define WIFI_MAX_SUPPORTED_RATES (8)

  maximum number of supported rates which can used

Typedefs

- typedef int(∗ wifi_event_notify_cb_t) (void ∗data)

Functions

- int wifi_event_process_handler (wifi_event_t event, uint8_t ∗payload, uint32_t length)

  Default event handler for system events.
- void wifi_install_default_event_handlers (void)

  Set discoverability and connectability mode for legacy bluetooth. This function should.
- int wifi_register_event_handler (wifi_event_t idx, wifi_event_handler_t handler)

  Set discoverability and connectability mode for legacy bluetooth. This function should.

4.7.1 Detailed Description

WIFI APIs.

4.7.2 Macro Definition Documentation

4.7.2.1 WIFI_BEACON_INTERVAL_LENGTH

```
#define WIFI_BEACON_INTERVAL_LENGTH (2)
```

Beacon interval length in a frame header.

4.7.2.2 WIFI_CAPABILITY_INFO_LENGTH

```
#define WIFI_CAPABILITY_INFO_LENGTH (2)
```

Length of capability information in a frame header.

4.7.2.3 WIFI_LENGTH_802_11

```
#define WIFI_LENGTH_802_11 (24)
```

Length of 802.11 MAC header.

4.7.2.4 WIFI_LENGTH_PASSPHRASE

```
#define WIFI_LENGTH_PASSPHRASE (64)
```

The maximum length of passphrase used in WPA-PSK and WPA2-PSK encryption types.

4.7.2.5 WIFI_MAC_ADDRESS_LENGTH

```
#define WIFI_MAC_ADDRESS_LENGTH (6)
```

MAC address length.

4.7.2.6 WIFI_MAX_LENGTH_OF_SSID

```
#define WIFI_MAX_LENGTH_OF_SSID (32+1)
```

The maximum length of SSID.

4.7.2.7 WIFI_MAX_SCAN_AP_NUM

```
#define WIFI_MAX_SCAN_AP_NUM (16)
```

maximum number of ap list items which can stored

4.7.2.8 WIFI_MAX_SUPPORTED_RATES

```
#define WIFI_MAX_SUPPORTED_RATES (8)
```

maximum number of supported rates which can used

4.7.3 Typedef Documentation

4.7.3.1 wifi_event_notify_cb_t

```
typedef int(* wifi_event_notify_cb_t) (void *data)
```

4.7.4 Function Documentation

4.7.4.1 wifi_event_process_handler()

```
int wifi_event_process_handler (
            wifi_event_t event,
            uint8_t * payload,
            uint32_t length )
```

Default event handler for system events.

This function performs default handling of system events. When using event_loop APIs, it is called automatically before invoking the user-provided callback function.

Applications which implement a custom event loop must call this function as part of event processing.

Parameters

in	*event*	event type Set the event type,Options are • WIFI_EVENT_INIT_COMPLETE • WIFI_EVENT_SCAN_COMPLETE • WIFI_EVENT_STA_START • WIFI_EVENT_STA_STOP • WIFI_EVENT_STA_CONNECTED • WIFI_EVENT_STA_DISCONNECTED • WIFI_EVENT_STA_CONNECTION_FAILED • WIFI_EVENT_STA_GOT_IP
in	*payload*	Data block that transmitted to event
in	*length*	The length of data block

Returns

0 : success
other : failed

4.7.4.2 wifi_install_default_event_handlers()

```
void wifi_install_default_event_handlers (
            void  )
```

Set discoverability and connectability mode for legacy bluetooth. This function should.

4.7.4.3 wifi_register_event_handler()

```
int wifi_register_event_handler (
            wifi_event_t idx,
            wifi_event_handler_t handler )
```

Set discoverability and connectability mode for legacy bluetooth. This function should.

Parameters

in	*idx*	one of the enums of bt_scan_mode_t
in	*handler*	the Wi-Fi event handler

Returns

0 : success
other : failed

4.8 WIFI Common APIs

Data Structures

- struct event_msg_t

  Send information to event by event_msg_t.
- union wifi_event_info_t

  wifi_event_info_t
- struct wifi_event_sta_connected_t

  wifi_event_sta_connected_t
- struct wifi_event_sta_disconnected_t

  wifi_event_sta_disconnected_t
- struct wifi_event_sta_got_ip_t

  wifi_event_sta_got_ip_t
- struct wifi_event_sta_scan_done_t

  wifi_event_sta_scan_done_t

Typedefs

- typedef int(∗ wifi_event_cb_t) (wifi_event_id_t event, void ∗data, uint16_t length)

  Application specified event callback function.

Functions

- int wifi_event_loop_init (wifi_event_cb_t cb)

  Event Loop Initialization Create the event handler and call back funtion.
- int wifi_event_loop_send (event_msg_t ∗msg)

  Send an event to event task.
- void wifi_event_loop_set_cb (wifi_event_cb_t cb, void ∗ctx)

  Set application specified event callback function.
- int wifi_event_process_handler (wifi_event_t event, uint8_t ∗payload, uint32_t length)

  Default event handler for system events.

4.8.1 Detailed Description

4.8.2 Typedef Documentation

4.8.2.1 wifi_event_cb_t

```
typedef int(* wifi_event_cb_t) (wifi_event_id_t event, void *data, uint16_t length)
```

Application specified event callback function.

4.8.3 Function Documentation

4.8.3.1 wifi_event_loop_init()

```
int wifi_event_loop_init (
            wifi_event_cb_t cb )
```

Event Loop Initialization Create the event handler and call back funtion.

Parameters

cb	: application specified event callback

Returns

0 : success
other : failed

4.8.3.2 wifi_event_loop_send()

```
int wifi_event_loop_send (
            event_msg_t * msg )
```

Send an event to event task.

Attention

1. Other task/modules, such as the TCPIP module, can call this API to send an event to event task

Parameters

event_msg_t	* msg: Send information to event by msg

Returns

0 : success
other : failed

4.8.3.3 wifi_event_loop_set_cb()

```
void wifi_event_loop_set_cb (
            wifi_event_cb_t cb,
            void * ctx )
```

Set application specified event callback function.

Attention

1. If cb is NULL, means application does not need to handle If cb is not NULL, it will be called when an event is received and after the default event callback is completed

Parameters

wifi_event_↩ cb_t	cb : callback
void	∗ctx : reserved for user

4.8.3.4 wifi_event_process_handler()

```
int wifi_event_process_handler (
            wifi_event_t event,
            uint8_t * payload,
            uint32_t length )
```

Default event handler for system events.

This function performs default handling of system events.

Applications which implement a custom event loop must call this function as part of event processing.

Parameters

in	*event*	event type Set the event type,Options are • WIFI_EVENT_INIT_COMPLETE • WIFI_EVENT_SCAN_COMPLETE • WIFI_EVENT_STA_START • WIFI_EVENT_STA_STOP • WIFI_EVENT_STA_CONNECTED • WIFI_EVENT_STA_DISCONNECTED • WIFI_EVENT_STA_CONNECTION_FAILED • WIFI_EVENT_STA_GOT_IP
in	*payload*	Data block transmitted to event
in	*length*	The length of the data block

Returns

0 : success
other : failed

4.9 WIFI STA APIs

Typedefs

- typedef int32_t(∗ wifi_event_handler_t) (wifi_event_t event, uint8_t ∗payload, uint32_t length)

  This defines the Wi-Fi event handler. Call wifi_connection_register_event_handler() to register a handler, then the Wi-Fi driver generates an event and sends it to the handler.
- typedef void(∗ wifi_init_complete_cb_t) (void ∗ctx)

  Initialization of complete callback function.
- typedef int32_t wifi_result_t

Functions

- int wifi_auto_connect_del_ap_info (u8 index)

  Delete automatically connected AP information stored in flash.
- int wifi_auto_connect_get_ap_info (u8 index, wifi_auto_connect_info_f ∗info)

  Get ap detailed information saved in flash.
- u8 wifi_auto_connect_get_ap_num (void)

  Get the number of automatically connected aps that have been saved in the flash.
- u8 wifi_auto_connect_get_mode (void)

  Get the status of the current automatic connection mode.
- int wifi_auto_connect_init (void)

  Initialize wifi automatic connection.
- int wifi_auto_connect_set_ap_num (u8 num)

  Save the number of automatically connected ap to flash.
- int wifi_auto_connect_set_mode (u8 mode)

  Set the connection type.
- int wifi_auto_connect_start (void)

  Start wifi automatic connection process.
- int wifi_config_get_bandwidth (wifi_mode_t interface, wifi_bandwidth_t ∗bandwidth)

  Get the bandwidth of OPL1000 specified interface.
- int wifi_config_get_bssid (uint8_t ∗bssid)

  get bssid after scan
- int wifi_config_get_channel (wifi_mode_t interface, uint8_t ∗channel)

  Get the primary/secondary channel of OPL1000.
- int wifi_config_get_dtim_interval (uint8_t ∗interval)

  Get the interval of DTIM.
- int wifi_config_get_listen_interval (uint8_t ∗interval)

  Get the interval of listen.
- int wifi_config_get_mac_address (wifi_mode_t interface, uint8_t ∗address)

  Get mac of specified interface.
- int wifi_config_get_opmode (uint8_t ∗mode)

  Set wifi operation mode.
- int wifi_config_get_skip_dtim (uint8_t ∗value)

  Get the Skip DTIM value in current wifi setting of OPL1000.
- int wifi_config_get_ssid (uint8_t ∗ssid, uint8_t ∗ssid_length)

  Get ssid value of AP.
- int wifi_config_set_bandwidth (wifi_mode_t interface, wifi_bandwidth_t bandwidth)

  Set the bandwidth of OPL1000 specified interface.
- int wifi_config_set_bssid (uint8_t ∗bssid)

config OPL1000 Wi-Fi bssid.

- int wifi_config_set_channel (wifi_mode_t interface, uint8_t channel)

  Set primary/secondary channel of OPL1000.
- int wifi_config_set_dtim_interval (uint8_t interval)

  Set the interval of DTIM.
- int wifi_config_set_listen_interval (uint8_t interval)

  Set the interval of listen.
- int wifi_config_set_mac_address (wifi_mode_t interface, uint8_t *address)

  Set MAC address of OPL1000 Wi-Fi station or the soft-AP interface.
- int wifi_config_set_opmode (uint8_t mode)

  Set wifi operation mode.
- int wifi_config_set_skip_dtim (uint8_t value)

  Set the Skip DTIM value of OPL1000.
- int wifi_config_set_ssid (wifi_mode_t interface, uint8_t *ssid, uint8_t ssid_length)

  Set the ssid value of the current device.
- int wifi_connection_connect (wifi_config_t *config)

  Connect OPL1000 Wi-Fi station to certain AP.
- int wifi_connection_disconnect_ap (void)

  Disconnect the link between OPL1000 and connected AP.
- int wifi_connection_disconnect_sta (uint8_t *address)

  Disconnect the link between the current device and the station.
- int wifi_connection_get_rssi (int8_t *rssi)

  get signal strength of AP
- int wifi_connection_register_event_handler (wifi_event_t event, wifi_event_handler_t handler)

  register wifi call back handler
- int wifi_connection_scan_start (uint8_t *ssid, uint8_t ssid_length, uint8_t *bssid, uint8_t scan_mode, uint8_t scan_option)

  Scan start.
- int wifi_connection_unregister_event_handler (wifi_event_t event, wifi_event_handler_t handler)

  unregister wifi call back handler
- int wifi_deinit (void)

  De-init Wi-Fi Initialization and Configuration functions.
- u8 wifi_fast_connect_get_mode (u8 ap_index)

  Get the status of AP fast connection.
- int wifi_fast_connect_set_mode (u8 mode, u8 ap_index)

  Set the fast connection type.
- int wifi_fast_connect_start (void)

  Start the fast connection process.
- int wifi_get_config (wifi_mode_t interface, wifi_config_t *conf)

  Get configuration of specified interface.
- int wifi_init (const wifi_init_config_t *config, wifi_init_complete_cb_t init_cb)

  Init Wi-Fi Initializes the wifi according to the specified parameters in the config.
- int wifi_scan_get_ap_list (wifi_scan_list_t *scan_list)

  Get list of APs that found in last scan operation.
- int wifi_scan_get_ap_num (uint16_t *number)

  Get the number of scanned APs.
- int wifi_scan_get_ap_records (uint16_t *number, wifi_scan_info_t *ap_records)

  Get AP list found in last scan operation.
- int wifi_scan_scan_stop (void)

  Stop scanning process.
- int wifi_scan_start (const wifi_scan_config_t *config, bool block)

Scan all available APs. After invoke the wifi_set_config() and wifi_start(), then call wifi_scan_start() to scan APs.

- int wifi_set_config (wifi_mode_t interface, wifi_config_t *conf)

  Set configuration of OPL1000 STA.
- int wifi_sta_get_ap_info (wifi_scan_info_t *ap_info)

  Get information of AP which OPL1000 station is associated with.
- int wifi_start (void)

  Start Wi-Fi working.
- int wifi_stop (void)

  Stop wifi working.

4.9.1 Detailed Description

4.9.2 Typedef Documentation

4.9.2.1 wifi_event_handler_t

```
typedef int32_t(* wifi_event_handler_t) (wifi_event_t event, uint8_t *payload, uint32_t length)
```

This defines the Wi-Fi event handler. Call wifi_connection_register_event_handler() to register a handler, then the Wi-Fi driver generates an event and sends it to the handler.

Parameters

in	*event*	is an optional event to register. For more details, please refer to wifi_event_t.
in	*payload*	is the payload for the event. When the event is WIFI_EVENT_IOT_CONNECTED in AP mode, payload is the connected STA's MAC address. When the event is WIFI_EVENT_IOT_CONNECTED in STA mode, payload is the connected AP's BSSID.
in	*length*	is the length of a packet.

Returns

The return value is reserved and it is ignored.

4.9.2.2 wifi_init_complete_cb_t

```
typedef void(* wifi_init_complete_cb_t) (void *ctx)
```

Initialization of complete callback function.

Invoked when Wi-Fi initialization is complete.

Parameters

ctx	is context pointer that provided to wifi_init(). It will be passed back to the callback.

4.9.2.3 wifi_result_t

```
typedef int32_t wifi_result_t
```

4.9.3 Function Documentation

4.9.3.1 wifi_auto_connect_del_ap_info()

```
int wifi_auto_connect_del_ap_info (
            u8 index )
```

Delete automatically connected AP information stored in flash.

Parameters

in	*index*	: Index of ap information,The range is 0 to 3

Returns

0 : success
other : failed

4.9.3.2 wifi_auto_connect_get_ap_info()

```
int wifi_auto_connect_get_ap_info (
            u8 index,
            wifi_auto_connect_info_f * info )
```

Get ap detailed information saved in flash.

Parameters

in	*index*	: Index of ap information,The range is 0 to 3
in	*info*	: wifi_auto_connect_info_f array to hold the found APs

Returns

0 : success
other : failed

4.9.3.3 wifi_auto_connect_get_ap_num()

```
u8 wifi_auto_connect_get_ap_num (
            void  )
```

Get the number of automatically connected aps that have been saved in the flash.

Returns

0-3 ap number

4.9.3.4 wifi_auto_connect_get_mode()

```
u8 wifi_auto_connect_get_mode (
            void  )
```

Get the status of the current automatic connection mode.

Returns

0 : off
1 : on

4.9.3.5 wifi_auto_connect_init()

```
int wifi_auto_connect_init (
            void  )
```

Initialize wifi automatic connection.

Returns

0 : success
other : failed

4.9.3.6 wifi_auto_connect_set_ap_num()

```
int wifi_auto_connect_set_ap_num (
            u8 num )
```

Save the number of automatically connected ap to flash.

Parameters

in	*Connection*	Type

Returns

0 : success
other : failed

4.9.3.7 wifi_auto_connect_set_mode()

```
int wifi_auto_connect_set_mode (
            u8 mode )
```

Set the connection type.

Parameters

in	*Connection*	Type • WIFI_MODE_STA • WIFI_MODE_AP (currently not support)

Returns

0 : success
other : failed

4.9.3.8 wifi_auto_connect_start()

```
int wifi_auto_connect_start (
            void  )
```

Start wifi automatic connection process.

Returns

0 : success
other : failed

4.9.3.9 wifi_config_get_bandwidth()

```
int wifi_config_get_bandwidth (
            wifi_mode_t interface,
            wifi_bandwidth_t * bandwidth )
```

Get the bandwidth of OPL1000 specified interface.

Attention

1. API returns false if try to get an interface which is not enable

Parameters

in	*interface*	Configure the current wifi working mode,The options are • WIFI_MODE_STA • WIFI_MODE_AP (currently not support)
out	*bandwidth*	Get the bandwidth value of the current wifi module working through the pointer

Returns

0 : success
other : failed

4.9.3.10 wifi_config_get_bssid()

```
int wifi_config_get_bssid (
            uint8_t * bssid )
```

get bssid after scan

Parameters

out	*bssid*	the string of bssid

Returns

0 : success
other : failed

4.9.3.11 wifi_config_get_channel()

```
int wifi_config_get_channel (
            wifi_mode_t interface,
            uint8_t * channel )
```

Get the primary/secondary channel of OPL1000.

Attention

1. API returns false if try to get an interface which is not enabled

Parameters

in	*interface*	Configure the current wifi working mode,The options are • WIFI_MODE_STA • WIFI_MODE_AP (currently not support)
out	*channel*	Get Current module wifi work channel number

Returns

0 : success
other : failed

4.9.3.12 wifi_config_get_dtim_interval()

```
int wifi_config_get_dtim_interval (
            uint8_t * interval )
```

Get the interval of DTIM.

Parameters

in	*interval*	the interval of DTIM

Returns

0 : success
other : failed

4.9.3.13 wifi_config_get_listen_interval()

```
int wifi_config_get_listen_interval (
            uint8_t * interval )
```

Get the interval of listen.

Parameters

in	*interval*	the interval of listen

Returns

0 : success
other : failed

4.9.3.14 wifi_config_get_mac_address()

```
int wifi_config_get_mac_address (
            wifi_mode_t interface,
            uint8_t * address )
```

Get mac of specified interface.

Parameters

in	*interface*	Configure the current wifi working mode,The options are • WIFI_MODE_STA • WIFI_MODE_AP (currently not support)
out	*address*	Get the MAC address of the device through this interface, The address is similar to this structure: xx:xx:xx:xx:xx:xx

Returns

0 : success
other : failed

4.9.3.15 wifi_config_get_opmode()

```
int wifi_config_get_opmode (
            uint8_t * mode )
```

Set wifi operation mode.

Parameters

mode	refer to wifi_mode_t

Returns

0 : success
other : failed

4.9.3.16 wifi_config_get_skip_dtim()

```
int wifi_config_get_skip_dtim (
            uint8_t * value )
```

Get the Skip DTIM value in current wifi setting of OPL1000.

Parameters

out	*value*	Get the Skip DTIM value in current wifi setting

Returns

0 : success
other : failed

4.9.3.17 wifi_config_get_ssid()

```
int wifi_config_get_ssid (
            uint8_t * ssid,
            uint8_t * ssid_length )
```

Get ssid value of AP.

Parameters

out	*ssid*	Get ssid by pointer
out	*ssid_length*	Get the length of the ssid character

Returns

0 : success
other : failed

4.9.3.18 wifi_config_set_bandwidth()

```
int wifi_config_set_bandwidth (
            wifi_mode_t interface,
            wifi_bandwidth_t bandwidth )
```

Set the bandwidth of OPL1000 specified interface.

Parameters

in	*interface*	Configure the current wifi working mode,The options are • WIFI_MODE_STA • WIFI_MODE_AP (currently not support)
in	*bandwidth*	Set the working bandwidth of wifi

Returns

0 : success
other : failed

4.9.3.19 wifi_config_set_bssid()

```
int wifi_config_set_bssid (
            uint8_t * bssid )
```

config OPL1000 Wi-Fi bssid.

Parameters

in	*bssid*	the string of bssid

Returns

0 : success
other : failed

4.9.3.20 wifi_config_set_channel()

```
int wifi_config_set_channel (
            wifi_mode_t interface,
            uint8_t channel )
```

Set primary/secondary channel of OPL1000.

Attention

1. This is a special API for sniffer
2. This API should be called after wifi_start()

Parameters

in	*interface*	Configure the current wifi working mode,The options are • WIFI_MODE_STA • WIFI_MODE_AP (currently not support)
in	*channel*	Set current Wi-Fi work channel number

Returns

0 : success
other : failed

4.9.3.21 wifi_config_set_dtim_interval()

```
int wifi_config_set_dtim_interval (
            uint8_t interval )
```

Set the interval of DTIM.

Parameters

in	*interval*	the interval of DTIM

Returns

0 : success
other : failed

4.9.3.22 wifi_config_set_listen_interval()

```
int wifi_config_set_listen_interval (
            uint8_t interval )
```

Set the interval of listen.

Parameters

in	*interval*	the interval of listen

Returns

0 : success
other : failed

4.9.3.23 wifi_config_set_mac_address()

```
int wifi_config_set_mac_address (
            wifi_mode_t interface,
            uint8_t * address )
```

Set MAC address of OPL1000 Wi-Fi station or the soft-AP interface.

Attention

1. This API can only be called when the interface is disabled
2. OPL1000 soft-AP and station have different MAC addresses, do not set them to be the same.

Parameters

in	*interface*	Configure the current wifi working mode,The options are • WIFI_MODE_STA • WIFI_MODE_AP (currently not support)
in	*address*	set MAC address

Returns

0 : success
other : failed

4.9.3.24 wifi_config_set_opmode()

```
int wifi_config_set_opmode (
            uint8_t mode )
```

Set wifi operation mode.

Parameters

mode	refer to wifi_mode_t

Returns

0 : success
other : failed

4.9.3.25 wifi_config_set_skip_dtim()

```
int wifi_config_set_skip_dtim (
            uint8_t value )
```

Set the Skip DTIM value of OPL1000.

Parameters

in	*value*	Set the Skip DTIM value

Attention

1. This API will set the skip DTIM value to share memory and stored in flash, please use wifi_config_get_skip_dtim() to check it.
2. The setting will be effect after next connect. We recommend re-connect AP after setting to make sure the value is correct.

Returns

0 : success
other : failed

4.9.3.26 wifi_config_set_ssid()

```
int wifi_config_set_ssid (
            wifi_mode_t interface,
            uint8_t * ssid,
            uint8_t ssid_length )
```

Set the ssid value of the current device.

Parameters

in	*interface*	Configure the current wifi working mode,The options are • WIFI_MODE_STA • WIFI_MODE_AP (currently not support)
in	*ssid*	Set the value of ssid
in	*ssid_length*	The length of ssid parameter

Returns

0 : success
other : failed

4.9.3.27 wifi_connection_connect()

```
int wifi_connection_connect (
            wifi_config_t * config )
```

Connect OPL1000 Wi-Fi station to certain AP.

Attention

1. This API only impact WIFI_MODE_STA or WIFI_MODE_AP mode
2. If OPL1000 is connected to an AP, call wifi_disconnect to disconnect.

Parameters

in	*config*	Establish connection parameters

Returns

0 : success
other : failed

4.9.3.28 wifi_connection_disconnect_ap()

```
int wifi_connection_disconnect_ap (
            void  )
```

Disconnect the link between OPL1000 and connected AP.

Returns

0 : success
other : failed

4.9.3.29 wifi_connection_disconnect_sta()

```
int wifi_connection_disconnect_sta (
            uint8_t * address )
```

Disconnect the link between the current device and the station.

Parameters

in	*address*	station address

Returns

0 : success
other : failed

4.9.3.30 wifi_connection_get_rssi()

```
int wifi_connection_get_rssi (
            int8_t * rssi )
```

get signal strength of AP

Attention

1. If the scan is successful, this API returns signal strength value, otherwise it will get wrong result

Parameters

out	*rssi*	rssi value

Returns

0 : success
other : failed

4.9.3.31 wifi_connection_register_event_handler()

```
int wifi_connection_register_event_handler (
            wifi_event_t event,
            wifi_event_handler_t handler )
```

register wifi call back handler

Parameters

in	*event*	The type of the registered event. Options are • WIFI_EVENT_INIT_COMPLETE • WIFI_EVENT_SCAN_COMPLETE • WIFI_EVENT_STA_START • WIFI_EVENT_STA_STOP • WIFI_EVENT_STA_CONNECTED • WIFI_EVENT_STA_DISCONNECTED • WIFI_EVENT_STA_CONNECTION_FAILED • WIFI_EVENT_STA_GOT_IP
in	*handler*	registered event handler

Returns

0 : success
other : failed

4.9.3.32 wifi_connection_scan_start()

```
int wifi_connection_scan_start (
            uint8_t * ssid,
            uint8_t ssid_length,
            uint8_t * bssid,
            uint8_t scan_mode,
            uint8_t scan_option )
```

Scan start.

Parameters

ssid	ssid string
ssid_length	ssid string length
bssid	bssid
scan_mode	refer to #wifi_scan_mode_ext in wpa_common_patch.h
scan_option	if scan_option is true, this API will block the caller until the scan is done, otherwise it will return immediately

Returns

0 : success
other : failed

4.9.3.33 wifi_connection_unregister_event_handler()

```
int wifi_connection_unregister_event_handler (
            wifi_event_t event,
            wifi_event_handler_t handler )
```

unregister wifi call back handler

Parameters

in	*event*	The type of the unregistered event. Options please refer to wifi_connection_register_event_handler()
in	*handler*	unregistered event handler

Returns

0 : success
other : failed

4.9.3.34 wifi_deinit()

```
int wifi_deinit (
            void  )
```

De-init Wi-Fi Initialization and Configuration functions.

Attention

1. This API should be called if want to remove Wi-Fi driver from the system

Returns

0 : success
other : failed

4.9.3.35 wifi_fast_connect_get_mode()

```
u8 wifi_fast_connect_get_mode (
            u8 ap_index )
```

Get the status of AP fast connection.

Parameters

in	*ap_index*	: Index of ap information,The range is 0 to 3

Returns

0 : success
other : failed

4.9.3.36 wifi_fast_connect_set_mode()

```
int wifi_fast_connect_set_mode (
            u8 mode,
            u8 ap_index )
```

Set the fast connection type.

Parameters

in	*mode*	: Configure the fast connect mode ,0 means disable fast connection, and 1 enable the fast connection mode
in	*ap_index*	: Index of ap information,The range is 0 to 3

Returns

0 : success
other : failed

4.9.3.37 wifi_fast_connect_start()

```
int wifi_fast_connect_start (
            void  )
```

Start the fast connection process.

Returns

0 : success
other : failed

4.9.3.38 wifi_get_config()

```
int wifi_get_config (
            wifi_mode_t interface,
            wifi_config_t * conf )
```

Get configuration of specified interface.

Parameters

in	*interface*	Configure wifi working mode,The options are • WIFI_MODE_STA • WIFI_MODE_AP (currently not support)
out	*conf*	return wifi's current operating parameters

Returns

0 : success
other : failed

4.9.3.39 wifi_init()

```
int wifi_init (
            const wifi_init_config_t * config,
            wifi_init_complete_cb_t init_cb )
```

Init Wi-Fi Initializes the wifi according to the specified parameters in the config.

Attention

1. This API must be called before other Wi-Fi APIs are invoked

Parameters

in	*config*	pointer to Wi-Fi init configuration structure; can point to a temporary variable.
in	*init_cb*	pointer to Wi-Fi init complete configuration structure; can point to a temporary variable.

Returns

0 : success
other : failed

4.9.3.40 wifi_scan_get_ap_list()

```
int wifi_scan_get_ap_list (
            wifi_scan_list_t * scan_list )
```

Get list of APs that found in last scan operation.

Attention

This API only be called when scan is completed, otherwise it may get wrong value.

Parameters

out	*scan_list*	store APs' informaton that found in last scan operation

Returns

0 : success
other : failed

4.9.3.41 wifi_scan_get_ap_num()

```
int wifi_scan_get_ap_num (
            uint16_t * number )
```

Get the number of scanned APs.

Parameters

out	*number*	store number of APs found in last scan operation

Attention

This API only be called when scan is completed, otherwise it may get wrong value.

Returns

the scan result of AP number

4.9.3.42 wifi_scan_get_ap_records()

```
int wifi_scan_get_ap_records (
            uint16_t * number,
            wifi_scan_info_t * ap_records )
```

Get AP list found in last scan operation.

Parameters

out	*number*	As input param, it stores max AP number that ap_records can hold. As output param, it receives the actual AP number that this API returns.
out	*ap_records*	wifi_scan_info_t array stores the found APs

Returns

0 : success
other : failed

4.9.3.43 wifi_scan_scan_stop()

```
int wifi_scan_scan_stop (
            void  )
```

Stop scanning process.

Attention

This API shall be called after wifi_scan_start()

Returns

0 : success
other : failed

4.9.3.44 wifi_scan_start()

```
int wifi_scan_start (
            const wifi_scan_config_t * config,
            bool block )
```

Scan all available APs. After invoke the wifi_set_config() and wifi_start(), then call wifi_scan_start() to scan APs.

Parameters

in	*config*	Configure parameters for scan operation
in	*block*	if block is true, this API blocks the caller until scan operation is done, otherwise it returns immediately

Returns

0 : success
other : failed

4.9.3.45 wifi_set_config()

```
int wifi_set_config (
            wifi_mode_t interface,
            wifi_config_t * conf )
```

Set configuration of OPL1000 STA.

Attention

1. This API is called only when specified interface is enabled, otherwise API calling will be failed
2. For station configuration, bssid_set shall be set to 0; set to 1 menas user want to check MAC address of certain AP.
3. OPL1000 is limited to working on one channel.

Parameters

in	*interface*	Configure wifi working mode,The options are • WIFI_MODE_STA • WIFI_MODE_AP (currently not support)
in	*conf*	structure of configuration paremeters

Returns

0 : success
other : failed

4.9.3.46 wifi_sta_get_ap_info()

```
int wifi_sta_get_ap_info (
            wifi_scan_info_t * ap_info )
```

Get information of AP which OPL1000 station is associated with.

Parameters

out	*ap_info*	get AP information from list

Returns

0 : success
other : failed

4.9.3.47 wifi_start()

```
int wifi_start (
            void  )
```

Start Wi-Fi working.

- If mode is WIFI_MODE_STA, it creates station control block and starts station

Returns

0 : success
other : failed

4.9.3.48 wifi_stop()

```
int wifi_stop (
            void  )
```

Stop wifi working.

- If mode is WIFI_MODE_STA, it stops station and releases station control block

Returns

0 : success
other : failed

4.10 Enumeration

Enumerations

- enum wifi_auth_mode_t {
  WIFI_AUTH_OPEN = 0, WIFI_AUTH_WEP, WIFI_AUTH_WPA_PSK, WIFI_AUTH_WPA2_PSK,
  WIFI_AUTH_WPA_WPA2_PSK, WIFI_AUTH_WPA2_ENTERPRISE }

  This enumeration defines the wireless authentication mode to indicate the Wi-Fi device authentication attribute.
- enum wifi_bandwidth_t { WIFI_BW_HT20 = 1, WIFI_BW_HT40 }
- enum wifi_cipher_type_t {
  WIFI_CIPHER_TYPE_NONE = 0, WIFI_CIPHER_TYPE_WEP40, WIFI_CIPHER_TYPE_WEP104,
  WIFI_CIPHER_TYPE_TKIP,
  WIFI_CIPHER_TYPE_CCMP, WIFI_CIPHER_TYPE_TKIP_CCMP, WIFI_CIPHER_TYPE_UNKNOWN }

  This enumeration defines wireless security cipher suits.
- enum wifi_event_t {
  WIFI_EVENT_NONE = -1, WIFI_EVENT_INIT_COMPLETE = 0, WIFI_EVENT_SCAN_COMPLETE,
  WIFI_EVENT_STA_START,
  WIFI_EVENT_STA_STOP, WIFI_EVENT_STA_CONNECTED, WIFI_EVENT_STA_DISCONNECTED,
  WIFI_EVENT_STA_CONNECTION_FAILED,
  WIFI_EVENT_STA_GOT_IP, WIFI_EVENT_MAX }

  This enumeration defines the supported events generated by the Wi-Fi driver. The event will be sent to the upper layer handler registered in wifi_register_event_handler().
- enum wifi_mode_t { WIFI_MODE_NULL = 0, WIFI_MODE_STA, WIFI_MODE_AP, WIFI_MODE_MAX }
- enum wifi_reason_code_t {
  WIFI_REASON_CODE_SUCCESS, WIFI_REASON_CODE_FIND_AP_FAIL,
  WIFI_REASON_CODE_PREV_AUTH_INVALID, WIFI_REASON_CODE_DEAUTH_LEAVING_BSS,
  WIFI_REASON_CODE_DISASSOC_INACTIVITY, WIFI_REASON_CODE_DISASSOC_AP_OVERLOAD,
  WIFI_REASON_CODE_CLASS_2_ERR, WIFI_REASON_CODE_CLASS_3_ERR,
  WIFI_REASON_CODE_DISASSOC_LEAVING_BSS, WIFI_REASON_CODE_ASSOC_BEFORE_AUTH,
  WIFI_REASON_CODE_DISASSOC_PWR_CAP_UNACCEPTABLE, WIFI_REASON_CODE_DISASSOC_SUP_CHS_UN
  ACCEPTABLE, WIFI_REASON_CODE_INVALID_INFO_ELEM = 13, WIFI_REASON_CODE_MIC_FAILURE,
  WIFI_REASON_CODE_4_WAY_HANDSHAKE_TIMEOUT, WIFI_REASON_CODE_GROUP_KEY_UPDATE_TIMEOUT,
  WIFI_REASON_CODE_DIFFERENT_INFO_ELEM, WIFI_REASON_CODE_GROUP_CIPHER_INVALID_VALID,
  WIFI_REASON_CODE_PAIRWISE_CIPHER_INVALID, WIFI_REASON_CODE_AKMP_INVALID,
  WIFI_REASON_CODE_UNSUPPORTED_RSNE_VERSION, WIFI_REASON_CODE_INVALID_RSNE_CAPABILITIES,
  WIFI_REASON_CODE_IEEE_802_1X_AUTH_FAILED, WIFI_REASON_CODE_CIPHER_REJECTED,
  WIFI_REASON_CODE_AUTO_CONNECT_FAILED = 200, WIFI_REASON_CODE_CONNECT_NOT_FOUND,
  WIFI_REASON_CODE_CONNECT_TIMEOUT }

  This enumeration defines the reason code of the WIFI_EVENT_STA_CONNECTION_FAILED event in wifi_event_t. Find the details for the reason code below.
- enum wifi_scan_method_t { WIFI_FAST_SCAN = 0, WIFI_ALL_CHANNEL_SCAN }
- enum wifi_scan_type_t { WIFI_SCAN_TYPE_ACTIVE = 0, WIFI_SCAN_TYPE_PASSIVE }

  This enumeration defines the wireless STA scan type.
- enum wifi_sort_method_t { WIFI_CONNECT_AP_BY_SIGNAL = 0, WIFI_CONNECT_AP_BY_SECURITY }

4.10.1 Detailed Description

4.10.2 Enumeration Type Documentation

4.10.2.1 wifi_auth_mode_t

`enum wifi_auth_mode_t`

This enumeration defines the wireless authentication mode to indicate the Wi-Fi device authentication attribute.

Enumerator

WIFI_AUTH_OPEN	authenticate mode : open
WIFI_AUTH_WEP	authenticate mode : WEP
WIFI_AUTH_WPA_PSK	authenticate mode : WPA_PSK
WIFI_AUTH_WPA2_PSK	authenticate mode : WPA2_PSK
WIFI_AUTH_WPA_WPA2_PSK	authenticate mode : WPA_WPA2_PSK
WIFI_AUTH_WPA2_ENTERPRISE	authenticate mode : WPA2_ENTERPRISE

4.10.2.2 wifi_bandwidth_t

`enum wifi_bandwidth_t`

Enumerator

WIFI_BW_HT20	Bandwidth is HT20
WIFI_BW_HT40	Bandwidth is HT40

4.10.2.3 wifi_cipher_type_t

`enum wifi_cipher_type_t`

This enumeration defines wireless security cipher suits.

Enumerator

WIFI_CIPHER_TYPE_NONE	0, the cipher type is none
WIFI_CIPHER_TYPE_WEP40	1, the cipher type is WEP40
WIFI_CIPHER_TYPE_WEP104	2, the cipher type is WEP104
WIFI_CIPHER_TYPE_TKIP	3, the cipher type is TKIP
WIFI_CIPHER_TYPE_CCMP	4, the cipher type is CCMP
WIFI_CIPHER_TYPE_TKIP_CCMP	5, the cipher type is TKIP and CCMP
WIFI_CIPHER_TYPE_UNKNOWN	6, the cipher type is unknown

4.10.2.4 wifi_event_t

`enum wifi_event_t`

This enumeration defines the supported events generated by the Wi-Fi driver. The event will be sent to the upper layer handler registered in wifi_register_event_handler().

Enumerator

WIFI_EVENT_NONE	Reserved
WIFI_EVENT_INIT_COMPLETE	Wi-Fi initialization complete event.
WIFI_EVENT_SCAN_COMPLETE	Scan completed event
WIFI_EVENT_STA_START	station start
WIFI_EVENT_STA_STOP	station stop
WIFI_EVENT_STA_CONNECTED	station connected to AP event
WIFI_EVENT_STA_DISCONNECTED	station disconnected from AP
WIFI_EVENT_STA_CONNECTION_FAILED	Connection has failed. For the reason code, please refer to wifi_reason_code_t.
WIFI_EVENT_STA_GOT_IP	station got IP from connected AP
WIFI_EVENT_MAX	

4.10.2.5 wifi_mode_t

`enum wifi_mode_t`

Enumerator

WIFI_MODE_NULL	null mode
WIFI_MODE_STA	Wi-Fi station mode
WIFI_MODE_AP	Wi-Fi soft-AP mode
WIFI_MODE_MAX	

4.10.2.6 wifi_reason_code_t

`enum wifi_reason_code_t`

This enumeration defines the reason code of the WIFI_EVENT_STA_CONNECTION_FAILED event in wifi_event_t. Find the details for the reason code below.

Enumerator

WIFI_REASON_CODE_SUCCESS	0 Reserved.
WIFI_REASON_CODE_FIND_AP_FAIL	1 (Internal) No AP found.
WIFI_REASON_CODE_PREV_AUTH_INVALID	2 Previous authentication is no longer valid.
WIFI_REASON_CODE_DEAUTH_LEAVING_BSS	3 Deauthenticated because sending STA is leaving (or has left) IBSS or ES.
WIFI_REASON_CODE_DISASSOC_INACTIVITY	4 Disassociated due to inactivity.
WIFI_REASON_CODE_DISASSOC_AP_OVERL↩ OAD	5 Disassociated because AP is unable to handle all currently associated STAs.
WIFI_REASON_CODE_CLASS_2_ERR	6 Class 2 frame received from nonauthenticated STA.
WIFI_REASON_CODE_CLASS_3_ERR	7 Class 3 frame received from nonauthenticated STA.

Enumerator

WIFI_REASON_CODE_DISASSOC_LEAVING_BSS	8 Disassociated because sending STA is leaving (or has left) BSS.
WIFI_REASON_CODE_ASSOC_BEFORE_AUTH	9 STA requesting (re)association is not authenticated with responding STA.
WIFI_REASON_CODE_DISASSOC_PWR_CAP_↩ UNACCEPTABLE	10 Disassociated because the information in the Power Capability element is unacceptable.
WIFI_REASON_CODE_DISASSOC_SUP_CHS_U↩ NACCEPTABLE	11 Disassociated because the information in the Supported Channels element is unacceptable.
WIFI_REASON_CODE_INVALID_INFO_ELEM	13 Invalid information element.
WIFI_REASON_CODE_MIC_FAILURE	14 Message integrity code (MIC) failure.
WIFI_REASON_CODE_4_WAY_HANDSHAKE_TI↩ MEOUT	15 4-Way Handshake time out.
WIFI_REASON_CODE_GROUP_KEY_UPDATE_↩ TIMEOUT	16 Group Key Handshake time out.
WIFI_REASON_CODE_DIFFERENT_INFO_ELEM	17 Information element in 4-Way Handshake different from (Re)Association Request/Probe Response/Beacon frame.
WIFI_REASON_CODE_GROUP_CIPHER_INVALI↩ D_VALID	18 Invalid group cipher.
WIFI_REASON_CODE_PAIRWISE_CIPHER_INV↩ ALID	19 Invalid pairwise cipher.
WIFI_REASON_CODE_AKMP_INVALID	20 Invalid AKMP.
WIFI_REASON_CODE_UNSUPPORTED_RSNE_↩ VERSION	21 Unsupported RSN information element version.
WIFI_REASON_CODE_INVALID_RSNE_CAPABI↩ LITIES	22 Invalid RSN information element capabilities.
WIFI_REASON_CODE_IEEE_802_1X_AUTH_FAI↩ LED	23 IEEE 802.1X authentication failed.
WIFI_REASON_CODE_CIPHER_REJECTED	24 Cipher suite rejected because of the security policy.
WIFI_REASON_CODE_AUTO_CONNECT_FAILED	200 Auto connect failed.
WIFI_REASON_CODE_CONNECT_NOT_FOUND	201 The target AP is not found.
WIFI_REASON_CODE_CONNECT_TIMEOUT	202 Connect to AP timeout.

4.10.2.7 wifi_scan_method_t

```
enum wifi_scan_method_t
```

Enumerator

WIFI_FAST_SCAN	Do fast scan, scan will end after find SSID match AP
WIFI_ALL_CHANNEL_SCAN	All channel scan, scan will end after scan all the channel

4.10.2.8 wifi_scan_type_t

`enum wifi_scan_type_t`

This enumeration defines the wireless STA scan type.

Enumerator

WIFI_SCAN_TYPE_ACTIVE	Actively scan a network by sending 802.11 probe(s)
WIFI_SCAN_TYPE_PASSIVE	Passively scan a network by listening for beacons from APs

4.10.2.9 wifi_sort_method_t

`enum wifi_sort_method_t`

Enumerator

WIFI_CONNECT_AP_BY_SIGNAL	Sort match AP in scan list by RSSI
WIFI_CONNECT_AP_BY_SECURITY	Sort match AP in scan list by security mode

Chapter 5

Data Structure Documentation

5.1 auto_conn_info_t Struct Reference

```
#include <controller_wifi_com_patch.h>
```

Data Fields

- u8 ap_channel
- u16 beacon_interval
- u8 bssid [MAC_ADDR_LEN]
- u16 capabilities
- u8 dtim_prod
- u8 fast_connect
- bool free_ocpy
- s8 hid_ssid [IEEE80211_MAX_SSID_LEN+1]
- u64 latest_beacon_rx_time
- s8 passphrase [MAX_LEN_OF_PASSPHRASE]
- u8 psk [32]
- u8 rsn_ie [100]
- s8 rssi
- s8 ssid [IEEE80211_MAX_SSID_LEN+1]
- u8 supported_rates [SUPPORTED_RATES_MAX]
- wpa_ie_data_t wpa_data
- u8 wpa_ie [100]

5.1.1 Field Documentation

5.1.1.1 ap_channel

```
u8 ap_channel
```

5.1.1.2 beacon_interval

```
u16 beacon_interval
```

5.1.1.3 bssid

```
u8 bssid[MAC_ADDR_LEN]
```

5.1.1.4 capabilities

```
u16 capabilities
```

5.1.1.5 dtim_prod

```
u8 dtim_prod
```

5.1.1.6 fast_connect

```
u8 fast_connect
```

5.1.1.7 free_ocpy

```
bool free_ocpy
```

5.1.1.8 hid_ssid

```
s8 hid_ssid[IEEE80211_MAX_SSID_LEN+1]
```

5.1.1.9 latest_beacon_rx_time

```
u64 latest_beacon_rx_time
```

5.1.1.10 passphrase

```
s8 passphrase[MAX_LEN_OF_PASSPHRASE]
```

5.1.1.11 psk

```
u8 psk[32]
```

5.1.1.12 rsn_ie

```
u8 rsn_ie[100]
```

5.1.1.13 rssi

```
s8 rssi
```

5.1.1.14 ssid

```
s8 ssid[IEEE80211_MAX_SSID_LEN+1]
```

5.1.1.15 supported_rates

```
u8 supported_rates[SUPPORTED_RATES_MAX]
```

5.1.1.16 wpa_data

```
wpa_ie_data_t wpa_data
```

5.1.1.17 wpa_ie

```
u8 wpa_ie[100]
```

5.2 auto_connect_cfg_t Struct Reference

`#include <controller_wifi_com_patch.h>`

Data Fields

- bool flag
- s8 front
- u8 max_save_num
- auto_conn_info_t * pFCInfo
- s8 rear
- u8 retryCount
- u8 targetIdx
- u32 uFCApNum

5.2.1 Field Documentation

5.2.1.1 flag

`bool flag`

5.2.1.2 front

`s8 front`

5.2.1.3 max_save_num

`u8 max_save_num`

5.2.1.4 pFCInfo

`auto_conn_info_t* pFCInfo`

5.2.1.5 rear

```
s8 rear
```

5.2.1.6 retryCount

```
u8 retryCount
```

5.2.1.7 targetIdx

```
u8 targetIdx
```

5.2.1.8 uFCApNum

```
u32 uFCApNum
```

5.3 event_msg_t Struct Reference

Send information to event by event_msg_t.

```
#include <event_loop.h>
```

Data Fields

- uint32_t event
- uint32_t length
- uint8_t * param

5.3.1 Detailed Description

Send information to event by event_msg_t.

5.3.2 Field Documentation

5.3.2.1 event

```
uint32_t event
```

event type

5.3.2.2 length

```
uint32_t length
```

Packet length

5.3.2.3 param

```
uint8_t* param
```

event parament

5.4 LE_BT_ADDR_T Struct Reference

```
#include <ble.h>
```

Data Fields

- BD_ADDR addr
- UINT8 type

5.4.1 Field Documentation

5.4.1.1 addr

```
BD_ADDR addr
```

address

5.4.1.2 type

```
UINT8 type
```

address type

5.5 LE_CM_CONNECTION_COMPLETE_IND_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 conn_interval
- UINT16 conn_latency
- UINT16 dev_id
- BD_ADDR peer_addr
- UINT8 peer_addr_type
- UINT8 role
- UINT16 status
- UINT16 supervison_timeout

5.5.1 Field Documentation

5.5.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.5.1.2 conn_interval

```
UINT16 conn_interval
```

connection interval

5.5.1.3 conn_latency

```
UINT16 conn_latency
```

connection latency

5.5.1.4 dev_id

```
UINT16 dev_id
```

device ID

5.5.1.5 peer_addr

```
BD_ADDR peer_addr
```

perr address

5.5.1.6 peer_addr_type

```
UINT8 peer_addr_type
```

peer address type

5.5.1.7 role

```
UINT8 role
```

master or slave

5.5.1.8 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.5.1.9 supervison_timeout

```
UINT16 supervison_timeout
```

supervision timeout

5.6 LE_CM_MSG_ADVERTISE_REPORT_IND_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- BD_ADDR addr
- UINT8 addr_type
- UINT8 data [1]
- UINT8 event_type
- UINT8 len
- INT8 rssi

5.6.1 Field Documentation

5.6.1.1 addr

```
BD_ADDR addr
```

address

5.6.1.2 addr_type

```
UINT8 addr_type
```

address type

5.6.1.3 data

```
UINT8 data[1]
```

5.6.1.4 event_type

```
UINT8 event_type
```

5.6.1.5 len

```
UINT8 len
```

5.6.1.6 rssi

```
INT8 rssi
```

RSSI

5.7 LE_CM_MSG_CONN_PARA_REQ_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 itv_max
- UINT16 itv_min
- UINT16 latency
- UINT32 sv_tmo

5.7.1 Field Documentation

5.7.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.7.1.2 itv_max

```
UINT16 itv_max
```

maxinum connection interval

5.7.1.3 itv_min

```
UINT16 itv_min
```

mininum connection interval

5.7.1.4 latency

```
UINT16 latency
```

slave latency

5.7.1.5 sv_tmo

```
UINT32 sv_tmo
```

supervision timeout

5.8 LE_CM_MSG_CONN_UPDATE_COMPLETE_IND_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 interval
- UINT16 latency
- UINT16 status
- UINT32 supervision_timeout

5.8.1 Field Documentation

5.8.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.8.1.2 interval

```
UINT16 interval
```

connection interval

5.8.1.3 latency

```
UINT16 latency
```

slave letency

5.8.1.4 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.8.1.5 supervision_timeout

```
UINT32 supervision_timeout
```

supervision timeout

5.9 LE_CM_MSG_DATA_LEN_CHANGE_IND_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 max_rx_octets
- UINT16 max_rx_time
- UINT16 max_tx_octets
- UINT16 max_tx_time

5.9.1 Field Documentation

5.9.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.9.1.2 max_rx_octets

```
UINT16 max_rx_octets
```

connMaxRxOctets

5.9.1.3 max_rx_time

```
UINT16 max_rx_time
```

connMaxRxTime

5.9.1.4 max_tx_octets

```
UINT16 max_tx_octets
```

connMaxTxOctets

5.9.1.5 max_tx_time

```
UINT16 max_tx_time
```

connMaxTxTime

5.10 LE_CM_MSG_DIRECT_ADV_REPORT_IND_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- BD_ADDR direct_addr
- UINT8 direct_addr_type
- BD_ADDR peer_addr
- UINT8 peer_addr_type
- INT8 rssi

5.10.1 Field Documentation

5.10.1.1 direct_addr

```
BD_ADDR direct_addr
```

direct address

5.10.1.2 direct_addr_type

```
UINT8 direct_addr_type
```

direct address type

5.10.1.3 peer_addr

```
BD_ADDR peer_addr
```

peer address

5.10.1.4 peer_addr_type

```
UINT8 peer_addr_type
```

peer address type

5.10.1.5 rssi

```
INT8 rssi
```

RSSI

5.11 LE_CM_MSG_DISCONNECT_COMPLETE_IND_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT8 reason
- UINT16 status

5.11.1 Field Documentation

5.11.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.11.1.2 reason

```
UINT8 reason
```

disconnect reason

5.11.1.3 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.12 LE_CM_MSG_ENCRYPTION_CHANGE_IND_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT8 enabled
- UINT16 status

5.12.1 Field Documentation

5.12.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.12.1.2 devid

```
UINT16 devid
```

device ID

5.12.1.3 enabled

```
UINT8 enabled
```

5.12.1.4 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.13 LE_CM_MSG_ENCRYPTION_REFRESH_IND_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- BOOL enabled
- UINT16 status

5.13.1 Field Documentation

5.13.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.13.1.2 devid

```
UINT16 devid
```

device ID

5.13.1.3 enabled

```
BOOL enabled
```

enable or disable

5.13.1.4 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.14 LE_CM_MSG_INIT_COMPLETE_CFM_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 status

5.14.1 Field Documentation

5.14.1.1 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.15 LE_CM_MSG_LTK_REQ_IND_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT16 ediv
- UINT8 rand [8]

5.15.1 Field Documentation

5.15.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.15.1.2 devid

```
UINT16 devid
```

device ID

5.15.1.3 ediv

```
UINT16 ediv
```

5.15.1.4 rand

```
UINT8 rand[8]
```

5.16 LE_CM_MSG_READ_ADV_TX_POWER_CFM_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- INT8 pwr_level
- UINT16 status

5.16.1 Field Documentation

5.16.1.1 pwr_level

```
INT8 pwr_level
```

power level

5.16.1.2 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.17 LE_CM_MSG_READ_BD_ADDR_CFM_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- BD_ADDR bd_addr
- UINT16 status

5.17.1 Field Documentation

5.17.1.1 bd_addr

```
BD_ADDR bd_addr
```

5.17.1.2 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.18 LE_CM_MSG_READ_CHANNEL_MAP_CFM_T Struct Reference

`#include <ble_cm_if.h>`

Data Fields

- UINT8 ch_map [5]
- UINT16 conn_hdl
- UINT16 status

5.18.1 Field Documentation

5.18.1.1 ch_map

`UINT8 ch_map[5]`

channel map

5.18.1.2 conn_hdl

`UINT16 conn_hdl`

connection handle

5.18.1.3 status

`UINT16 status`

refer to LE_ERR_STATE in ble_err.h

5.19 LE_CM_MSG_READ_RESOLVING_LIST_SIZE_CFM_T Struct Reference

`#include <ble_cm_if.h>`

Data Fields

- UINT8 size
- UINT16 status

5.19.1 Field Documentation

5.19.1.1 size

```
UINT8 size
```

resolving list size

5.19.1.2 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.20 LE_CM_MSG_READ_RSSI_CFM_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- INT8 rssi
- UINT16 status

5.20.1 Field Documentation

5.20.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.20.1.2 rssi

```
INT8 rssi
```

RSSI

5.20.1.3 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.21 LE_CM_MSG_READ_TX_POWER_CFM_T Struct Reference

`#include <ble_cm_if.h>`

Data Fields

- UINT16 conn_hdl
- UINT16 status
- INT8 tx_power

5.21.1 Field Documentation

5.21.1.1 conn_hdl

`UINT16 conn_hdl`

connection handle

5.21.1.2 status

`UINT16 status`

refer to LE_ERR_STATE in ble_err.h

5.21.1.3 tx_power

`INT8 tx_power`

tx power

5.22 LE_CM_MSG_READ_WHITE_LIST_SIZE_CFM_T Struct Reference

`#include <ble_cm_if.h>`

Data Fields

- UINT8 size
- UINT16 status

5.22.1 Field Documentation

5.22.1.1 size

```
UINT8 size
```

white list size

5.22.1.2 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.23 LE_CM_MSG_SET_DATA_LENGTH_CFM_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 status

5.23.1 Field Documentation

5.23.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.23.1.2 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.24 LE_CM_MSG_SET_DISCONNECT_CFM_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 handle
- UINT16 status

5.24.1 Field Documentation

5.24.1.1 handle

```
UINT16 handle
```

connection handle

5.24.1.2 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.25 LE_CM_MSG_SIGNAL_UPDATE_REQ_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 identifier
- UINT16 interval_max
- UINT16 interval_min
- UINT16 slave_latency
- UINT32 timeout_multiplier

5.25.1 Field Documentation

5.25.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.25.1.2 identifier

```
UINT16 identifier
```

5.25.1.3 interval_max

```
UINT16 interval_max
```

maxinum connection interval

5.25.1.4 interval_min

```
UINT16 interval_min
```

mininum connection interval

5.25.1.5 slave_latency

```
UINT16 slave_latency
```

slave latency

5.25.1.6 timeout_multiplier

```
UINT32 timeout_multiplier
```

5.26 LE_CM_REQ_STATUS_T Struct Reference

```
#include <ble_cm_if.h>
```

Data Fields

- UINT16 status

5.26.1 Field Documentation

5.26.1.1 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.27 LE_CONN_PARA_T Struct Reference

```
#include <ble.h>
```

Data Fields

- UINT16 itv_max
- UINT16 itv_min
- UINT16 latency
- UINT16 sv_timeout

5.27.1 Field Documentation

5.27.1.1 itv_max

```
UINT16 itv_max
```

maxinum connection interval

5.27.1.2 itv_min

```
UINT16 itv_min
```

mininum connection interval

5.27.1.3 latency

```
UINT16 latency
```

slave latency

5.27.1.4 sv_timeout

```
UINT16 sv_timeout
```

supervision timeout

5.28 LE_GAP_ADVERTISING_PARAM_T Struct Reference

`#include <ble_gap_if.h>`

Data Fields

- UINT8 channel_map
- UINT8 filter_policy
- UINT16 interval_max
- UINT16 interval_min
- UINT8 own_addr_type
- BD_ADDR peer_addr
- UINT8 peer_addr_type
- UINT8 type

5.28.1 Field Documentation

5.28.1.1 channel_map

`UINT8 channel_map`

advertising channel map

5.28.1.2 filter_policy

`UINT8 filter_policy`

advertising filter policy

5.28.1.3 interval_max

`UINT16 interval_max`

maxinum advertising interval

5.28.1.4 interval_min

`UINT16 interval_min`

mininum advertising interval

5.28.1.5 own_addr_type

```
UINT8 own_addr_type
```

owner address type

5.28.1.6 peer_addr

```
BD_ADDR peer_addr
```

peer address

5.28.1.7 peer_addr_type

```
UINT8 peer_addr_type
```

peer address type

5.28.1.8 type

```
UINT8 type
```

advertising type

5.29 LE_GAP_CONN_PARAM_T Struct Reference

```
#include <ble_gap_if.h>
```

Data Fields

- UINT16 interval_max
- UINT16 interval_min
- UINT16 latency
- UINT16 supervision_timeout

5.29.1 Field Documentation

5.29.1.1 interval_max

```
UINT16 interval_max
```

maxinum connection interval

5.29.1.2 interval_min

```
UINT16 interval_min
```

mininum connection interval

5.29.1.3 latency

```
UINT16 latency
```

slave latency

5.29.1.4 supervision_timeout

```
UINT16 supervision_timeout
```

supervision timeout for the LE Link

5.30 LE_GAP_SCAN_PARAM_T Struct Reference

```
#include <ble_gap_if.h>
```

Data Fields

- UINT8 filter_policy
- UINT16 interval
- UINT8 own_addr_type
- UINT8 type
- UINT16 window

5.30.1 Field Documentation

5.30.1.1 filter_policy

```
UINT8 filter_policy
```

scan filter policy

5.30.1.2 interval

```
UINT16 interval
```

scan interval

5.30.1.3 own_addr_type

```
UINT8 own_addr_type
```

owner address type

5.30.1.4 type

```
UINT8 type
```

scan type

5.30.1.5 window

```
UINT16 window
```

scan window

5.31 LE_GATT_ATTR_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 format
- UINT16 handle
- UINT16 len
- UINT16 maxLen
- UINT16 permit
- UINT16 *const pUuid
- UINT8 *const pVal

5.31.1 Field Documentation

5.31.1.1 format

```
UINT8 format
```

UUID type

5.31.1.2 handle

```
UINT16 handle
```

handle

5.31.1.3 len

```
UINT16 len
```

value length

5.31.1.4 maxLen

```
UINT16 maxLen
```

maxinum value length

5.31.1.5 permit

```
UINT16 permit
```

permit

5.31.1.6 pUuid

```
UINT16* const pUuid
```

UUID

5.31.1.7 pVal

```
UINT8* const pVal
```

value

5.32 LE_GATT_MSG_ACCESS_READ_IND_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 offset

5.32.1 Field Documentation

5.32.1.1 conn_hdl

`UINT16 conn_hdl`

connection handle

5.32.1.2 devid

`UINT16 devid`

device index

5.32.1.3 handle

`UINT16 handle`

attribute handle

5.32.1.4 offset

`UINT16 offset`

attribute handle value

5.33 LE_GATT_MSG_ACCESS_WRITE_IND_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT8 flag
- UINT16 handle
- UINT16 len
- UINT16 offset
- UINT8 * pVal

5.33.1 Field Documentation

5.33.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.33.1.2 devid

```
UINT16 devid
```

device ID

5.33.1.3 flag

```
UINT8 flag
```

refer to LE_GATT_FLAG_* in ble_gatt_if.h

5.33.1.4 handle

```
UINT16 handle
```

attribute handle

5.33.1.5 len

```
UINT16 len
```

length written

5.33.1.6 offset

```
UINT16 offset
```

attribute handle value

5.33.1.7 pVal

```
UINT8* pVal
```

value written

5.34 LE_GATT_MSG_CHAR_DESCRIPTOR_INFO_IND_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT8 format
- UINT16 handle
- UINT16 uuid [8]

5.34.1 Field Documentation

5.34.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.34.1.2 devid

```
UINT16 devid
```

device ID

5.34.1.3 format

```
UINT8 format
```

UUID type

5.34.1.4 handle

```
UINT16 handle
```

characteristic descriptor handle

5.34.1.5 uuid

```
UINT16 uuid[8]
```

UUID

5.35 LE_GATT_MSG_CHARACTERISTIC_DECL_INFO_IND_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT8 format
- UINT16 handle
- UINT8 property
- UINT16 uuid [8]
- UINT16 val_hdl

5.35.1 Field Documentation

5.35.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.35.1.2 devid

```
UINT16 devid
```

device ID

5.35.1.3 format

```
UINT8 format
```

UUID type

5.35.1.4 handle

```
UINT16 handle
```

characteristic declaration handle

5.35.1.5 property

```
UINT8 property
```

property

5.35.1.6 uuid

```
UINT16 uuid[8]
```

UUID

5.35.1.7 val_hdl

```
UINT16 val_hdl
```

characteristic value handle

5.36 LE_GATT_MSG_CHARACTERISTIC_VAL_IND_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 len
- UINT16 offset
- UINT8 * val

5.36.1 Field Documentation

5.36.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_* in ble_att_if.h

5.36.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.36.1.3 devid

```
UINT16 devid
```

device ID

5.36.1.4 handle

```
UINT16 handle
```

characteristic value handle

5.36.1.5 len

```
UINT16 len
```

value length

5.36.1.6 offset

```
UINT16 offset
```

value position offset

5.36.1.7 val

```
UINT8* val
```

value

5.37 LE_GATT_MSG_CONFIRMATION_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle

5.37.1 Field Documentation

5.37.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.37.1.2 devid

```
UINT16 devid
```

device ID

5.37.1.3 handle

```
UINT16 handle
```

attribute handle

5.38 LE_GATT_MSG_EXCHANGE_MTU_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 current_rx_mtu
- UINT16 devid

5.38.1 Field Documentation

5.38.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.38.1.2 current_rx_mtu

```
UINT16 current_rx_mtu
```

current receive MTU

5.38.1.3 devid

```
UINT16 devid
```

device ID

5.39 LE_GATT_MSG_EXCHANGE_MTU_IND_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 client_rx_mtu
- UINT16 conn_hdl
- UINT16 devid

5.39.1 Field Documentation

5.39.1.1 client_rx_mtu

```
UINT16 client_rx_mtu
```

client receive MTU

5.39.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.39.1.3 devid

```
UINT16 devid
```

device ID

5.40 LE_GATT_MSG_EXECUTE_WRITE_RELIABLE_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 err_hdl
- UINT16 status

5.40.1 Field Documentation

5.40.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.40.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.40.1.3 devid

```
UINT16 devid
```

device ID

5.40.1.4 err_hdl

```
UINT16 err_hdl
```

TBD

5.40.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.41 LE_GATT_MSG_FIND_ALL_CHAR_DESC_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.41.1 Field Documentation

5.41.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_* in ble_att_if.h

5.41.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.41.1.3 devid

```
UINT16 devid
```

device ID

5.41.1.4 handle

```
UINT16 handle
```

characteristic descriptor handle

5.41.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.42 LE_GATT_MSG_FIND_ALL_PRIMARY_SERVICE_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.42.1 Field Documentation

5.42.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.42.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.42.1.3 devid

```
UINT16 devid
```

device ID

5.42.1.4 handle

```
UINT16 handle
```

5.42.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.43 LE_GATT_MSG_FIND_CHARACTERISTIC_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.43.1 Field Documentation

5.43.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.43.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.43.1.3 devid

```
UINT16 devid
```

device ID

5.43.1.4 handle

```
UINT16 handle
```

characteristic descriptor handle

5.43.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.44 LE_GATT_MSG_FIND_INCLUDED_SERVICE_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.44.1 Field Documentation

5.44.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.44.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.44.1.3 devid

```
UINT16 devid
```

device ID

5.44.1.4 handle

```
UINT16 handle
```

include service start handle

5.44.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.45 LE_GATT_MSG_FIND_PRIMARY_SERVICE_BY_UUID_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.45.1 Field Documentation

5.45.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.45.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.45.1.3 devid

```
UINT16 devid
```

device ID

5.45.1.4 handle

```
UINT16 handle
```

service start handle

5.45.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.46 LE_GATT_MSG_INCLUDE_SERVICE_INFO_IND_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT16 end_hdl
- UINT8 format
- UINT16 handle
- UINT16 start_hdl
- UINT16 uuid [8]

5.46.1 Field Documentation

5.46.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.46.1.2 devid

```
UINT16 devid
```

device ID

5.46.1.3 end_hdl

```
UINT16 end_hdl
```

end handle

5.46.1.4 format

```
UINT8 format
```

UUID type

5.46.1.5 handle

```
UINT16 handle
```

include servie handle

5.46.1.6 start_hdl

```
UINT16 start_hdl
```

start handle

5.46.1.7 uuid

```
UINT16 uuid[8]
```

UUID

5.47 LE_GATT_MSG_INDICATE_IND_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 len
- UINT8 * val

5.47.1 Field Documentation

5.47.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.47.1.2 devid

```
UINT16 devid
```

device ID

5.47.1.3 handle

```
UINT16 handle
```

attribute handle

5.47.1.4 len

```
UINT16 len
```

value length

5.47.1.5 val

```
UINT8* val
```

value

5.48 LE_GATT_MSG_NOTIFY_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.48.1 Field Documentation

5.48.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.48.1.2 devid

```
UINT16 devid
```

device ID

5.48.1.3 handle

```
UINT16 handle
```

attribute handle

5.48.1.4 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.49 LE_GATT_MSG_NOTIFY_IND_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 len
- UINT8 * val

5.49.1 Field Documentation

5.49.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.49.1.2 devid

```
UINT16 devid
```

device ID

5.49.1.3 handle

```
UINT16 handle
```

attribute handle

5.49.1.4 len

```
UINT16 len
```

value length

5.49.1.5 val

```
UINT8* val
```

value

5.50 LE_GATT_MSG_OPERATION_TIMEOUT_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_op
- UINT16 conn_hdl
- UINT16 devid

5.50.1 Field Documentation

5.50.1.1 att_op

```
UINT8 att_op
```

refer to LE_ATT_OP_* in ble_att_if.h

5.50.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.50.1.3 devid

```
UINT16 devid
```

device ID

5.51 LE_GATT_MSG_PREPARE_WRITE_RELIABLE_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.51.1 Field Documentation

5.51.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.51.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.51.1.3 devid

```
UINT16 devid
```

device ID

5.51.1.4 handle

```
UINT16 handle
```

attribute handle

5.51.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.52 LE_GATT_MSG_READ_CHAR_VAL_BY_UUID_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.52.1 Field Documentation

5.52.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.52.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.52.1.3 devid

```
UINT16 devid
```

device ID

5.52.1.4 handle

```
UINT16 handle
```

characteristic value handle

5.52.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.53 LE_GATT_MSG_READ_CHARACTERISTIC_VALUE_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.53.1 Field Documentation

5.53.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.53.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.53.1.3 devid

```
UINT16 devid
```

device ID

5.53.1.4 handle

```
UINT16 handle
```

characteristic value handle

5.53.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.54 LE_GATT_MSG_READ_LONG_CHAR_VAL_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.54.1 Field Documentation

5.54.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.54.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.54.1.3 devid

```
UINT16 devid
```

device ID

5.54.1.4 handle

```
UINT16 handle
```

characteristic value handle

5.54.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.55 LE_GATT_MSG_READ_MULTIPLE_CHAR_VAL_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 err_hdl
- UINT16 len
- UINT16 status
- UINT8 * val

5.55.1 Field Documentation

5.55.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_* in ble_att_if.h

5.55.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.55.1.3 devid

```
UINT16 devid
```

device ID

5.55.1.4 err_hdl

```
UINT16 err_hdl
```

TBD

5.55.1.5 len

```
UINT16 len
```

value length

5.55.1.6 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.55.1.7 val

```
UINT8* val
```

value

5.56 LE_GATT_MSG_SERVICE_INFO_IND_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT16 end_hdl
- UINT8 format
- UINT16 start_hdl
- UINT16 uuid [8]

5.56.1 Field Documentation

5.56.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.56.1.2 devid

```
UINT16 devid
```

device ID

5.56.1.3 end_hdl

```
UINT16 end_hdl
```

end handle

5.56.1.4 format

```
UINT8 format
```

UUID type

5.56.1.5 start_hdl

```
UINT16 start_hdl
```

start handle

5.56.1.6 uuid

```
UINT16 uuid[8]
```

UUID

5.57 LE_GATT_MSG_SIGNED_WRITE_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.57.1 Field Documentation

5.57.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.57.1.2 devid

```
UINT16 devid
```

device ID

5.57.1.3 handle

```
UINT16 handle
```

attribute handle

5.57.1.4 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.58 LE_GATT_MSG_WRITE_CHAR_VAL_RELIABLE_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.58.1 Field Documentation

5.58.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.58.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.58.1.3 devid

```
UINT16 devid
```

device ID

5.58.1.4 handle

```
UINT16 handle
```

characteristic value handle

5.58.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.59 LE_GATT_MSG_WRITE_CHAR_VALUE_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.59.1 Field Documentation

5.59.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_* in ble_att_if.h

5.59.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.59.1.3 devid

```
UINT16 devid
```

device ID

5.59.1.4 handle

```
UINT16 handle
```

attribute handle

5.59.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.60 LE_GATT_MSG_WRITE_LONG_CHAR_VALUE_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT8 att_err
- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.60.1 Field Documentation

5.60.1.1 att_err

```
UINT8 att_err
```

0 is ok, others refer to LE_ATT_ERR_∗ in ble_att_if.h

5.60.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.60.1.3 devid

```
UINT16 devid
```

device ID

5.60.1.4 handle

```
UINT16 handle
```

characteristic value handle

5.60.1.5 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.61 LE_GATT_MSG_WRITE_NO_RSP_CFM_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT16 devid
- UINT16 handle
- UINT16 status

5.61.1 Field Documentation

5.61.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.61.1.2 devid

```
UINT16 devid
```

device ID

5.61.1.3 handle

```
UINT16 handle
```

attribute handle

5.61.1.4 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.62 LE_GATT_SERVICE_T Struct Reference

```
#include <ble_gatt_if.h>
```

Data Fields

- UINT16 endHdl
- LE_GATT_ATTR_T * pAttr
- UINT16 startHdl
- UINT16 svc_id

5.62.1 Field Documentation

5.62.1.1 endHdl

```
UINT16 endHdl
```

end handle

5.62.1.2 pAttr

```
LE_GATT_ATTR_T* pAttr
```

pointer attribute table

5.62.1.3 startHdl

```
UINT16 startHdl
```

start handle

5.62.1.4 svc_id

```
UINT16 svc_id
```

service ID

5.63 LE_SMP_MSG_ENCRYPTION_CHANGE_IND_T Struct Reference

`#include <ble_smp_if.h>`

Data Fields

- UINT16 conn_hdl
- BOOL enable

5.63.1 Field Documentation

5.63.1.1 conn_hdl

`UINT16 conn_hdl`

connection handle

5.63.1.2 enable

`BOOL enable`

enable or disable

5.64 LE_SMP_MSG_ENCRYPTION_REFRESH_IND_T Struct Reference

`#include <ble_smp_if.h>`

Data Fields

- UINT16 conn_hdl
- UINT16 status

5.64.1 Field Documentation

5.64.1.1 conn_hdl

`UINT16 conn_hdl`

connection handle

5.64.1.2 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.65 LE_SMP_MSG_OOB_DATA_REQUEST_IND_T Struct Reference

```
#include <ble_smp_if.h>
```

Data Fields

- UINT16 conn_hdl

5.65.1 Field Documentation

5.65.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.66 LE_SMP_MSG_PAIRING_ACTION_IND_T Struct Reference

```
#include <ble_smp_if.h>
```

Data Fields

- UINT8 action
- UINT16 conn_hdl
- BOOL lost_bond
- UINT8 sc

5.66.1 Field Documentation

5.66.1.1 action

```
UINT8 action
```

refer to LE_SM_IO_CAP_∗ in ble_smp_if.h

5.66.1.2 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.66.1.3 lost_bond

```
BOOL lost_bond
```

remote lost bond

5.66.1.4 sc

```
UINT8 sc
```

secure connection

5.67 LE_SMP_MSG_PAIRING_COMPLETE_IND_T Struct Reference

```
#include <ble_smp_if.h>
```

Data Fields

- UINT8 authenticated
- UINT8 bonded
- UINT16 conn_hdl
- LE_BT_ADDR_T peer_id_addr
- UINT8 sc
- UINT16 status

5.67.1 Field Documentation

5.67.1.1 authenticated

```
UINT8 authenticated
```

authenticated

5.67.1.2 bonded

```
UINT8 bonded
```

bonded

5.67.1.3 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.67.1.4 peer_id_addr

```
LE_BT_ADDR_T peer_id_addr
```

peer device address

5.67.1.5 sc

```
UINT8 sc
```

secure connection

5.67.1.6 status

```
UINT16 status
```

refer to LE_ERR_STATE in ble_err.h

5.68 LE_SMP_MSG_PASSKEY_DISPLAY_IND_T Struct Reference

```
#include <ble_smp_if.h>
```

Data Fields

- UINT16 conn_hdl
- UINT32 passkey

5.68.1 Field Documentation

5.68.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.68.1.2 passkey

```
UINT32 passkey
```

passkey

5.69 LE_SMP_MSG_PASSKEY_INPUT_IND_T Struct Reference

```
#include <ble_smp_if.h>
```

Data Fields

- UINT16 conn_hdl

5.69.1 Field Documentation

5.69.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.70 LE_SMP_MSG_SC_OOB_DATA_REQUEST_IND_T Struct Reference

```
#include <ble_smp_if.h>
```

Data Fields

- UINT16 conn_hdl

5.70.1 Field Documentation

5.70.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.71 LE_SMP_MSG_SLAVE_SECURITY_REQUEST_IND_T Struct Reference

`#include <ble_smp_if.h>`

Data Fields

- UINT8 bondable
- UINT16 conn_hdl
- UINT8 keypress
- UINT8 mitm
- UINT8 sc

5.71.1 Field Documentation

5.71.1.1 bondable

`UINT8 bondable`

bonding

5.71.1.2 conn_hdl

`UINT16 conn_hdl`

connection handle

5.71.1.3 keypress

`UINT8 keypress`

keypress status

5.71.1.4 mitm

`UINT8 mitm`

MITM

5.71.1.5 sc

`UINT8 sc`

secure connection

5.72 LE_SMP_MSG_USER_CONFIRM_IND_T Struct Reference

`#include <ble_smp_if.h>`

Data Fields

- UINT32 confirm_num
- UINT16 conn_hdl

5.72.1 Field Documentation

5.72.1.1 confirm_num

`UINT32 confirm_num`

confirm number

5.72.1.2 conn_hdl

`UINT16 conn_hdl`

connection handle

5.73 LE_SMP_SC_OOB_DATA_T Struct Reference

`#include <ble_smp_if.h>`

Data Fields

- UINT8 confirm [16]
- UINT8 rand [16]

5.73.1 Field Documentation

5.73.1.1 confirm

`UINT8 confirm[16]`

confirm data

5.73.1.2 rand

```
UINT8 rand[16]
```

random data

5.74 LE_SYS_MSG_BUF_OVERFLOW_T Struct Reference

```
#include <ble_msg.h>
```

Data Fields

- UINT16 conn_hdl

5.74.1 Field Documentation

5.74.1.1 conn_hdl

```
UINT16 conn_hdl
```

connection handle

5.75 mw_wifi_auto_connect_ap_info_t Struct Reference

```
#include <controller_wifi_com_patch.h>
```

Data Fields

- u8 ap_channel
- u16 beacon_interval
- u8 bssid [MAC_ADDR_LEN]
- u16 capabilities
- u8 dtim_prod
- u8 fast_connect
- bool free_ocpy
- s8 hid_ssid [IEEE80211_MAX_SSID_LEN+1]
- u64 latest_beacon_rx_time
- s8 passphrase [64]
- u8 psk [32]
- u8 rsn_ie [100]
- s8 rssi
- s8 ssid [IEEE80211_MAX_SSID_LEN+1]
- u8 supported_rates [SUPPORTED_RATES_MAX]
- wpa_ie_data_t wpa_data
- u8 wpa_ie [100]

5.75.1 Field Documentation

5.75.1.1 ap_channel

```
u8 ap_channel
```

5.75.1.2 beacon_interval

```
u16 beacon_interval
```

5.75.1.3 bssid

```
u8 bssid[MAC_ADDR_LEN]
```

5.75.1.4 capabilities

```
u16 capabilities
```

5.75.1.5 dtim_prod

```
u8 dtim_prod
```

5.75.1.6 fast_connect

```
u8 fast_connect
```

5.75.1.7 free_ocpy

```
bool free_ocpy
```

5.75.1.8 hid_ssid

```
s8 hid_ssid[IEEE80211_MAX_SSID_LEN+1]
```

5.75.1.9 latest_beacon_rx_time

```
u64 latest_beacon_rx_time
```

5.75.1.10 passphrase

```
s8 passphrase[64]
```

5.75.1.11 psk

```
u8 psk[32]
```

5.75.1.12 rsn_ie

```
u8 rsn_ie[100]
```

5.75.1.13 rssi

```
s8 rssi
```

5.75.1.14 ssid

```
s8 ssid[IEEE80211_MAX_SSID_LEN+1]
```

5.75.1.15 supported_rates

```
u8 supported_rates[SUPPORTED_RATES_MAX]
```

5.75.1.16 wpa_data

```
wpa_ie_data_t wpa_data
```

5.75.1.17 wpa_ie

```
u8 wpa_ie[100]
```

5.76 MwFimAutoConnectCFG_t Struct Reference

```
#include <controller_wifi_com_patch.h>
```

Data Fields

- bool flag
- s8 front
- u8 max_save_num
- s8 rear
- u8 targetIdx

5.76.1 Field Documentation

5.76.1.1 flag

```
bool flag
```

5.76.1.2 front

```
s8 front
```

5.76.1.3 max_save_num

```
u8 max_save_num
```

5.76.1.4 rear

```
s8 rear
```

5.76.1.5 targetIdx

```
u8 targetIdx
```

5.77 T_RfCmd Struct Reference

```
#include <controller_wifi_patch.h>
```

Data Fields

- int iArgc
- char * saArgv [RF_CMD_PARAM_NUM]
- uint32_t u32Type

5.77.1 Field Documentation

5.77.1.1 iArgc

```
int iArgc
```

5.77.1.2 saArgv

```
char* saArgv[RF_CMD_PARAM_NUM]
```

5.77.1.3 u32Type

```
uint32_t u32Type
```

5.78 T_RfEvt Struct Reference

```
#include <controller_wifi_patch.h>
```

Data Fields

- void * pParam
- uint16_t u16RfMode
- uint16_t u16RxCnt
- uint16_t u16RxCrcOkCnt
- uint32_t u32Freq
- uint32_t u32Mode
- uint32_t u32RfChannel
- uint32_t u32Type
- uint8_t u8Freq
- uint8_t u8IpcEnable
- uint8_t u8Len
- uint8_t u8Pkt
- uint8_t u8Reserved
- uint8_t u8Status
- uint8_t u8Unicast

5.78.1 Field Documentation

5.78.1.1 pParam

```
void* pParam
```

5.78.1.2 u16RfMode

```
uint16_t u16RfMode
```

5.78.1.3 u16RxCnt

```
uint16_t u16RxCnt
```

5.78.1.4 u16RxCrcOkCnt

```
uint16_t u16RxCrcOkCnt
```

5.78.1.5 u32Freq

```
uint32_t u32Freq
```

5.78.1.6 u32Mode

```
uint32_t u32Mode
```

5.78.1.7 u32RfChannel

```
uint32_t u32RfChannel
```

5.78.1.8 u32Type

```
uint32_t u32Type
```

5.78.1.9 u8Freq

```
uint8_t u8Freq
```

5.78.1.10 u8IpcEnable

```
uint8_t u8IpcEnable
```

5.78.1.11 u8Len

```
uint8_t u8Len
```

5.78.1.12 u8Pkt

```
uint8_t u8Pkt
```

5.78.1.13 u8Reserved

```
uint8_t u8Reserved
```

5.78.1.14 u8Status

```
uint8_t u8Status
```

5.78.1.15 u8Unicast

```
uint8_t u8Unicast
```

5.79 wifi_active_scan_time_t Struct Reference

Range of active scan times per channel.

```
#include <wifi_types.h>
```

Data Fields

- uint32_t max
- uint32_t min

5.79.1 Detailed Description

Range of active scan times per channel.

5.79.2 Field Documentation

5.79.2.1 max

```
uint32_t max
```

maximum active scan time per channel, units: millisecond, values above 1500ms may cause station to disconnect from AP and are not recommended.

5.79.2.2 min

```
uint32_t min
```

minimum active scan time per channel, units: millisecond

5.80 wifi_ap_config_t Struct Reference

This structure is the Wi-Fi configuration for initialization for Soft-AP mode.

```
#include <wifi_types.h>
```

Data Fields

- wifi_auth_mode_t auth_mode
- uint16_t beacon_interval
- uint8_t channel
- wifi_cipher_type_t encrypt_type
- uint8_t max_connection
- uint8_t password [WIFI_LENGTH_PASSPHRASE]
- uint8_t password_length
- uint8_t ssid [WIFI_MAX_LENGTH_OF_SSID]
- uint8_t ssid_hidden
- uint8_t ssid_length

5.80.1 Detailed Description

This structure is the Wi-Fi configuration for initialization for Soft-AP mode.

5.80.2 Field Documentation

5.80.2.1 auth_mode

```
wifi_auth_mode_t auth_mode
```

The authentication mode.

5.80.2.2 beacon_interval

```
uint16_t beacon_interval
```

Beacon interval, 100 ~ 60000 ms, default 100 ms

5.80.2.3 channel

```
uint8_t channel
```

The channel of Soft-AP.

5.80.2.4 encrypt_type

```
wifi_cipher_type_t encrypt_type
```

The encryption mode.

5.80.2.5 max_connection

```
uint8_t max_connection
```

Max number of stations allowed to connect in, default 4, max 4

5.80.2.6 password

```
uint8_t password[WIFI_LENGTH_PASSPHRASE]
```

The password of the Soft-AP.

5.80.2.7 password_length

```
uint8_t password_length
```

The length of the password.

5.80.2.8 ssid

```
uint8_t ssid[WIFI_MAX_LENGTH_OF_SSID]
```

The SSID of the Soft-AP.

5.80.2.9 ssid_hidden

```
uint8_t ssid_hidden
```

Broadcast SSID or not, default 0, broadcast the SSID

5.80.2.10 ssid_length

```
uint8_t ssid_length
```

The length of the SSID.

5.81 wifi_auto_connect_info_f Struct Reference

WiFi auto connect info parameters.

```
#include <wifi_types.h>
```

Data Fields

- uint8_t ap_channel
- uint16_t beacon_interval
- uint8_t bssid [WIFI_MAC_ADDRESS_LENGTH]
- uint16_t capabilities
- uint8_t dtim_prod
- uint8_t fast_connect
- bool free_ocpy
- int8_t hid_ssid [WIFI_MAX_LENGTH_OF_SSID]
- unsigned long latest_beacon_rx_time
- int8_t passphrase [WIFI_LENGTH_PASSPHRASE]
- uint8_t psk [32]
- uint8_t rsn_ie [100]
- int8_t rssi
- int8_t ssid [WIFI_MAX_LENGTH_OF_SSID]
- uint8_t supported_rates [WIFI_MAX_SUPPORTED_RATES]
- wpa_ie_data_t wpa_data
- uint8_t wpa_ie [100]

5.81.1 Detailed Description

WiFi auto connect info parameters.

5.81.2 Field Documentation

5.81.2.1 ap_channel

```
uint8_t ap_channel
```

5.81.2.2 beacon_interval

```
uint16_t beacon_interval
```

5.81.2.3 bssid

```
uint8_t bssid[WIFI_MAC_ADDRESS_LENGTH]
```

5.81.2.4 capabilities

```
uint16_t capabilities
```

5.81.2.5 dtim_prod

```
uint8_t dtim_prod
```

5.81.2.6 fast_connect

```
uint8_t fast_connect
```

5.81.2.7 free_ocpy

```
bool free_ocpy
```

5.81.2.8 hid_ssid

```
int8_t hid_ssid[WIFI_MAX_LENGTH_OF_SSID]
```

5.81.2.9 latest_beacon_rx_time

```
unsigned long latest_beacon_rx_time
```

5.81.2.10 passphrase

```
int8_t passphrase[WIFI_LENGTH_PASSPHRASE]
```

5.81.2.11 psk

```
uint8_t psk[32]
```

5.81.2.12 rsn_ie

```
uint8_t rsn_ie[100]
```

5.81.2.13 rssi

```
int8_t rssi
```

5.81.2.14 ssid

```
int8_t ssid[WIFI_MAX_LENGTH_OF_SSID]
```

5.81.2.15 supported_rates

```
uint8_t supported_rates[WIFI_MAX_SUPPORTED_RATES]
```

5.81.2.16 wpa_data

```
wpa_ie_data_t wpa_data
```

5.81.2.17 wpa_ie

```
uint8_t wpa_ie[100]
```

5.82 wifi_config_t Union Reference

Wi-Fi configuration for initialization.

```
#include <wifi_types.h>
```

Data Fields

- wifi_ap_config_t ap_config
- wifi_sta_config_t sta_config

5.82.1 Detailed Description

Wi-Fi configuration for initialization.

5.82.2 Field Documentation

5.82.2.1 ap_config

```
wifi_ap_config_t ap_config
```

The configurations for certain AP. It should be set when the OPMODE is #WIFI_MODE_AP_ONLY .

5.82.2.2 sta_config

```
wifi_sta_config_t sta_config
```

The configurations for the STA. It should be set when the OPMODE is #WIFI_MODE_STA_ONLY.

5.83 wifi_event_info_t Union Reference

wifi_event_info_t

```
#include <wifi_event.h>
```

Data Fields

- wifi_event_sta_connected_t connected
- wifi_event_sta_disconnected_t disconnected
- wifi_event_sta_got_ip_t got_ip
- wifi_event_sta_scan_done_t scan_done

5.83.1 Detailed Description

wifi_event_info_t

5.83.2 Field Documentation

5.83.2.1 connected

`wifi_event_sta_connected_t connected`

station connected to AP

5.83.2.2 disconnected

`wifi_event_sta_disconnected_t disconnected`

station disconnected to AP

5.83.2.3 got_ip

`wifi_event_sta_got_ip_t got_ip`

station got IP, first time got IP or when IP is changed

5.83.2.4 scan_done

`wifi_event_sta_scan_done_t scan_done`

station scan (APs) done

5.84 wifi_event_sta_connected_t Struct Reference

wifi_event_sta_connected_t

`#include <wifi_event.h>`

Data Fields

- wifi_auth_mode_t authmode
- uint8_t bssid [6]
- uint8_t channel
- uint8_t ssid [32]
- uint8_t ssid_len

5.84.1 Detailed Description

wifi_event_sta_connected_t

5.84.2 Field Documentation

5.84.2.1 authmode

```
wifi_auth_mode_t authmode
```

5.84.2.2 bssid

```
uint8_t bssid[6]
```

BSSID of connected AP

5.84.2.3 channel

```
uint8_t channel
```

channel of connected AP

5.84.2.4 ssid

```
uint8_t ssid[32]
```

SSID of connected AP

5.84.2.5 ssid_len

```
uint8_t ssid_len
```

SSID length of connected AP

5.85 wifi_event_sta_disconnected_t Struct Reference

wifi_event_sta_disconnected_t

```
#include <wifi_event.h>
```

Data Fields

- uint8_t bssid [6]
- uint8_t reason
- uint8_t ssid [32]
- uint8_t ssid_len

5.85.1 Detailed Description

wifi_event_sta_disconnected_t

5.85.2 Field Documentation

5.85.2.1 bssid

```
uint8_t bssid[6]
```

BSSID of disconnected AP

5.85.2.2 reason

```
uint8_t reason
```

reason of disconnection

5.85.2.3 ssid

```
uint8_t ssid[32]
```

SSID of disconnected AP

5.85.2.4 ssid_len

```
uint8_t ssid_len
```

SSID length of disconnected AP

5.86 wifi_event_sta_got_ip_t Struct Reference

wifi_event_sta_got_ip_t

```
#include <wifi_event.h>
```

Data Fields

- bool ip_changed

5.86.1 Detailed Description

wifi_event_sta_got_ip_t

5.86.2 Field Documentation

5.86.2.1 ip_changed

```
bool ip_changed
```

5.87 wifi_event_sta_scan_done_t Struct Reference

wifi_event_sta_scan_done_t

```
#include <wifi_event.h>
```

Data Fields

- uint8_t number
- uint8_t scan_id
- uint32_t status

5.87.1 Detailed Description

wifi_event_sta_scan_done_t

5.87.2 Field Documentation

5.87.2.1 number

```
uint8_t number
```

The number of devices scanned

5.87.2.2 scan_id

```
uint8_t scan_id
```

scan id

5.87.2.3 status

```
uint32_t status
```

status of scanning APs

5.88 wifi_fast_scan_threshold_t Struct Reference

Structure describing parameters for a Wi-Fi fast scan.

```
#include <wifi_types.h>
```

Data Fields

- wifi_auth_mode_t authmode
- int8_t rssi

5.88.1 Detailed Description

Structure describing parameters for a Wi-Fi fast scan.

5.88.2 Field Documentation

5.88.2.1 authmode

```
wifi_auth_mode_t authmode
```

The weakest authmode to accept in the fast scan mode

5.88.2.2 rssi

```
int8_t rssi
```

The minimum rssi to accept in the fast scan mode

5.89 wifi_init_config_t Struct Reference

WiFi stack configuration parameters.

```
#include <wifi_types.h>
```

Data Fields

- wifi_event_notify_cb_t event_handler
- int magic

5.89.1 Detailed Description

WiFi stack configuration parameters.

5.89.2 Field Documentation

5.89.2.1 event_handler

```
wifi_event_notify_cb_t event_handler
```

WiFi event handler

5.89.2.2 magic

```
int magic
```

WiFi init magic number, it should be the last field

5.90 wifi_scan_config_t Struct Reference

Parameters for an SSID scan.

```
#include <wifi_types.h>
```

Data Fields

- uint8_t * bssid
- uint8_t channel
- wifi_scan_time_t scan_time
- wifi_scan_type_t scan_type
- bool show_hidden
- uint8_t * ssid

5.90.1 Detailed Description

Parameters for an SSID scan.

5.90.2 Field Documentation

5.90.2.1 bssid

```
uint8_t* bssid
```

MAC address of AP

5.90.2.2 channel

```
uint8_t channel
```

channel, scan the specific channel

5.90.2.3 scan_time

```
wifi_scan_time_t scan_time
```

scan time per channel

5.90.2.4 scan_type

```
wifi_scan_type_t scan_type
```

scan type, active or passive

5.90.2.5 show_hidden

```
bool show_hidden
```

enable to scan AP whose SSID is hidden

5.90.2.6 ssid

```
uint8_t* ssid
```

SSID of AP

5.91 wifi_scan_info_t Struct Reference

This structure defines the inforamtion of scanned APs.

```
#include <wifi_types.h>
```

Data Fields

- wifi_auth_mode_t auth_mode
- uint16_t beacon_interval
- uint8_t bssid [WIFI_MAC_ADDRESS_LENGTH]
- uint16_t capability_info
- uint8_t channel
- wifi_cipher_type_t group_cipher
- wifi_cipher_type_t pairwise_cipher
- int rssi
- uint8_t ssid [WIFI_MAX_LENGTH_OF_SSID]
- uint8_t ssid_length

5.91.1 Detailed Description

This structure defines the inforamtion of scanned APs.

5.91.2 Field Documentation

5.91.2.1 auth_mode

```
wifi_auth_mode_t auth_mode
```

Please refer to the definition of wifi_auth_mode_t.

5.91.2.2 beacon_interval

```
uint16_t beacon_interval
```

Indicates the beacon interval.

5.91.2.3 bssid

```
uint8_t bssid[WIFI_MAC_ADDRESS_LENGTH]
```

AP's MAC address.

5.91.2.4 capability_info

```
uint16_t capability_info
```

The Capability Information field contains a number of subfields that are used to indicate requested or advertised optional capabilities.

5.91.2.5 channel

```
uint8_t channel
```

The channel used.

5.91.2.6 group_cipher

```
wifi_cipher_type_t group_cipher
```

group cipher of AP

5.91.2.7 pairwise_cipher

```
wifi_cipher_type_t pairwise_cipher
```

pairwise cipher of AP, Please refer to the definition of #wifi_encrypt_type_t.

5.91.2.8 rssi

```
int rssi
```

Records the RSSI value when probe response is received.

5.91.2.9 ssid

```
uint8_t ssid[WIFI_MAX_LENGTH_OF_SSID]
```

Stores the predefined SSID.

5.91.2.10 ssid_length

```
uint8_t ssid_length
```

Length of the SSID.

5.92 wifi_scan_list_t Struct Reference

This structure defines the list of scanned APs with their corresponding information.

```
#include <wifi_types.h>
```

Data Fields

- wifi_scan_info_t ap_record [WIFI_MAX_SCAN_AP_NUM]
- int num

5.92.1 Detailed Description

This structure defines the list of scanned APs with their corresponding information.

5.92.2 Field Documentation

5.92.2.1 ap_record

```
wifi_scan_info_t ap_record[WIFI_MAX_SCAN_AP_NUM]
```

The information about an AP obtained through the scan result is stored

5.92.2.2 num

```
int num
```

number of AP in the list

5.93 wifi_scan_time_t Union Reference

Aggregate of active & passive scan time per channel.

```
#include <wifi_types.h>
```

Data Fields

- wifi_active_scan_time_t active
- uint32_t passive

5.93.1 Detailed Description

Aggregate of active & passive scan time per channel.

5.93.2 Field Documentation

5.93.2.1 active

```
wifi_active_scan_time_t active
```

active scan time per channel, units: millisecond.

5.93.2.2 passive

```
uint32_t passive
```

passive scan time per channel, units: millisecond, values above 1500ms may cause station to disconnect from AP and are not recommended.

5.94 wifi_sta_config_t Struct Reference

This structure is the Wi-Fi configuration for initialization for STA mode.

```
#include <wifi_types.h>
```

Data Fields

- uint8_t bssid [WIFI_MAC_ADDRESS_LENGTH]
- uint8_t bssid_present
- uint8_t password [WIFI_LENGTH_PASSPHRASE]
- uint8_t password_length
- wifi_scan_method_t scan_method
- wifi_sort_method_t sort_method
- uint8_t ssid [WIFI_MAX_LENGTH_OF_SSID]
- uint8_t ssid_length
- wifi_fast_scan_threshold_t threshold

5.94.1 Detailed Description

This structure is the Wi-Fi configuration for initialization for STA mode.

5.94.2 Field Documentation

5.94.2.1 bssid

```
uint8_t bssid[WIFI_MAC_ADDRESS_LENGTH]
```

The MAC address of the target AP.

5.94.2.2 bssid_present

```
uint8_t bssid_present
```

The BSSID is present if it is set to 1. Otherwise, it is set to 0.

5.94.2.3 password

```
uint8_t password[WIFI_LENGTH_PASSPHRASE]
```

The password of the target AP.

5.94.2.4 password_length

```
uint8_t password_length
```

The length of the password. If the length is 64, the password is regarded as PMK.

5.94.2.5 scan_method

```
wifi_scan_method_t scan_method
```

do all channel scan or fast scan

5.94.2.6 sort_method

```
wifi_sort_method_t sort_method
```

sort the connect AP in the list by rssi or security mode

5.94.2.7 ssid

```
uint8_t ssid[WIFI_MAX_LENGTH_OF_SSID]
```

The SSID of the target AP.

5.94.2.8 ssid_length

```
uint8_t ssid_length
```

The length of the SSID.

5.94.2.9 threshold

```
wifi_fast_scan_threshold_t threshold
```

When scan_method is set to WIFI_FAST_SCAN, only APs which have an auth mode that is more secure than the selected auth mode and a signal stronger than the minimum RSSI will be used.

Index