INSTALLATION GUIDE

Tapware & Fittings

Correct installation protects both your new fittings and your warranty. Tapware must be installed by a licensed plumber to meet Australian plumbing standards.

01

Before you start

- Use a licensed plumber, it is a legal requirement and protects your warranty.
- Check the product is correct and undamaged before installing.
- Isolate the water supply and flush all lines to clear debris.

02

Pressure & temperature

Fittings perform best within the recommended pressure and temperature range. Where mains pressure is high, fit a pressure limiting valve. Excess pressure or temperature can damage internal parts and void cover.

03

Sealing & fitting

- Use suitable thread seals and washers.
- Hand-tighten, then gently firm up, do not over-tighten.
- Never grip the finished surface with tools.

04

Protect the finish

During and after install

Keep the protective wrapping on until the last moment.

Remove any adhesive, grout or plaster straight away with a soft, damp cloth, before it sets.

KEEP THIS HANDY

Record the model and keep your proof of purchase and this guide. You may need them for any future service.

05

After installation

- Run the fittings and check for leaks.
- Clean the aerator if flow seems low after building work.
- Follow the care guide from day one.

This installation guide is general information only. Always follow the instructions supplied with your product and use a suitably licensed tradesperson. If you are unsure, please contact OnWood Tiles.