

# compute\_sjsdm\_artifact\_content\_hash.R

August 12, 2026

## Contents

|                                               |          |
|-----------------------------------------------|----------|
| compute_sjsdm_artifact_content_hash . . . . . | 1        |
| <b>Index</b>                                  | <b>3</b> |

---

|                                               |
|-----------------------------------------------|
| compute_sjsdm_artifact_content_hash           |
| <i>Compute an sjSDM Artifact Content Hash</i> |

---

## Description

Computes the stable xxHash64 identity of one v2 artifact while excluding materialization and migration-trace provenance.

## Usage

```
compute_sjsdm_artifact_content_hash(  
  schema_version = NULL,  
  artifact_type = NULL,  
  payload = NULL,  
  provenance = NULL  
)
```

## Arguments

|                |                                                                        |
|----------------|------------------------------------------------------------------------|
| schema_version | Non-empty character scalar schema version.                             |
| artifact_type  | Registered non-empty character scalar artifact type.                   |
| payload        | Non-empty named list containing the artifact payload.                  |
| provenance     | One-row provenance data frame containing the common provenance fields. |

## Value

Character scalar xxHash64 content digest.

**Examples**

```
compute_sjsdm_artifact_content_hash(  
  schema_version = "2.0.0",  
  artifact_type = "sjsdm_cv_predictions",  
  payload = list(data_predictions = tibble::tibble()),  
  provenance = tibble::tibble(  
    created_at = as.POSIXct("2026-08-11", tz = "UTC"),  
    pipeline_id = "pipeline_paleo_core",  
    configuration_profile = "project_cz_paleo",  
    source_schema_version = "2.0.0",  
    migration_applied = FALSE,  
    migration_function = NA_character_  
  )  
)
```

# Index

`compute_sjsdm_artifact_content_hash`, [1](#)