

# compute\_sjsdm\_decomposition\_fold\_effects.R

August 12, 2026

## Contents

|                                                    |          |
|----------------------------------------------------|----------|
| compute_sjsdm_decomposition_fold_effects . . . . . | 1        |
| <b>Index</b>                                       | <b>3</b> |

---

|                                                         |
|---------------------------------------------------------|
| compute_sjsdm_decomposition_fold_effects                |
| <i>Compare Matched-Fold sjSDM Decomposition Metrics</i> |

---

## Description

Pairs full and reduced sjSDM metrics by repeat, fold, taxon, and metric, retaining raw component-removal effects and explicit evaluability statuses.

## Usage

```
compute_sjsdm_decomposition_fold_effects(  
  data_fold_metrics = NULL,  
  data_taxon_eligibility = NULL  
)
```

## Arguments

|                        |                                                                       |
|------------------------|-----------------------------------------------------------------------|
| data_fold_metrics      | Long-format metric table containing full and reduced model variants.  |
| data_taxon_eligibility | Taxon table containing unique ‘taxon’ and logical ‘eligible’ columns. |

## Details

For Tjur R2 and AUC, the effect is full minus reduced. For log loss and Brier score, the effect is reduced minus full. Negative effects are retained.

## Value

A tibble with one row per reduced variant, repeat, fold, taxon, and metric. ‘delta\_full\_advantage’ is positive when the full model performs better.

**Examples**

```
## Not run:
compute_sjsdm_decomposition_fold_effects(
  data_fold_metrics = data_metrics,
  data_taxon_eligibility = data_eligibility
)

## End(Not run)
```

# Index

`compute_sjsdm_decomposition_fold_effects,`  
[1](#)