

load_sjsdm_tuning_summaries.R

August 12, 2026

Contents

load_sjsdm_tuning_summaries 1

Index 3

load_sjsdm_tuning_summaries
Collect sjSDM Tuning Summaries

Description

Reads compact resolution-specific tuning summaries from isolated unit targets stores for a shared tier-selection stage.

Usage

```
load_sjsdm_tuning_summaries(  
  store_paths = NULL,  
  resolution_ids = NULL,  
  target_prefix = "list_sjsdm_cv_tuning_artifact",  
  target_names = NULL,  
  read_target_function = targets::tar_read_raw  
)
```

Arguments

store_paths	Non-empty character vector of unit targets-store paths.
resolution_ids	Non-empty character vector of mapped model-resolution identifiers.
target_prefix	Non-empty character scalar placed before each resolution identifier. Defaults to the existing public tuning-summary target prefix. Explicit round prefixes allow the tier store to collect one staged round at a time.
target_names	Optional character vector paired with 'resolution_ids'. When supplied, reads these exact public target names instead of constructing suffixed names.
read_target_function	Injectable target reader. Defaults to [targets::tar_read_raw()].

Value

Bound tuning-summary tibble with 'source_store' and 'resolution_id' provenance columns. Every requested store-resolution target must be readable. The function aborts with the failed store and target when evidence is incomplete.

Examples

```
## Not run:
load_sjsdm_tuning_summaries(
  store_paths = c("store_a", "store_b"),
  resolution_ids = c("genus", "family")
)

## End(Not run)
```

Index

`load_sjsdm_tuning_summaries`, [1](#)