

# save\_continental\_functional\_type\_classification.R

August 12, 2026

## Contents

|                                                           |          |
|-----------------------------------------------------------|----------|
| save_continental_functional_type_classification . . . . . | 1        |
| <b>Index</b>                                              | <b>3</b> |

---

|                                                                     |  |
|---------------------------------------------------------------------|--|
| save_continental_functional_type_classification                     |  |
| <i>Save Functional-Type Classification for One Continental Unit</i> |  |

---

## Description

Saves a pre-computed functional-type classification tibble as a dated ‘.qs’ file in ‘path\_processed’. The classification is produced upstream by ‘assign\_functional\_type\_clusters()’ via the ‘data\_functional\_type\_classification’ pipeline target.

## Usage

```
save_continental_functional_type_classification(  
  continent_id,  
  data_functional_type_classification,  
  path_classification_directory = here::here("Data/Processed/Traits"),  
  classification_source_prefix = NULL,  
  verbose = TRUE  
)
```

## Arguments

**continent\_id** A single non-empty character string identifying the continental unit (e.g. “eu-rope”, “america”, “asia”). Used only for naming the output file.

**data\_functional\_type\_classification** A data frame containing the functional-type classification, as returned in the ‘classification’ element of ‘assign\_functional\_type\_clusters()’. Typically has columns ‘taxon\_name’, ‘functional\_type’, and ‘silhouette\_width’.

**path\_classification\_directory** A single character string giving the directory where the ‘.qs’ output file will be written. Default: ‘here::here("Data/Processed/Traits")’.

|                              |                                                                                                                                                                                                                                            |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| classification_source_prefix | Optional single non-empty character string to prepend to the 'continent_id' portion of the file name. Use 'NULL' (default) for the historical paleo/global naming convention, or "modern" for modern-data functional-type classifications. |
| verbose                      | Logical. If 'TRUE' (default), progress messages are printed to the console via 'cli'.                                                                                                                                                      |

## Details

**\*\*Steps performed\*\*:**

1. Validate arguments.
2. Save 'data\_functional\_type\_classification' with 'RUtilpol::save\_latest\_file()' as a dated '.qs' file in 'path\_classification\_directory'. The file is only overwritten when the content has changed since the previous version.
3. Resolve the path of the just-saved file via 'RUtilpol::get\_latest\_file\_name()'.
4. Return the file path as a character string.

Data filtering, distance computation, hierarchical clustering, ft-groups selection are all handled upstream by 'select\_continental\_trait\_table()', 'compute\_trait\_dissimilarity()', 'fit\_hierarchical\_clustering()', and 'assign\_functional\_type\_clusters()' respectively.

## Value

A single character string: the absolute path to the '.qs' file that was written. The file is saved via 'RUtilpol::save\_latest\_file()' using the name stem 'data\_functional\_type\_classification\_continent\_id' when 'classification\_source\_prefix = NULL', or 'data\_functional\_type\_classification\_classification\_source\_prefix\_continent\_id' otherwise. The final file name includes a date stamp and content hash appended by 'RUtilpol' (e.g. 'data\_functional\_type\_classification\_europe\_2026-05-07\_\_abc123\_\_qs').

## See Also

[select\_continental\_trait\_table()], [compute\_trait\_dissimilarity()], [fit\_hierarchical\_clustering()], [assign\_functional\_type\_clusters()]

# Index

save\_continental\_functional\_type\_classification,  
[1](#)