

aggregate_trait_values.R

June 18, 2026

Contents

aggregate_trait_values	1
Index	3

aggregate_trait_values

Aggregate Trait Values to Single Value per Group

Description

Aggregates a long-format trait data frame to one row per group (by default per taxon x trait combination) using a specified summary function. Intended to be applied after outlier removal.

Usage

```
aggregate_trait_values(  
  data,  
  trait_col = "trait_value",  
  group_cols = c("taxon_name", "trait_domain_name"),  
  fn = c("median", "mean")  
)
```

Arguments

data	A data frame in long format with at least the columns specified by 'trait_col' and 'group_cols'.
trait_col	A character string naming the numeric column containing trait values. Default: "trait_value".
group_cols	A character vector of column names used to define groups for aggregation. Default: c("taxon_name", "trait_domain_name").
fn	A character string specifying the aggregation function. One of "median" (default) or "mean". Matched with 'match.arg()'.

Details

The 'fn' argument is processed via 'match.arg()', so partial matching is supported (e.g. 'fn = "med"' resolves to "median").

Value

A data frame with one row per unique combination of ‘group_cols’ and a new column ‘trait_value_aggregated’ containing the aggregated value.

See Also

[filter_trait_outliers()], [make_trait_table()]

Index

`aggregate_trait_values`, [1](#)